SPEC SHEET





Consult this chart to confirm the availability of the desired combination before specifying below.

Colour Rendering Index (CRI)		STD/V CRI 83+				ARTIST/V/B CRI 98+				
Luminous Flux (Im,	700	1000	1300	2000	3000	4000	700	1000	1300	2000
Consumption (W)	6.5	9.5	14	23	35	46	9	13	19	32
Colour T° 2700 K	•		•	•	•		• 🛦	• 🛦	• 🛦	• 🛦
3000 K	•				•	•	•			
3500 K	•	•		•	•		•			
4000 K	•	•	•	•	•	•	•	•		
ELV dimming DIM	•	•	•	•	•		•	•	•	•
0-10 V dimming LCS/ELDO	•	•	•	•	•	•	•	•	•	•
STD	•					•	•			
= available	_ A =	- YTM	Roguit	,						

spot light monopoint

SPECIFICATIONS LETO 15

GENERAL

fully adjustable beam direction

- consistent colour, uniform beam
- LED lifetime of 50,000h
- infrared and UV free beam
- $\bullet\,$ different colour T° and lumen output available, please refer to the chart

ELECTRICAL

- standard 120 V driver included
- 277V available upon request, consult Senso for details

FINISH

· satin power coat finish

CONSTRUCTION

· aluminium construction

INSTALLATION

- fits on standard junction box
- canopy included


OPTIONS / ACCESSORIES


- · honeycomb filter
- step-down transformer for 277 V and 347 V circuits

WEIGHT

2.4 kg [5.3 lbs]

DIMENSION





Please specify:

MODEL	615 – canopy
COLOUR RENDERING INDEX	581 - 83+ 781 - 98+ 781B - Beauty (2700K only) 881 - Vibrant (3000K only) 981 - Vibrant/artist (3000K only)
BEAM ANGLE	611 –24° 612 – 40°
COLOUR TEMPERATURE	90 – 2700K 70 – 3000K 60 – 3500K 40 – 4000K
FINISH	01 – white 02 – black 08 – silver
LUMEN	07 – 700 10 – 1000 13 – 1300 20 – 2000 30 – 3000 40 – 4000
DRIVER	STD – not dimmable DIM – dimmable LCS – 0-10V control ELDO-LCS – 0-10V control ELDO-DALI – addressable control

QUANTITY	PROJECT
NOTE	



