SPEC SHEET



Consult this chart to confirm the availability of the desired combination before specifying below.

Colour Rendering Index (CRI)	STD/V CRI 83+						ARTIST/V/B CRI 98+			
Luminous Flux (Im)	700	1000	1300	2000	3000	4000	700	1000	1300	2000
Consumption (W)	6.5	9.5	14	23	35	46	9	13	19	32
Colour T° 2700 K		•		•		•	• 🛦	• 🛦	• 🛦	• 🛦
3000 K				•						
3500 K			•	•			•			•
4000 K	•	•	•	•	•	•	•	•	•	•
ELV dimming DIM	•	•	•	•	•		•	•	•	•
0-10 V dimming LCS/ELDO	•	•	•	•	•	•	•	•	•	•
STD	•	•	•	•	•	•	•		•	•
available	A =	XTM	Beauty	/						

spot light, track mounted

SPECIFICATIONS LETO 15

GENERAL

fully adjustable beam direction

- consistent colour, uniform beam
- LED lifetime of 50,000h
- infrared and UV free beam
- $\bullet\,$ different colour T° and lumen output available, please refer to the chart

ELECTRICAL

- standard 120 V driver included
- 277V available upon request, consult Senso for details

FINISH

• satin powder coat finish

CONSTRUCTION

· aluminium construction

INSTALLATION

• includes two circuits track adapter contact us for track compatibility


OPTIONS / ACCESSORIES


- honeycomb filter
- driver for 277V is available

WEIGHT

2.4 kg [5.3 lbs]

DIMENSION





Please specify:

MODEL	659 – two phase only
COLOUR RENDERING INDEX	581 - 83 + 781 - 98 + 781B - Beauty (2700K only) 881 - vibrant (3000K only) 981 - vibrant/artist (3000K only)
REFLECTOR	611 – 24° 612 – 40°
COLOUR TEMPERATURE	90 – 2700K 70 – 3000K 60 – 3500K 40 – 4000K
FINISH	01 – white 02 – black 08 – silver
LUMEN	07 – 700 10 – 1000 13 – 1300 20 – 2000 30 – 3000 40 – 4000
DRIVER	STD – not dimmable DIM – dimmable LCS – 0-10V control ELDO-LCS – 0-10V control ELDO-DALI – addressable control LUT – based on submittal drawing

PROJECT



