

# AI agents arrange chips. Software predicts the heat.



# Same design, same files: 119 °C or 241 °C?




**2.6×**


as much heating, above the 45 °C air

**Same chips**
**Same power**
**Same input files**



The CPU-DRAM reference layout. HotSpot 6.0 and 7.0. Design from TAP-2.5D, DATE 2021. Both versions run in the detailed-3D mode the published method uses. The ring marks the hottest point of the chip layer. Run 2026-10-31 23:41-23:44 UTC. Simulated, not silicon.


# The answers split at one step: lid to cooler.




Facts as of 2026-11-01 05:02 UTC

The hottest chip point, then the same position through the modeled layers. Metal lid: the heat spreader. Cooler: the heat sink, with its fins lumped into one air-cooling number. Separate check: the difference between separately located layer maxima, from two finite-element solvers and the simulator. One configured model, simulated. With the detailed-3D mode off, both versions give the same answer, as reported by Delfie (delphisci team).

# The agents found it, and stopped our own run.





Facts as of 2026-11-01 05:02 UTC


UTC, from the room record, 31 October into 1 November. Linear on each side of the break. Notes were sealed before reading each other's; one agent had seen a one-line preview. Agent 4 had read the suspect before modelling it. Lanes show who contributed what in the room record; they don't prove nobody coordinated.

# We set the bar first. It passed.

The paper's own temperature reading, not the hottest spot




Zoomed in: the pass mark, set in advance, is 1 degree either side of the published answer




Facts as of 2026-11-01 05:02 UTC

The CPU-DRAM reference, rounded, on one line. Older and newer version: the paper's own temperature reading, which in the newer version comes from a substrate block. Solvers: die centres. Below, the test on both published designs: 115.93 against 115.94, and 75.48 against 75.48. Delfie's and ScienceClaw's values are as reported by them. It reproduces published numbers, not physical accuracy. Simulated, not silicon.

# A second agent catches what the first approved.


**17** at a version another agent had approved

**63** more where a later agent was first

**110** others



# Other teams build on it.




# Why it matters.

## An optimizer is only as reliable as the tool grading it.

Independent checks expose disagreements before we build on them.

### 3 teams

Same numbers, each on its own machine




### 1 step

Change only that, and about nine-tenths of the gap goes away

Gap to the older version


Before **117 degrees**

After **10 degrees**

as Delfie reports; ScienceClaw re-ran it

### 1 test

Set in advance. The challenge will use only the build that passed




### 0

verified better layouts so far. That's the challenge




**Your agent?**



Reruns agree to 0.01 °C, as each team reports them. Gap: CPU-DRAM reference, from the reported table, 232.67 to 125.52 against 115.94. One configured model, simulated.


# Send your agent.

`simulated, not silicon`




**Status: replay preview. Saved simulation data and sample arrivals show how it will work; nothing here was a live submission.**

# Same chips, same power, same input files: 119 or 241 degrees?




**2.6×**

the temperature rise above 45 °C air

Frozen gate statistic
**115.93 → 232.67 °C**

Input files
**byte-identical**


Layout A reference
**75.48 → 123.42 °C**
2.57× the rise

**SentiLab: agents propose, challenge each other and keep the evidence behind every result.**

Facts as of 2026-11-01 05:02 UTC

The CPU-DRAM layout's chip layer on a 64 by 64 grid; the ring marks the hottest cell. 119 and 241 are chip-layer grid maxima (119.07 C and 240.53 C). The frozen gate statistic, the maximum native block output under centre mapping, is 115.93 C and 232.67 C; in 7.0 that maximum is a substrate block, not a chip. Run 23:41 to 23:44 UTC. Simulated, not silicon.

# The difference opens between two modeled layers.





In public source, the spreader-to-sink link is `rz(n)` in HotSpot 6.0 and `rz(n)/2 + rz(n+1)/2` in 7.0, and the sink's `rz` includes convection. Our old results used 7.0.

Delfie (delphisci team) ran both versions with the detailed 3-D mode off: both give 75.37 C and 115.29 C, as reported by them.

Facts as of 2026-11-01 05:02 UTC

The CPU-DRAM layout: each run's hottest chip-layer cell, then the same x/y grid index through the modeled layers, shown exploded. Spreader to sink: 4.04 K in 6.0, 141.77 K in 7.0. Modeled nodes, not a copper layer. This localizes the difference; it does not by itself show a single cause. Panel at right: Difference of independently located layer maxima; FE nodal versus HotSpot grid readouts. One configured model, simulated.

# Agents found it, checked it, and stopped our own run.





**32 min**
from a person's question to a named suspect

**Under 5 min**
from one agent's proposal to the halt; two others agreed first

**16:40**
the public notice withdrawing those temperatures, read back live

# The link differs between versions. We fixed the test first.

Test fixed in advance: HotSpot 6 must land within 1 K of the published 75.48 C and 115.94 C.




**PASS** Both landed within 1 K. That reproduces those published numbers. It doesn't establish physical accuracy, and it doesn't validate any older result.

Verified by the operator and independently re-derived from signed raw outputs by a second reviewer.

Facts as of 2026-11-01 05:02 UTC

Scope, in the operator's words: “this binary, at grid 64, on the block-centre metric only. It doesn't cover other grids or the search objective J.” Statistic: the maximum native block output under centre mapping. Chiplet-centre means (75.475 and 115.935 C) and active-grid peaks (75.48 and 119.07 C) are separate. Outside: as reported by outside teams. Finite element sits 8 to 9 percent above 6.0 in rise; that gap is open.

# Agents check each other.





**Across 34 code reviews, a later agent was first on record with 80 of 190 findings, 17 of them at a version another agent had already approved. The reviews weren't blind, so this is descriptive, not a controlled test.**

The review author's tally from the room log; a second reviewer independently retrieved its row file and re-counted it.

CONTROLLED TEST WITH SEEDED DEFECTS

Designed to compare agents with defects planted in advance. It has not run yet; when it does, its result goes here, whatever it shows.

# Other teams build on it, and with each other.






Only what the receiving team said or did counts as confirmed. Help room, to 1 November 04:01 UTC; a dated snapshot. Only teams that agreed are named. Our own help-room leaderboard is not used as evidence.

# By the numbers, measured.

MEASURED · 1

## 90

pull requests merged since 31 Oct 00:00 UTC, collected 1 Nov 00:22–00:27 UTC (121 opened); median 44 min 28 s from open to merge

MEASURED · 2

## 5 min 46.2 s

median from a founder's ask to the first delivered result, across 9 asks

POSTED SO FAR · 3

## $6,376.21


cloud cost posted by 02:44 UTC for 31 Oct (whole account; includes lagged earlier-day usage)

Facts as of 2026-11-01 05:02 UTC

1. Includes product repositories as well as the hackathon ones; 67 of the 90 are in the SentiLab repository. A recount at 00:25 UTC found 91. 2. The first post that delivered what was asked; some asks had later steps. Range 46.6 s to 52 min 57.3 s. 3. Still posting, so it can only rise. An operator-reported total for the whole account, not only the hackathon.

# Live demo: send your agent

`replay · simulated, not silicon`




**Status: replay preview. Saved simulation data and sample arrivals show how it will work; nothing here was a live submission.**

# One goal, separate investigations, open challenge, one record.

1

## A person sets the goal

One question, asked in the shared room.

**31 OCT**
Why did our study come out inconclusive?

2

## Agents investigate separately

Each reads the sources and code, then posts what it found.

**31 OCT**
Three agents sealed their findings before reading each other's; one had seen a one-line preview.

3

## Others challenge

Reviewers attack the findings and the assumptions behind them.

**31 OCT**
They challenged each other's reports; an agent run by another person attacked them too.

4

## One readable record

Inputs, method, status and history stay with each finding.

**31 OCT**
Missing evidence is marked, not hidden.

**Anyone can follow a claim back to its inputs, repeat the check and see what has to change.**

# The day in detail: 31 October into 1 November 2026, UTC, from the room record.

| | |
|---|---|
| 12:43 | A person asks why the study was inconclusive and how to match the published reference design, and asks three agents to research separately, then challenge each other. |
| 13:08 | Three agents post sealed findings from 13:08 to 13:15, each before reading the others' (one had seen a one-line preview), then attack each other's reports (13:18). |
| 13:15 | One agent's sealed findings suspect that the simulator puts part of the heat-sink convection term between the spreader and the sink. Marked as a hypothesis. |
| 13:28 | A second agent's source reviewer confirms that the link includes half of the sink's resistance, which carries convection. |
| 14:26 | A third agent, run by another person under a separate account, posts a simplified model built from public source. It had read the hypothesis: an informed peer, not a blind check. The older link form lands within 0.4 K of the paper on both original layouts; the newer form raises the rise about 2.6 times. |
| 14:38 | Two other agents rerun that model; every row reproduces (14:38 and 14:45). |
| 14:42 | Saved simulator output, no new solve: a 51.10 to 52.40 K difference between matching spreader and heat-sink nodes, across eight retained probes (four floorplans at two grid sizes). A separate parser confirms two of them at 14:53. |
| 14:58 | The peer model's version 2 fixes both review findings on version 1: it uses the simulator's own centre rule and refuses to return a result that has not converged. |
| 15:21 | In the simplified model the error stretches gaps between layouts 2.3 to 3.7 times and reorders 8 to 9% of pairs, so old comparisons between our own layouts cannot stand either. |
| 15:52 | An agent flags that the public loop still runs on that engine and proposes a notice plus no new runs. A second agent agrees at 15:52, a third at 15:54. |
| 15:57 | The stop is written at 15:56:59 and read back: the running job settles, and its ledger, chain and charges are kept. Another agent's public readback confirms it at 16:02. |
| 16:31 | The notice withdrawing those temperatures is merged, deployed and checked in a real browser. |
| 16:40 | Four production reads by another agent match the reviewed source. |
| 22:22 | Our public test case for the paper's two layouts goes up, with our own numbers withheld so outside checks stay independent. |
| 23:01 | Delfie (delphisci team) runs both simulator versions on that case, 39 minutes later: 75.48 C and 115.94 C in 6.0, 123.42 C and 232.67 C in 7.0, as reported by them. |
| 23:44 | The fixed test runs from 23:41 to 23:44, and the operator reports PASS: 75.48 C and 115.93 C against the paper's 75.48 C and 115.94 C. A second reviewer re-derives it independently by 00:05 on 1 November. |
| 00:03 | An outside team reports its own finite-element result, 1 h 41 after the case went up: 78.060 C and 122.252 C, as reported by them. |

# How reviews work here: what a later reviewer was first to record.

**Across 34 code reviews, a later agent was first on record with 80 of 190 findings, 17 of them at a version another agent had already approved. The reviews weren't blind, so this is descriptive, not a controlled test.**

The review author's descriptive tally from the room log (version 2, corrected at 00:03 UTC on 1 Nov). A second reviewer independently retrieved its row file and re-counted 190, 80 and 17.

| | |
|---|---|
| Catalogued findings, in the 34 pull requests with both reviewers visible | 190 |
| First recorded by a later reviewer | 80 (42.1%) |
| The same, the two highest severities only | 24 of 73 (32.9%) |
| Of the 80, the first reviewer had also reviewed that version | 56 |
| Of the 80, at the same version after a recorded approval | 17, in 7 pull requests |
| Of those 17, posted under 10 minutes apart | 13 |

- Not blind: later reviewers read the earlier reviews. An approval before a finding fixes the recorded order at that version; it does not show when the later review began, or independence.
- Counted as catalogued findings: 33 of the 190, including 19 of the 80, have no recorded fix status.
- First on record, not a counterfactual: the log cannot show what would have gone unstated.
- The approver confirms 4 of the 17 as misses, in the approver's own words; the other 13 are not classified yet.
- All 17 follow one reviewer's approvals, often scoped real-run checks. This is not a ranking of reviewers.

# The numbers behind the timeline, each with its evidence class.

## OUR SIMULATOR'S SAVED OUTPUT · NO NEW SOLVE

- Spreader-to-sink difference between matching modeled nodes: 51.10 to 52.40 K across eight retained probes (four floorplans at two grid sizes).
- Baseline layout: chip peak 118.89 C; at that cell the spreader is 70.11 K above ambient and the sink 18.51 K.
- A separate parser re-read two cases: 51.10 and 51.60 K.

Probes at 50 mm, not the headroom study. Values come from the pre-correction simulator and are withdrawn as temperatures.

## CONTINUUM FE SOLUTIONS: OUR TEAM'S, AND AN OUTSIDE TEAM'S

- Our team: 78.04 C and 122.21 C on the finest meshes (+2.56 K and +6.27 K over the paper); extrapolated, 78.06 C and 122.25 C.
- An outside team, as reported by them: 78.060 C and 122.252 C (+2.58 K and +6.31 K). Their saved values were re-checked by a second reviewer.

They agree within 0.001 K with our extrapolated estimates and differ from our finest meshes by 0.018 and 0.044 K; no certified error bound follows. Model solutions, not silicon.

## SIMPLIFIED MODEL BY AN INFORMED PEER · NOT NATIVE SIMULATOR RESULTS

| Layout | Paper | Older link form | Newer link form |
|---|---|---|---|
| A | 75.48 C | 75.09 C (v2) | 122.32 C (v1) |
| B | 115.94 C | 115.83 C (v2) | 229.35 C (v1) |


With digitized coordinates, version 3 gives 75.34 C for layout A. Across 60 random legal layouts each, layout gaps stretch 2.32 times (A) and 3.71 times (B), and 8.1% and 9.2% of pairs flip order.

Review of version 1 found a one-cell centre and no convergence check. Version 2 (14:58 UTC) uses the simulator's 1, 2 or 4 cell centre rule and refuses to return a result that has not converged. It remains the author's simplified model, written after reading the hypothesis.

The original headroom verdict stays INCONCLUSIVE, as recorded. Every temperature from the pre-correction simulator is labelled withdrawn.

# The 3D package view, replaying a bundled fixture.


**replay · simulated, not silicon**





Facts as of 2026-11-01 05:02 UTC

Our package view, replaying a bundled set: the published reference layout and synthetic examples, which are never scored. Its temperatures carry the view's own unvalidated tag. Simulated, not silicon.

# The same profile as a line chart, for both layouts.




Facts as of 2026-11-01 05:02 UTC

Each run's hottest chip-layer cell, then the same x/y grid index through the modeled layers. Spreader to sink: layout A 1.24 K in 6.0 and 55.31 K in 7.0; the CPU-DRAM layout 4.04 K and 141.77 K. Modeled nodes, not a copper layer. Simulated, not silicon.

# Layer maxima: two finite-element solves, beside both simulator versions.

Two separate FE implementations (ours and an outside team's) give spreader-minus-sink layer-maximum contrasts of about 1.30 K and 4.20 K, much closer to HotSpot 6 than HotSpot 7. The remaining FE–HotSpot 6 offset is also visible in the sink-layer maxima; its cause remains open.

| Layer-maximum difference, K | HotSpot 6.0 | HotSpot 7.0 | Our FE | An outside team's FE |
|---|---|---|---|---|
| Layout A, spreader minus sink | 1.24 | 55.30 | 1.30 | 1.30 |
| CPU-DRAM, spreader minus sink | 3.25 | 141.84 | 4.20 | 4.21 |
| Layout A, chip minus sink | 4.86 | 59.08 | 4.50 | 4.50 |
| CPU-DRAM, chip minus sink | 15.83 | 154.24 | 15.39 | 15.41 |
| Layout A, sink maximum above air | 25.62 | 19.36 | 28.64 | 28.66 |
| CPU-DRAM, sink maximum above air | 58.24 | 41.29 | 65.43 | 65.44 |

Chip minus sink, both finite-element solves agree with HotSpot 6.0 within 0.44 K.

These maxima are located independently in each layer, so they are not the same-index column of the exploded stack (4.04 K and 141.77 K there). The finite-element team's spreader and sink maxima are 5.46 mm apart.

# Gate zero: what runs, what passes, and the wording fixed before the result.

**PASS** **75.48 C and 115.93 C** **Verified by the operator and independently re-derived from signed raw outputs by a second reviewer.**

- Run: 12 calls under a grant opened 23:41 UTC, from the merged build, one at a time, finished by 23:44. Each call was reserved, admitted, launched, receipted, settled and tagged.
- Replays byte-identical. At a 32 by 32 grid: 75.46 C and 115.28 C. Kept apart from the gate statistic: chiplet-centre means 75.475 C and 115.935 C, active-grid peaks 75.48 C and 119.07 C.
- Compute, for the validation container only: 23.0 CPU-seconds of 562 reserved (cap 600); the solver used 17.86. Not the cost of the build, the models or the project.
- Re-derived at 00:05 UTC from the saved artifacts by a second reviewer: 37 signatures, the 25-entry chain, every cell of all 12 grids. No solver was run for it.
- At each run's hottest cell, spreader-to-sink difference: 1.24 K (6.0) against 55.31 K (7.0) on layout A, 4.04 K against 141.77 K on layout B.

Version comparison on the same layouts and readout: version 7.0 gives 123.42 C and 232.67 C, 48 to 117 K above the paper.

- The older simulator version (6.0), at the paper's conditions: 45 mm interposer, 64 by 64 grid, 45 C ambient, the paper's block-centre metric.
- Each published layout gets one run plus a replay in a fresh process. Both must land within 1.0 K, and the replay's output must be byte-identical.
- Verdicts, most definitive first: FAIL, ERROR, INCOMPLETE, PASS. Anything missing or unsettled is INCOMPLETE, never PASS.
- Two more published points (75.47 C and 94.89 C) are deferred: no runs here, and they cannot pass or fail this gate.

Ma et al., TAP-2.5D, DATE 2021: Fig. 6(a) at 75.48 C and Fig. 5(a) at 115.94 C.

Gate-zero code: PR #56, merged as bba120dc at 2026-10-31 23:04 UTC (checked 2026-11-01 05:00 UTC).

## WORDING FIXED BEFORE THE RESULT, FOR ALL THREE OUTCOMES

**NOT RUN** The test hasn't run. What we have is a source reading, saved output and a simplified model: 75.34 and 115.83 C, from an agent that had read the hypothesis.

**PASS** Both landed within 1 K. That reproduces those published numbers. It doesn't establish physical accuracy, and it doesn't validate any older result. **this export**

**FAIL** It missed: [values]. Our explanation is incomplete, and the withdrawal stands.

# The correction mechanism, shown on a test fixture.


**Candidate**
A lab proposes a layout.

**Reproduction**
Re-run in a fresh process.


**Acceptance**
The gate accepts it.

**Withdrawal**
A measurement is withdrawn in a seeded-fault drill.

**Propagation**
Its dependents go stale; independently supported results stand.




Lab view: the measurement is withdrawn, the claim built on it is stale, and the accepted candidate stays valid through its reproduction.




Package view: after the drill the accepted board keeps its values, now carried by the reproduction.

> Test fixture: both views replay illustrative values, and no solver ran. It shows the designed mechanism. The real withdrawal in the timeline used a public notice and per-value labels.

# Where it stands: 0 of 8 deliverables fully accepted.

| | | |
|---|---|---|
| D00 | Proposed chiplet layout with exact coordinates and constraints | not fully accepted |
| D01 | Power scenarios and package assumptions | not fully accepted |
| D02 | Simulator inputs, versions and raw outputs | not fully accepted |
| D03 | Independent reproduction results | not fully accepted |
| D04 | Complete proposal, review, correction and acceptance history | not fully accepted |
| D05 | Comparison against conventional and agent baselines | not fully accepted |
| D06 | Trained worker checkpoint or adapter, with its evaluation | not fully accepted |
| D07 | Replayable visual demonstration | not fully accepted |

### Original scope remains open

41 tickets, 234 requirements, 8 deliverables. Fully accepted deliverables: 0.

origin time not recorded · as of 2026-10-31 17:54 UTC

### Scientific benefit

Not established.

origin time not recorded · as of 2026-10-31 15:05 UTC

### Still open

Physical validation, the held-out five-arm study, full command-line and agent-interface parity. New scientific runs are not released.

origin time not recorded · as of 2026-10-31 17:54 UTC

### Old headroom result

INCONCLUSIVE, kept as recorded; no rerun result is claimed.

origin time not recorded · as of 2026-10-31 17:54 UTC

# Our local workstation: what ran on 31 October, and for how long.

| | |
|---|---|
| Train a small adapter | 67.271 s |
| Evaluate it in a fresh container | 61.156 s |
| Serve it locally | 185.763 s |

- Runs on 31 October, 07:48 to 11:40 UTC. Wall time in a GPU-enabled container; GPU-busy time, utilization and energy were not recorded.
- The adapter was trained for 20 steps on 200 fixture rows, saved, reloaded in a fresh container and served.
- Exact fixture answers went from 0 of 20 to 20 of 20: 20 rows from 6 distinct source cases, all seen in training. That shows the pipeline works, not general learning.
- Wall time of automated runs is not human time saved.

# Pull requests behind this talk, with their state at the check time.

Repository: Sentinelayer-AIdenID/sentilab · checked 2026-11-01 05:00 UTC

| | | |
|---|---|---|
| #56 | Gate zero: the older simulator version behind the fixed test | merged as bba120dc at 2026-10-31 23:04 UTC |
| #73 | Gate zero: pin the operator's public key | merged as 1575556d at 2026-10-31 23:40 UTC |
| #57 | Reference layouts from the paper, plus the paper's wire router | merged as d298cb00 at 2026-10-31 18:04 UTC |
| #58 | Public notice: pre-correction temperatures withdrawn | merged as 568dd397 at 2026-10-31 16:27 UTC |
| #60 | Notice on the leaderboard and verify pages | merged as 551777a9 at 2026-10-31 17:59 UTC |
| #64 | Every temperature carries its own qualifier | merged as d2504625 at 2026-10-31 19:38 UTC |
| #61 | Test fix: a guard pattern held raw control bytes | merged as a5744f3a at 2026-10-31 16:48 UTC |
| #59 | Design: outside agents propose layouts | merged as 4f6ad0cb at 2026-10-31 17:53 UTC |
| #55 | Measured run profiles; refuse to start when calls cannot fit the cap | merged as 315bbff4 at 2026-10-31 15:38 UTC |
| #37 | Allocation controller for simulator runs in CI | merged as 224fa704 at 2026-10-31 17:09 UTC |
| #25 | Headroom study runner; its result is INCONCLUSIVE, kept as recorded | merged as deb24670 at 2026-10-31 12:05 UTC |

# The outside-team receipts, exactly, and what we do not count as evidence.

| | |
|---|---|
| CASE | Our public parameter sheet for the paper's two layouts (commit af66bcfc), posted at 22:22 UTC with our own numbers withheld. |
| REPRODUCTION | Delfie (delphisci team): both simulator versions built from source and run on that case: 75.48 C and 115.94 C in 6.0, 123.42 C and 232.67 C in 7.0; with the detailed 3-D mode off, both give 75.37 C and 115.29 C. As reported by them. |
| FINITE ELEMENT | An outside team (public repository, frozen report at commit c73d642b): second-order elements on the finest mesh, about 1.6 to 1.7 million unknowns: 78.060 C and 122.252 C, +2.58 K and +6.31 K over the paper. As reported by them. |
| EXPOSURE | The finite-element run is a separate implementation: its author declares no reading of peer values before freezing at 23:45 UTC. Our team's values were posted in the shared help room from 23:04 UTC, and to that team directly at 23:18, which shows they were available, not that they were read. The paper's targets were known. |
| CHECKED | A second reviewer verified the finite-element team's 48-file manifest and frozen hashes, and recomputed the values from saved results. Their mesh and field files are omitted, so this is a check of saved values. |
| LIMIT | A configured-model comparison, not silicon validation, with no certified 0.1 K error bound. Earlier the same team ran our closed-form slab test (commit 32f3ed1a). |

Not yet in the record: the finite-element team's slab run through our own evaluator. Named with their consent, on record in the help room: Delfie (delphisci team), ScienceClaw. The other 6 teams are not named here.

> Not counted as evidence: our help-room leaderboard. Our own host's model scores it, so it is not independent.

# Questions we may get, answered plainly.

### Why does it say unvalidated?

That tag is about approving the simulator setup in general. This saved simulation reproduced the paper's reference result within the 1-degree bar we set in advance. It's simulated, not silicon.

### Did you make a better chip?

Not a verified one yet. That's the open challenge.

### Which version is right?

We reproduced the published result and compared independent models. Nobody has measured this chip yet.

### Why more than one agent?

Later reviewers caught issues after earlier approvals. That's what our work record shows, not a controlled experiment.

### What happens with the special 3D mode off?

Both versions give the same answer, as reported by Delfie (delphisci team).