



Storage Management GUI (Poseidonos-GUI)

Samsung Poseidon

User Manual

Contents

1	Introduction	4
2	Poseidonos-GUI: Getting started.....	5
2.1	Accessing the Poseidonos-GUI	6
2.2	Poseidonos-GUI Dashboard.....	7
2.3	Poseidonos-GUI Storage Management	8
2.3.1	Array Management	9
2.3.2	Volume Management	14
2.4	Poseidonos-GUI User Management	23
2.5	Poseidonos-GUI Storage Management Start or Stop Operations.....	25
3	How to install Poseidonos-GUI	27
4	How to Uninstall Poseidonos-GUI	29

Overview

This document describes the POS Storage Management GUI (also called as Poseidonos-GUI). Poseidonos-GUI enables a user to perform the following functions:

- Dashboard
- Array management
- Volume management
- System resource availability
- User management
- System status

This document covers the following topics:

- Introduction
- Getting started with Poseidonos-GUI
- Array and volume configuration
- User management
- POS start and stop operations

1 Introduction

POS Storage Management GUI aka Poseidonos-GUI enables an easy way to administer POS storage system.

The major objectives of Poseidonos-GUI are:

- **Availability:** Poseidonos-GUI is available from various devices, platforms and systems.
- **Speed:** Poseidonos-GUI provides data with highest performance so that users have access to important data at right times.
- **Simplicity:** A simple and intuitive design to help productivity and overall cost.
- **Commonality:** Commonly used graphics, widgets and terminology enable easy integration with existing systems and onboarding the users quickly.

With these deliverables in mind, a System Administrator can use the Poseidonos-GUI to configure and prepare the storage system for the user workloads quickly after completing the setup. Then the System Administrator can manage the system with minimal knowledge.

Array and volume storage configuration and management is streamlined in Poseidonos-GUI. User management is simplified.

2 Poseidonos-GUI: Getting started

This section describes how to accomplish the following tasks:

- Accessing the Poseidonos-GUI
- Managing and monitoring the POS system (e.g. array or volume management)
- User management

2.1 Accessing the Poseidonos-GUI

The Poseidonos-GUI can be accessed using Firefox Mozilla and Google Chrome browser.

The Poseidonos-GUI supports the use of a single point of authentication function for the GUI through a centralized data in a lightweight database.

Poseidonos-GUI is accessible from the browser as shown in Figure1




Figure 1. Poseidonos-GUI URL

On the first page for Poseidonos-GUI, user needs to log on as an administrator.

1. Poseidonos-GUI URL: <http://<Poseidonos-GUI ip>>

Note: Poseidonos-GUI URL may come pre-installed and typically the IP address of the server that the Poseidonos-GUI software is installed on

2. On a new system, users can use the following default credentials:

- User = admin
- Password = admin

After initial login, user can add additional users using admin privileges

Note: Poseidonos-GUI supports "admin" role only at this time.




Figure 2. Poseidonos-GUI login page

2.2 Poseidonos-GUI Dashboard

Dashboard provides user an overview of the Poseidon Storage. It has three sections,

- Performance overview
- Storage Details
- Storage Summary

In addition, it also has links to few admin tasks such as storage management functions, etc. It also shows the current working status of the storage management system and the last time the status is updated.

1. **Performance Overview** shows health metrics and the basic performance details such as Latency, Bandwidth and Throughput of the storage management box.
2. **Last-Updated** shows when the last status was retrieved.
3. **Status Label** shows whether the storage management is available or not.
4. Host IP, MAC address and name.
5. **Storage Details** shows the space utilization.

6. **Array Summary** provides the array level information in the storage management box.
7. **Volume Summary** provides the volume level information in the storage management box.




Figure 3. Poseidonos-GUI dashboard page

2.3 Poseidonos-GUI Storage Management

The Storage Management page allows user to create an array and volumes, view existing array and volumes and manage existing arrays and volumes.

1. User can create one or more arrays based on the types of disks selected in the slots .i.e. Storage, Spare and Write Buffer Disks.
2. User can create a single or multiple volumes at a time by specifying the volume name, volume size, volume count and description.
3. User can view the volume information including volume name, volume size, used size, IP, description and status in a tabular format.
4. User can view the existing space for volume creation process.




Figure 4. Poseidonos-GUI storage management page

2.3.1 Array Management

Array management option allows user to create and manage one or more arrays.

Create Array

Follow the steps below to create sample array creation process:

1. **Array Name** - Select a name for the array (e.g. name = array_1; Max length = 63 characters)
2. **Fault Tolerance Level** – Select from the dropdown

Note: Currently “RAID-5” is the only one supported.

3. **Disk Type** - Select storage disks from the dropdown list. The 2 options for disk type are (Minimum Storage Disks = 3; Maximum Storage Disks = 32; Minimum Spare Disks = 0; Maximum Spare Disks = 29)
 - Storage Disk
 - Spare Disk
4. **Write Buffer Path** – Select from the dropdown list.
5. User can view the available disks.

The max number of allowable disks is 32.

6. User can view the color codes for various types of disk supported by Poseidonos-GUI. User can view additional details - name, size- by hovering over disk number
7. User can view the **NUMA** value of the disks.
8. Click **Create Array** button




Figure 5. Poseidonos-GUI Array Management

Follow the steps below to create sample array creation process:

1. Selected storage disk is shown in green
2. Select spare disk is shown in blue
3. Additional details of the disk can be seen when hovering on the colored bar

4. Click on the “Create Array” to create an array

Storage Management

CREATE

MANAGE

Array Name

Array_One

Fault tolerance Level

RAID5

Disk Type

STORAGE DISK

Write Buffer Path

uram0

0

1

0

2

0

3

0

4

0

5

0

6

0

7

0

8

0

9

0

10

0

11

0

12

1

13

1

14

1

15

1

16

1

17

1

18

1

19

1

20

1

21

1

22

1

23

1

24

25

26

27

28

29

30

31

32

Selected Storage Disk

Selected Spare Disk

Not Selected

Used Disk

Empty Slot

NUMA

Create Array

Figure 6. Poseidonos-GUI Array creation steps

A confirmation message, **"Array Created Successfully"** displayed.

Storage Management

CREATE **MANAGE**

Select Array
Array_One

Fault tolerance Level
RAID 5

Status: Mounted

Write Buffer Path
uram0

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23				
			REMOVE SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK	ADD SPARE DISK

Storage disk
Spare disk
Used by Another Array
Not Selected
Empty Slot
NUMA

UNMOUNT ARRAY DELETE ARRAY

Figure 7. Poseidonos-GUI shows array details after successful array creation

Manage Array

After successful array creation, user has the option to either **delete** or **unmount** an array through the manage section.




Figure 8. Poseidonos-GUI successful array creation and ability to unmount and delete

2.3.1.1 Delete Array

Follow the steps below to delete array:

1. Click **Delete Array** button
2. A confirmation message is displayed, click **Yes** button to confirm the delete operation




Figure 9. Poseidonos-GUI array deletion confirmation

A confirmation message, **“Array Deleted Successfully”** displayed.




Figure 10. Poseidonos-GUI successful array deletion confirmation

2.3.1.2 Unmount Array

Follow the steps below to unmount array:

1. Click “**Unmount Array**” button
2. By hovering over the “**Unmount Array**” button, the additional info is displayed




Figure 11. Poseidonos-GUI unmount array operation

A confirmation message, “**Array Unmounted Successfully**” displayed.




Figure 12. Poseidonos-GUI successful array unmount confirmation

2.3.2 Volume Management

Volume management option allows user to create and manage one volume or multiple volumes.

Follow the steps below to Manage Volume:

1. User can choose to create one volume or multiple volume. User can enter the number of volume he or she wishes to create.
2. User can enter the volume name (max length of the name is 255). When user tries to create multiple volumes, then user can enter the suffix value to append to the multiple volumes that need to be created.
3. User can choose a number suffix value. For example, if user chooses to create 5 volumes with a volume name as “*volume_company*” and numeric suffix value of 0, then volumes with the following names would be created.
 - Volume_company0
 - Volume_company1 and so on to ...
 - volume_company4
4. User can choose the max volume size (i.e. enter 0) or a predefined value.
5. User can choose the max IOPS value (i.e. enter 0) or a predefined value.
6. User can choose the max bandwidth size (i.e. enter 0) or a predefined value.
7. User can choose to mount the volume or leave it unmounted.

8. User can stop the volume creation process when an error occurs.

The screenshot displays the 'Array_One' management interface. At the top, the status is 'Mounted' with a green arrow pointing to it. Below this is a disk layout grid with 27 slots. Slots 1-4 are yellow (Storage disk), slot 4 is also labeled 'REMOVE SPARE DISK', slots 5-15 are brown (Used by Another Array), slots 16-24 are blue (Spare disk), and slots 25-27 are grey (Empty Slot). A legend at the bottom identifies these colors. The 'Create Volume' section (labeled 1) shows 'Volume Count' as 1, 'Mount Volume' checked, 'Volume Name' as 'vol', 'Volume Size' as 0 GB, and 'Maximum Bandwidth (MB/s)' as 0. It also has fields for 'Suffix Start Value' (0) and 'Maximum IOPS (KIOPS)' (0). A 'CREATE VOLUME' button (labeled 3) is at the bottom. The 'Volume Statistics' section (labeled 2) shows 'Number of volumes: 0' and a bar chart with 'Used Space : 0 Bytes' (blue) and 'Available for Volume Creation : 3.39 TB' (green). Buttons for 'UNMOUNT ARRAY' and 'DELETE ARRAY' are on the right.

Figure 13. Poseidonos-GUI create volume from Array Manage Page

Below is a screen showing the volume creation step for 5 volumes.

The screenshot shows a web form titled "Create Volume". It contains several input fields and checkboxes. The "Volume Count" field is set to 5. The "Mount Volume" checkbox is checked. A note states: "For Volume Count > 1, please provide a seed in the Suffix Start Value field (e.g. 0,1)". The "Volume Name" field contains "volume_company". The "Volume Size" field is set to 10 GB. The "Maximum Bandwidth (MB/s)" field is set to 0. The "Suffix Start Value" field is set to 0. The "Maximum IOPS (KIOPS)" field is set to 0. The "Stop Multi-Volume Creation on Error" checkbox is unchecked. A "CREATE VOLUME" button is at the bottom left.

Create Volume

Volume Count *

5

☒ Mount Volume

For Volume Count > 1, please provide a seed in the Suffix Start Value field (e.g. 0,1)

Volume Name *

volume_company

Volume Size *

10 GB

Maximum Bandwidth (MB/s) *

0

Suffix Start Value

0

Maximum IOPS (KIOPS) *

0

☐ Stop Multi-Volume Creation on Error

CREATE VOLUME

Figure 14. Poseidonos-GUI sample volume create steps

A user can hit the “CREATE VOLUME” button for Poseidonos-GUI to create the required volumes. Poseidonos-GUI may take a few seconds depending on how many volumes are selected for creation.

Figure 15. Poseidonos-GUI volume creation intermediate step waiting for processing

Below is a screen showing the volume information for the newly created volumes.

1. User can search for specific volumes by using search terms for size, name, etc.
2. User can select all volumes to delete them.

Note: Multi volume edit is not supported at this time.

3. User can select a specific volume to either delete it or edit it.
4. User can mount or unmount a volume
5. User has option to either mount or unmount the volume by toggling the button.
6. User can select edit option for a specific volume
7. User can view the total number of volumes in the system

Volume List 1 <input type="text" value="Search"/>							
<input type="checkbox"/>	Name	Total Size	Used Size	Max IOPS (KIOPS)	Max Bandwidth (MB/s)	Mount Status	Update
<input type="checkbox"/>	volume_company4	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>	4
<input type="checkbox"/>	volume_company3	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>	5
<input type="checkbox"/>	volume_company2	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	volume_company1	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	volume_company0	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>	
6 5 rows <input type="button" value="5 rows"/> < < 1-5 of 5 > >							

Figure 16. Poseidonos-GUI volume information

Below is a screen showing *search function* for volume data.

<input type="checkbox"/>	Name	Total Size	Used Size	Max IOPS (KIOPS)	Max Bandwidth (MB/s)	Mount Status	Update
<input type="checkbox"/>	volume_company2	10 GB	0 Bytes	MAX	MAX		

Figure 17. Poseidonos-GUI search volume information by keywords

Below is a screen showing delete function for all volumes.

1. User can select the checkbox to select all volumes
2. User can click on the delete icon to perform delete operation on all volumes

<input checked="" type="checkbox"/>	Name	Total Size	Used Size	Max IOPS (KIOPS)	Max Bandwidth (MB/s)	Mount Status	Update
<input checked="" type="checkbox"/>	volume_company4	10 GB	0 Bytes	MAX	MAX		
<input checked="" type="checkbox"/>	volume_company3	10 GB	0 Bytes	MAX	MAX		
<input checked="" type="checkbox"/>	volume_company2	10 GB	0 Bytes	MAX	MAX		
<input checked="" type="checkbox"/>	volume_company1	10 GB	0 Bytes	MAX	MAX		
<input checked="" type="checkbox"/>	volume_company0	10 GB	0 Bytes	MAX	MAX		

Figure 18. Poseidonos-GUI delete all volumes

Below is a screen that shows delete function for one or many volumes.

1. User is notified whether one, many or all volumes are selected
2. User can select the checkbox to select one or many volumes
3. User can click on the delete icon to perform delete operation on the selected volumes

Volume List							3
Search							
1	Name	Total Size	Used Size	Max IOPS (KIOPS)	Max Bandwidth (MB/s)	Mount Status	Update
2	<input checked="" type="checkbox"/> volume_company4	10 GB	0 Bytes	MAX	MAX		
	<input type="checkbox"/> volume_company3	10 GB	0 Bytes	MAX	MAX		
	<input type="checkbox"/> volume_company2	10 GB	0 Bytes	MAX	MAX		
	<input type="checkbox"/> volume_company1	10 GB	0 Bytes	MAX	MAX		
	<input type="checkbox"/> volume_company0	10 GB	0 Bytes	MAX	MAX		
5 rows < < 1-5 of 5 > >							

Figure 19. Poseidonos-GUI delete one or more volumes

The screen below shows confirmation of the unmount operation.




Figure 20. Poseidonos-GUI unmount volume confirmation

The screen below shows unmount or mount operation on a given volume.

1. User is notified whether volume is mounted or unmounted
2. User can view the mount status of the volume




Figure 21. Poseidonos-GUI successful unmount operation confirmation

The screen below shows update function for a given volume.

1. User can update the name of the volume
2. User can update the IOPS value
3. User can update the bandwidth value
4. User can click on the “OK” or “Cancel” button to update or cancel the changes

Volume List							Search	×
<input type="checkbox"/>	Name	Total Size	Used Size	Max IOPS (KIOPS)	Max Bandwidth (MB/s)	Mount Status	Update	
<input type="checkbox"/>	volume_company4 1	10 GB	0 Bytes	0 2	200 3	<input type="checkbox"/>	✓ 4	✕
<input type="checkbox"/>	volume_company3	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>		
<input type="checkbox"/>	volume_company2	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>		
<input type="checkbox"/>	volume_company1	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>		
<input type="checkbox"/>	volume_company0	10 GB	0 Bytes	MAX	MAX	<input checked="" type="checkbox"/>		
5 rows < < 1-5 of 5 > >								

Figure 22. Poseidonos-GUI update volume information

Screen below shows update operation on a given volume.

1. User is notified whether volume is updated successfully
2. User can view the updated data of the volume




Figure 23. Poseidonos-GUI update volume information confirmation

2.4 Poseidonos-GUI User Management

The user management page allows admins to add a new user and modify Username, Email Id, Mobile Number fields of an existing user.

2.4.1.1 New User

User Addition requires six fields i.e. Username, Role, Password, Confirm password, Mobile Number and Email ID.

Follow the steps below to add a new user:

1. User can add a new user by providing
 - User name
 - Password
 - Phone
2. User can choose the default role "Admin"
3. User can save changes by clicking on "**Submit**" button

Figure 24. Poseidonos-GUI add new user information

2.4.1.2 Delete User

User Deletion allows the admins to delete the entire user(s) details.

Note: If a user record is deleted by the admin, the user would not be able to login to the management portal.

1. Admins can view or update existing users and their information.
2. Admins can use **Add New User** functionality to re-add the user.

Figure 25. Poseidonos-GUI user management page

2.4.1.3 Modify User

User Modification allows the admins to modify Username, Active Status, Email Id, Mobile Number fields of an existing user.

Note: If a user's active status is disabled by the admin, then the user would not be able to login till the status is reverted to active state by the admin

Follow the steps below to update a given user information:

1. User can update the phone
2. User can update an email
3. User can either save changes or discard them




Figure 26. Poseidonos-GUI update user information

2.5 Poseidonos-GUI Storage Management Start or Stop Operations

This page allows users to start or stop the Storage Management system. This will provide the real time status of the system. This feature is available for admin users only.

This page enables users to:

1. View the current status of the storage management system
2. Either start or stop the storage management system based on current status
3. View the response of the operation on the storage management system




Figure 27. Poseidonos-GUI start and stop operation page

3 How to install Poseidonos-GUI

Follow the steps below to set up and run the Poseidonos-GUI (the scripts shown below are available in the root directory)

Prerequisites

1. python3
2. go v1.14+
3. nodejs 14.x
4. InfluxDB (1.8.x)

Supported OS and Version

1. Linux Ubuntu 18.04

Download and Install dependencies

1. Clone the project from GitHub - <https://github.com/poseidonos/poseidonos-gui.git>
2. Navigate to poseidonos-gui directory
3. Run scripts as described below to install and run the application
4. Access the application in the browser (e.g. `http://<local_ip_addr>`)

1. `git clone https://github.com/poseidonos/poseidonos-gui.git`
2. `cd poseidonos-gui`
3. `./script/install_all.sh`
4. `./script/build_all.sh`
5. `./script/run_all.sh`

1. Install Packages

These packages are required for proper working of the Poseidonos-GUI. This will install required packages such as influxdb, chronograf, kapacitor on the host.

```
./script/install_all.sh
```

2. Build the application

```
./script/build_all.sh
```

3. Run application

To run various applications, use this command below.

```
./script/run_all.sh
```

3. Access the Poseidonos-GUI application via browser

The server will run on the local web server and will be accessible from the browser

```
http://<ip_address>
```

4 How to Uninstall Poseidonos-GUI

Follow the steps below to uninstall the Poseidonos-GUI (the scripts shown below are available in the root directory)

1. Uninstall services and applications running

```
./script/uninstall.sh
```