

Variety Digital Matrix

VDM - Series

CT104-U/CR104-U

CT104-U와 CR104-U는 4K 해상도의 HDMI 신호와 RS-232 신호를 CAT5e/CAT6(UTP/STP)를 통해 장거리 전송하기 위한 송신기와 수신기입니다. CT104-U는 HDMI신호 그리고 RS-232 신호를 CAT5e/CAT6(UTP/STP) 신호로 변환하고 CR104-U는 CAT5e/CAT6 (UTP/STP) 신호를 다시 HDMI신호 그리고 RS-232 신호로 복원합니다.

HDBaseT 기술을 적용, 하나의 CATx 케이블을 이용하여 최대 100m까지 전송이 가능합니다.



제품사양

CT104-U	
Input Signal	HDMI + RS-232
Output Signal	HDBaseT 0,1,2,3+/-
Data Transmission Speed	3.4 Gbps/ch, Total 10.2 Gbps Max
Supporting Display Resolutions	Up to Ultra HD 4K 4096 x 2160 @24/25/30Hz (RGB 4:4:4, YCbCr 4:4:4, 4:2:2, 4:2:0)
Max Distance	1920 x 1200 @ 60Hz or at 1080p : 4Kx2K@ 30Hz : 330 ft (100m : BELDEN CI 6522)
Conformations	HDMI 1.4, HDBaseT
HDCP Compliance	HDCP 1.X
EDID Interface	Pass-Through
Power Rating	DC +12V 2A
Dimension	4.4' x 2.8' x 1.0' (112 x 72 x 26 mm)
Weight	0.57 lbs (0.26 Kg)



제품사양

CR104-U	
Input Signal	HDBaseT 0,1,2,3+/-
Output Signal	HDMI + RS-232
Data Transmission Speed	3.4 Gbps/ch, Total 10.2 Gbps Max
Supporting Display Resolutions	Up to Ultra HD 4K 4096 x 2160 @24/25/30Hz (RGB 4:4:4, YCbCr 4:4:4, 4:2:2, 4:2:0)
Max Distance	1920 x 1200 @ 60Hz or at 1080p : 4Kx2K@ 30Hz : 330 ft (100m : BELDEN CI 6522)
Conformations	HDMI 1.4, HDBaseT
HDCP Compliance	HDCP 1.X
EDID Interface	Pass-Through
Power Rating	DC +12V 2A
Dimension	4.4' x 2.8' x 1.0' (112 x 72 x 26 mm)
Weight	0.59 lbs (0.27Kg)