

Variety Digital Matrix

VDM - Series (Extender)

FT103-U-H/FR103-U

FT103-U-H과 FR103-U는 비디오와 오디오 그리고 RS-232 신호를 광케이블을 통해 장거리 전송하기 위한 벽부형 송신기와 수신기입니다. FT103-U-H는 비디오와 오디오 그리고 RS-232 신호를 광신호로 변환하고 FR103-U는 광신호를 다시 비디오와 오디오 그리고 RS-232 신호로 복원합니다. FT103-U-H는 디지털 신호인 DVI 혹은 HDMI를 지원합니다. FR103-U는 디지털 신호인 DVI 혹은 HDMI를 지원합니다. 광신호를 사용하여 최대 2km까지 전송할 수 있으며 외부신호의 영향으로부터 안전하게 신호를 전송할 수 있어서 보안을 요하는 기업이나 군부대 그리고 정부기관 등에 적합한 전송장비입니다.



제품사양

FT103-U-H	
Input Signal	DVI / HDMI (TMDS), 3.5mm Stereo Audio
Output Signal	Fiber Optical Output (> -10dbm (after 6,600ft (2km) transmission))
Data Transmission Speed	3.4 Gbps/ch, Total 10.2 Gbps Max
Supporting Display Resolutions	PC: VGA ~ WUXGA (up to 1920 x 1200 @60Hz) HDTV: 480i ~ 1080p
Max Distance	Single Mode Fiber: 1920 x 1200 @ 60Hz or at 1080p : 6,600 ft (2km) Multi Mode Fiber: 1920 x 1200 @ 60Hz or at 1080p : 1,650 ft (500m)
Conformations	DVI 1.0 , HDMI 1.4
HDCP Compliance	HDCP 1.X
Power Rating	DC +12V 2A
Dimension	3.6' x 4.24' x 2.24' (91.44 x 107.95 x 57.15mm)
Weight	0.82 lbs (0.37 Kg)



제품사양

FR103-U	
Input Signal	Fiber Optical Output (> -10dbm (after 6,600ft (2km) transmission))
Output Signal	DVI / HDMI (TMDS), 3.5mm stereo audio
Data Transmission Speed	3.4 Gbps/ch, Total 10.2 Gbps Max
Supporting Display Resolutions	PC: VGA ~ WUXGA (up to 1920 x 1200 @60Hz) HDTV: 480i ~ 1080p
Max Distance	Single Mode Fiber: 1920 x 1200 @ 60Hz or at 1080p : 6,600 ft (2km) Multi Mode Fiber: 1920 x 1200 @ 60Hz or at 1080p : 1,650 ft (500m)
Conformations	DVI 1.0, HDMI 1.4
HDCP Compliance	HDCP 1.X
Power Rating	DC +12V 2A
Dimension	3.6' x 4.24' x 2.24' (91.44 x 107.95 x 57.15mm)
Weight	0.82 lbs (0.37 Kg)