CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the October/November 2015 series

9702 PHYSICS

9702/21 Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2015 series for most Cambridge IGCSE®, Cambridge International A and AS Level components and some Cambridge O Level components.

CAMBRIDGE
International Examinations

1	**(a)** temperature	B1	
	current	B1	[2]
	(allow amount of substance, luminous intensity)		
	(b) (i) 1. E = (stress / strain =) [force / area] / [extension / original length]		
	units of stress: kg m s^{-2} / m^2 and no units for strain	B1	
	units of E: kg m^{-1} s^{-2}	A0	[1]
	2. units for T: s, l: m and M: kg		
	$K^2 = T^2 E / M l^3$ hence units: s^2 kg m^{-1} s^{-2} / kg^3 (= m^{-4})	C1	
	units of K: m^{-2}	A1	[2]
	(ii) % uncertainty in E = 4% (for T^2) + 0.6% (for l^3) + 0.1% (for M) + 3% (for K^2) = 7.7%	B1	
	$E = [(1.48 \times 10^5)^2 \times 0.2068 \times (0.892)^3] / (0.45)^2 = 1.588 \times 10^{10}$	C1	
	7.7% of $E = 1.22 \times 10^9$	C1	
	$E = (1.6 \pm 0.1) \times 10^{10}$ kg m^{-1} s^{-2}	A1	[4]
2	**(a)** ps = 10^{-12} (s) **or** $T = 4 \times 50 \times 10^{-12}$ (s)	B1	
	$v = f\lambda$ **or** $v = \lambda / T$	C1	
	$\lambda = 3.0 \times 10^8 \times 4 \times 50 \times 10^{-12}$	C1	
	= 0.06(0) m	A1	[4]
	(b) 1500 = $3.0 \times 10^8 \times 4 \times$ time-base setting **or** $T = 5 \times 10^{-6}$ s	C1	
	time-base setting = 1.3 (1.25) μs cm^{-1}	A1	[2]
3	**(a)** work done is force × distance moved in direction of force **or** no work done along PQ as no displacement/distance moved in direction of force	B1	
	work done is same in vertical direction as same distance moved in direction of force	B1	[2]

(b) (i)	at maximum height $t = 1.5$ (s) **or** $s = ½(u + v)t$, $s = 11$ m and $t = 1.5$ s	C1	
	$V_v = 0 + 9.81 \times 1.5$ $\qquad V_v = (11 \times 2) / 1.5$		
	$= 15$ (14.7) m s^{-1}	A1	[2]
(ii)	straight line from (0,0) to (3.00, 25.5)	B1	[1]
(iii)	at maximum height $V_h = 25.5/3$ (= 8.5 m s^{-1})	B1	
	ratio $= mgh / ½mv^2$	C1	
	$= (2 \times 9.81 \times 11.0)/(8.5)^2$		
	$= 3.0$ (2.99)	A1	[3]
(iv)	deceleration is greater/resultant force (weight and friction force) is greater	M1	
	time is less	A1	[2]
4 (a)	density = mass / volume	C1	
	mass = $7900 \times 4.5 \times 24 \times 10^{-6} = 0.85$ (0.853) kg	M1	[2]
(b)	pressure = force / area	C1	
	force = $W \cos 40°$	C1	
	pressure $= (0.85 \times 9.81 \cos 40°) / 24 \times 10^{-4}$		
	$= 2.7$ (2.66) $\times 10^3$ Pa	A1	[3]
(c)	$F = ma$	C1	
	$W \sin 40° - f = ma$	C1	
	$0.85 \times 9.81 \times \sin 40° - f = 0.85 \times 3.8$		
	f (= 5.36 – 3.23) = 2.1 N [5.38 – 3.242 if 0.8532 kg is used for the mass]	A1	[3]

5	**(a)**		progressive: all particles have same amplitude stationary: no nodes or antinodes or maximum to minimum/zero amplitude	B1	
			progressive: adjacent particles are not in phase stationary: waves particles are in phase (between adjacent nodes)	B1	[2]
	(b)	**(i)**	wavelength 1.2 m (zero displacement at 0.0, 0.60 m, 1.2 m, 1.8 m, 2.4 m)		
			either peaks at 0.30 m and 1.5 m and troughs at 0.90 m and 2.1 m or vice versa (but not both)	B1	
			maximum amplitude 5.0 mm	B1	[2]
		(ii)	180° or π rad	A1	[1]
		(iii)	at $t = 0$ particle has kinetic energy as particle is moving	B1	
			at $t = 5.0$ ms no kinetic energy as particle is stationary so decrease in kinetic energy (between $t = 0$ and $t = 5.0$ ms)	B1	[2]
6	**(a)**		energy converted from chemical to electrical per unit charge	B1	[1]
	(b)	**(i)**	current $= E/(R + r)$	C1	
			$= 6.0/(16 + 0.5)$ $= 0.36$ (0.364) A	A1	[2]
		(ii)	terminal p.d. = $(0.36 \times 16) = 5.8$ V **or** $(6 – 0.36 \times 0.5)$ $= 5.8$ V	A1	[1]
	(c)	**(i)**	use of $R = \rho l/A$ or proportionality with length and inverse proportionality with area or d^2	C1	
			$d/2$ and $l/2$ gives resistance of Z = $2R_Y = 24$ (Ω)	C1	
			R = resistance of parallel combination = $[1/24 + 1/12]^{-1}$ $= 8(.0)$ (Ω)	A1	[3]
		(ii)	resistance of circuit less therefore current larger	B1	
			lost volts greater therefore terminal p.d. less	B1	[2]
	(d)		power = I^2R **or** VI **or** V^2/R	C1	
			current in second circuit (= 6.0 / 12.5) = 0.48 (A)	B1	
			ratio = $[(0.36)^2 \times 16] / [(0.48)^2 \times 12] = 0.75$ [0.77 if full s.f. used]	B1	[3]

7 **(a)** **(i)** curved path towards negative (–) plate (right-hand side) B1 [1]

(ii) range of α-particle is only few cm in air/loss of energy of the α-particles due to collision with air molecules/ionisation of the air molecules B1 [1]

(iii) $V = E \times d$ C1

$= 140 \times 10^6 \times 12 \times 10^{-3} = 1.7\ (1.68)$ MV A1 [2]

(b) β have opposite charge to α therefore deflection in opposite direction B1

β has a range of velocities/energies hence number of different deflections B1

β have less mass or q / m is larger hence deflection is greater
or
β with (very) high speed (may) have less deflection B1 [3]

(c)

emitted particle	change in Z	change in A
α-particle	–2	–4
β-particle	+1	0

A1 [1]