

## Exercise 2:

### Contents

- question
- Answer

### question



## Day 3, Exercise # 2: RL



A bee is foraging among two flowers (yellow and blue) in search of nectar. The amount of nectar for each flower is stochastic, following normal distribution, blue with mean 1 and yellow with mean 0.5, both with 0.25 standard deviation.

The model bee has a stochastic policy, which means that it chooses blue and yellow flowers with probabilities that we write as  $P[b]$  and  $P[y]$  respectively. A convenient way to parameterize these probabilities is to use the softmax distribution:

$$P[b] = \frac{\exp(\beta m_b)}{\exp(\beta m_b) + \exp(\beta m_y)} \quad P[y] = \frac{\exp(\beta m_y)}{\exp(\beta m_b) + \exp(\beta m_y)}$$

If the bee chooses a blue flower on a trial and receives nectar volume  $r_b$ , it should update the action value  $m_b$  according to the prediction error by  $m_b \rightarrow m_b + \varepsilon \delta$  with  $\delta = r_b - m_b$ , and leave  $m_y$  unchanged. If it lands on a yellow flower,  $m_y$  is changed to  $m_y \rightarrow m_y + \varepsilon \delta$  with  $\delta = r_y - m_y$ , and  $m_b$  is unchanged.

Simulate this model bee for 100 number of actions.

- Draw the reward distribution for each flower using MATLAB "hist" function for 1000 samples to compare their average rewards.
- Use  $\beta = 1$  and  $\varepsilon = 0.1$ , and draw the cumulative visits to yellow and blue flowers versus history of actions.
- Draw the action values ( $m_y, m_b$ ) versus history of actions.
- Change the parameter  $\beta$  to 0.1 and then 10. What do you observe?

### Answer

```
clc
clear
close all

N_samples = 1000;
Reward_y = normrnd(0.5, 0.25, 1, N_samples);
Reward_b = normrnd(1, 0.25, 1, N_samples);

N_actions = 100;

beta = 1; %this is a trade-off between exploration and exploitation (something like a learning rate!)
% very large beta values may lead to the wrong decision (choosing yellow)
epsilon = 0.1;

my_exp = zeros(1,N_actions);
mb_exp = zeros(1,N_actions);
ch = zeros(1,N_actions);

ch(1) = round(rand);
for i = 1:N_actions-1

    if ch(i) == 0
        my_exp(i+1) = my_exp(i) + epsilon * (Reward_y(i) - my_exp(i));
        mb_exp(i+1) = mb_exp(i);
    elseif ch(i) == 1
        mb_exp(i+1) = mb_exp(i) + epsilon * (Reward_b(i) - mb_exp(i));
        my_exp(i+1) = my_exp(i);
    end

    P_dens = exp(beta*my_exp(i+1)) + exp(beta*mb_exp(i+1));
    py = exp(beta * my_exp(i+1)) / P_dens;
    pb = exp(beta * mb_exp(i+1)) / P_dens;

    xy = py * rand(1);
```

```

xb = pb * rand(1);
if xy > xb
    ch(i+1) = 0;
elseif xb > xy
    ch(i+1) = 1;
end

end

% - plotting

bins = -2:0.1:3;

figure
subplot(2,2,1); hold on
hist(Reward_y, bins)
xlabel('Reward value (Yellow)')
ylabel('Probability')

subplot(2,2,2); hold on
hist(Reward_b, bins)
xlabel('Reward value (Blue)')
ylabel('Probability')

subplot(2,2,3); hold on
plot(cumsum(ch==0), 'LineWidth',2, 'Color','y')
plot(cumsum(ch==1), 'LineWidth',2, 'Color','b')
xlabel('Action history')
ylabel('Sum action')

subplot(2,2,4); hold on
plot(my_exp, 'LineWidth',2, 'color', 'y')
plot(mb_exp, 'LineWidth',2, 'color', 'b')
xlabel('Action history')
ylabel('Expected reward')

```

