## ELEN4011: Design II

---

## Design of a robust codec for a fading channel.

---

Author
Elias Sepuru - 1427726

Supervisor
Prof. Fambirai Takawira

School of Electrical and Information Engineering, University of the Witwatersrand, Johannesburg 2050, South Africa

25 October 2019

**Abstract**

# Contents

# 1 Introduction

The aim of modern and next-generation wireless communication systems is to provide communication services with high data rates and low probability of error, this also helps in catering for numerous requests from various applications and devices [1, 2, 3]. The reliability of such communication systems is often hindered by strong shadowing, intersymbol interference (ISI) and attenuation due to the destructive addition of multipaths propagation in the transmission channel [1, 4]. Such a channel is often accurately modeled using a Rayleigh model known as the Rayleigh Fading Channel (RFC) [4]. To combat the effect of fading and scattering due to RFC, several methods have been proposed. Methods such as Selection Diversity, Equal Gain Combining and Maximal Ratio Combining were proposed. However the methods proved to be inefficient and ineffective in dealing with the requirement of high data rates as per modern communication needs [5]. This lead to the development of Multiple-Input Multiple-Output (MIMO) systems. MIMO leverages off the multipath characteristic of the Rayleigh Fading Channel. It transmits data over the multiple paths, therefore increasing the amount of information the communication system carries [6]. MIMO uses multiple transmit and receive antennas to significantly increase the data throughput and link range without additional bandwidth or transmit power [7]. However MIMO cannot achieve all this without robust Forward Error Correction (FEC) and modem schemes.

This paper presents the design of a robust codec for a fading channel. The codec is to operate at a rate of at least 2 bits/Hz over a Raleigh Fading Channel. The design of the codec focuses mainly on FEC, modulation and MIMO. The codec input data input is expected to be at 10 Mbps. The design assumes that the data stream has already been converted from analog to digital, hence source encoding is neglected. Encryption is also left out as it does not affect the Bit Error Rate (BER) and spectral efficiency. The below sections present the mathematical description of the designed codec together with testing, results and analysis. All simulations and computations are carried out in MATLAB.

# References

[1] A. S. Behbahani, R. Merched, and A. M. Eltawil. "Optimizations of a MIMO relay network." *IEEE Transactions on Signal Processing*, vol. 56, no. 10, pp. 5062–5073, 2008.

[2] A. M. Alsahlany, M. J. Alhasan, and Q. Jalil. "Performance Investigation of Interleaving and BCH code in MIMO System." *International Journal of Innovative Research in Science, Engineering and Technology*, vol. 7, no. 6, pp. 6883–6891, 2018.

[3] S. S. Sarnin, N. F. Nairn, and W. N. S. W. Muhamad. "Performance evaluation of phase shift keying modulation technique using BCH code, Cyclic code and Hamming code through AWGN channel model in communication system." In *The 3rd International Conference on Information Sciences and Interaction Sciences*, pp. 60–65. IEEE, 2010.

[4] V. Tarokh, H. Jafarkhani, and A. R. Calderbank. "Space-time block coding for wireless communications: performance results." *IEEE Journal on selected areas in communications*, vol. 17, no. 3, pp. 451–460, 1999.

[5] B. Kumbhani and R. S. Kshetrimayum. *MIMO wireless communications over generalized fading channels*. CRC Press, 2017.

[6] G. Lawton. "Is MIMO the future of wireless communications?" *computer*, vol. 37, no. 7, pp. 20–22, 2004.

[7] D. Tse and P. Viswanath. *Fundamentals of wireless communication*. Cambridge university press, 2005.