

NetworkParser config.json Reference

NetworkParserConfig arguments and defaults (240 fields)

Usage: place only the settings you want to override in a JSON file and pass it with `--config <file.json>`. JSON uses true/false/null; tuple-like defaults are shown as JSON-style lists for readability. Deprecated/legacy aliases are retained because they are present in NetworkParserConfig.

1) Input / Output behavior

Argument	Type	Default	Short description
include_intermediate_files	bool	true	Write intermediate processing files.
generic_name	str	"matrix"	Generic base name used for matrix-related outputs.

2) VCF-level QC / callability (DataLoader + query)

Argument	Type	Default	Short description
qual_threshold	float	30.0	Minimum VCF record QUAL.
min_dp_per_sample	int	10	Minimum per-sample read depth (DP).
min_gq_per_sample	int	20	Minimum per-sample genotype quality (GQ); set 0 when GQ is unavailable.
mq_threshold	float	40.0	Minimum INFO mapping quality (MQ).
mq0f_threshold	float	0.1	Maximum fraction of reads with mapping quality 0 (MQ0F).
biallelic_only	bool	true	Retain only biallelic variant records.
vcf_supported_ploidies	tuple	[1, 2]	Ploidies accepted by the VCF interpreter.
vcf_respect_filter	bool	true	Apply the VCF FILTER field.
vcf_allowed_filters	str	"PASS, ."	Comma-separated FILTER values accepted as passing.
assume_absent_variant_is_reference	bool	false	Treat an absent site in a variant-only VCF as the reference allele.
expand_gvcf_ref_blocks	bool	true	Resolve gVCF reference blocks (END) as callable reference.
validate_ref_against_genome	bool	false	Check VCF REF alleles against the loaded reference genome.
min_feature_recovery_fraction	float	0.5	Minimum fraction of selected features recovered at query time.
min_callable_fraction	float	0.5	Minimum callable fraction required at query time.
enforce_query_callability_gates	bool	true	Enforce query-time feature recovery/callability thresholds.
fastq_emit_gvcf	bool	true	Emit callable reference sites in gVCF-style FASTQ-derived calls.
fastq_gvcf_min_dp	int	10	Minimum depth for FASTQ-derived gVCF reference calls.
max_missing_fraction	float	0.5	Legacy overall missingness limit, used for both axes unless overridden.
max_missing_fraction_per_sample	Optional[float]	null	Maximum missing fraction per sample; null uses legacy setting.
max_missing_fraction_per_feature	Optional[float]	null	Maximum missing fraction per feature; null uses legacy setting.
drop_high_missing_samples	bool	true	Remove samples exceeding the missingness threshold.
drop_high_missing_features	bool	true	Remove features exceeding the missingness threshold.
genotype_impute_strategy	Literal['none', 'baseline', 'feature_mode', 'constant']	"baseline"	Method used to impute missing genotypes for algorithms that require complete data.
genotype_impute_constant	float	0.0	Constant used when genotype_impute_strategy is constant.
add_missing_indicator_features	bool	false	Add indicator variables marking missing genotypes.
allow_missing_as_category	bool	false	Permit missing values to be treated as a category.
contig_alias_map	Optional[str]	null	Explicit mapping from query contig names to training/manifest contig names.
reference_id	Optional[str]	null	Declared biological reference identifier.
reference_circular_contigs	Optional[str]	null	Comma-separated names of explicitly circular reference contigs.
allow_position_only_vcf_match	bool	false	Allow VCF matching by position alone; normally disabled.
min_spacing_bp	int	10	Minimum spacing between retained genomic features, in bp.

3) Cohort-level SNP filtering

Argument	Type	Default	Short description
----------	------	---------	-------------------

Argument	Type	Default	Short description
<code>min_sample_presence</code>	int	10	Minimum number of samples in which a SNP must be observed.

4) Binary encoding strategy

Argument	Type	Default	Short description
<code>ancestral_allele</code>	Literal["Y", 'N']	"Y"	Binary encoding strategy flag for ancestral/reference allele handling.

5) Lightweight preprocessing

Argument	Type	Default	Short description
<code>remove_invariant</code>	bool	true	Remove features with only one observed state.
<code>min_minor_count</code>	int	10	Minimum cohort count of the minority binary state.

6) Artifact filtering controls

Argument	Type	Default	Short description
<code>matrices_min_count</code>	int	10	Minimum count used by matrix artifact filtering.
<code>matrices_repeat_number</code>	int	5	Repeat-number threshold used by matrix artifact filtering.
<code>matrices_type</code>	Literal["all", 'coding', 'sense-mutations']	"all"	Feature type retained by matrix filtering.
<code>matrices_fix</code>	str	" "	Optional matrix-filter correction/fix specification.
<code>matrices_redundancy_sample_threshold</code>	int	2000	Sample-count threshold for redundancy subsampling.
<code>matrices_redundancy_sample_size</code>	int	256	Subsample size used for redundancy checks.

7) Central statistical feature filtering

Argument	Type	Default	Short description
<code>run_central_feature_filtering</code>	bool	true	Run central statistical feature filtering.
<code>central_feature_filter_method</code>	Literal['auto', 'rf_fdr', 'chi2_fdr', 'fisher_fdr', 'chi2_perm_fdr']	"auto"	Central feature-selection method; auto resolves from legacy settings.
<code>resolved_central_feature_filter_method</code>	str	"rf_fdr"	Resolved internal central-filter method.
<code>statistical_test</code>	Literal['chi2', 'fisher']	"chi2"	Statistical association test used by non-RF central filtering.
<code>significance_level</code>	float	0.05	Nominal statistical significance level.
<code>fdr_alpha</code>	float	0.05	False-discovery-rate alpha.
<code>fdr_threshold</code>	float	0.05	FDR-adjusted significance threshold.
<code>chi2_min_expected</code>	int	5	Minimum expected count required for chi-square testing.
<code>n_permutation_tests</code>	int	1000	Number of permutation tests.
<code>feature_filter_fallback_strategy</code>	Literal['stop', 'unfiltered']	"stop"	Action if central statistical filtering cannot provide features.
<code>prefilter_alpha</code>	float	0.05	Legacy prefilter significance threshold.
<code>min_nonmissing_prefilter</code>	float	0.2	Minimum non-missing fraction for legacy prefiltering.
<code>min_maf_prefilter</code>	float	0.0	Minimum minor-allele frequency for legacy prefiltering.
<code>max_prefiltered_features</code>	Optional[int]	10000	Maximum number of features retained by legacy prefiltering.
<code>multiple_testing_method</code>	Literal['fdr_bh', 'bonferroni']	"fdr_bh"	Multiple-testing correction method.
<code>run_rf_fdr_feature_selection</code>	bool	true	Enable RF-based empirical FDR feature selection.
<code>rf_selector_n_estimators</code>	int	300	Number of trees in the RF feature selector.
<code>rf_selector_n_observed_repeats</code>	int	10	Number of repeated observed RF fits.
<code>rf_selector_n_permutations</code>	int	1000	Number of label permutations for RF-FDR.

Argument	Type	Default	Short description
<code>rf_selector_fdr_alpha</code>	float	0.05	FDR alpha for RF feature selection.
<code>rf_selector_max_features</code>	str	"sqrt"	RF max_features setting.
<code>rf_selector_min_samples_leaf</code>	int	1	Minimum samples per RF leaf.
<code>rf_selector_class_weight</code>	Optional[str]	"balanced"	Class weighting used by the RF selector.
<code>rf_selector_min_importance</code>	float	0.0	Minimum RF feature importance.
<code>rf_selector_top_n</code>	Optional[int]	null	Optional maximum number of RF-selected features.
<code>rf_selector_random_state</code>	int	42	Random seed for RF feature selection.
<code>rf_selector_fallback_strategy</code>	Literal['top_n', 'unfiltered', 'stop']	"stop"	RF-selector behavior when FDR selection fails.
<code>rf_selector_fallback_top_n</code>	int	500	Top-N feature count used by exploratory RF fallback.
<code>allow_hierarchy_rf_fallback</code>	bool	false	Allow an explicitly recorded RF fallback model in hierarchy training.
<code>allow_two_level_rf_fallback</code>	bool	false	Deprecated alias of <code>allow_hierarchy_rf_fallback</code> .

8) Decision Tree parameters (capacity constrained)

Argument	Type	Default	Short description
<code>max_depth</code>	Optional[int]	12	Maximum decision-tree depth.
<code>max_branch_depth</code>	int	3	Maximum depth of a conditional tree branch.
<code>min_samples_split</code>	int	4	Minimum samples required to split a tree node.
<code>min_samples_leaf</code>	int	2	Minimum samples required in a tree leaf.
<code>min_information_gain</code>	float	0.001	Minimum information gain required for a tree split.
<code>min_group_size</code>	int	2	Legacy/group-size setting synchronized with <code>min_samples_split</code> .

9) Tree-path interaction candidates (POST-TREE)

Argument	Type	Default	Short description
<code>epistasis_strength_threshold</code>	float	0.05	Mutual-information synergy threshold for interaction candidates.
<code>max_tree_path_interaction_candidates</code>	int	50	Maximum post-tree interaction candidates.
<code>max_epistatic_interactions</code>	int	50	Deprecated alias of <code>max_tree_path_interaction_candidates</code> .
<code>interaction_min_joint_support</code>	int	10	Minimum joint sample support for an interaction.
<code>interaction_min_bootstrap_stability</code>	float	0.5	Minimum bootstrap stability for an interaction.
<code>interaction_fdr_alpha</code>	float	0.05	FDR alpha for interaction testing.

10) Post-tree bootstrap / stability

Argument	Type	Default	Short description
<code>n_bootstrap_resamples</code>	int	100	Number of independent cohort bootstrap resamples.
<code>bootstrap_cohort_sample_fraction</code>	float	1.0	Fraction of the cohort sampled with replacement per bootstrap.
<code>n_bootstrap</code>	int	100	Legacy alias for <code>n_bootstrap_resamples</code> .
<code>bootstrap_sample_fraction</code>	float	1.0	Legacy alias for <code>bootstrap_cohort_sample_fraction</code> .
<code>n_bootstrap_samples</code>	int	100	Legacy alias for number of bootstrap resamples.
<code>bootstrap_samples_per_iter</code>	int	100	Deprecated legacy bootstrap setting.
<code>bootstrap_outer_iters</code>	int	1	Deprecated bootstrap outer-loop count.
<code>min_bootstrap_support</code>	float	0.7	Minimum bootstrap support required.

11) Optional matrix compression

Argument	Type	Default	Short description
<code>use_integer_variant_ids</code>	bool	false	Use integer identifiers for variants to reduce storage overhead.

12) Performance & reproducibility

Argument	Type	Default	Short description
----------	------	---------	-------------------

Argument	Type	Default	Short description
n_jobs	int	-1	Parallel worker setting; -1 uses all available cores where supported.
random_state	int	42	Global random seed.
memory_efficient	bool	false	Enable memory-saving processing where implemented.
query_parallel_samples	bool	true	Process independent query samples in parallel.
query_parallel_n_jobs	Optional[int]	null	Optional query worker count; null follows automatic/default behavior.
hierarchy_parallel_fallback_training	bool	true	Train independent hierarchy fallback models in parallel.
level2_parallel_group_training	bool	true	Train independent Level-2 group models in parallel.
hierarchy_parallel_child_nodes	bool	true	Train sibling hierarchy nodes in parallel.
feature_panel_parallel_scoring	bool	true	Score candidate feature panels in parallel.
association_test_batch_size	int	250	Number of features processed per association-test batch.
parallel_memory_per_worker_gb	float	4.0	Estimated RAM per outer parallel worker, used to cap concurrency.
parallel_max_workers	Optional[int]	null	Optional hard cap on parallel workers.
hierarchy_resume_completed_nodes	bool	false	Reuse already completed hierarchy nodes when possible.
hierarchy_preset	Optional[str]	null	Optional named biological hierarchy preset.

13) FASTQ query preprocessing

Argument	Type	Default	Short description
fastq_max_parallel_samples	int	1	Maximum FASTQ samples processed concurrently.
fastq_threads	Optional[int]	null	Optional thread count per FASTQ sample.
fastq_memory_per_sample_mb	Optional[int]	null	Optional memory limit per FASTQ sample.
fastq_clean_intermediates	bool	false	Delete FASTQ-processing intermediate files.
fastq_auto_index_reference	bool	true	Automatically create missing reference indices.
fastq_min_mapping_quality	int	20	Minimum mapping quality for FASTQ-derived calls.
fastq_sample_platform	str	"ILLUMINA"	Sequencing-platform label used for FASTQ processing.
fastq_sort_memory	str	"1G"	Legacy samtools sort-memory setting.
fastq_multi_lane_policy	Literal['fail', 'merge']	"fail"	How multiple R1/R2 lanes for one sample are handled.
fastq_ploidy	int	1	Ploidy used for FASTQ-derived variant calling.
fastq_sort_memory_per_thread	str	"512M"	samtools sort memory per thread.
fastq_write_alignment_stats	bool	true	Write alignment statistics for FASTQ processing.
fastq_normalize_vcf	bool	true	Normalize FASTQ-derived VCF/gVCF against the reference.
fastq_call_mode	Literal['full', 'panel_bcftools', 'panel_majority']	"full"	FASTQ variant-calling strategy.
fastq_panel_sites_bed	Optional[str]	null	Optional BED file specifying trained panel sites.
fastq_panel_manifest	Optional[str]	null	Optional trained-feature manifest for panel calling.
fastq_panel_min_depth	int	10	Minimum depth for panel-majority calls.
fastq_panel_min_majority_fraction	float	0.7	Minimum majority-base fraction for panel-majority calls.
fastq_panel_min_base_quality	int	20	Minimum base quality for panel-majority calls.
fastq_panel_emit_reference_sites	bool	false	Emit explicit reference calls at panel sites.

14) Pipeline mode

Argument	Type	Default	Short description
pipeline_mode	Literal['matrix_onl y', 'decision_tree_onl y', 'ml_only', 'both', 'hierarchy', 'two_level']	"both"	Overall pipeline branch/mode.
run_ml_protocol	bool	false	Legacy switch enabling the ML protocol.
level1_label_column	Optional[str]	null	Metadata column used as Level-1 hierarchy label.
level2_label_column	Optional[str]	null	Metadata column used as Level-2 hierarchy label.
global_level2_label_column	Optional[str]	null	Optional broader target for the global Level-2 fallback.
train_global_level2	bool	true	Train the global Level-2 model.

Argument	Type	Default	Short description
min_level2_samples_per_group	Optional[int]	null	Optional absolute minimum sample count for Level-2 group training.
level2_drop_low_support_classes	bool	true	Exclude Level-2 classes with insufficient sample support.
level2_min_class_count	int	2	Minimum samples required for a Level-2 class.
low_support_review_enabled	bool	true	Flag predictions involving classes rare in training for review.
low_support_review_min_class_count	int	10	Training-count threshold defining a low-support class.
low_support_review_label	str	"low_support_review_required"	Label emitted for low-support review cases.
low_support_review_action_message	str	"Manually review this sample or merge rare classes in metadata if that grouping is biologically appropriate."	Review message attached to low-support predictions.
amr_weak_evidence_review_enabled	bool	true	Enable review logic for weak AMR marker evidence.
amr_weak_evidence_mode	Literal['warn', 'block']	"warn"	Keep and warn, or block, an AMR call with weak evidence.
amr_weak_evidence_min_resolved_fraction	float	0.05	Minimum resolved resistance-marker fraction for AMR evidence.
amr_weak_evidence_review_label	str	"amr_evidence_review_required"	Review label for weak AMR evidence.
amr_weak_evidence_review_action_message	str	"Branch AMR prediction had insufficient resolved resistance-marker evidence. Manually review the resistance phenotype or inspect marker coverage before accepting a susceptible call."	Review message for weak AMR evidence.
amr_evidence_guard_label_columns	Optional[str]	null	Optional label columns to which the AMR evidence guard applies.
hierarchy_global_amr_fallback_on_weak_evidence	bool	true	Use a saved global AMR fallback when branch evidence is weak.
hierarchy_global_amr_fallback_minimum_resistant_probability	float	0.5	Minimum resistant probability for the global AMR fallback.
hierarchy_global_fallback_labels	str	"none"	Comma-separated hierarchy labels receiving global fallback models.
hierarchy_train_parent_conditioned_fallbacks	bool	true	Train fallback models conditioned on the parent node.
hierarchy_train_global_lineage_fallback	bool	true	Train a global lineage fallback model.
hierarchy_global_lineage_fallback_label	Optional[str]	null	Optional label column for the global lineage fallback.
hierarchy_global_lineage_fallback_on_low_confidence	bool	true	Use global lineage fallback on low-confidence branch calls.
hierarchy_global_lineage_fallback_on_disagreement	bool	true	Use global lineage fallback when lineage models disagree.
hierarchy_global_lineage_fallback_minimum_support_delta	float	0.0	Minimum support difference controlling lineage fallback.
level2_train_binary_global_fallback	bool	false	Train an additional global binary Level-2 fallback.
level2_binary_label_column	Optional[str]	null	Metadata column for the binary Level-2 fallback.
level2_binary_label_mapping_file	Optional[str]	null	Optional file mapping detailed labels to binary states.
level2_binary_resistant_values	str	"R,resistant,RESISTANT,Resistant,1,true,TRUE,True"	Values interpreted as resistant by the binary mapping.
level2_binary_susceptible_values	str	"S,susceptible,SUSCEPTIBLE,Susceptible,0,false,FALSE,False"	Values interpreted as susceptible by the binary mapping.

15) Updated orchestration flags

Argument	Type	Default	Short description
run_model_selector	bool	true	Run automatic model selection.
run_conditional_dt	bool	true	Enable the conditional decision-tree branch.
disable_conditional_dt	bool	false	Explicitly disable the conditional decision-tree branch.
trigger_decision_tree_on_selected	bool	true	Run decision tree when selected by model-selection logic.
trigger_decision_tree_if_candidate	bool	true	Run decision tree when it meets candidate criteria.
decision_tree_requires_selector_match	bool	false	Require model-selector agreement before running the decision tree.

Argument	Type	Default	Short description
h			
decision_tree_candidate_top_k	int	2	Top-k probe-score rank required for DT candidacy.
decision_tree_candidate_max_margin	float	0.05	Maximum score margin from the best probe for DT candidacy.
decision_tree_always_run_interpretability	bool	false	Always run DT as an interpretability stage when applicable.

16) ML protocol branch

Argument	Type	Default	Short description
ml_algorithm	str	"auto"	ML algorithm; auto invokes model-selection logic.
ml_lr_max_iter	int	2000	Maximum iterations for logistic regression.
ml_min_decision_threshold	float	0.5	Minimum decision/support threshold considered.
ml_max_decision_threshold	float	1.0	Maximum decision/support threshold considered.
ml_step_decision_threshold	float	0.1	Step size across candidate decision thresholds.
ml_min_sensitivity	float	0.5	Deprecated alias of ml_min_decision_threshold.
ml_max_sensitivity	float	1.0	Deprecated alias of ml_max_decision_threshold.
ml_step_sensitivity	float	0.1	Deprecated alias of ml_step_decision_threshold.
ml_threshold_objective	Literal['min_called_error_subject_to_coverage', 'utility', 'balanced_called_and_coverage', 'accuracy_called_only', 'call_rate', 'accuracy_end_to_end']	"min_called_error_subject_to_coverage"	Objective used to select the decision threshold from out-of-fold predictions.
ml_threshold_min_coverage	float	0.5	Minimum call-rate constraint for threshold selection.
ml_threshold_utility_reward_correct	float	1.0	Utility reward assigned to a correct call.
ml_threshold_utility_cost_wrong	float	2.0	Utility cost assigned to an incorrect call.
ml_threshold_utility_cost_abstain	float	0.5	Utility cost assigned to an abstention.
ml_threshold_objective_called_weight	float	0.5	Weight of called-sample accuracy in the combined objective.
ml_threshold_objective_coverage_weight	float	0.5	Weight of call rate in the combined objective.
ml_calibrate_support_scores	bool	false	Calibrate model support scores.
ml_calibration_method	Literal['none', 'isotonic']	"none"	Support-score calibration method.
ml_select_threshold_out_of_fold	bool	true	Select decision threshold using out-of-fold predictions.
ml_threshold_cv_splits	int	5	CV folds used for threshold selection.
selector_linear_score_high	float	0.85	Score threshold favoring a linear model when nonlinear gain is small.
selector_nonlinear_delta_ignore	float	0.03	Nonlinear improvement small enough to ignore.
selector_nonlinear_delta_prefer	float	0.05	Nonlinear improvement large enough to prefer nonlinear models.
selector_run_clustering_diagnostics	bool	false	Run clustering diagnostics during model selection.
bootstrap_min_successful_resamples	int	20	Minimum successful bootstrap resamples for stability reporting.
ml_empty_symbol	str	""	Symbol representing an empty ML input field.
ml_remove_empty_field_threshold	float	1.0	Missing/empty fraction at which an ML field is removed.
cv_group_column	Optional[str]	null	Metadata column used for grouped/blocked cross-validation.
cv_preprocessing_mode	Literal['strict', 'exploratory_transductive']	"strict"	Whether CV preprocessing is strict fold-local or exploratory transductive.
cv_allow_partial_results	bool	false	Allow publication summaries when some requested CV folds fail.
cv_min_groups_per_class	int	2	Minimum distinct groups per class for grouped CV.
run_nested_cv_evaluation	bool	true	Run nested CV in the main single-label workflow.
cv_n_repeats	int	3	Number of CV repeats.
cv_n_splits	int	5	Number of CV folds.

17) Ranked feature-panel separability check

Argument	Type	Default	Short description
run_feature_panel_separability_check	bool	true	Evaluate ranked top-N feature panels before model fitting.
feature_panel_sizes	tuple	[100, 200, 500, 1000]	Candidate top-N panel sizes.
feature_panel_metric	Literal['balanced_accuracy', 'adjusted_rand', 'normalized_mutual_info', 'silhouette']	"balanced_accuracy"	Metric used to score candidate panels.
feature_panel_classifier	Literal['lr', 'rf']	"lr"	Probe classifier used to score candidate panels.
feature_panel_lr_max_iter	int	2000	Maximum iterations for the panel logistic-regression probe.
feature_panel_lr_tol	float	0.0001	Tolerance for the panel logistic-regression probe.
feature_panel_rf_n_estimators	int	300	Trees in the panel RF probe.
feature_panel_rf_max_features	Optional[str]	"sqrt"	RF max_features for panel scoring.
feature_panel_rf_min_samples_leaf	int	1	Minimum samples per leaf in panel RF scoring.
feature_panel_rf_class_weight	Optional[str]	"balanced"	Class weighting for panel RF scoring.
feature_panel_rf_n_jobs	Optional[int]	null	Optional worker count for panel RF scoring.
feature_panel_min_score	float	0.75	Minimum score a candidate panel must reach.
feature_panel_selection_rule	Literal['smallest_passing', 'best_passing', 'best_available']	"smallest_passing"	Rule for choosing among candidate panels.
feature_panel_cv_splits	int	5	CV folds used to evaluate feature panels.
feature_panel_always_include_full_filtered	bool	false	Also evaluate the complete centrally filtered matrix.
feature_panel_threshold_failure_strategy	Literal['stop', 'best_available']	"stop"	Action when no candidate panel reaches the minimum score.
feature_panel_max_silhouette_samples	int	5000	Maximum samples used for silhouette calculations.
feature_panel_run_clustering_diagnostics	bool	false	Run clustering diagnostics during panel evaluation.
feature_panel_large_feature_threshold	int	5000	Feature-count threshold defining a large matrix.
feature_panel_large_max_scoring_features	int	5000	Maximum features scored in large-matrix panel evaluation.
feature_panel_large_pool_multiplier	int	4	Multiplier controlling the candidate pool for large matrices.
feature_panel_score_full_large_matrix	bool	false	Score the complete large filtered matrix.
feature_panel_allow_variance_prefilter	bool	false	Allow variance prefiltering before panel scoring.
feature_panel_strict_failure	bool	true	Treat panel-selection failure as a hard failure.
seed_known_markers	bool	false	Prioritize known/catalogue mutations within statistically supported phenotype features.
known_markers_path	Optional[str]	null	Path to a known-mutation catalogue or Feature_ID list.
seed_known_markers_mode	Literal['force_include', 'rank_boost']	"force_include"	How known markers are prioritized in feature panels.
seed_known_markers_stage_substrings	tuple	['amr', 'resistance', 'pheno', 'profile', 'resistant', 'susceptible']	Stage-name terms identifying endpoints eligible for known-marker prioritization.
seed_known_markers_max	Optional[int]	null	Optional maximum number of known markers to prioritize.
rf_selector_permutation_resolution_policy	Literal['warn', 'fail']	"warn"	Warn or fail when RF permutation count gives insufficient p-value resolution.
cv_relax_input_filters	bool	true	Relax input-level cohort filters before fold-specific CV filtering.

18) Two-level binary model bundle output

Argument	Type	Default	Short description
build_model_bundle	bool	true	Automatically build a portable .npb model bundle after hierarchy training.
model_bundle_filename	str	"networkparser_model_bundle.npb"	Filename of the generated model bundle.

Argument	Type	Default	Short description
<code>model_bundle_include_model_payloads</code>	<code>bool</code>	<code>b"true"</code>	Include fitted model payloads in the bundle.
<code>model_bundle_include_feature_manifests</code>	<code>bool</code>	<code>true</code>	Include selected-feature manifests in the bundle.
<code>model_bundle_include_ranked_feature_tables</code>	<code>bool</code>	<code>true</code>	Include ranked feature tables in the bundle.
<code>model_bundle_fail_on_error</code>	<code>bool</code>	<code>false</code>	Fail training if model-bundle construction fails.

Source: `network_parser/config.py`, `NetworkParserConfig` dataclass supplied by the user. Defaults shown are the values declared in that class before any `__post_init__` normalization or alias synchronization.