

★ How to Reconfigure Oracle Restart (Doc ID 986740.1)

[To Bottom](#)

In this Document

[Goal](#)[Solution](#)

- [1. Remove Oracle Restart configuration](#)
- [2. reconfigure Oracle Restart](#)
- [3. Add ASM back to Oracle Restart configuration](#)
- [4. Start up ASM instance](#)
- [5. Recreate ASM server parameter file \(SPFILE\)](#)
- [6. Restart HAS stack](#)
- [7. Add components back to Oracle Restart Configuration](#)
 - [7.1. Add database component](#)
 - [7.2. Add listener component](#)
 - [7.3. Add other components](#)

Was this document helpful?

- ☐ Yes
☐ No

Document Details

Type:	HOWTO	
Status:	PUBLISHED	
Last Major Update:	May 12, 2020	
Last Update:	Mar 5, 2023	
Language:	<div>English ▼</div>	

Related Products

Oracle Database Cloud Schema Service
Gen 1 Exadata Cloud at Customer (Oracle Exadata Database Cloud Machine)
Oracle Database Exadata Express Cloud Service
Oracle Cloud Infrastructure - Database Service
Oracle Database Cloud Exadata Service

[Show More](#)

APPLIES TO:

Oracle Database Cloud Schema Service - Version N/A and later
Gen 1 Exadata Cloud at Customer (Oracle Exadata Database Cloud Machine) - Version N/A and later
Oracle Database Exadata Express Cloud Service - Version N/A and later
Oracle Cloud Infrastructure - Database Service - Version N/A and later
Oracle Database Cloud Exadata Service - Version N/A and later
Information in this document applies to any platform.

GOAL

This document is about reconfiguring Oracle Restart. One reason for such action might be if the server (host) was renamed. If that was the case and the server was rebooted, the ASM startup would fail with ORA-29701.

The solution is to reconfigure Oracle Restart.

SOLUTION

1. Remove Oracle Restart configuration

This step should be performed as privileged (root) user.

```
# $GRID_HOME/crs/install/roothas.pl -deconfig -force
```

The expected result is "Successfully deconfigured Oracle Restart stack".

2. reconfigure Oracle Restart

This step should also be performed as privileged (root) user.

```
# $GRID_HOME/crs/install/roothas.pl
```

The expected result is "Successfully configured Oracle Grid Infrastructure for a Standalone Server"

3. Add ASM back to Oracle Restart configuration

This step should be performed as Grid Infrastructure owner (grid user).

```
$ srvctl add asm
```

Information Centers

Oracle Catalog: Information Centers and Advisors for All Products and Services [50.2]

Information Center: OCI Networking - Email Delivery [2886428.2]

Information Center: OCI Cloud Guard [2765346.2]

Information Center: OCI Container Instances [2922704.2]

Information Center: Oracle Cloud Infrastructure (OCI) & Platform as a Service (PaaS) Overview [2048297.2]

[Show More](#)

Document References

No References available for this document.

Recently Viewed

CLSU-00105 CLSU-00103
CLSU-00104: additional error information: need ha priv [1634671.1]

How To Purge The UNIFIED AUDIT TRAIL [1582627.1]

Materialized View Refresh Failing with errors ORA-12008 ORA-31600 ORA-30372 [2738707.1]

RMAN Catalog Start with "<>" Failed with no files found and RMAN-06571 [1315732.1]

The expected result is no output, just a return to the operating system prompt.

4. Start up ASM instance

This step should be performed as Grid Infrastructure owner (grid user).

```
$ srvctl start asm
```

That should start ASM. Note that at this time there will be no ASM initialization or server parameter file.

5. Recreate ASM server parameter file (SPFILE)

This step should be performed as Grid Infrastructure owner (grid user).

Create a temporary initialization parameter file (e.g. /tmp/init+ASM.ora) with the following content (specify you

```
asm_diskgroups='<DG_NAME>', '<DG_2_NAME>'
instance_type='asm'
large_pool_size=12M
remote_login_passwordfile='EXCLUSIVE'
```

Mount the disk group where the new server parameter file (SPFILE) will reside (e.g. <DG_NAME>) and create SPFILE

```
$ sqlplus / as sysasm

SQL> alter diskgroup <DG_NAME> mount;
Diskgroup altered.

SQL> create spfile='+<DG_NAME>' from pfile='/tmp/init+ASM.ora';
File created.

SQL> show parameter spfile
NAME TYPE VALUE
-----
spfile string +<DG_NAME>/asm/asmpparameterfile/registry.253.707737977
```

6. Restart HAS stack

```
crsctl stop has
crsctl start has
```

7. Add components back to Oracle Restart Configuration

If you had the database, listener and other components, add them back to the Oracle Restart Configuration.

7.1. Add database component

This step should be performed as RDBMS owner (oracle user).

```
srvctl add database -d <db_unique_name> -o <oracle_home>
```

7.2. Add listener component

This step should be performed as Grid Infrastructure owner (grid user).

```
srvctl add listener
```

7.3. Add other components

For information on how to add back additional components, please review:
 Oracle database Administrator's Guide 11g Release 2 (11.2)
 Chapter 4 Configuring Automatic Restart of an Oracle database
 Section Configuring Oracle Restart

Didn't find what you are looking for?

 Ask in Community...

Related

Products

- [Oracle Cloud > Oracle Platform Cloud > Oracle Database Cloud Service > Oracle Database Cloud Schema Service](#)
- [Oracle Cloud > Oracle Infrastructure Cloud > Oracle Cloud at Customer > Gen 1 Exadata Cloud at Customer \(Oracle Exadata Database Cloud Machine\)](#)
- [Oracle Cloud > Oracle Platform Cloud > Oracle Database Cloud Service > Oracle Database Exadata Express Cloud Service](#)
- [Oracle Cloud > Oracle Platform Cloud > Oracle Cloud Infrastructure - Database Service > Oracle Cloud Infrastructure - Database Service](#)
- [Oracle Cloud > Oracle Platform Cloud > Oracle Database Cloud Exadata Service > Oracle Database Cloud Exadata Service](#)

RMAN Active Duplicate Failed with RMAN-04014: startup failed: ORA-27125: unable to create shared memory segment [2188974.1]

[Show More](#)

- [Oracle Cloud > Oracle Platform Cloud > Oracle Database Backup Service > Oracle Database Backup Service](#)
- [Oracle Cloud > Oracle Platform Cloud > Oracle Database Cloud Service > Oracle Database Cloud Service](#)
- [Oracle Database Products > Oracle Database Suite > Oracle Database > Oracle Database - Enterprise Edition > STORAGE](#)
- [Oracle Database Products > Oracle Database Suite > Oracle Database > Oracle Database - Enterprise Edition > Clusterware](#)

Keywords

11G RELEASE 2; 11GR2; ASM; CONFIGURATION; CREATE SPFILE FROM; DECONFIGURED; DISK GROUP; DISKGROUP; GRID; INFRASTRUCTURE; RECONFIGURE; RESTART; ROTHAS.PL; SERVER PARAMETER FILE; SPFILE; SRVCTL

Errors

[ORA-29701](#)

Translations

- English [Source](#)
- Chinese [简体中文](#)
- Japanese [日本語](#)

[⬆️ Back to Top](#)