# Ansys Actions

Version: main



#### / Hk package clean except

Perform versions cleanup - except certain tags

```
- name: Perform versions cleanup - except certain
    tags
uses: ansys/actions/hk-package-clean-except@v8.1
with:
    package-name: mypackage
    tags-kept: latest, latest-unstable
    token: ${{ secrets.GITHUB_TOKEN }}
```

**Ref**: Perform versions cleanup - except certain tags

#### / Code style

Running code style checks

```
    name: Run PyAnsys code style checks
uses: ansys/actions/code-style@v8.1
```

Ref: Running code style checks

#### / Check vulnerabilities

Check library vulnerabilities

```
- uses: ansys/actions/check-vulnerabilities@v8.1
with:
    dev-mode: ${{ github.ref != "refs/heads/main"}}
    python-package-name: ansys-<product>-<library>
    python-version: ${{ env.MAIN_PYTHON_VERSION }}
    token: ${{ secrets.PYANSYS_CI_BOT_TOKEN }}
```

Ref: Check library vulnerabilities

## / Release github

Release to github

```
- name: Release to GitHub
  uses: ansys/actions/release-github@v8.1
  with:
    library-name: ansys-cproduct>-<library>
```

Ref: Release to GitHub

## / Docker style

Docker style

Ref: Docker style

```
- uses: ansys/actions/docker-style@v8.1
with:
   directory: docker
   error-level: 1
   recursive: true
```

## / Release pypi test

Release to test pypi

```
- name: Release to the test PyPI repository
  uses: ansys/actions/release-pypi-test@v8.1
  with:
    library-name: ansys-product>-<library>
    twine-token: ${{ secrets.PYANSYS_PYPI_TEST_PAT
     }}
  twine-username: __token__
```

**Ref**: Release to test PyPI

#### / Doc build

Installing additional system dependencies for building documentation

```
- name: Run Ansys documentation building action
uses: ansys/actions/doc-build@v8.1
with:
   dependencies: graphviz mermaid-cli
```

 $\boldsymbol{Ref}\colon$  Installing additional system dependencies for building documentation

Building library documentation that using xvfb

```
- name: Run Ansys documentation building action
uses: ansys/actions/doc-build@v8.1
with:
    requires-xvfb: true
```

Ref: Building library documentation that using XVFB Building library documentation

```
    name: Run Ansys documentation building action
uses: ansys/actions/doc-build@v8.1
```

Ref: Building library documentation

### / Doc style

Running documentation style checks

```
- name: Running documentation style checks
uses: ansys/actions/doc-style@v8.1
with:
   token: ${{ secrets.GITHUB_TOKEN }}
```

Ref: Running documentation style checks

#### / Check pr title

Check pull-request title follows conventional commits

```
- uses: ansys/actions/check-pr-title@v8.1
  with:
    token: ${{ secrets.GITHUB_TOKEN }}
```

Ref: Check pull-request title follows conventional commits

#### / Doc changelog

Create changelog fragment

```
- uses: ansys/actions/doc-changelog@v8.1
with:
   bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
     }}
token: ${{ secrets.PYANSYS_CI_BOT_TOKEN }}
```

Ref: Create changelog fragment

#### / Release pypi public

Release to public pypi using trusted publisher

```
- name: Release to the public PyPI repository
    using Trusted Publisher
uses: ansys/actions/release-pypi-public@v8.1
with:
    library-name: ansys-<product>-<library>
    use-trusted-publisher: true
```

Ref: Release to public PyPI using Trusted Publisher Release to public pypi

```
- name: Release to the public PyPI repository
uses: ansys/actions/release-pypi-public@v8.1
with:
   library-name: ansys-<product>-<library>
   twine-token: ${{ secrets.PYPI_TOKEN }}
   twine-username: __token__
```

Ref: Release to public PyPI

## / Doc deploy changelog

Update changelog for new tag

```
- uses: ansys/actions/doc-deploy-changelog@v8.1
with:
  bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
     }}
token: ${{ secrets.PYANSYS_CI_BOT_TOKEN }}
```

Ref: Update CHANGELOG for new tag

#### / Build ci wheels

Build a c-extension library

- name: Build a C-extension library wheel artifacts uses: ansys/actions/build-ci-library@v8.1

Ref: Build a C-extension library

#### / Check licenses

Check library dependencies ship with valid licenses

```
- name: Validate third party licenses
  uses: ansys/actions/check-licenses@v8.1
  with:
    python-version: ${{ env.MAIN_PYTHON_VERSION }}
```

**Ref**: Check library dependencies ship with valid licenses

## / Doc deploy dev

Deploy developers documentation

```
- name: Deploy the latest documentation
  uses: ansys/actions/doc-deploy-dev@v8.1
  with:
    bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
    bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME }}
    cname: <library>.docs.pyansys.com
    token: ${{ secrets.GITHUB_TOKEN }}
```

**Ref**: Deploy developers documentation

## / Build library

Build library basic example

```
- name: Build library source and wheel artifacts
uses: ansys/actions/build-library@v8.1
with:
   library-name: ansys-product>-<library>
```

Ref: Build library basic example

### / Doc deploy stable

Deploy stable documentation

```
- name: Deploy the stable documentation
  uses: ansys/actions/doc-deploy-stable@v8.1
  with:
    bot-email: ${{ secrets.PYANSYS_CI_BOT_EMAIL }}
```

```
bot-user: ${{ secrets.PYANSYS_CI_BOT_USERNAME
      }}
cname: <library>.docs.pyansys.com
token: ${{ secrets.GITHUB_TOKEN }}
```

**Ref**: Deploy stable documentation

#### / Tests pytest

Testing library with different operating systems and python versions

 ${\it Ref}$ : Testing library with different operating systems and Python versions

Optimized testing with different operating systems and python versions

```
name: Login into the GitHub container registry
uses: docker/login-action@v2.1.0
with:
  password: ${{ secrets.GITHUB_TOKEN }}
  registry: ghcr.io
  username: ${{ secrets.GH_USERNAME }}
  LICENSE_SERVER: ${{ secrets.LICENSE_SERVER }}
name: Pull, launch and verify desired Ansys
    service
run: '...'
name: Run pytest with desired markers and extra
  arguments
uses: ansys/actions/tests-pytest@v8.1
with:
  pytest-extra-args: ${{ matrix.cfg.extra-args }}
  pytest-markers: ${{ matrix.cfg.markers }}
```

```
requires-xvfb: true
```

**Ref**: Optimized testing with different operating systems and Python versions

### / Release pypi private

Release to private pypi

```
name: Release to the private PyPI repository
uses: ansys/actions/release-pypi-private@v8.1
with:
   library-name: ansys-product>-<library>
   twine-token: ${{
      secrets.PYANSYS_PYPI_PRIVATE_PAT }}
twine-username: __token__
```

**Ref**: Release to private PyPI

#### / Build wheelhouse

Build wheelhouse for latest python versions

```
- name: Build a wheelhouse of the Python library
uses: ansys/actions/build-wheelhouse@v8.1
with:
   library-name: <ansys-product-library>
   operating-system: ${{ matrix.os }}
   python-version: ${{ matrix.python-version }}
```

**Ref**: Build wheelhouse for latest Python versions

### / Hk package clean untagged

Perform untagged versions cleanup

```
- name: Perform untagged versions cleanup
uses:
    ansys/actions/hk-package-clean-untagged@v8.1
with:
    package-name: mypackage
    token: ${{ secrets.GITHUB_TOKEN }}
```

Ref: Perform untagged versions cleanup