

# Introduction to LSTM

---

## The RNN Problem

### ◆ Gradient Flow in RNNs

- In **backpropagation through time (BPTT)**, the gradient has to pass backward through **many time steps**.
- Each step multiplies the gradient by weight matrices (e.g.,  $W_{hh}$ ) and derivatives of activations (like  $\tanh$ ).
- This repeated multiplication causes:

#### 1. Vanishing Gradient

- Gradients shrink → earlier layers (long-term past) get almost no updates.
- RNNs fail to learn **long-term dependencies**.

#### 2. Exploding Gradient

- Gradients grow exponentially → unstable training.
  - Often fixed by **gradient clipping**.
- 

## Short-Term vs Long-Term Dependencies

- **Short-term dependency**: The output depends on inputs from the **recent past**.

Example:

- Sentence: *"The cat sat on the \_\_\_\_"*.
- Predicting the next word "mat" mainly depends on the last 2–3 words.

- **Long-term dependency**: The output depends on inputs from the **distant past**.

Example:

- Sentence: *"I grew up in France ... I speak fluent \_\_\_\_"*.

- To predict “French”, the model must remember “France” from far back.
  - **Vanilla RNNs usually fail here** because the gradient fades over many steps.
- 

## Enter LSTM (Long Short-Term Memory)

**LSTM** is a special type of RNN architecture designed to overcome the **vanishing gradient problem** and handle long-term dependencies effectively.

---



### Core Idea

- Instead of a single hidden state, LSTMs maintain a **cell state** ( $C_t$ ) that acts like a “conveyor belt” carrying long-term memory through the sequence with minimal changes.
  - Gates control what information is added, removed, or output from memory.
- 

## LSTM Architecture

### Quick overview / purpose

An **LSTM (Long Short-Term Memory)** cell is a recurrent unit that maintains two things each time step:

- a **cell state**  $C_t$  (long-term memory / “conveyor belt”), and
- a **hidden state**  $h_t$  (short-term memory / what’s “exposed” to the outside).

LSTM uses **gates** (sigmoid units) to control what gets written, kept, or read from the cell state — this is what lets it learn long-range dependencies better than a vanilla RNN.

---

### Notation & dimensions

- Input at time  $t$ :  $x_t \in \mathbb{R}^D$
- Hidden size:  $H$

- Hidden state:  $h_t \in \mathbb{R}^H$
  - Cell state:  $C_t \in \mathbb{R}^H$
  - You'll see weight matrices for each gate. Two common parameterizations:
    - **Separate matrices per gate** (clearer): e.g.  $W_f \in \mathbb{R}^{H \times D}$ ,  $U_f \in \mathbb{R}^{H \times H}$ ,  $b_f \in \mathbb{R}^H$ .
    - **Combined matrices** (efficient): stack the 4 gates into one matmul:  
 $W \in \mathbb{R}^{4H \times D}$ ,  $U \in \mathbb{R}^{4H \times H}$ ,  $b \in \mathbb{R}^{4H}$ .
- 

## Canonical LSTM equations (separate matrices)

At each time step:

1. **Forget gate** — what to forget from previous cell:

$$f_t = \sigma(W_f x_t + U_f h_{t-1} + b_f)$$

2. **Input (update) gate** — how much new information to write:

$$i_t = \sigma(W_i x_t + U_i h_{t-1} + b_i)$$

3. **Candidate (new content)** — new information proposed for the cell:

$$\tilde{C}_t = \tanh(W_c x_t + U_c h_{t-1} + b_c)$$

4. **Cell state update** — combine old and new:

$$C_t = f_t \odot C_{t-1} + i_t \odot \tilde{C}_t$$

(Here  $\odot$  is element-wise product.)

5. **Output gate** — decide what to output:

$$o_t = \sigma(W_o x_t + U_o h_{t-1} + b_o)$$

6. **Hidden state (the exposed output of the cell):**

$$h_t = o_t \odot \tanh(C_t)$$

If you compute all four in one go (stacked), you do two big matmuls:  $W x_t$  and  $U h_{t-1}$ , add  $b$ , then split into four chunks and apply activations.

---

## Component-by-component detail & intuition

### Forget gate $f_t$

- Range: elements in (0,1) by sigmoid.
- Purpose: **scale** the previous cell  $C_{t-1}$ . If an element of  $f_t$  is near 0, that dimension of  $C_{t-1}$  is erased; if near 1, it's retained.
- Intuition: selective forgetting — the network learns *when not to keep old info*.

### Input gate $i_t$ and candidate $\tilde{C}_t$

- $i_t$  (sigmoid) decides **how much of the candidate** to write into the cell.
- $\tilde{C}_t$  (tanh) is the new candidate content (in  $[-1,1]$ ).
- Together,  $i_t \odot \tilde{C}_t$  is the update term added into the cell.

### Cell state $C_t$ (the conveyor belt)

- Crucial property: **linear path** with elementwise gating,

$$C_t = f_t \odot C_{t-1} + i_t \odot \tilde{C}_t,$$

which allows information (and gradients) to flow across many time steps with limited distortion.

- Because the update is a *sum* of retained memory and new content, gradients can flow back through the addition instead of repeated nonlinear compressions.

### Output gate $o_t$ and hidden state $h_t$

- $o_t$  decides which parts of the (squashed) cell state to expose as hidden output.
  - $h_t = o_t \odot \tanh(C_t)$  — this is typically fed to the next layer (or used to predict  $y_t$ ).
- 

## Why LSTM helps vanishing gradients (math intuition)

When backpropagating, the derivative of  $C_t$  w.r.t.  $C_{t-1}$  is:

$$\frac{\partial C_t}{\partial C_{t-1}} = \text{diag}(f_t)$$

So the signal is multiplied elementwise by  $f_t$  (not by recurrent weight matrices and repeated tanh derivatives). If the network learns  $f_t \approx 1$  for relevant dimensions, gradients are preserved across many steps — this is the **constant error carousel** idea.

---

## Variants & extensions (brief)

- **Peephole connections:** gates also receive the previous cell  $C_{t-1}$  (terms like  $V_f \odot C_{t-1}$ ), giving gates direct access to cell content.
  - **Coupled input-forget gates:** sometimes  $i_t = 1 - f_t$  to reduce parameters.
  - **GRU (Gated Recurrent Unit):** simpler 2-gate variant (update + reset) with one hidden state (no separate cell state).
  - **Bidirectional LSTM:** process sequence forwards and backwards and concatenate outputs.
  - **Stacked LSTM:** multiple LSTM layers stacked for hierarchical features.
  - **Regularization:** dropout between layers, recurrent dropout variants, layer normalization.
- 

## Implementation & performance tips

- **Efficient compute:** combine gates into single matmuls for  $Wx_t$  and  $Uh_{t-1}$ , then split — this is how frameworks implement it.
- **Initialization:** biases for forget gate  $b_f$  are often initialized to a positive value (e.g., 1) to encourage remembering at start of training.
- **Training:** still use gradient clipping to handle exploding gradients; use truncated BPTT (limit sequence length) for long sequences.
- **Batching / padded sequences:** handle variable lengths with masks or packed sequences.

## Short pseudocode (forward, high level)

```
for t in 1..T:
    z = W @ x_t + U @ h_{t-1} + b    # z shape = 4H
    f, i, o, g = split(z)           # apply σ, σ, σ, tanh respectively
    C_t = f * C_{t-1} + i * g
    h_t = o * tanh(C_t)
```

## Summary (one paragraph)

An LSTM augments the vanilla RNN with a **cell state** and **learned gates** (forget, input, output) that control reading, writing and erasing memory. The gates are elementwise sigmoids and the candidate uses tanh. Because the cell state update uses gated *additions* rather than repeated nonlinear transforms, gradients can flow much more freely across long sequences — solving (or greatly reducing) the vanishing gradient problem and enabling learning of long-term dependencies.

## Why LSTM is Better than Vanilla RNN

Problem in Vanilla RNN	How LSTM Fixes It
<b>Vanishing Gradient</b>	The cell state has <b>linear paths</b> with controlled gates → allows gradients to flow back without vanishing quickly.

Problem in Vanilla RNN	How LSTM Fixes It
<b>Forgetting old info</b>	Forget gate explicitly decides what to erase.
<b>Storing long-term info</b>	Input + cell state keep useful info across long sequences.
<b>Short-term vs Long-term</b>	Gates balance between remembering recent info and far-past info.

## Summary with Intuition

- **Vanilla RNN:** Think of it like writing on paper with an eraser that smudges over time — the old info fades.
- **LSTM:** Think of it like a notebook with tabs (gates):
  - *Forget gate:* erase old notes.
  - *Input gate:* add new notes.
  - *Output gate:* decide which notes to share now.
- This makes LSTM capable of learning **both short-term and long-term dependencies**.

## LSTM Training

### 1. Forward pass (recap)

At each timestep  $t$ , an LSTM computes:

$$\begin{aligned}
f_t &= \sigma(W_f x_t + U_f h_{t-1} + b_f) \\
i_t &= \sigma(W_i x_t + U_i h_{t-1} + b_i) \\
\tilde{C}_t &= \tanh(W_c x_t + U_c h_{t-1} + b_c) \\
C_t &= f_t \odot C_{t-1} + i_t \odot \tilde{C}_t \\
o_t &= \sigma(W_o x_t + U_o h_{t-1} + b_o) \\
h_t &= o_t \odot \tanh(C_t) \\
y_t &= W_{hy} h_t + b_y
\end{aligned}$$


---

## 2. Loss calculation

Suppose you have a sequence of length  $T$ , with predictions  $\{y_t\}$  and targets  $\{\hat{y}_t\}$ . The total loss is usually the **sum (or mean)** over timesteps:

$$\mathcal{L} = \sum_{t=1}^T \ell(y_t, \hat{y}_t)$$


---

## 3. Backpropagation Through Time (BPTT) — general idea

- You **unroll the LSTM across timesteps** (like a deep feedforward network with shared weights).
- Then you apply standard backpropagation *through the unrolled graph*.
- The challenge: **gradients at timestep  $t$  depend not just on  $h_{t-1}$ , but also indirectly on all previous hidden and cell states**.

So, the error at time  $t$  flows back through:

- The output layer weights ( $W_{hy}$ )
  - The output gate and cell state at time  $t$
  - The **previous hidden state**  $h_{t-1}$  and **previous cell state**  $C_{t-1}$
  - Repeated until you reach the start of the sequence.
-



## 4. Gradients in LSTM (math intuition)

### Key idea: two “paths” for error flow

- Via **hidden state**  $h_t$  (nonlinear, can still vanish/explode).
  - Via **cell state**  $C_t$  (linear + forget gate, reduces vanishing gradient).
- 

#### 1. Gradient flow for cell state

From the update:

$$C_t = f_t \odot C_{t-1} + i_t \odot \tilde{C}_t$$

The derivative is:

$$\frac{\partial C_t}{\partial C_{t-1}} = f_t$$

So, when you backpropagate:

$$\frac{\partial \mathcal{L}}{\partial C_{t-1}} = \frac{\partial \mathcal{L}}{\partial C_t} \odot f_t$$

👉 This means **if**  $f_t \approx \mathbf{1}$ , the gradient flows backward almost unchanged — solving the vanishing gradient problem.

---

#### 2. Gradients for gates

Each gate gets its own error signal:

- Forget gate:

$$\frac{\partial \mathcal{L}}{\partial f_t} = \frac{\partial \mathcal{L}}{\partial C_t} \odot C_{t-1}$$

- Input gate:

$$\frac{\partial \mathcal{L}}{\partial i_t} = \frac{\partial \mathcal{L}}{\partial C_t} \odot \tilde{C}_t$$

- Candidate:

$$\frac{\partial \mathcal{L}}{\partial \tilde{C}_t} = \frac{\partial \mathcal{L}}{\partial C_t} \odot i_t$$

- Output gate:

$$\frac{\partial \mathcal{L}}{\partial o_t} = \frac{\partial \mathcal{L}}{\partial h_t} \odot \tanh(C_t)$$

Then you backprop through the activations (sigmoid/tanh), and compute parameter updates using:

$$\Delta W = \sum_t \frac{\partial \mathcal{L}}{\partial W}$$

## 5. Tricks used in practice

- **Truncated BPTT:** Instead of unrolling for the entire sequence, cut it into smaller chunks (e.g. 20–50 steps). Prevents memory blowup and helps stability.
- **Gradient clipping:** Prevents exploding gradients by capping the gradient norm.
- **Bias init for forget gate:** Often set  $b_f \approx 1$  so that  $\text{ftf}_t$  starts near 1 (helps preserve memory early in training).
- **Layer normalization/dropout:** Help stabilize training.

### ✓ Summary

Training LSTMs = run forward pass (compute hidden + cell states), compute loss, and apply **BPTT** by unrolling across timesteps.

- Gradients flow both through the hidden states and the cell state.
- The **cell state provides a nearly-linear highway for gradients**, controlled by forget gates — this is why LSTMs handle long-term dependencies better than vanilla RNNs.

- Practical training uses truncated BPTT + gradient clipping for efficiency and stability.
- 

# Main Drawbacks of LSTMs

## A. Architectural Limitations

### 1 *Sequential Processing (No Parallelization)*

- LSTMs process sequences **token by token**, where each step depends on the previous one.
- This means you **can't parallelize** time steps — only batches.
- So, training is **slow** compared to models like Transformers that process entire sequences simultaneously via self-attention.

... Example:

If your sentence has 200 words, the LSTM must process them one by one — unlike Transformers that process all 200 words in parallel.

---

### 2 *Difficulty with Very Long Dependencies*

- Even though LSTMs improve over vanilla RNNs, they **still struggle** with dependencies spanning hundreds or thousands of time steps.
- The memory cell helps, but it's not perfect — gradients can still diminish over very long sequences.

... Example:

In a document, connecting a noun introduced 100 sentences earlier to a pronoun now is often beyond an LSTM's capacity.

---

### 3 *Fixed-Length Hidden State Bottleneck*

- All sequence information must be compressed into a **fixed-size hidden vector** (`ht`).

- This forces the model to “stuff” all context into a limited-size memory — leading to **information loss** for long texts.
- 

## B. Computational Limitations

### 4 *Slow Training and Inference*

- Sequential nature + many gates → computationally heavy.
  - Backpropagation through time (BPTT) makes gradient updates slow.
  - More parameters per cell than simple RNNs or GRUs.
- 

### 5 *Memory Usage*

- LSTMs store multiple gates (input, forget, output, and cell) per timestep, so memory consumption can be high.
  - Especially problematic for long sequences or large batch sizes.
- 

## C. Practical Limitations

### 6 *Hard to Scale*

- Increasing LSTM depth (many layers) leads to **unstable training** and **gradient issues** again.
  - Transformers, by contrast, can scale up to hundreds of layers stably with residual connections and normalization.
- 

### 7 *Difficult to Model Global Context*

- LSTMs process input **in order** (left-to-right or bidirectional), but they lack **direct connections** between distant tokens.
  - This limits their ability to capture **global relationships** (e.g., between subject and verb far apart).
- 

### 8 *Poor Interpretability*

- Internal gating dynamics are hard to interpret or visualize.
  - Unlike attention maps in Transformers, you can't easily see what the model is focusing on.
-