

---

**sample-maven-site**  
**v. 1.0.0-SNAPSHOT**  
**User Guide**

---



# Indice

<b>Indice</b> .....	<b>i</b>
1. <b>Introduzione</b> .....	<b>1</b>
2. <b>Guide</b> .....	<b>2</b>
2.1. Quick reference .....	3
2.2. Markdown sample .....	4
2.3. Esempi mermaid .....	8



# 1 Introduzione

---

## Introduzione

Esempio di documentazione generata con il [maven site plugin](#)

## 2 Guide

.....  
Guide

## 3 Quick reference

---

### Quick reference

#### 3.1 Comandi MAVEN per creazione sito

Task	Comando	Output root
Creazione documentazione	<code>mvn clean site</code>	<code>\${project.basedir}/target/site</code>
Pubblicazione su repository remoto	<code>mvn clean site-deploy</code>	Github /AzureDevops

#### 3.2 Doxia

[Doxia formati di riferimento](#)

#### 3.3 Configurazione plugin checkstyle

[https://checkstyle.sourceforge.io/version/4.4/5.x/config\\_javadoc.html](https://checkstyle.sourceforge.io/version/4.4/5.x/config_javadoc.html)

## 4 Markdown sample

### MARKDOWN

#### 4.1 Header

A First Level Header with =

or

A First Level Header with #

#### 4.2 A Second Level Header with --

or

#### 4.3 A Second Level Header with ##

##### 4.3.1 Header 3 with ###

#### 4.4 HTML link

- with HTML [Markdown syntax reference](#)
- This is [an example](#) inline link.
- [This link](#) has no title attribute.
- Automatic link <http://example.com/>

#### 4.5 BLOCKQUOTE

This is a blockquote.

This is the second paragraph in the blockquote.

#### 4.6 This is an H2 in a blockquote

#### 4.7 TABLE

Colons can be used to align columns.

Tables	Are	Cool
col 3 is	right-aligned	\$1600
col 2 is	centered	\$12
zebra stripes	are neat	\$1

There must be at least 3 dashes separating each header cell. The outer pipes (|) are optional, and you don't need to make the raw Markdown line up prettily. You can also use inline Markdown.

Markdown	Less	Pretty
<i>Still</i>	renders	<b>nicely</b>



1

2

3

## 4.8 CODE BLOCK

This is a normal html paragraph:

```
This is a code block with html
```

One level of indentation — 4 spaces or 1 tab — is removed from each line of the code block. For example, this: Here is an example of AppleScript:

```
tell application "Foo"
    beep
end tell
```

### 4.8.1 Codeblock with space

```
You can also indent
blocks to display
code or poetry.
```

```
Indented code/poetry blocks
can be hard-wrapped.
```

Or, wrap your code in three backticks:

```
function codeBlocks() {
    return "Can be inserted"
}
```

```
function test() {
    console.log("Print status");
}
```

## 4.9 STYLE

This is a paragraph with ~style~ *italic italic* **bold bold**

## 4.10 IMAGE AND LINK



Hello [link](#)

Hello [link](#) from Italy

Hello from [link](#) to **everyone** reading this

Here's an **important** [anchor link](#).

line 1 line 2

### 4.10.1 Block Quotes

You can insert quotes by preceeding each line with >.

Blockquotes can also contain line breaks.

## 4.11 Lists

### 4.11.1 Unordered lists

- Unordered
- Lists
- Hello

### 4.11.2 Ordered lists

1. Ordered
  2. Lists
  3. Numbers are ignored
  4. Ordered
- 
1. Ordered lists can start
  2. with any number and
  3. use . as well as ) as a separator.

### 4.11.3 Task lists

- [ ] Task 1
- [x] Task 2
- [ ] Task 3
- Regular list item

## 5 Esempi mermaid

---

### Esempio con Mermaid

- con mermaid.js

```
graph TD; A-->B; A-->C; B-->D; C-->D; sequenceDiagram participant Alice participant Bob Alice->>John: Hello John, how are you? loop Healthcheck John->>John: Fight against hypochondria end Note right of John: Rational thoughts prevail! John-->>Alice: Great! John->>Bob: How about you? Bob-->>John: Jolly good!
```

- con AzureDevops