
sample-maven-site
v. 1.0.0-SNAPSHOT
User Guide

Indice

Indice	i
1. Introduzione	1
2. Guide	2
2.1. Quick reference	3
2.2. Markdown sample	4
2.3. Esempi mermaid	9

1 Introduzione

Introduzione

Esempio di documentazione generata con il [maven site plugin](#)

2 Guide

.....
Guide

3 Quick reference

Quick reference

3.1 Comandi MAVEN per creazione sito

Task	Comando	Output root
Creazione documentazione	<code>mvn clean site</code>	<code>\${project.basedir}/target/site</code>
Pubblicazione su repository remoto	<code>mvn clean site-deploy</code>	Github /AzureDevops

3.2 Doxia

Doxia formati di riferimento

3.3 Configurazione plugin checkstyle

https://checkstyle.sourceforge.io/version/4.4/5.x/config_javadoc.html

4 Markdown sample

MARKDOWN

4.1 Header

A First Level Header with =
or

A First Level Header with #

4.2 A Second Level Header with --

or

4.3 A Second Level Header with

4.3.1 Header 3 with

4.4 HTML link

- with HTML [Markdown syntax reference](#)
- This is [an example](#) inline link.
- [This link](#) has no title attribute.
- Automatic link <http://example.com/>
- *Hello [link](#)*
- Hello *[link](#)* from Italy
- Hello from *[link](#)* to **everyone** reading this
- Here's an [important anchor link to style](#).

4.5 BLOCKQUOTE

This is a blockquote.

This is the second paragraph in the blockquote.

4.6 This is an H2 in a blockquote

Regular line

You can insert quotes by preceeding each line with >.

Blockquotes can also contain line breaks.

4.7 TABLE

Colons can be used to align columns.

Tables	Are	Cool
col 3 is	right-aligned	\$1600
col 2 is	centered	\$12

zebra stripes	are neat	\$1
---------------	----------	-----

There must be at least 3 dashes separating each header cell. The outer pipes (|) are optional, and you don't need to make the raw Markdown line up prettily. You can also use inline Markdown.

Markdown	Less	Pretty
<i>Still</i>	renders	nicely
1	2	3

4.8 CODE BLOCK

This is a normal html paragraph:

```
This is a code block with html
```

One level of indentation — 4 spaces or 1 tab — is removed from each line of the code block. For example, this: Here is an example of AppleScript:

```
tell application "Foo"
    beep
end tell
```

4.8.1 Codeblock with space

```
You can also indent
blocks to display
code or poetry.

Indented code/poetry blocks
can be hard-wrapped.
```

Or, wrap your code in three backticks:


```
function codeBlocks() {
    return "Can be inserted"
}
```


```
function test() {  
  console.log("Print status");  
}
```

4.9 STYLE

This is a paragraph with *~style~ italic italic* **bold bold**

4.10 IMAGE





4.11 Lists

4.11.1 Unordered lists

- Unordered
- Lists
- Hello

4.11.2 Ordered lists

1. Ordered
 2. Lists
 3. Numbers are ignored
 4. Ordered
-
1. Ordered lists can start
 2. with any number and
 3. use . as well as) as a separator.

4.11.3 Task lists

- [] Task 1
- [x] Task 2
- [] Task 3
- Regular list item

5 Esempi mermaid

Esempio con Mermaid

- con mermaid.js

```
graph TD
  A[Developer writes Code and Docs] -->|commit| B[Code and Docs review and Testing]
  B --> C{Release?}
  C -->|Yes| D[Artifacts and Docs are published]
  C -->|No| A
  A --> Write
  Write --> Review
  Review --> Test
  Test --> Write
  Write --> Merge
  Merge --> Build
  Build --> Deploy
  Build --> Write
  Deploy --> Write
  Write --> [*]
```

sequenceDiagram
 participant Alice
 participant Bob
 Alice->>John: Hello John, how are you?
 loop Healthcheck
 John->>John: Fight against hypochondria
 end
 Note right of John: Rational thoughts prevail!
 John->>Alice: Great!
 John->>Bob: How about you?
 Bob->>John: Jolly good!

- con AzureDevops