# PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
# บริษัท ปิโตรเลี่ยม อควปเม้นท์ (ไทยแลนด์) จำกัด

## MILL TEST CERTIFICATE EN10204 3.1, GOST 10692

| Customer | FORPOST-M LTD | Certificate №: | 20260310005-5 | PO: | PETH-3003-UA, SP.15 |
|---|---|---|---|---|---|
| Purchaser | FORPOST-M LTD | Date of Issue: | 2026.03.10 | Specification: | DSTU 8938:2019 |
| Product: | Hot rolled seamless carbon steel pipe | Length: | 3.5-12m | Flatten | GOOD |

| No | Grade | Heat No | Dimension | | Quantity | | Chemical Composition | | | | | | | | Physical Property | | | NDT/HP |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | (mm) Diameter | (mm) Thickness | BUNDLES | Weight, tons | C | Si | Mn | P | S | Ni | Cr | Cu | TENSILE STRENGTH (Mpa) | YIELD STRENGTH (Mpa) | ELONGATION EL(%) | |
| 1 | 20# | C251025 | 89x16 | | 2 | 5.052 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 | NDT |
| 2 | 20# | A251026 | 108x16 | | 4 | 9.985 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 | NDT |
| 3 | 20# | F251027 | 168x16 | | 1 | 2.881 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 | NDT |
| 4 | 20# | D251037 | 168x18 | | 1 | 2.361 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 | NDT |
| 5 | 20# | B250938 | 180x16 | | 2 | 3.055 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 | NDT |
| 6 | 20# | E251039 | 273x18 | | 4 | 4.681 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 | NDT |
| 7 | 20# | C251026 | 325x16 | | 3 | 4.442 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 | NDT |
| 8 | 20# | A251027 | 426x16 | | 1 | 1.955 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 | NDT |
| 9 | 20# | F251028 | 530x 8 | | 5 | 5.453 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 | NDT |
| 10 | 20# | D251038 | 530x10 | | 5 | 5.451 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 | NDT |
| 11 | 20# | B250939 | 530x12 | | 2 | 2.793 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 | NDT |
| 12 | 20# | E251040 | 530x20 | | 2 | 4.129 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 | NDT |
| Total: | | | | | 32 | 52.238 | | | | | | | | | | | | |

| Surveyor: | We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements.<br>Residual Magnetism does not exceed 30 Gaus<br>The test result is only responsible for sample | Inspector: Chief: |
|---|---|---|
| | | Stamp of Mill Inspector |

PETROLEUM EQUIPMENT (THAILAND) CO., LTD. PET QC PASS