PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
บริษัท ปิโตรเลี่ยม อควปเม้นท์ (ไทยแลนด์) จำกัด

MILL TEST CERTIFICATE EN10204 3.1, GOST 10692

Customer			FORPOST-M LTD			Certificate №:	20260310005-2		PO:	PETH-3003-UA, SP.15										
Purchaser			FORPOST-M LTD			Date of Issue:	2026.03.10		Specification:	DSTU 8938:2019										
Product:			Hot rolled seamless carbon steel pipe			Length:	3.5-12m		Flatten	GOOD										
No	Grade	Heat No	Dimension		Quantity		Chemical Composition										Physical Property			NDT/HP
			(mm) Diameter	(mm) Thickness	BUNDLES	Weight, tons	C	Si	Mn	P	S	Ni	Cr	Cu			TENSILE STRENGTH (Mpa)	YIELD STRENGTH (Mpa)	ELONGATION EL(%)	
1	20#	D251030	102x20		1	2.784	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006			479	279	32	NDT
2	20#	B250931	102x22		2	4.146	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007			485	280	31	NDT
3	20#	E251032	108x25		1	2.881	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007			481	280	30	NDT
4	20#	C251019	114x20		2	5.311	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006			479	279	32	NDT
5	20#	A251020	127x28		1	2.034	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007			485	280	31	NDT
6	20#	F251021	127x30		2	4.038	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007			481	280	30	NDT
7	20#	D251031	133x20		2	3.195	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007			485	280	31	NDT
8	20#	B250932	140x20		2	5.395	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007			481	280	30	NDT
9	20#	E251033	146x16		2	3.156	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006			479	279	32	NDT
10	20#	C251020	152x36		1	2.101	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007			485	280	31	NDT
11	20#	A251021	159x36		2	4.02	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007			481	280	30	NDT
12	20#	F251022	168x22		2	4.922	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006			479	279	32	NDT
13	20#	D251032	168x32		2	3.146	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007			481	280	30	NDT
Total:					22	47.129														

Surveyor:

We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements.
Residual Magnetism does not exceed 30 Gaus
The test result is only responsible for sample

Inspector: Chief:

Stamp of Mill Inspector

PETROLEUM EQUIPMENT (THAILAND) CO., LTD. PET QC PASS