# PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
# บริษัท ปิโตรเลี่ยม อควปเม้นท์ (ไทยแลนด์) จำกัด

## MILL TEST CERTIFICATE EN10204 3.1, GOST 10692

| Customer | | | FORPOST-M LTD | | | | Certificate №: | | | 20251008001 | | | PO: | | PETH-3003-UA, SP.14 | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Purchaser | | | FORPOST-M LTD | | | | Date of Issue: | | | 2025.10.08 | | | Specification: | | DSTU 8938:2019 | | |
| Product: | | | Hot rolled seamless carbon steel pipe | | | | Length: | | | 4--5.8 | | | Flatten | | GOOD | | |
| No | Grade | Heat No | Dimension | | Quantity | | Chemical Composition | | | | | | | | Physical Property | | |
| | | | (mm) Diameter | (mm) Thickness | BUNDLES | Weight, tons | C | Si | Mn | P | S | Ni | Cr | Cu | TENSILE STRENGTH (Mpa) | YIELD STRENGTH (Mpa) | ELONGATION EL(%) |
| 1 | 20# | D250713 | 60x14 | | 1 | 3.096 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 2 | 45# | B250714 | 60x14 | | 1 | 2.11 | 0.45 | 0.27 | 0.6 | 0.011 | 0.005 | 0.01 | 0.013 | 0.007 | 605 | 340 | 20 |
| 3 | 20# | C250619 | 102x18 | | 2 | 4.81 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 |
| 4 | 20# | A250702 | 108x22 | | 2 | 5.436 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 5 | 20# | E250614 | 114x16 | | 2 | 4.976 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 6 | 20# | D250714 | 121x16 | | 2 | 4.09 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 7 | 20# | B250715 | 121x20 | | 2 | 4.072 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 8 | 20# | C250620 | 121x25 | | 1 | 2.934 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 9 | 20# | A250703 | 127x16 | | 2 | 4.97 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 10 | 20# | E250615 | 127x20 | | 2 | 4.496 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 11 | 20# | D250715 | 127x25 | | 1 | 2.884 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 |
| 12 | 20# | B250716 | 133x25 | | 1 | 2.694 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 13 | 20# | C250621 | 133x30 | | 2 | 3.446 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 14 | 20# | A250704 | 203x36 | | 2 | 3.154 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 |
| 15 | 20# | E250616 | 245x18 | | 2 | 4.902 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 16 | 20# | D250716 | 245x20 | | 2 | 5.898 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 17 | 20# | B250717 | 245x25 | | 2 | 4.748 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 |
| 18 | 20# | C250622 | 245x30 | | 2 | 6.456 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 19 | 20# | A250705 | 245x50 | | 2 | 4.574 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 |
| 20 | 20# | E250617 | 245x60 | | 1 | 2.436 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |

PETROLEUM EQUIPMENT (THAILAND) CO.,LTD.
PET
QC PASS

| | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 21 | 20# | D250717 | 273x16 | 12 | 4.982 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 22 | 20# | B250718 | 273x20 | 6 | 3.146 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 |
| 23 | 20# | C250623 | 299x30 | 4 | 4.182 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 24 | 20# | A250706 | 299x50 | 4 | 6.186 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 25 | 20# | E250618 | 325x25 | 6 | 4.838 | 0.2 | 0.26 | 0.47 | 0.012 | 0.006 | 0.009 | 0.011 | 0.007 | 481 | 280 | 30 |
| 26 | 20# | D250718 | 325x30 | 2 | 2.116 | 0.21 | 0.26 | 0.48 | 0.013 | 0.005 | 0.009 | 0.012 | 0.006 | 479 | 279 | 32 |
| 27 | 20# | B250719 | 508x32 | 2 | 3.302 | 0.19 | 0.27 | 0.51 | 0.011 | 0.006 | 0.01 | 0.013 | 0.007 | 485 | 280 | 31 |
| Total: | | | | 70 | 110.934 | | | | | | | | | | | |

| | | |
|---|---|---|
| Surveyor: | We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements.<br>Residual Magnetism does not exceed 30 Gaus<br>The test result is only responsible for sample | Inspector: Chief:<br>Stamp of Mill Inspector |

PETROLEUM EQUIPMENT (THAILAND) CO., LTD. PET QC PASS