PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
บริษัท ปิโตรเลียม อีควิปเม้นท์ (ไทยแลนด์) จำกัด

MILL TEST CERTIFICATE

Consignee-Buyer:			LLC "TPC INVESTMASH" UKRAINE, 49047, DNIPROPETROVSK REGION, DNIPRO CITY, STR. ROBOCHA, BUILDING 91, FLAT 40				Certificate №:			20250730001			Commercial Invoice:		C42 DD 30.07.2025				
							Date of Issue:			30.07.2025			Specification:		DSTU 8938:2019				
Product:			Hot rolled seamless steel pipe										Flatten		GOOD				
No	Grade	Heat No	Dimension		Quantity		Length	Chemical Composition								Physical Property			NDT/HP
			OD (mm)	WT (mm)	PCS	Weight, tons	mm	C	Si	Mn	P	S	Ni	Cr	Cu	TENSILE STRENGTH (Mpa)	YIELD STRENGTH (Mpa)	ELONGATION EL (%)	
1	20	B250308	25	4,0	52	1,012	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	476	278	31	NDT
2	20	D250211	32	6,0	139	0,995	1920	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	478	276	30	NDT
3	20	D250211	32	6,0	93	0,860	2400	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
4	20	D250211	32	6,0	116	1,320	2920	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
5	20	D250211	32	6,0	213	2,732	3234	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	478	276	30	NDT
6	20	C250217	33,7	4,0	63	1,875	11000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
7	20	E250312	40	5,0	46	1,500	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
8	45	B250309	40	10,0	9	0,432	6000-12000	0,45	0,27	0,6	0,012	0,006	0,009	0,013	0,007	606	340	20	NDT
9	20	D250212	42	10,0	9	0,486	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	476	278	31	NDT
10	20	C250218	57	10,0	26	1,965	6000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	478	276	30	NDT
11	20	A250316	60	3,5	12	0,466	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
12	20	E250313	63,5	12,0	9	1,044	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
13	20	B250310	70	12,0	8	0,942	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	476	278	31	NDT
14	20	D250213	70	14,0	5	1,116	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	478	276	30	NDT
15	20	C250219	76	8,0	8	0,928	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
16	20	A250317	76	12,0	23	2,968	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
17	45	E250314	76	12,0	6	0,902	6000-12000	0,45	0,27	0,6	0,012	0,006	0,009	0,013	0,007	606	340	20	NDT
18	20	B250311	76	14,0	5	1,144	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	476	275	30	NDT

PETROLEUM EQUIPMENT (THAILAND) CO., LTD. QC PASS

19	45	D250214	76	16,0	3	0,802	6000-12000	0,45	0,27	0,6	0,012	0,006	0,009	0,013	0,007	606	340	20	NDT
20	20	C250220	80	10,0	7	0,928	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
21	20	A250318	80	12,0	4	0,906	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
22	45	E250315	83	18,0	3	0,896	6000-12000	0,45	0,27	0,6	0,012	0,006	0,009	0,013	0,007	606	340	20	NDT
23	45	B250312	89	18,0	3	1,052	6000-12000	0,45	0,27	0,6	0,012	0,006	0,009	0,013	0,007	606	340	20	NDT
24	20	D250215	89	22,0	6	2,430	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	476	278	31	NDT
25	20	C250221	89	25,0	3	1,194	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	478	276	30	NDT
26	20	A250319	95	12,0	7	1,910	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
27	20	E250316	95	14,0	4	1,060	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
28	20	B250313	102	10,0	6	1,418	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	476	278	31	NDT
29	20	D250216	102	12,0	4	1,066	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	478	276	30	NDT
30	20	C250222	102	16,0	3	1,202	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
31	20	A250320	108	16,0	5	2,018	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
32	20	E250317	108	18,0	15	5,962	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	476	278	31	NDT
33	20	B250314	114	10,0	3	0,950	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	478	276	30	NDT
34	20	D250217	121	16,0	2	0,802	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
35	20	C250223	159	22,0	2	1,606	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
36	20	A250321	180	32,0	1	1,056	6000-12000	0,21	0,26	0,48	0,013	0,005	0,009	0,012	0,006	475	275	30	NDT
37	20	E250318	219	8,0	2	1,040	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
38	45	B250315	245	20,0	1	1,354	6000-12000	0,45	0,27	0,6	0,012	0,006	0,009	0,013	0,007	606	340	20	NDT
39	20	D250218	273	28,0	2	2,128	6000-12000	0,2	0,25	0,47	0,012	0,004	0,008	0,012	0,005	480	280	31	NDT
Total:					**928**	**54,467**													

Surveyor:	We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements. Residual Magnetism does not exceed 30 Gaus The test result is only responsible for sample	Inspector:	Chief:
		Stamp of Mill Inspector	

PETROLEUM EQUIPMENT (THAILAND) CO., LTD. PET