PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
บริษัท ปิโตรเลี่ยม อควปเม้นท์ (ไทยแลนด์) จำกัด

MILL TEST CERTIFICATE EN10204 3.1, GOST 10692

Customer			FORPOST-M LTD				Certificate №:			20250926001			PO:		PETH-3003-UA, SP.12			
Purchaser			FORPOST-M LTD				Date of Issue:			2025.09.26			Specification:		DSTU 8938:2019			
Product:			Hot rolled seamless carbon steel pipe				Length:			4--12			Flatten		GOOD			
No	Grade	Heat No	Dimension		Quantity		Chemical Composition								Physical Property			NDT/HP
			(mm) Diameter	(mm) Thickness	BUNDLES	Weight, tons	C	Si	Mn	P	S	Ni	Cr	Cu	TENSILE STRENGTH (Mpa)	YIELD STRENGTH (Mpa)	ELONGATION EL(%)	
1	20#	C250613	70x16		2	4.194	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
2	20#	E250514	83x16		2	5.266	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
3	20#	D250519	83x22		1	2.548	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
4	45#	B250602	83x22		1	1.086	0.45	0.27	0.6	0.011	0.005	0.01	0.013	0.007	605	340	20	NDT
5	20#	C250614	89x20		2	6.28	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
6	20#	E250515	89x25		2	4.732	0.21	0.27	0.51	0.011	0.005	0.01	0.013	0.007	481	279	31	NDT
7	20#	D250520	127x30		2	4.762	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
8	20#	B250603	140x30		2	4.032	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
9	20#	C250615	273x45		6	7.234	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
10	20#	E250516	273x50		4	5.456	0.21	0.27	0.51	0.011	0.005	0.01	0.013	0.007	481	279	31	NDT
11	20#	D250521	299x50		2	2.942	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
12	20#	B250604	530x20		4	4.024	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
13	20#	C250616	530x60		1	2.912	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
14	20#	E250517	95x16		3	7.912	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
15	20#	D250522	180x20		2	4.87	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
16	20#	B250605	180x30		1	3.346	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
17	20#	C250617	530x12		3	4.084	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
18	20#	E250518	630x10		7	7.524	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
Total:					47	83.204												

Surveyor:	We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements. Residual Magnetism does not exceed 30 Gaus The test result is only responsible for sample	Inspector: Chief Stamp of Mill Inspector

PETROLEUM EQUIPMENT (THAILAND) CO., LTD. PET QC PASS