PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
บริษัท ปิโตรเลี่ยม อควปเม้นท์ (ไทยแลนด์) จำกัด

MILL TEST CERTIFICATE EN10204 3.1, GOST 10692

Customer			FORPOST-M LTD				Certificate №:		20250417005-2				PO:		PETH-3003-UA, SP.10				
Purchaser			FORPOST-M LTD				Date of Issue:		2025.04				Specification:		DSTU 8938:2019				
Product:			Hot rolled seamless carbon steel pipe				Length:		4--12m				Flatten		GOOD				
No	Grade	Heat No	Dimension		Quantity		Chemical Composition								Physical Property			NDT/HE	
			(mm) Diameter	(mm) Thickness	BUNDLES	Weight, tons	C	Si	Mn	P	S	Ni	Cr	Cu	TENSILE STRENGTH (Mpa)	YIELD STRENGTH (Mpa)	ELONGATION EL(%)		
1	20	D241018	508x32		2	2.378	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT	
2	20	B241019	530x20		6	6.060	0.20	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT	
3	20	C241020	530x25		4	4.786	0.20	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT	
4	20	A241021	530x60		1	2.336	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	31	NDT	
5	20	D241019	630x30		1	2.324	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT	
6	20	D241109	108x16		7	18.510	0.20	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT	
7	20	B241110	530x 8		4	3.262	0.20	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT	
8	20	C241111	530x10		4	4.376	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	31	NDT	
9	20	A241112	530x12		2	3.772	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT	
10	20	D241110	530x14		5	6.900	0.20	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT	
11	20	B241111	530x16		3	5.786	0.20	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT	
12	20	C241112	630x10		3	3.228	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	31	NDT	
13	20	A241113	630x12		5	5.900	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT	
Total:					47	69.618													

Surveyor:	We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements. Residual Magnetism does not exceed 30 Gaus The test result is only responsible for sample	Inspector: Chief Stamp of Mill Inspector