PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
บริษัท ปิโตรเลี่ยม อควปเม้นท์ (ไทยแลนด์) จำกัด

MILL TEST CERTIFICATE EN10204 3.1, GOST 10692

Customer			FORPOST-M LTD				Certificate №:				202500815001-1			PO:	PETH-3003-UA, SP.11			
Purchaser			FORPOST-M LTD				Date of Issue:				2025.08			Specification:	DSTU 8938:2019			
Product:			Hot rolled seamless carbon steel pipe				Length:				4--5.8			Flatten	GOOD			
No	Grade	Heat No	Dimension		Quantity		Chemical Composition								Physical Property			
			(mm) Diameter	(mm) Thickness	BUNDLES	Weight, tons	C	Si	Mn	P	S	Ni	Cr	Cu	TENSILE STRENGTH (Mpa)	YIELD STRENGTH (Mpa)	ELONGATION EL(%)	NDT/HP
1	20#	B250512	73x16		1	0.938	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
2	45#	D250611	73x16		1	1.082	0.45	0.27	0.6	0.011	0.005	0.01	0.013	0.007	605	340	20	NDT
3	20#	A250517	73x20		2	4.138	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
4	20#	C250612	83x18		2	4.854	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
5	20#	E250513	89x16		3	5.954	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
6	45#	B250513	89x16		1	0.966	0.45	0.27	0.6	0.011	0.005	0.01	0.013	0.007	605	340	20	NDT
7	20#	D250612	95x18		2	3.218	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
8	20#	A250518	102x18		2	5.342	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
9	20#	C250613	102x28		2	4.054	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
10	45#	E250514	102x28		2	3.236	0.45	0.27	0.6	0.011	0.005	0.01	0.013	0.007	605	340	20	NDT
11	20#	B250514	108x30		1	2.82	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
12	20#	D250613	180x25		2	5.314	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
13	20#	A250519	245x40		2	5.828	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
4	20#	C250614	245x45		2	4.004	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
5	20#	E250515	273x40		5	3.916	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
6	20#	B250515	273x42		3	2.362	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
7	20#	D250614	325x35		5	6.244	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
	20#	A250520	325x45		2	2.902	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT

PETROLEUM EQUIPMENT (THAILAND) CO., LTD. PET COMPASS

19	20#	C250615	325x60	4	5.468	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
20	20#	E250516	351x35	3	3.462	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
21	20#	B250516	351x60	2	3.636	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
22	20#	D250615	377x50	2	3.712	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
23	20#	A250521	406x20	2	1.714	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
24	20#	C250616	457x40	2	2.724	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
25	20#	E250517	457x60	1	2.63	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
26	20#	B250517	480x40	2	3.136	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
27	20#	D250616	508x12	4	2.478	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
28	20#	A250522	530x35	2	3.496	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
29	20#	C250617	630x16	6	5.268	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31	NDT
30	20#	E250518	630x20	2	2.136	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30	NDT
31	20#	B250518	630x40	2	3.94	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32	NDT
Total:				74	110.972												

Surveyor:	We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements. Residual Magnetism does not exceed 30 Gaus The test result is only responsible for sample	Inspector:
		Stamp of Mill Inspector

PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
PET
QC PASS