PETROLEUM EQUIPMENT (THAILAND) CO., LTD.
บริษัท ปิโตรเลี่ยม อควปเม้นท์ (ไทยแลนด์) จำกัด

MILL TEST CERTIFICATE EN10204 3.1, GOST 10692

Customer	FORPOST-M LTD	Certificate №:	20251008001	PO:	PETH-3003-UA, SP.14
Purchaser	FORPOST-M LTD	Date of Issue:	2025.10.08	Specification:	DSTU 8938:2019
Product:	Hot rolled seamless carbon steel pipe	Length:	4--5.8	Flatten	GOOD

No	Grade	Heat No	Dimension		Quantity		Chemical Composition								Physical Property		
			(mm) Diameter	(mm) Thickness	BUNDLES	Weight, tons	C	Si	Mn	P	S	Ni	Cr	Cu	TENSILE STRENGTH (Mpa)	YIELD STRENGTH (Mpa)	ELONGATION EL(%)
1	20#	D250713	60x14		1	3.096	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
2	45#	B250714	60x14		1	2.11	0.45	0.27	0.6	0.011	0.005	0.01	0.013	0.007	605	340	20
3	20#	C250619	102x18		2	4.81	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31
4	20#	A250702	108x22		2	5.436	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
5	20#	E250614	114x16		2	4.976	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32
6	20#	D250714	121x16		2	4.09	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
7	20#	B250715	121x20		2	4.072	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32
8	20#	C250620	121x25		1	2.934	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
9	20#	A250703	127x16		2	4.97	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32
10	20#	E250615	127x20		2	4.496	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
11	20#	D250715	127x25		1	2.884	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31
12	20#	B250716	133x25		1	2.694	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
13	20#	C250621	133x30		2	3.446	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32
14	20#	A250704	203x36		2	3.154	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31
15	20#	E250616	245x18		2	4.902	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
16	20#	D250716	245x20		2	5.898	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	32
17	20#	B250717	245x25		2	4.748	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31
18	20#	C250622	245x30		2	6.456	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30
19	20#	A250705	245x50		2	4.574	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	31
20	20#	E250617	245x60		1	2.436	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	30

PETROLEUM EQUIPMENT (THAILAND) CO.,LTD. PET QC PASS

21	20#	D250717	273x16	12	4.982	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	
22	20#	B250718	273x20	6	3.146	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	
23	20#	C250623	299x30	4	4.182	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	
24	20#	A250706	299x50	4	6.186	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	
25	20#	E250618	325x25	6	4.838	0.2	0.26	0.47	0.012	0.006	0.009	0.011	0.007	481	280	
26	20#	D250718	325x30	2	2.116	0.21	0.26	0.48	0.013	0.005	0.009	0.012	0.006	479	279	
27	20#	B250719	508x32	2	3.302	0.19	0.27	0.51	0.011	0.006	0.01	0.013	0.007	485	280	
Total:				70	110.934											

Surveyor:	We certify that all products has been manufactured, sampled, tested and inspected in accordance with the DSTU 8938:2019 and was found to meet the requirements. Residual Magnetism does not exceed 30 Gaus The test result is only responsible for sample	Inspector: Stamp of Mill Inspector

PETROLEUM EQUIPMENT (THAILAND)
PET
Chief
QC PASS