

Modeling Basic Aspects of Cyber-Physical Systems, Part II

Yingfu Zeng*, Chad Rose*, Paul Brauner*, Walid Taha* **, **Jawad Masood****, Roland Philippsen**,
Marcia O'Malley*, and Robert Cartwright *

* Rice University, USA

**Halmstad University, Sweden

Motivation

- Educating designers
- Developing expressive, efficient, and robust modeling and simulation tool

Vision



Design better simulation tool to support virtual testing and analysis of **cyber-physical systems** at both **industrial** and **academic** levels.

Problem



Today to model and analyze a cyber physical system, one need to connect several domains, this brings forward the challenge of adding features to support **innovative design process**.

[illegible]


We are working on a tool called **Acumen**.
Small language for hybrid systems modeling.
We use Acumen to model and analyze two
sophisticated standard **robotics** examples and
add features to support **design innovation
process**.

Newtonian and Lagrangian Formulations

- Why Newtonian?
 - Non-conservative forces
 - Vector base
 - Solve constraints equations
- Why Lagrangian?
 - Direct specification
 - Calculate potential and kinetic energies
 - Compact without constraints


Case Study 1- Quadcopter

- Complex mechatronic system
- 6-degree of freedom
- Underactuation
- Cover different domains



Case Study 1- Quadcopter

- Mathematical Model
 - Newton-Euler formulation
 - Vectors



$$\sum F = m\bar{a} = G + RT$$

$$\begin{bmatrix} \ddot{\phi} \\ \ddot{\theta} \\ \ddot{\psi} \end{bmatrix} = \begin{bmatrix} 0 \\ \dot{\phi}C_{\phi}T_{\theta} + \dot{\theta}\frac{S_{\phi}}{C_{\theta}^2} \\ -\dot{\phi}S_{\phi}C_{\theta} + \dot{\theta}\frac{C_{\phi}}{C_{\theta}^2} \end{bmatrix}$$

$$\begin{bmatrix} \ddot{x} \\ \ddot{y} \\ \ddot{z} \end{bmatrix} = -g \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix} + \frac{T}{m} \begin{bmatrix} C_{\psi}S_{\theta}\dot{C}_{\phi} + S_{\psi}S_{\phi} \\ S_{\psi}S_{\theta}C_{\phi} - C_{\psi}S_{\phi} \\ C_{\theta}C_{\phi} \end{bmatrix}$$

$$+ \nu + W_{\eta}^{-1}\dot{\nu}$$

Case Study 1- Quadcopter

- Acumen Model

Case Study 2a- Double Pendulum

- Mathematical Model
 - Lagrangian formulation
 - Generalized Coordinates

$$\forall i \in \{1 \dots |q|\}, \frac{d}{dt} \left(\frac{\partial L}{\partial \dot{q}_i} \right) - \frac{\partial L}{\partial q_i} = Q$$


- description of components

$$q = (\theta_1, \theta_2)$$

- define total kinetic and potential energy

$$T = \frac{1}{2} m_1 v_1^2 + \frac{1}{2} m_2 v_2^2$$


$$V = m_1 g z_1 + m_2 g z_2$$



Case Study 2a- Double Pendulum

- identify non-conservative forces

$$Q = 0$$





- substitution in Euler-Lagrangian equation

$$\ddot{\theta}_1 = m_2 l_2 (\ddot{\theta}_2 \cos(\theta_1 - \theta_2) + \dot{\theta}_2^2 \sin(\theta_1 - \theta_2) + (m_1 + m_2)g \cos(\theta_1)) / (-l_1(m_1 + m_2))$$

$$\ddot{\theta}_2 = m_2 l_1 (\ddot{\theta}_1 \cos(\theta_1 - \theta_2) - \dot{\theta}_1^2 \sin(\theta_1 - \theta_2) + m_2 g \cos(\theta_2)) / -l_1 m_2$$

Case Study 2- RICEWRIST

- Rehabilitation
- 3-degree of freedom
- Gibril
- Cover different domains



Case Study 2- RICEWRIST

- Mathematical Model
 - Lagrangian formulation
 - Generalized Coordinates

$$\forall i \in \{1 \dots |q|\}, \frac{d}{dt} \left(\frac{\partial L}{\partial \dot{q}_i} \right) - \frac{\partial L}{\partial q_i} = Q$$


- description of components

$$q = (\theta_1, \theta_2, \theta_3)$$

- define total kinetic and potential energy

$$V = m_1 g h_1 + m_2 g h_2 + m_3 g h_3$$

$$= -m_1 g l_2 \cos(\theta_1) + m_3 g l_3 \sin(\theta_1) \sin(\theta_3)$$




Case Study 2- RICEWRIST

- identify non-conservative forces

$$Q = 0$$


- substitution in Euler-Lagrangian equation

$$\frac{1}{2} \frac{d}{dt} \left(I_2 \frac{\partial \omega_2 \cdot \omega_2}{\partial \dot{\theta}_2} + I_3 \frac{\partial \omega_3 \cdot \omega_3}{\partial \dot{\theta}_2} \right) - \frac{1}{2} \left(I_2 \frac{\partial \omega_2 \cdot \omega_2}{\partial \theta_2} + I_3 \frac{\partial \omega_3 \cdot \omega_3}{\partial \theta_2} \right) = 0$$



Case Study 1- RICEWRIST

- Acumen Model



Summary

- Untyped core formulation.
- Effectively modeling.
- Newton-Euler formulation.
- Lagrangian formulation.
- Partial static derivatives inclusion.

Thank you for your attention!
Questions

Jawad.masood@hh.se
@jamatics