

Endpoint	Preconditions	Steps to reproduce	Expected result
Add a new pet to the store	-	Execute the following curl in Postman: <pre>curl -X 'POST' 'https://petstore.swagger.io/v2/pet' -H 'accept: application/json' -H 'Content-Type: application/json' -d '{ "id": 5, "category": { "id": 0, "name": "string" }, "name": "doggie", "photoUrls": ["string"], "tags": [{ "id": 0, "name": "string" }], "status": "available" }'</pre>	Response is status code 200 OK Body: <pre>{ "id": 5, "category": { "id": 0, "name": "string" }, "name": "doggie", "photoUrls": ["string"], "tags": [{ "id": 0, "name": "string" }], "status": "available" }</pre>
Add a new pet to the store without body	-	Execute the following curl in Postman: <pre>curl -X 'POST' 'https://petstore.swagger.io/v2/pet' -H 'accept: application/json' -H 'Content-Type: application/json'</pre>	Response is status code 405 Method not allowed Body: <pre>{ "code": 405, "type": "unknown", "message": "no data" }</pre>

Delete pet	Pet with id=5 exists in the store	Execute the following curl in Postman: curl -X 'DELETE' 'https://petstore.swagger.io/v2/pet/5' -H 'accept: application/json' -H 'api_key: special-key'	Response is status code 200 OK Body: { "code": 200, "type": "unknown", "message": "5" }
Delete pet tat does not exist	Pet with id=5 does not exist in the store	curl -X 'DELETE' 'https://petstore.swagger.io/v2/pet/5' -H 'accept: application/json' -H 'api_key: special-key'	Response is status code 404 Not found
Find pet by id	Pet with id=5 exists in the store	Execute the following curl in postman: curl -X 'GET' 'https://petstore.swagger.io/v2/pet/5' -H 'accept: application/json'	Response status code is 200 OK Body: { "id": 5, "category": { "id": 0, "name": "string" }, "name": "doggie", "photoUrls": ["string"], "tags": [{ "id": 0, "name": "string" }], "status": "available" }

Find pet by id that does not exist	Pet with id=18 does not exist	Execute the following curl in postman: curl -X 'GET' 'https://petstore.swagger.io/v2/pet/18' -H 'accept: application/json'	Response status code is 404 Not found Body: { "code": 1, "type": "error", "message": "Pet not found" }
Update pet	Pet with: id =5 name !=doggie status != available exists	Execute the following curl in postman: curl -X 'POST' 'https://petstore.swagger.io/v2/pet/5' -H 'accept: application/json' -H 'Content-Type: application/x-www-form-urlencoded' -d 'name=cat&status=sold'	Response status code is 200 OK Body: { "code": 200, "type": "unknown", "message": "5" }
Update pet that does not exist	Pet with id =10 does not exist	Execute the following curl in postman: curl -X 'POST' 'https://petstore.swagger.io/v2/pet/10' -H 'accept: application/json' -H 'Content-Type: application/x-www-form-urlencoded' -d 'name=cat&status=sold'	Response status code is 404 Not found Body: { "code": 404, "type": "unknown", "message": "not found" }
Create order	-	Execute the following curl in postman: curl -X 'POST' 'https://petstore.swagger.io/v2/store/order' -H 'accept: application/json' -H 'Content-Type: application/json' -d '{ "id": 1, "petId": 104804398545467, "quantity": 2,	Response status code is 200 OK Body: { "id": 1, "petId": 10480439854 5467,

		<pre>"shipDate": "2022-05-28T13:47:17.116+0000", "status": "approved", "complete": false }'</pre>	<pre>"quantity": 2, "shipDate": "2022-05-28T13:47:17.116+0000", "status": "approved", "complete": false }</pre>
Find order by id	Order with id=1 exists	<p>Execute the following curl in postman:</p> <pre>curl -X 'GET' 'https://petstore.swagger.io/v2/store/order/1' -H 'accept: application/json'</pre>	<p>Response status code is 200 OK</p> <p>Body:</p> <pre>{ "id": 1, "petId":104804398545467 , "quantity": 2, "shipDate": "2022-05-28T13:47:17.116+0000", "status": "approved", "complete": false }</pre>
Find order by id that does not exist	Order with id=100000 does not exist	<p>Execute the following curl in postman:</p> <pre>curl -X 'GET' 'https://petstore.swagger.io/v2/store/order/100000' -H 'accept: application/json'</pre>	<p>Response status code is 404 Not found</p> <p>Body:</p> <pre>{ "code": 1, "type": "error", "message": "Order not found" }</pre>

Delete order by id	Order with id=1 exists	Execute the following curl in postman: curl -X 'DELETE' 'https://petstore.swagger.io/v2/store/order/1' -H 'accept: application/json'	Response status code is 200 OK Body: { "code": 200, "type": "unknown", "message": "1" }
Delete order by id that does not exist	Order with id=15 does not exist	Execute the following curl in postman: curl -X 'DELETE' 'https://petstore.swagger.io/v2/store/order/15' -H 'accept: application/json'	Response status code is 404 Not found Body: { "code": 404, "type": "unknown", "message": "Order Not Found" }
Create user	-	Execute the following curl in postman: curl -X 'POST' 'https://petstore.swagger.io/v2/user' -H 'accept: application/json' -H 'Content-Type: application/json' -d '{ "id": 219793243182825, "username": "user", "firstName": "Ivan", "lastName": "Petrov", "email": "email", "password": "33a19eb0ee854f07a523b4b38ad937cb", "phone": "489d25375d9f43108c090d9a4cddb514", "userStatus": 1930 }'	Response status code is 200 OK Body: { "code": 200, "type": "unknown", "message": "219793243182825" }

Log in user	User with username=user and password=33a19eb0ee854f07a523b4b38ad937 exists	Execute the following curl in postman: curl -X 'GET' 'https://petstore.swagger.io/v2/user/login?username=user&password=33a19eb0ee854f07a523b4b38ad937cb' -H 'accept: application/json'	Response status code is 200 OK Body: { "code": 200, "type": "unknown", "message": "logged in user session:1654073299191" }
Delete user	User with username-user exists	curl -X 'DELETE' 'https://petstore.swagger.io/v2/user/user' -H 'accept: application/json'	Response status code is 200 OK Body: { "code": 200, "type": "unknown", "message": "user" }
Delete user that does not exist	User with username=user 123 does not exist	curl -X 'DELETE' 'https://petstore.swagger.io/v2/user/user123' -H 'accept: application/json'	Response status code is 404 Not found
Update user	User with username-user exists	curl -X 'PUT' 'https://petstore.swagger.io/v2/user/user' -H 'accept: application/json' -H 'Content-Type: application/json' -d '{ "id": 219793243182825, "username": "user", "firstName": "Ivan", "lastName": "Petrov", "email": "emailChanged", "password": "33a19eb0ee854f07a523b4b38ad937cb", "phone": "489d25375d9f43108c090d9a4cddb514", "userStatus": 1930 '	Response status code is 200 OK Body: { "code": 200, "type": "unknown", "message": "219793243182825" }

