
Enterprise Marketplace















This sheet is perfect for both developers and designers. It'll list all the structure controls and tests you can do with twig's engine. Assets, templates, filters, operators won't be a hard thing to remember with that sheet.



■ README.md

#Twig-Cheat-Sheet



This sheet is perfect for both developers and designers. It'll list all the structure controls and tests you can do with twig's engine. Assets, templates, filters, operators won't be a hard thing to remember with that sheet.

Table of Contents

- Operators
- Variables
- Filters
- Comment
- Whitespace Control
- Macro
- Escaping
- Control Structures
- Templates and Blocks
- Built-in Filters
- Global Functions
- Automatic Escaping
- Symfony2

Operators

Operator	Purpose
[not] in	Containment operator
is [not]	Test operator
	Creates a sequence
	Applies a filter
~	Concatenation
. or []	Gets an attribute of an object
?:	Ternary operator
{{ }}	Used to print the result of an expression evalution
{% %}	Used to execute statements

Variables

Print

```
{{ a_variable }}
{{ foo.bar }}
{{ foo['bar'] }}
```

Set

Filters

```
{{ foo|striptags }}
{% filter upper %}This text becomes uppercase{% endfilter %}
```

Back to top

Comment

```
{# single line comment #}
```

Back to top

Whitespace Control

```
remove white space inside the attribute {%- foo -%}
```

Back to top

Macro

```
{% macro link(url,label) %}
 <a href="{{ url }}"> {{ label }}</a>
{% endmacro %}
{{ _self.link('index.html','Home') }}
{% import "forms.html" as forms %}
{% from 'forms.html' import input as input_field %}
{{ form.input('foobar') }}
{{ input_field('foobar') }}
```

Back to top

Escaping

```
{{ '{{' }}}
{% raw %}
 {% set value = 'Lorem Ipsum' %}
 <h1>{{ value }}</h1>
{% endraw %}
```

Back to top

{{ key }} {% endfor %}

Control Structures

```
FOR
   {% for item in collection %} {{ item }} {% endfor %}
  {% for letter in 'a'..'z' %}
   {{ letter }}
  {% endfor %}
  {% for i in 0..9 %}
   {{ i }}
  {% endfor %}
  {% for item in collection %}
   {{ item }}
  {% else %}
   No item.
  {% endfor %}
  {% for i in range(0,10,2) %}
   {{ i }}
  {% endfor %}
  {% for item in collection %}
   {{ loop.index }}
  {% endfor %}
  {% for key in items | keys %}
```

ΙF

```
{% if foo %}
...
{% elseif bar %}
...
{% else %}
...
{% endif %}
```

Back to top

Templates and Blocks

```
Define a block (redefine is existing)

"" (% block sidebar %) ... (% endblock %) ""

Parent block

"" (% block sidebar %) {{ parent() }} {% endblock %} ""

Extends a template

"" (% extends "base.html.twig" %) ""

Include a template

"" (% include "header.html.twig" %) ""

Include with access options

"" (% include "header.html.twig" with { 'foo' : 'bar' } only %) ""

Import blocks from a template

"" (% use "blocks.html.twig" %) ""

Import blocks with alias

"" (% use "blocks.html.twig" with sidebar as base_sidebar %) ""

Call a block
```

```
``` {{ block('base_sidebar') }} ``` [Back to top](#twig-cheat-sheet)
##Built-in Filters date
 {{ post.created_at|date("d/m/Y") }}
 {{ "now" | date("d/m/Y") }}
format
 format {{ "I like %s and %s"|format(foo, 'bar') }}
replace
 {{ "Hello %name% !"|replace({'%name%': 'world'}) }}
 url_encode URL encodes a given string.
 json_encode Return the JSON representation of a given string.
 title
 Return a titlecased version of the value.
 capitalize Return a capitalized version of the value.
 upper
 Convert a value to uppercase
 lower
 Convert a value to lowercase
 striptags \mbox{Strips SGML/XML} tags and replace adjacent whitespaces by one space
join
 {{ [a, b, c]|join(', ') }} {# return "a,b,c" #}
 {{ [a, b, c]|join }} {# return abc #}
 Reverses an array or an object implementing the iterator interface
 reverse
 length
 Return the number of items of a sequence or array, or the length of a string
 sort
 Sort an array
default
 {{ var|default('var is not defined') }}
keys
 {% for key in array | keys %} ... {% endfor %}
 escape, e Convert a string to HTML-safe sequences.
```

raw Value will not be escaped

merge Merge an array with the value.

#### Back to top

##Global Functions range

```
{% for i in range(0, 3) %} {{ i }} {% endfor %}
{# returns 0, 1, 2, 3 #}
{% for i in range (0, 6, 2) %} {{ i }} {% endfor %}
```

cycle

```
{% for i in 0..10 %}
 {{ cycle(['odd', 'even'], i) }}
{% endfor %}
```

constant

```
Returns the constant value for a given string.
{{ some_date|date(constant('DATE_W3C')) }}
```

#### Back to top

##Automatic Escaping

```
{% autoescape %}
Everything will be automatically escaped in this block
using the HTML strategy
{% endautoescape %}
{% autoescape 'html' %}
Everything will be automatically escaped in this block
using the HTML strategy
{% endautoescape %}
{% autoescape 'js' %}
Everything will be automatically escaped in this block
using the js escaping strategy
{% endautoescape %}
{% autoescape false %}
Everything will be outputted as is in this block
{% endautoescape %}
```

#### Back to top

##Symfony2 Generate URL

```
{{ path('route_name', {'param': 'value'}) }}
```

Generate absolute URL

```
{{ url('route_name') }}
```

Link to Assets

```
<link rel="stylesheet" href="{{ asset('css/style.css') }}" type="text/css" />
```

© 2019 GitHub, Inc. Terms Privacy Security Status Help

Contact GitHub Pricing API Training Blog About