

Deep Generative Models

Lecture 4

Roman Isachenko

 Ozon Masters

Spring, 2022

Recap of previous lecture

Variational lower Bound (ELBO)

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \mathcal{L}(q, \boldsymbol{\theta}) + KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})) \geq \mathcal{L}(q, \boldsymbol{\theta}).$$

$$\mathcal{L}(q, \boldsymbol{\theta}) = \int q(\mathbf{z}) \log \frac{p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta})}{q(\mathbf{z})} d\mathbf{z} = \mathbb{E}_q \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - KL(q(\mathbf{z})||p(\mathbf{z}))$$

Log-likelihood decomposition

$$\log p(\mathbf{x}|\boldsymbol{\theta}) = \mathbb{E}_q \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - KL(q(\mathbf{z})||p(\mathbf{z})) + KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})).$$

- ▶ Instead of maximizing incomplete likelihood, maximize ELBO

$$\max_{\boldsymbol{\theta}} p(\mathbf{x}|\boldsymbol{\theta}) \rightarrow \max_{q, \boldsymbol{\theta}} \mathcal{L}(q, \boldsymbol{\theta})$$

- ▶ Maximization of ELBO by variational distribution q is equivalent to minimization of KL

$$\max_q \mathcal{L}(q, \boldsymbol{\theta}) \equiv \min_q KL(q(\mathbf{z})||p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta})).$$

Recap of previous lecture

EM-algorithm

► E-step

$$q^*(\mathbf{z}) = \arg \max_q \mathcal{L}(q, \boldsymbol{\theta}^*) = \arg \min_q KL(q(\mathbf{z}) || p(\mathbf{z}|\mathbf{x}, \boldsymbol{\theta}^*));$$

► M-step

$$\boldsymbol{\theta}^* = \arg \max_{\boldsymbol{\theta}} \mathcal{L}(q^*, \boldsymbol{\theta});$$

Amortized variational inference

Restrict a family of all possible distributions $q(\mathbf{z})$ to a parametric class $q(\mathbf{z}|\mathbf{x}, \phi)$ conditioned on samples \mathbf{x} with parameters ϕ .

Variational Bayes

► E-step

$$\phi_k = \phi_{k-1} + \eta \nabla_{\phi} \mathcal{L}(\phi, \boldsymbol{\theta}_{k-1})|_{\phi=\phi_{k-1}}$$

► M-step

$$\boldsymbol{\theta}_k = \boldsymbol{\theta}_{k-1} + \eta \nabla_{\boldsymbol{\theta}} \mathcal{L}(\phi_k, \boldsymbol{\theta})|_{\boldsymbol{\theta}=\boldsymbol{\theta}_{k-1}}$$

Recap of previous lecture

$$\mathcal{L}(\phi, \theta) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \left[\log p(\mathbf{x}|\mathbf{z}, \theta) - \log \frac{q(\mathbf{z}|\mathbf{x}, \phi)}{p(\mathbf{z})} \right] \rightarrow \max_{\phi, \theta}.$$

M-step: $\nabla_{\theta} \mathcal{L}(\phi, \theta)$, Monte Carlo estimation

$$\begin{aligned} \nabla_{\theta} \mathcal{L}(\phi, \theta) &= \int q(\mathbf{z}|\mathbf{x}, \phi) \nabla_{\theta} \log p(\mathbf{x}|\mathbf{z}, \theta) d\mathbf{z} \approx \\ &\approx \nabla_{\theta} \log p(\mathbf{x}|\mathbf{z}^*, \theta), \quad \mathbf{z}^* \sim q(\mathbf{z}|\mathbf{x}, \phi). \end{aligned}$$

E-step: $\nabla_{\phi} \mathcal{L}(\phi, \theta)$, reparametrization trick

$$\begin{aligned} \nabla_{\phi} \mathcal{L}(\phi, \theta) &= \int r(\epsilon) \nabla_{\phi} \log p(\mathbf{x}|g(\mathbf{x}, \epsilon, \phi), \theta) d\epsilon - \nabla_{\phi} \text{KL} \\ &\approx \nabla_{\phi} \log p(\mathbf{x}|g(\mathbf{x}, \epsilon^*, \phi), \theta) - \nabla_{\phi} \text{KL} \end{aligned}$$

Variational assumption

$$r(\epsilon) = \mathcal{N}(0, \mathbf{I}); \quad q(\mathbf{z}|\mathbf{x}, \phi) = \mathcal{N}(\mu_{\phi}(\mathbf{x}), \sigma_{\phi}^2(\mathbf{x})).$$

$$\mathbf{z} = g(\mathbf{x}, \epsilon, \phi) = \sigma_{\phi}(\mathbf{x}) \cdot \epsilon + \mu_{\phi}(\mathbf{x}).$$


Outline

1. Variational autoencoder (VAE)
2. Posterior collapse and decoder weakening techniques
3. Tighter variational bound

Outline

1. Variational autoencoder (VAE)
2. Posterior collapse and decoder weakening techniques
3. Tighter variational bound

Generative models zoo



Variational autoencoder (VAE)

Final EM-algorithm

- ▶ pick random sample $\mathbf{x}_i, i \sim U[1, n]$.
- ▶ compute the objective:

$$\epsilon^* \sim r(\epsilon); \quad \mathbf{z}^* = g(\mathbf{x}, \epsilon^*, \phi);$$

$$\mathcal{L}(\phi, \theta) \approx \log p(\mathbf{x}|\mathbf{z}^*, \theta) - KL(q(\mathbf{z}^*|\mathbf{x}, \phi)||p(\mathbf{z}^*)).$$

- ▶ compute a stochastic gradients w.r.t. ϕ and θ


$$\begin{aligned}\nabla_{\phi}\mathcal{L}(\phi, \theta) &\approx \nabla_{\phi} \log p(\mathbf{x}|g(\mathbf{x}, \epsilon^*, \phi), \theta) - \nabla_{\phi} KL(q(\mathbf{z}|\mathbf{x}, \phi)||p(\mathbf{z})); \\ \nabla_{\theta}\mathcal{L}(\phi, \theta) &\approx \nabla_{\theta} \log p(\mathbf{x}|\mathbf{z}^*, \theta).\end{aligned}$$

- ▶ update θ, ϕ according to the selected optimization method (SGD, Adam, RMSProp):

$$\begin{aligned}\phi &:= \phi + \eta \nabla_{\phi} \mathcal{L}(\phi, \theta), \\ \theta &:= \theta + \eta \nabla_{\theta} \mathcal{L}(\phi, \theta).\end{aligned}$$


Variational autoencoder (VAE)

- ▶ VAE learns stochastic mapping between \mathbf{x} -space, from complicated distribution $\pi(\mathbf{x})$, and a latent \mathbf{z} -space, with simple distribution.
- ▶ The generative model learns a joint distribution $p(\mathbf{x}, \mathbf{z}|\theta) = p(\mathbf{z})p(\mathbf{x}|\mathbf{z}, \theta)$, with a prior distribution $p(\mathbf{z})$, and a stochastic decoder $p(\mathbf{x}|\mathbf{z}, \theta)$.
- ▶ The stochastic encoder $q(\mathbf{z}|\mathbf{x}, \phi)$ (inference model), approximates the true but intractable posterior $p(\mathbf{z}|\mathbf{x}, \theta)$ of the generative model.



Variational Autoencoder

$$\mathcal{L}(\phi, \theta) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \left[\log p(\mathbf{x}|\mathbf{z}, \theta) - \log \frac{q(\mathbf{z}|\mathbf{x}, \phi)}{p(\mathbf{z})} \right] \rightarrow \max_{\phi, \theta}.$$



Variational autoencoder (VAE)

- ▶ Encoder $q(\mathbf{z}|\mathbf{x}, \phi) = \text{NN}_e(\mathbf{x}, \phi)$ outputs $\mu_\phi(\mathbf{x})$ and $\sigma_\phi(\mathbf{x})$.
- ▶ Decoder $p(\mathbf{x}|\mathbf{z}, \theta) = \text{NN}_d(\mathbf{z}, \theta)$ outputs parameters of the sample distribution.




image credit:

<https://lilianweng.github.io/lil-log/2018/08/12/from-autoencoder-to-beta-vae.html>

VAE limitations

- ▶ Poor generative distribution (decoder)

$$p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{z}), \boldsymbol{\sigma}_{\boldsymbol{\theta}}^2(\mathbf{z})) \quad \text{or} \quad = \text{Softmax}(\boldsymbol{\pi}_{\boldsymbol{\theta}}(\mathbf{z})).$$

- ▶ Loose lower bound

$$\log p(\mathbf{x}|\boldsymbol{\theta}) - \mathcal{L}(q, \boldsymbol{\theta}) = (?).$$

- ▶ Poor prior distribution

$$p(\mathbf{z}) = \mathcal{N}(0, \mathbf{I}).$$

- ▶ Poor variational posterior distribution (encoder)

$$q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi}) = \mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_{\boldsymbol{\phi}}(\mathbf{x}), \boldsymbol{\sigma}_{\boldsymbol{\phi}}^2(\mathbf{x})).$$

VAE as Bayesian model

Posterior distribution

$$p(\theta|\mathbf{X}) = \frac{p(\mathbf{X}|\theta)p(\theta)}{p(\mathbf{X})}$$

ELBO

$$\begin{aligned}\log p(\theta|\mathbf{X}) &= \log p(\mathbf{X}|\theta) + \log p(\theta) - \log p(\mathbf{X}) \\ &= \mathcal{L}(q, \theta) + KL(q||p) + \log p(\theta) - \log p(\mathbf{X}) \\ &\geq [\mathcal{L}(q, \theta) + \log p(\theta)] - \log p(\mathbf{X}).\end{aligned}$$

EM-algorithm

► E-step

$$q(\mathbf{z}) = \arg \max_q \mathcal{L}(q, \theta^*) = \arg \min_q KL(q||p) = p(\mathbf{z}|\mathbf{x}, \theta^*);$$

► M-step

$$\theta^* = \arg \max_{\theta} [\mathcal{L}(q, \theta) + \log p(\theta)].$$

Outline

1. Variational autoencoder (VAE)
2. Posterior collapse and decoder weakening techniques
3. Tighter variational bound

VAE limitations

- ▶ **Poor generative distribution (decoder)**

$$p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{z}), \boldsymbol{\sigma}_{\boldsymbol{\theta}}^2(\mathbf{z})) \quad \text{or} \quad = \text{Softmax}(\boldsymbol{\pi}_{\boldsymbol{\theta}}(\mathbf{z})).$$

- ▶ Loose lower bound

$$\log p(\mathbf{x}|\boldsymbol{\theta}) - \mathcal{L}(q, \boldsymbol{\theta}) = (?).$$

- ▶ Poor prior distribution

$$p(\mathbf{z}) = \mathcal{N}(0, \mathbf{I}).$$

- ▶ Poor variational posterior distribution (encoder)

$$q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi}) = \mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_{\boldsymbol{\phi}}(\mathbf{x}), \boldsymbol{\sigma}_{\boldsymbol{\phi}}^2(\mathbf{x})).$$

Posterior collapse

LVM

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta}) d\mathbf{z} = \int p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) p(\mathbf{z}) d\mathbf{z}$$

ELBO objective

$$\mathcal{L}(\phi, \boldsymbol{\theta}) = [\mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}))] .$$

- ▶ More powerful $p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})$ leads to more powerful generative model $p(\mathbf{x}|\boldsymbol{\theta})$.
- ▶ If the decoder $p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})$ is too powerful (it could model $p(\mathbf{x}|\boldsymbol{\theta})$), then the latent variables \mathbf{z} becomes irrelevant. ELBO avoids paying any cost $KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}))$ ($q(\mathbf{z}|\mathbf{x}, \phi) \approx p(\mathbf{z})$), the variational posterior $q(\mathbf{z}|\mathbf{x}, \phi)$ will not carry any information about \mathbf{x} .

How to make the generative model $p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})$ more powerful?


PixelVAE

Autoregressive decoder

$$p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) = \prod_{j=1}^m p(x_j|\mathbf{x}_{1:j-1}, \mathbf{z}, \boldsymbol{\theta})$$

- ▶ Global structure is captured by latent variables.
- ▶ Local statistics are captured by limited receptive field autoregressive model.

MNIST results



Decoder weakening techniques

- ▶ Powerful decoder $p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta})$ makes the model expressive, but posterior collapse is possible.
- ▶ PixelVAE model uses the autoregressive PixelCNN model with small number of layers to limit receptive field.

How to force the model encode information about \mathbf{x} into \mathbf{z} ?

KL annealing

$$\mathcal{L}(\phi, \boldsymbol{\theta}, \beta) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - \beta \cdot KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}))$$

Start training with $\beta = 0$, increase it until $\beta = 1$ during training.

Free bits

$$\mathcal{L}(\phi, \boldsymbol{\theta}, \lambda) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) - \max(\lambda, KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}))).$$

It ensures the use of less than λ bits of information and results in $KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z})) \geq \lambda$.

Bowman S. R. et al. *Generating Sentences from a Continuous Space*, 2015

Kingma D. P. et al. *Improving Variational Inference with Inverse Autoregressive Flow*, 2016

Outline

1. Variational autoencoder (VAE)
2. Posterior collapse and decoder weakening techniques
3. Tighter variational bound

VAE limitations

- ▶ Poor generative distribution (decoder)

$$p(\mathbf{x}|\mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{z}), \boldsymbol{\sigma}_{\boldsymbol{\theta}}^2(\mathbf{z})) \quad \text{or} \quad = \text{Softmax}(\boldsymbol{\pi}_{\boldsymbol{\theta}}(\mathbf{z})).$$

- ▶ **Loose lower bound**

$$\log p(\mathbf{x}|\boldsymbol{\theta}) - \mathcal{L}(q, \boldsymbol{\theta}) = (?).$$

- ▶ Poor prior distribution

$$p(\mathbf{z}) = \mathcal{N}(0, \mathbf{I}).$$

- ▶ Poor variational posterior distribution (encoder)

$$q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi}) = \mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_{\boldsymbol{\phi}}(\mathbf{x}), \boldsymbol{\sigma}_{\boldsymbol{\phi}}^2(\mathbf{x})).$$

Importance sampling

LVM

$$\begin{aligned} p(\mathbf{x}|\theta) &= \int p(\mathbf{x}, \mathbf{z}|\theta) d\mathbf{z} = \int \left[\frac{p(\mathbf{x}, \mathbf{z}|\theta)}{q(\mathbf{z}|\mathbf{x}, \phi)} \right] q(\mathbf{z}|\mathbf{x}, \phi) d\mathbf{z} \\ &= \int f(\mathbf{x}, \mathbf{z}) q(\mathbf{z}|\mathbf{x}, \phi) d\mathbf{z} = \mathbb{E}_{\mathbf{z} \sim q(\mathbf{z}|\mathbf{x}, \phi)} f(\mathbf{x}, \mathbf{z}) \end{aligned}$$

Here $f(\mathbf{x}, \mathbf{z}) = \frac{p(\mathbf{x}, \mathbf{z}|\theta)}{q(\mathbf{z}|\mathbf{x}, \phi)}$.

ELBO: derivation 1

$$\begin{aligned} \log p(\mathbf{x}|\theta) &= \log \mathbb{E}_{\mathbf{z} \sim q(\mathbf{z}|\mathbf{x}, \phi)} f(\mathbf{x}, \mathbf{z}) \geq \mathbb{E}_{\mathbf{z} \sim q(\mathbf{z}|\mathbf{x}, \phi)} \log f(\mathbf{x}, \mathbf{z}) = \\ &= \mathbb{E}_{\mathbf{z} \sim q(\mathbf{z}|\mathbf{x}, \phi)} \log \frac{p(\mathbf{x}, \mathbf{z}|\theta)}{q(\mathbf{z}|\mathbf{x}, \phi)} = \mathcal{L}(q, \theta). \end{aligned}$$

Could we choose better $f(\mathbf{x}, \mathbf{z})$?

Importance Weighted Autoencoders (IWAE)

$$p(\mathbf{x}|\theta) = \int \left[\frac{p(\mathbf{x}, \mathbf{z}|\theta)}{q(\mathbf{z}|\mathbf{x}, \phi)} \right] q(\mathbf{z}|\mathbf{x}, \phi) d\mathbf{z} = \mathbb{E}_{\mathbf{z} \sim q(\mathbf{z}|\mathbf{x}, \phi)} f(\mathbf{x}, \mathbf{z})$$

Let define

$$f(\mathbf{x}, \mathbf{z}_1, \dots, \mathbf{z}_K) = \frac{1}{K} \sum_{k=1}^K \frac{p(\mathbf{x}, \mathbf{z}_k|\theta)}{q(\mathbf{z}_k|\mathbf{x}, \phi)}$$

$$\mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x}, \phi)} f(\mathbf{x}, \mathbf{z}_1, \dots, \mathbf{z}_K) = p(\mathbf{x}|\theta)$$

ELBO

$$\begin{aligned} \log p(\mathbf{x}|\theta) &= \log \mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x})} f(\mathbf{x}, \mathbf{z}, \dots, \mathbf{z}_K) \geq \\ &\geq \mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x}, \phi)} \log f(\mathbf{x}, \mathbf{z}, \dots, \mathbf{z}_K) = \\ &= \mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x}, \phi)} \log \left[\frac{1}{K} \sum_{k=1}^K \frac{p(\mathbf{x}, \mathbf{z}_k|\theta)}{q(\mathbf{z}_k|\mathbf{x}, \phi)} \right] = \mathcal{L}_K(q, \theta). \end{aligned}$$

Importance Weighted Autoencoders (IWAE)

VAE objective

$$\log p(\mathbf{x}|\boldsymbol{\theta}) \geq \mathcal{L}(q, \boldsymbol{\theta}) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log \frac{p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta})}{q(\mathbf{z}|\mathbf{x}, \phi)} \rightarrow \max_{q, \boldsymbol{\theta}}$$

$$\mathcal{L}(q, \boldsymbol{\theta}) = \mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x}, \phi)} \left(\frac{1}{K} \sum_{k=1}^K \log \frac{p(\mathbf{x}, \mathbf{z}_k|\boldsymbol{\theta})}{q(\mathbf{z}_k|\mathbf{x}, \phi)} \right) \rightarrow \max_{q, \boldsymbol{\theta}}.$$

IWAE objective

$$\mathcal{L}_K(q, \boldsymbol{\theta}) = \mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x}, \phi)} \log \left(\frac{1}{K} \sum_{k=1}^K \frac{p(\mathbf{x}, \mathbf{z}_k|\boldsymbol{\theta})}{q(\mathbf{z}_k|\mathbf{x}, \phi)} \right) \rightarrow \max_{q, \boldsymbol{\theta}}.$$

If $K = 1$, these objectives coincide.

Importance Weighted Autoencoders (IWAE)

Theorem

1. $\log p(\mathbf{x}|\theta) \geq \mathcal{L}_K(q, \theta) \geq \mathcal{L}_M(q, \theta)$, for $K \geq M$;
2. $\log p(\mathbf{x}|\theta) = \lim_{K \rightarrow \infty} \mathcal{L}_K(q, \theta)$ if $\frac{p(\mathbf{x}, \mathbf{z}|\theta)}{q(\mathbf{z}|\mathbf{x}, \phi)}$ is bounded.

If $K > 1$ the bound could be tighter.

$$\mathcal{L}(q, \theta) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log \frac{p(\mathbf{x}, \mathbf{z}|\theta)}{q(\mathbf{z}|\mathbf{x}, \phi)};$$

$$\mathcal{L}_K(q, \theta) = \mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x}, \phi)} \log \left(\frac{1}{K} \sum_{k=1}^K \frac{p(\mathbf{x}, \mathbf{z}_k|\theta)}{q(\mathbf{z}_k|\mathbf{x}, \phi)} \right).$$

- ▶ $\mathcal{L}_1(q, \theta) = \mathcal{L}(q, \theta)$;
- ▶ $\mathcal{L}_\infty(q, \theta) = \log p(\mathbf{x}|\theta)$.
- ▶ Which $q^*(\mathbf{z}|\mathbf{x}, \phi)$ gives $\mathcal{L}(q^*, \theta) = \log p(\mathbf{x}|\theta)$?

Importance Weighted Autoencoders (IWAE)

Objective

$$\mathcal{L}_K(q, \theta) = \mathbb{E}_{\mathbf{z}_1, \dots, \mathbf{z}_K \sim q(\mathbf{z}|\mathbf{x}, \phi)} \log \left(\frac{1}{K} \sum_{k=1}^K \frac{p(\mathbf{x}, \mathbf{z}_k | \theta)}{q(\mathbf{z}_k | \mathbf{x}, \phi)} \right) \rightarrow \max_{\phi, \theta}.$$

Gradient

$$\Delta_K = \nabla_{\theta, \phi} \log \left(\frac{1}{K} \sum_{k=1}^K \frac{p(\mathbf{x}, \mathbf{z}_k | \theta)}{q(\mathbf{z}_k | \mathbf{x}, \phi)} \right), \quad \mathbf{z}_k \sim q(\mathbf{z} | \mathbf{x}, \phi).$$

Theorem


$$\text{SNR}_K = \frac{\mathbb{E}[\Delta_K]}{\sigma(\Delta_K)}; \quad \text{SNR}_K(\theta) = O(\sqrt{K}); \quad \text{SNR}_K(\phi) = O\left(\sqrt{\frac{1}{K}}\right).$$

Hence, increasing K vanishes gradient signal of inference network $q(\mathbf{z}|\mathbf{x}, \phi)$.

Importance Weighted Autoencoders (IWAE)

Theorem

$$\text{SNR}_K = \frac{\mathbb{E}[\Delta_K]}{\sigma(\Delta_K)}; \quad \text{SNR}_K(\theta) = O(\sqrt{K}); \quad \text{SNR}_K(\phi) = O\left(\sqrt{\frac{1}{K}}\right).$$



- ▶ IWAE makes the variational bound tighter and extends the class of variational distributions.
- ▶ Gradient signal becomes really small, training is complicated.
- ▶ IWAE is a standard quality measure for VAE models.

Summary

- ▶ The VAE model is an LVM with two neural network: stochastic encoder $q(\mathbf{z}|\mathbf{x}, \phi)$ and stochastic decoder $p(\mathbf{x}|\mathbf{z}, \theta)$.
- ▶ VAE is not a "true" bayesian model since parameters θ do not have a prior distribution.
- ▶ Standart VAE has several limitations that we will address later in the course.
- ▶ More powerful decoder in VAE leads to more expressive generative model. However, too expressive decoder could lead to the posterior collapse.
- ▶ The decoder weakening is a set of techniques to avoid the posterior collapse.
- ▶ The IVAE could get the tighter lower bound to the likelihood, but the training of such model becomes more difficult.