YAMAHA

AVENTAGE

AV Receiver

RX-AS710
RX-AS710 D

Owner's Manual

Read the supplied booklet "Safety Brochure" before using the unit.

English

CONTENTS

Updating the unit's firmware via the network 124

APPENDIX 125

Frequently asked questions 125

Troubleshooting 126

Error indications on the front display 134

Ideal speaker layout 135

Glossary 136

Supported devices and file formats 138

Information on HDMI 141

Reference diagram (rear panel) 144

Trademarks 145

Specifications 146

Index 149

Accessories

Check that the following accessories are supplied with the product.

☐ Remote control

☐ Batteries (AAA, R03, UM-4) (x2)

Insert the batteries the right way round.

☐ AM antenna (RX-AS710)

☐ FM antenna (RX-AS710)

*One of the above is supplied depending on the region of purchase.

☐ DAB/FM antenna (RX-AS710D)

☐ YPAO microphone

☐ Power cable

*The supplied power cable varies depending on the region of purchase.

☐ CD-ROM (Owner's Manual)
☐ Easy Setup Guide
☐ Safety Brochure

Operating range of the remote control

• Point the remote control at the remote control sensor on the unit and remain within the operating range shown below.

Within
6 m (20 ft)

30°   30°

• The illustrations of the main unit and remote control used in this manual are of the RX-AS710 (Europe model), unless otherwise specified.

• In this manual, illustrations of English menu screens are used as examples.

• Some features are not available in certain regions.

• Due to product improvements, specifications and appearance are subject to change without notice.

• This manual explains operations using the supplied remote control.

• This manual describes all the "iPod" and "iPhone" as the "iPod". "iPod" refers to both "iPod" and "iPhone" unless otherwise specified.

• ! indicates precautions for use of the unit and its feature limitations.

• indicates supplementary explanations for better use.

FEATURES

What you can do with the unit

Wide variety of supported content

- *Bluetooth* ➲ **p.66**
- iPod/iPhone ➲ **p.67**
- USB ➲ **p.70**
- Media server (PC/NAS) ➲ **p.73**
- Internet radio ➲ **p.77**
- AirPlay ➲ **p.80**

iPod/iPhone/
Bluetooth device

Network contents

USB device

Control

Audio

Supports 2- to 7.1-channel speaker system. Allows you to enjoy your favorite acoustic spaces in various styles.

- Automatically optimizing the speaker settings to suit your room (YPAO) ➲ **p.32**
- Reproducing stereo or multichannel sounds with the sound fields like actual movie theaters and concert halls (CINEMA DSP) ➲ **p.49**
- Enjoying compressed music with enhanced sound (Compressed Music Enhancer) ➲ **p.53**
- Playing back music in multiple rooms (multi-zone) ➲ **p.82**

Speakers

Audio

4K Ultra HD signals and HDCP 2.2 supported

HDMI Control

Audio/Video

BD/DVD player

AV receiver (the unit)

HDMI Control

Audio

Audio/Video

TV

Change the input source and favorite settings with one touch (SCENE)
➲ **p.47**

Sequential operation of a TV, AV receiver, and BD/DVD player (HDMI Control)
➲ **p.141**

TV remote control

Full of useful functions!

❑ Connecting various devices (p.23)

A number of HDMI jacks and various input/output jacks on the unit allow you to connect video devices (such as BD/DVD players), audio devices (such as CD players), game consoles, camcorders, and other devices.

❑ Playing back TV audio in surround sound with a single HDMI cable connection (Audio Return Channel: ARC) (p.22)

When using an ARC-compatible TV, you only need one HDMI cable to enable video output to the TV, audio input from the TV, and the transmission of HDMI Control signals.

HDMI Control
TV audio

Video from
external device

❑ Various wireless connection methods (p.37)

The unit supports the Wi-Fi feature that allows the unit to connect to your wireless router (access point) without a network cable connection. In addition, Wireless Direct enables connecting a mobile device to the unit directly without router.

Wi-Fi or
Wireless Direct

❑ Creating 3-dimensional sound fields (p.49)

Connecting presence speakers allows you to create a natural 3-dimensional sound field in your own room (CINEMA DSP 3D). Even when no presence speakers are connected, the Virtual Presence Speaker (VPS) function produces 3D surround sound. In addition, the unit creates Virtual Surround Back Speaker (VSBS) using the surround speakers to add a sense of depth to the rear sound field even when no surround back speakers are connected.

VSBS

❑ Surround playback with 5 speakers placed in front (p.51)

If you have surround speakers but there is no space to place them in the rear of your room, you can place them in the front and enjoy multichannel surround sound with the 5 speakers placed in the front (Virtual CINEMA FRONT).

❑ Low power consumption (p.117)

The ECO mode (power saving function) reduces the unit's power consumption.

Useful tips

The combination of video/audio input jacks does not match an external device...
Use "Audio In" in the "Input" menu to change the combination of video/audio input jacks so that it matches the output jack(s) of your external device (p.24).

Video and audio are not synchronized...
Use "Lipsync" in the "Setup" menu to adjust the delay between video and audio output (p.108).

I want to hear audio from the TV speakers...
Use "Audio Output" in the "Setup" menu to select the output destination of signals input into the unit (p.112). Your TV speakers may be selected as an output destination.

I want to get more bass sounds…
Set "Extra Bass" in the "Option" menu to "On" to enjoy enhanced bass sounds (p.94).

I want to change the on-screen menu language...
Use "Language" in the "Setup" menu to select a language from English, Japanese, French, German, Spanish, Russian, Italian and Chinese (p.31).

I want to update the firmware...
Use "UPDATE" in the "ADVANCED SETUP" menu to update the unit's firmware (p.123). If the unit is connected to the Internet, a message will be displayed on the TV when a firmware update is available (p.124).

Many other settings are available that let you to customize the unit. For details, see the following pages.

• Input settings (p.95)
• SCENE settings (p.98)
• Sound program and surround decoder settings (p.100)
• Various function settings (p.103)
• Information view (such as audio signal and video signal) (p.119)
• System settings (p.120)

Useful applications

■ AV CONTROLLER

"AV CONTROLLER" will turn your smartphone/tablet into a Wi-Fi enabled remote control for your Yamaha network products. This application provides you the flexibility to control the available inputs, volume, mute, power commands and playback source.

Functions

- Power on/off and volume adjustment
- Input, scene and sound mode selection
- DSP Parameter adjustment
- Playback control (including music selection for some sources)

- For details, search for "AV CONTROLLER" on the App Store or Google Play.

■ AV SETUP GUIDE (for tablet)

"AV SETUP GUIDE" is an application that assists you with cable connections between AV receiver and source devices as well as AV receiver setup. This application guides you through the various settings such as speaker connections, TV and video/audio device connections and selecting the speaker system.

Functions

- Connection guide (speakers, TV and video/audio devices)
- Setup guide (YPAO settings and various setup assistance with illustrations)
- Viewing owner's manual

- For details, search for "AV SETUP GUIDE" on the App Store or Google Play.

Part names and functions

Front panel

(RX-AS710 Europe model)

① ZONE key

Enables/disables the audio output to Zone2 (p.85).

② INFO (WPS) key

Selects the information displayed on the front display (p.91). Enters the wireless network connection setup (WPS push button configuration) by holding down for 3 seconds (p.40).

③ Remote control sensor

Receives remote control signals (p.5).

④ Front display

Displays information (p.10).

⑤ PURE DIRECT key

Enables/disables Pure Direct (p.53).

⑥ INPUT knob

Select an input source.

⑦ ⏻ (power) key

Turns on/off (standby) the unit.

⑧ Standby indicator

Lights up when the unit is in standby mode under any of the following conditions.
- HDMI Control is enabled (p.111)
- Standby Through is enabled (p.112)
- Network Standby is enabled (p.113)
- An iPod is being charged (p.67)

⑨ PHONES jack

For connecting headphones.

⑩ YPAO MIC jack

For connecting the supplied YPAO microphone (p.32).

⑪ STRAIGHT key

Enables/disables the straight decode mode (p.52).

⑫ PROGRAM keys

Select a sound program or a surround decoder (p.48).

⑬ SCENE keys

Select the registered input source, sound program, and various settings with one touch. Also, turns on the unit when it is in standby mode (p.47).

⑭ AUX (AUDIO) jack

For connecting devices, such as portable audio players (p.26).

⑮ USB jack

For connecting a USB storage device (p.70) or an iPod (p.67).

⑯ VOLUME knob

Adjusts the volume.

Front display (indicators)

① ECO
Lights up when the unit is in the eco mode (p.117).

② HDMI
Lights up when HDMI signals are being input or output.

OUT
Lights up when HDMI signals are being output.

③ ENHANCER
Lights up when Compressed Music Enhancer (p.53) is working.

④ CINEMA DSP
Lights up when CINEMA DSP or CINEMA DSP 3D (p.49) is working.

⑤ STEREO
Lights up when the unit is receiving a stereo FM radio signal.

TUNED
Lights up when the unit is receiving an FM/AM radio station signal (RX-AS710) or an FM radio station (RX-AS710D) signal.

⑥ Signal strength indicator
Indicates the strength of the wireless network signal (p.37).

⑦ *Bluetooth* indicator
Lights up when the unit is connecting to a *Bluetooth* device (p.66).

⑧ PARTY
Lights up when the unit is in the party mode. (p.86)

⑨ SLEEP
Lights up when the sleep timer is on.

⑩ ZONE2
Lights up when audio output to Zone2 is enabled (p.85).

⑪ MUTE
Blinks when audio is muted.

⑫ Volume indicator
Indicates the current volume.

⑬ VIRTUAL
Lights up when the Virtual Presence Speaker (VPS) or Virtual Surround Back Speaker (VSBS) (p.49), or the virtual surround processing (p.51) is working.

⑭ Cursor indicators
Indicate the remote control cursor keys currently operational.

⑮ Information display
Displays the current status (such as input name and sound mode name). You can switch the information by pressing INFO (p.91).

⑯ ADAPTIVE DRC
Lights up when Adaptive DRC (p.93) is working.

⑰ Speaker indicators
Indicate speaker terminals from which signals are output.

- **L** Front speaker (L)
- **R** Front speaker (R)
- **C** Center speaker
- **SL** Surround speaker (L)
- **SR** Surround speaker (R)
- **SBL** Surround back speaker (L)
- **SBR** Surround back speaker (R)
- **SB** Surround back speaker
- **FPL** Presence speaker (L)
- **FPR** Presence speaker (R)
- **SW** Subwoofer

Rear panel

(RX-AS710 Europe model)

* The area around the video/audio output jacks is marked in white on the actual product to prevent improper connections.

① **AUDIO 1–2 jacks**

For connecting to audio playback devices and inputting audio signals (p.26).

② **TRIGGER OUT jack**

For connecting to a device that supports the trigger function (p.29).

③ **HDMI OUT jack**

For connecting to HDMI-compatible TVs and outputting video/audio signals (p.22). When using ARC, TV audio signal can also be input through the HDMI OUT jack.

④ **HDMI 1–6 jacks**

For connecting to HDMI-compatible playback devices and inputting video/audio signals (p.23).

⑤ **Wireless antenna**

For connecting to a network device wirelessly (p.37).

⑥ **NETWORK jack**

For connecting to a network with a network cable (p.28).

⑦ **AC IN jack**

For connecting the supplied power cable (p.30).

⑧ **AV 1–4 jacks**

For connecting to video/audio playback devices and inputting video/audio signals (p.23).

⑨ **PHONO jacks**

For connecting to a turntable (p.26).

⑩ **REMOTE IN/OUT jacks**

For connecting to an infrared signal receiver/emitter that allows you to operate the unit and other devices from another room (p.84).

⑪ **ANTENNA jacks**

For connecting to radio antennas (p.27).

⑫ **ZONE2 OUT jacks**

For connecting to the external amplifier used in Zone2 and for outputting audio (p.83).

⑬ **SUBWOOFER PRE OUT 1–2 jacks**

For connecting to a subwoofer with built-in amplifier (p.19).

⑭ **SPEAKERS terminals**

For connecting to speakers (p.18).

⑮ **VOLTAGE SELECTOR**

(General model only)
Selects the switch position according to your local voltage (p.30).

Remote control

1 Remote control signal transmitter

Transmits infrared signals.

2 ⏻ (receiver power) key

Turns on/off (standby) the unit.

3 Input selection keys

Select an input source for playback.

HDMI 1–6	HDMI 1–6 jacks
AUX	AUX jack (on the front panel)
AV 1–4	AV 1–4 jacks
AUDIO	AUDIO 1–2 jacks (press repeatedly to select "AUDIO1" or "AUDIO2")
TUNER	FM/AM radio (RX-AS710), DAB/FM radio (RX-AS710D)
BLUETOOTH	*Bluetooth* connection (the unit as a *Bluetooth* receiver)
USB	USB jack (on the front panel)
NET	NETWORK sources (press repeatedly to select a desired network source)
PHONO	PHONO jacks

4 MAIN/ZONE2 switch

Changes the zone (main zone or Zone2) that is controlled by the remote control (p.85).

5 SCENE keys

Select the registered input source, sound program, and various settings with one touch. Also, turns on the unit when it is in standby mode (p.47).

6 PROGRAM keys

Select a sound program (p.48).

7 External device operation keys

Displays menus for the HDMI Control-compatible playback device (p.141).

8 ON SCREEN key

Displays the on-screen menu on the TV.

9 Menu operation keys

Cursor keys	Select a menu or a parameter.
ENTER	Confirms a selected item.
RETURN	Returns to the previous screen.

10 MODE key

Switches the iPod operation modes (p.69).

11 Radio keys

Operate the FM/AM/DAB radio when "TUNER" is selected as the input source (p.54, p.58).

BAND	Switches between FM and AM radio (RX-AS710), or DAB and FM (RX-AS710D).
PRESET	Select a preset station.
TUNING	Select the radio frequency.

External device operation keys

Let you perform playback operations when "USB" or "NET" is selected as the input source, or control playback of the HDMI Control-compatible playback device (p.141).

12 Sound mode keys

Select a sound mode (p.48).

13 INFO key

Selects the information displayed on the front display (p.91).

14 SLEEP key

Switches the unit to standby mode automatically after a specified period of time has elapsed (sleep timer). Press repeatedly to set the time (120 min, 90 min, 60 min, 30 min, off).

15 Numeric keys

Let you enter numerical values, such as radio frequencies.

MEMORY key

Registers FM/AM/DAB radio stations as presets (p.55, p.59, p.63).

16 HDMI OUT key

Enables/disables video/audio output from the HDMI OUT jack (p.46).

17 PARTY key

Turns on/off the party mode (p.86).

18 VOLUME keys

Adjust the volume.

19 MUTE key

Mutes the audio output.

20 OPTION key

Displays the option menu (p.92).

21 DISPLAY key

Displays status information on the TV (p.91).

PREPARATIONS

General setup procedure

1 Placing speakers (p.14)

Select the speaker layout for the number of speakers that you are using and place them in your room.

2 Connecting speakers (p.18)

Connect the speakers to the unit.

3 Connecting a TV (p.22)

Connect a TV to the unit.

4 Connecting playback devices (p.23)

Connect video devices (such as BD/DVD players) and audio devices (such as CD players) to the unit.

5 Connecting the radio antennas (p.27)

Connect the supplied radio antennas to the unit.

6 Connecting a network cable or preparing the wireless antenna (p.28)

Connect the unit to a router (access point) with a network cable, or prepare the wireless antenna for establishing a wireless network connection.

7 Connecting other devices (p.29)

Connect a device compatible with the trigger function.

8 Connecting the power cable (p.30)

After all the connections are complete, plug in the power cable.

9 Selecting an on-screen menu language (p.31)

Select the desired on-screen menu language (default: English).

10 Optimizing the speaker settings automatically (YPAO) (p.32)

Optimize the speaker settings, such as volume balance and acoustic parameters, to suit your room (YPAO).

11 Connecting to a network device wirelessly (p.37)

Connect the unit to a wireless router (access point) or a mobile device by establishing a wireless connection.

This completes all the preparations. Enjoy playing movies, music, radio and other content with the unit!

1 Placing speakers

Select the speaker layout for the number of speakers that you are using and place the speakers and subwoofer (with built-in amplifier) in your room. This section describes the representative speaker layout examples.

Caution

- Under its default settings, the unit is configured for 8-ohm speakers. When connecting 6-ohm speakers, set the unit's speaker impedance to "6 Ω MIN". In this case, you can also use 4-ohm speakers as the front speakers. For details, see "Setting the speaker impedance" (p.17).

Speaker type	Abbr.	Function	Speaker system (the number of channels)							
			7.1	7.1	6.1	5.1	Front 5.1	4.1	3.1	2.1
Front (L)	FL	Produce front left/right channel sounds (stereo sounds).	●	●	●	●	●	●	●	●
Front (R)	FR		●	●	●	●	●	●	●	●
Center	C	Produces center channel sounds (such as movie dialogue and vocals).	●	●	●	●	●		●	
Surround (L)	SL	Produce surround left/right channel sounds. Surround speakers also produce surround back channel sounds when no surround back speakers are connected.	●	●	●	●	O*1	●		
Surround (R)	SR		●	●	●	●	O*1	●		
Surround back (L)	SBL	Produce surround back left/right channel sounds.	●							
Surround back (R)	SBR		●							
Surround back	SB	Produces sounds mixed from surround back left/right channel sounds.			●					
Presence (L)	FPL	Produce CINEMA DSP effect sounds. In combination with CINEMA DSP 3D (p.49), the presence speakers create a natural 3-dimensional sound field in your room.		●			O*2			
Presence (R)	FPR			●			O*2			
Subwoofer	SW	Produces LFE (low-frequency effect) channel sounds and reinforces the bass parts of other channels. This channel is counted as "0.1". You can connect 2 subwoofers (with built-in amplifier) to the unit.	●	●	●	●	●	●	●	●

If you use five speakers in the front side, use two of them as front surround speakers (*1) or presence speakers (*2). We recommend using them as front surround speakers for enjoying unprocessed playback (p.52) or presence speakers for enjoying stereoscopic sound fields (p.49).

- For information on the ideal speaker layout, see "Ideal speaker layout" (p.135).
- If you have seven speakers, use two of them as surround back speakers or presence speakers.
  To reinforce the rear left/right sounds, use them as surround back speakers.
  To create a natural 3-dimensional sound field, use them as presence speakers.
- Two subwoofers connected to the unit output the same sounds.

7.1-channel system (using surround back speakers)

This speaker system creates Virtual Presence Speaker (VPS) using the front, center and surround speakers to produce a 3-dimensional sound field, and also allows you to enjoy extended surround sounds using the surround back speakers.

7.1-channel system (using presence speakers)

This speaker system uses the front presence speakers to produce a natural 3-dimensional sound field, and also creates Virtual Surround Back Speaker (VSBS) using the surround speakers to add a sense of depth to the rear sound field. This system is suited for enjoying not only 5.1-channel but also for 7.1-channel contents.

6.1-channel system

This speaker system creates Virtual Presence Speaker (VPS) using the front, center and surround speakers to produce a 3-dimensional sound field, and also allows you to enjoy extended surround sounds using the surround back speaker.

5.1-channel system

This speaker system creates Virtual Presence Speaker (VPS) using the front, center and surround speakers to produce a 3-dimensional sound field, and also creates Virtual Surround Back Speaker (VSBS) using the surround speakers to add a sense of depth to the rear sound field. This system is suited for enjoying not only 5.1-channel but also for 7.1-channel contents.

Front 5.1-channel system (using surround speakers)

Even when surround speakers are placed in the front side, the unit creates the virtual surround speakers in the rear side to allow you to enjoy multichannel surround sound (Virtual CINEMA FRONT) when "Layout (Surround)" (p.106) in the "Setup" menu is set to "Front".

- You can enjoy surround sound even without the center speaker (front 4.1-channel system).

Front 5.1-channel system (using presence speakers)

This speaker system uses the front presence speakers to produce a natural 3-dimensional sound field, and creates the virtual surround speakers using the front speakers to allow you to enjoy multichannel surround sound (Virtual CINEMA DSP).

4.1-channel system

2.1-channel system

Even when no surround speakers are connected, the unit creates the virtual surround speakers using the front speakers to allow you to enjoy multichannel surround sound (Virtual CINEMA DSP).

- Add the center speaker to configure a 3.1-channel system.

■ Setting the speaker impedance

Under its default settings, the unit is configured for 8-ohm speakers. When using a 6-ohm speaker for any channel, set the speaker impedance to "6 Ω MIN". In this case, you can also use 4-ohm speakers as the front speakers.

1 Before connecting speakers, connect the power cable to an AC wall outlet.

2 While holding down STRAIGHT on the front panel, press ⏻ (power).

⏻ (power)

STRAIGHT

3 Check that "SP IMP." is displayed on the front display.

```
SP IMP...8ΩMIN
```

4 Press STRAIGHT to select "6 Ω MIN".

5 Press ⏻ (power) to set the unit to standby mode and remove the power cable from the AC wall outlet.

You are now ready to connect the speakers.

2 Connecting speakers

Connect the speakers placed in your room to the unit. The following diagrams provide connections for 7.1- and 6.1-channel systems as examples. For other systems, connect speakers while referring to the connection diagram for the 6.1-channel system.

Caution

- Remove the unit's power cable from an AC wall outlet and turn off the subwoofer before connecting the speakers.
- Ensure that the core wires of the speaker cable do not touch one another or come into contact with the unit's metal parts. Doing so may damage the unit or the speakers. If the speaker cables short circuit, "Check SP Wires" will appear on the front display when the unit is turned on.

Cables required for connection (commercially available)

Speaker cables (x the number of speakers)

Audio pin cable (two for connecting two subwoofers)

7.1-channel system (using surround back speakers)

The unit (rear)

7.1-channel system (using presence speakers)

The unit (rear)

6.1-channel system

The unit (rear)

When using only one surround back speaker, connect it to the SINGLE jack (L side).

■ Connecting speaker cables

Speaker cables have two wires. One is for connecting the negative (-) terminal of the unit and the speaker, and the other is for the positive (+) terminal. If the wires are colored to prevent confusion, connect the black wire to the negative and the other wire to the positive terminal.

① Remove approximately 10 mm (3/8") of insulation from the ends of the speaker cable and twist the bare wires of the cable firmly together.

② Loosen the speaker terminal.

③ Insert the bare wires of the cable into the gap on the side (upper right or bottom left) of the terminal.

④ Tighten the terminal.

+ (red)

- (black)

Using a banana plug

(Canada, Australia and General models only)

① Tighten the speaker terminal.

② Insert a banana plug into the end of the terminal.

Banana plug

■ Connecting the subwoofer

Use an audio pin cable to connect the subwoofer.

Audio pin cable

Connecting front speakers that support bi-amp connections

When using front speakers that support bi-amp connections, connect them to the FRONT jacks and ZONE2/F.PRESENCE/SURROUND BACK/BI-AMP jacks.

To enable the bi-amp function, set "Power Amp Assign" (p.105) in the "Setup" menu to "5ch BI-AMP" after connecting the power cable to an AC wall outlet.

Caution

- Before making bi-amp connections, remove any brackets or cables that connect a woofer with a tweeter. Refer to the instruction manual of the speakers for details. If you are not making bi-amp connections, make sure that the brackets or cables are connected before connecting the speaker cables.
- Surround back speakers cannot be used during bi-amp connections.

The unit (rear)

- The FRONT jacks and ZONE2/F.PRESENCE/SURROUND BACK/BI-AMP jacks output the same signals.

Input/output jacks and cables

■ Video/audio jacks

❑ HDMI jacks

Transmit digital video and digital sound through a single jack. Use an HDMI cable.

HDMI cable

!

• Use a 19-pin HDMI cable with the HDMI logo. We recommend using a cable less than 5.0 m (16.4 ft) long to prevent signal quality degradation.

💡

• The unit's HDMI jacks support the HDMI Control, Audio Return Channel (ARC), and 3D and 4K Ultra HD video transmission features.

• Use high speed HDMI cables to enjoy 3D or 4K Ultra HD videos.

■ Video jacks

❑ COMPONENT VIDEO jacks

Transmit video signals separated into three components: luminance (Y), chrominance blue (P_B), and chrominance red (P_R). Use a component video cable with three plugs.

Component video cable

❑ VIDEO jacks

Transmit analog video signals. Use a video pin cable.

Video pin cable

■ Audio jacks

❑ OPTICAL jacks

Transmit digital audio signals. Use a digital optical cable. Remove the tip protector (if available) before using the cable.

Digital optical cable

❑ COAXIAL jacks

Transmit digital audio signals. Use a digital coaxial cable.

Digital coaxial cable

❑ AUDIO jacks

(Stereo L/R jacks)

Transmit analog stereo audio signals. Use a stereo pin cable (RCA cable).

Stereo pin cable

(Stereo mini jack)

Transmit analog stereo audio signals. Use a stereo mini-plug cable.

Stereo mini-plug cable

3 Connecting a TV

Connect a TV to the unit by using HDMI cable, so that video input to the unit can be output to the TV.

You can also enjoy playback of TV audio on the unit.

■ HDMI connection

Connect the TV to the unit with an HDMI cable and a digital optical cable.

• You do not make a digital optical cable connection between the TV and the unit in the following cases:

   – If your TV supports Audio Return Channel (ARC)

   – If you will receive TV broadcasts only from the set-top box

• If you connect a TV that supports HDMI Control to the unit with an HDMI cable, you can control the unit's power and volume with the TV's remote control.

To use HDMI Control and ARC, you need to configure the HDMI settings on the unit. For details on the settings, see "Information on HDMI" (p.141).

About Audio Return Channel (ARC)

• ARC allows audio signals to travel both ways. If you connect a TV that supports ARC to the unit with a single HDMI cable, you can output video/audio to the TV or input TV audio to the unit.

• When using ARC, connect a TV with an HDMI cable that supports ARC.

4 Connecting playback devices

The unit is equipped with a variety of input jacks including HDMI input jacks to allow you to connect different types of playback devices. For information on how to connect an iPod or a USB storage device, see the following pages.

– Connecting an iPod (p.67)

– Connecting a USB storage device (p.70)

Connecting video devices (such as BD/DVD players)

Connect video devices such as BD/DVD players, set-top boxes (STBs) and game consoles to the unit. Depending on the video/audio output jacks available on your video device, choose one of the following connections. We recommend using an HDMI connection if the video device has an HDMI output jack.

💡

• If the combination of video/audio input jacks available on the unit does not match your video device, change its combination according to the output jacks of your device (p.24).

■ HDMI connection

Connect a video device to the unit with an HDMI cable.

The unit (rear)

HDMI 1–6 jacks

HDMI output

Video device

If you select the input source by pressing HDMI 1–6, the video/audio played back on the video device will be output from the unit.

❗

• If your video device supports HDCP 2.2, connect the device to the HDMI 1–3 jacks.

■ Component video connection

Connect a video device to the unit with a component video cable and an audio cable (digital optical or digital coaxial). Choose a set of input jacks (on the unit) depending on the audio output jacks available on your video device.

Output jacks on video device		Input jacks on the unit
Video	**Audio**	
Component video	Digital optical	AV 1 (COMPONENT VIDEO + OPTICAL)
	Digital coaxial	AV 2 (COMPONENT VIDEO + COAXIAL)

AV 1–2 (COMPONENT VIDEO) jacks

Video output (component video)

The unit (rear)

Video device

AV 1 (OPTICAL) jack or AV 2 (COAXIAL) jack

Audio output (digital optical or digital coaxial)

If you select the input source by pressing AV 1–2, the video/audio played back on the video device will be output from the unit.

■ Composite video connection

Connect a video device to the unit with a video pin cable and an audio cable (stereo pin cable).

Output jacks on video device		Input jacks on the unit
Video	Audio	
Composite video	Analog stereo	AV 3-4 (VIDEO + AUDIO)

Video output
(composite video)

AV 3–4 (VIDEO)
jack

Video device

The unit (rear)   AV 3-4 (AUDIO) jacks

Audio output
(analog stereo)

If you select the input source by pressing AV 3–4, the video/audio played back on the video device will be output from the unit.

■ Changing the combination of video/audio input jacks

If the combination of video/audio input jacks available on the unit does not match your video device, change its combination according to the output jacks of your device. You can connect a video device that has the following video/audio output jacks.

Output jacks on video device		Input jacks on the unit	
Video	Audio	Video	Audio
HDMI	Digital optical	HDMI 1–6	AV 1 (OPTICAL) AUDIO 1 (OPTICAL)
	Digital coaxial	HDMI 1–6	AV 2 (COAXIAL) AUDIO 2 (COAXIAL)
	Analog stereo	HDMI 1–6	AV 3-4 (AUDIO)
Component video	Analog stereo	AV 1–2 (COMPONENT VIDEO)	AV 3-4 (AUDIO)

❏ Necessary setting

For example, if you have connected a video device to AV 2 (COMPONENT VIDEO) and AV 4 (AUDIO) jacks of the unit, change the combination setting as follows.

Video output
(component video)

COMPONENT
VIDEO

The unit (rear)   AV 2 (COMPONENT VIDEO)
jacks

AUDIO

Video device

AV 4 (AUDIO) jacks   Audio output
(analog stereo)

!

• If the video output from the video device is something other than 480i/576i, please set the video output to 480i/576i, or connect the video device directly to the TV with a component cable.

❗

• The following operation is available only when your TV is connected to the unit via HDMI.

1 After connecting external devices (such as a TV and playback devices) and power cable of the unit, turn on the unit.

2 Press AV 2 to select "AV 2" (video input jack to be used) as the input source.

AV 2

ON SCREEN
Cursor keys
ENTER

3 Press ON SCREEN.

4 Use the cursor keys to select "Input" and press ENTER.

5 Use the cursor keys (◁/▷) to select "AV2" (video input jack to be used) and press the cursor key (△).

6 Use the cursor keys to select "Audio In" and press ENTER.

7 Use the cursor keys to select "AV4" (audio input jack to be used).

8 Press ON SCREEN.

This completes the necessary settings.
If you select "AV 2" as the input source by pressing AV 2, the video/audio played back on the video device will be output from the unit.

Connecting audio devices (such as CD players)

Connect audio devices such as CD players, MD players, and a turntable to the unit.
Depending on the audio output jacks available on your audio device, choose one of the following connections.

Audio output jacks on audio device	Audio output jacks on the unit
Digital optical	AV 1 (OPTICAL) AUDIO 1 (OPTICAL)
Digital coaxial	AV 2 (COAXIAL) AUDIO 2 (COAXIAL)
Analog stereo	AV 3-4 (AUDIO)
Turntable (PHONO)	PHONO

Audio output
(either digital optical,
digital coaxial, or analog stereo)

The unit (rear)

AV 1–4 jacks
AUDIO 1–2 jacks

Audio device

PHONO jacks

Ground lead

Audio output (PHONO)

Turntable

If you select the input source by pressing AV 1–4, AUDIO 1–2 or PHONO, the audio played back on the audio device will be output from the unit.

When connecting a turntable

- The PHONO jack of the unit is compatible with an MM cartridge. To connect a turntable with a low-output MC cartridge, use a boosting transformer.
- Connecting the turntable to the GND terminal of the unit may reduce noise in the signal.

Connecting to the jacks on the front panel

Use the AUX jack on the front panel to temporarily connect devices such as portable audio players to the unit.

Before making a connection, stop playback on the device and turn down the volume on the unit.

The unit (front)

AUX (AUDIO) jack

Portable audio player

If you select "AUX" as the input source by pressing INPUT, the audio played back on the device will be output from the unit.

- You need to prepare an audio cable that matches the output jacks on your device.

- For details on how to connect an iPod or a USB storage device, see "Connecting an iPod" (p.67) or "Connecting a USB storage device" (p.70).

5 Connecting the radio antennas

■ FM/AM antennas (RX-AS710)

Connect the supplied FM/AM antennas to the unit.

Fix the end of the FM antenna to a wall, and place the AM antenna on a flat surface.

FM antenna   AM antenna

The unit (rear)

Assembling and connecting the AM antenna

Hold down ➡ Insert ➡ Release

• Unwind only the length of cable needed from the AM antenna unit.

• The wires of the AM antenna have no polarity.

■ DAB/FM antenna (RX-AS710D)

Connect the supplied DAB/FM antenna to the unit and fix the antenna ends to a wall.

DAB/FM antenna

The unit (rear)

• The antenna should be stretched out horizontally.

• If you cannot obtain good reception on the radio, adjust the height, direction or placement of the DAB/FM antenna.

6 Connecting a network cable or preparing the wireless antenna

Connect the unit to a router (access point) with a network cable, or prepare the wireless antenna for establishing a wireless network connection.

You can enjoy Internet radio or music files stored on media servers, such as PCs and Network Attached Storage (NAS), on the unit.

Connecting the network cable

Connect the unit to your router with a commercially-available STP network cable (CAT-5 or higher straight cable).

💡
- If you want to use a wired (network cable) connection when a wireless connection has been made, set "Network Connection" (p.112) in the "Setup" menu to "Wired".

- If you are using a router that supports DHCP, you do not need to configure any network settings for the unit, as the network parameters (such as the IP address) will be assigned automatically to it. You only need to configure the network settings if your router does not support DHCP or if you want to configure the network parameters manually (p.113).

- You can check whether the network parameters (such as IP address) are properly assigned to the unit in "Network" (p.119) in the "Information" menu.

❗
- Some security software installed on your PC or the firewall settings of network devices (such as a router) may block the access of the unit to the network devices or the Internet. In these cases, configure the security software or firewall settings appropriately.

- Each server must be connected to the same subnet as the unit.

- To use the service via the Internet, broadband connection is strongly recommended.

Preparing the wireless antenna

If you want to establish a wireless network connection, stand the wireless antenna up straight.

For information on how to connect the unit to a network device wirelessly, see "Connecting to a network device wirelessly" (p.37).

❗
- Do not apply excessive force on the antenna. Doing so may damage it.

7 Connecting other devices

Connecting a device compatible with the trigger function

The trigger function can control an external device in conjunction with operating the unit (such as powering on/off and input selection). If you have a Yamaha subwoofer that supports a system connection or a device with a trigger input jack, you can use the trigger function by connecting the external device to the TRIGGER OUT jack with a monaural mini-plug cable.

TRIGGER OUT jack

The unit (rear)

System connector jack

Yamaha subwoofer that supports a system connection

• You can configure the trigger function settings in "Trigger Output" (p.116) in the "Setup" menu.

8 Connecting the power cable

Before connecting the power cable (General model only)

Set the switch position of VOLTAGE SELECTOR according to your local voltage. Voltages are AC 110–120/220–240 V, 50/60 Hz.

!

- Make sure you set VOLTAGE SELECTOR of the unit BEFORE plugging the power cable into an AC wall outlet. Improper setting of VOLTAGE SELECTOR may cause damage to the unit and create a potential fire hazard.

VOLTAGE SELECTOR

The unit (rear)

After all the connections are complete, plug in the power cable.

The unit (rear)

To an AC wall outlet

9 Selecting an on-screen menu language

Select the desired on-screen menu language from English, Japanese, French, German, Spanish, Russian, Italian and Chinese.

1 Press ⏻ (receiver power) to turn on the unit.

2 Turn on the TV and switch the TV input to display video from the unit (HDMI OUT jack).

> 💡
> • If you turn on the unit for the first time, the message regarding the network setup appears. For now, press RETURN and proceed to Step 3.

3 Press ON SCREEN.

4 Use the cursor keys to select "Setup" and press ENTER.

Setup

5 Use the cursor keys (◁/▷) to select "Language" and the cursor keys (△/▽) to select the desired language.

Language

6 To confirm the setting, press ENTER.

7 To exit from the menu, press ON SCREEN.

> 💡
> • The information on the front display is provided in English only.

ON SCREEN

Cursor keys
ENTER
RETURN

En **31**

10 Optimizing the speaker settings automatically (YPAO)

The Yamaha Parametric room Acoustic Optimizer (YPAO) function detects speaker connections, measures the distances from them to your listening position(s), and then automatically optimizes the speaker settings, such as volume balance and acoustic parameters, to suit your room.

- The YPAO function of the unit adopts the YPAO-R.S.C. (Reflected Sound Control) technology that enables to create natural sound fields like a room specifically designed for acoustic perfection.

- Note the following regarding YPAO measurement.
  - Test tones are output at high volume and may surprise or frighten small children.
  - Test tone volume cannot be adjusted.
  - Keep the room as quiet as possible
  - Stay in a corner of the room behind the listening position so that you do not become an obstacle between speakers and the YPAO microphone.
  - Do not connect headphones.

1 Press ⏻ (receiver power) to turn on the unit.

2 Turn on the TV and switch the TV input to display video from the unit (HDMI OUT jack).

- If you turn on the unit for the first time, the message regarding the network setup appears. For now, press RETURN and proceed to Step 3.

3 Turn on the subwoofer and set the volume to half. If the crossover frequency is adjustable, set it to maximum.

- If you want to use the presence speakers for 7.1-channel system (using presence speakers) (p.15), set "Power Amp Assign" (p.105) in the "Setup" menu to "Presence" before starting YPAO.

- If you are using bi-amp connection or Zone2 speakers, set "Power Amp Assign" (p.105) in the "Setup" menu to the appropriate setting before starting YPAO.

- If you want to use the surround speakers for the front 5.1-channel system (Virtual CINEMA FRONT) (p.16), set "Layout (Surround)" (p.106) in the "Setup" menu to "Front".

4 Place the YPAO microphone at your listening position and connect it to the YPAO MIC jack on the front panel.

- Place the YPAO microphone at your listening position (same height as your ears). We recommend the use of a tripod as a microphone stand. You can use the tripod screws to stabilize the microphone.

The following screen appears on the TV.

This completes the preparations.

5 **To start the measurement, use the cursor keys to select "Measure" and press ENTER.**

The measurement will start in 10 seconds. Press ENTER again to start the measurement immediately.

• To cancel the measurement temporarily, press RETURN.

The following screen appears on the TV when the measurement finishes.

• If any error message (such as E-1) or warning message (such as W-1) appears, see "Error messages" (p.35) or "Warning messages" (p.36).

• To check the measurement results, select "Result". For details, see "Checking the measurement results" (p.34).

6 **Use the cursor keys to select "Save/Cancel" and press ENTER.**

7 **To save the measurement results, use the cursor keys (◁/▷) to select "SAVE" and press ENTER.**

The adjusted speaker settings are applied.

• To finish the measurement without saving the result, select "CANCEL".

8 **Use the cursor keys (◁/▷) to select "YES" or "NO" to enable/disable YPAO Volume and press ENTER.**

• If YPAO Volume is enabled, the high- and low-frequency levels are automatically adjusted according to the volume so that you can enjoy natural sounds even at low volume.

• You can also enable/disable YPAO Volume in "YPAO Volume" (p.93) in the "Option" menu.

9 **Disconnect the YPAO microphone from the unit.**

This completes optimization of the speaker settings.

Caution

• The YPAO microphone is sensitive to heat, so should not be placed anywhere where it could be exposed to direct sunlight or high temperatures (such as on top of AV equipment).

Cursor keys
ENTER
RETURN

Checking the measurement results

You can check the YPAO measurement results.

1 **After the measurement, use the cursor keys to select "Result" and press ENTER.**

💡

- You can also select "Result" from "Auto Setup" (p.103) in the "Setup" menu, which displays the previous measurement results.

The following screen appears.

① **Measurement result items**

② **Measurement result details**

2 **Use the cursor keys to select an item.**

Wiring	Polarity of each speaker **Reverse:** The speaker cable may be connected with the reverse polarity (+/-).
Size	Size of each speaker (cross-over frequency of the subwoofer) **Large:** The speaker can reproduce low-frequency signals effectively. **Small:** The speaker cannot reproduce low-frequency signals effectively.
Distance	Distance from the listening position to each speaker
Level	Output level adjustment for each speaker

3 **To finish checking the results and return to the previous screen, press RETURN.**

Reloading the previous YPAO adjustments

When the speaker settings you have configured manually are not suitable, follow the procedure below to discard the manual settings and reload the previous YPAO adjustments.

1 **In the "Setup" menu, select "Speaker", "Auto Setup", and then "Result" (p.102).**

2 **Use the cursor keys to select "Setup Reload" and press ENTER.**

3 **To exit from the menu, press ON SCREEN.**

ON SCREEN

Cursor keys
ENTER
RETURN

Error messages

If any error message is displayed during the measurement, resolve the problem and perform YPAO again.

Error message	Cause	Remedy
E-1: No Front SP	Front speakers are not detected.	Follow the on-screen instructions to exit YPAO, turn off the unit, and then check the speaker connections.
E-2: No Sur. SP	One of the surround speakers cannot be detected.	
E-3: No F.PRNS SP	One of the presence speakers cannot be detected.	
E-4: SBR → SBL	A surround back speaker is connected to the R side only.	When using only one surround back speaker, you need to connect it to the SINGLE jack (L side). Follow the on-screen instructions to exit YPAO, turn off the unit, and then reconnect the speaker.
E-5: Noisy	The noise is too loud.	Keep the room quiet and follow the on-screen instructions to start the measurement again. If you select "PROCEED", YPAO takes the measurement again and ignores any noise detected.
E-6: Check Sur.	Surround back speakers are connected, but no surround speakers are connected.	Surround speakers need to be connected in order to use surround back speakers. Follow the on-screen instructions to exit YPAO, turn off the unit, and then reconnect the speakers.
E-7: No MIC	The YPAO microphone has been removed.	Connect the YPAO microphone to the YPAO MIC jack firmly and follow the on-screen instructions to start the measurement again.
E-8: No Signal	The YPAO microphone cannot detect test tones.	Connect the YPAO microphone to the YPAO MIC jack firmly and follow the on-screen instructions to start the measurement again. If this error occurs repeatedly, contact the nearest authorized Yamaha dealer or service center.
E-9: User Cancel	The measurement has been canceled.	Follow the on-screen instructions to start the measurement again. To cancel the measurement, select "EXIT".
E-10: Internal Error	An internal error has occurred.	Follow the on-screen instructions to exit YPAO, turn off and on the unit. If this error occurs repeatedly, contact the nearest authorized Yamaha dealer or service center.

Warning messages

If a warning message is displayed after the measurement, you can still save the measurement results by following on-screen instructions.

However, we recommend you perform YPAO again in order to use the unit with the optimal speaker settings.

Warning message	Cause	Remedy
W-1: Out of Phase	A speaker cable may be connected with the reverse polarity (+/-).	Select "Wiring" in "Result" (p.34) and check the cable connections (+/-) of the speaker identified by "Reverse". **If the speaker is connected incorrectly:** Turn off the unit and then reconnect the speaker cable. **If the speaker is connected correctly:** Depending on the type of speakers or room environment, this message may appear even if the speakers are connected correctly. In this case, you can ignore the message.
W-2: Over Distance	A speaker is placed more than 24 m (80 ft) from the listening position.	Select "Distance" in "Result" (p.34) and move the speaker identified by ">24.00m (>80.0ft)" within 24 m (80 ft) of the listening position.
W-3: Level Error	There are significant volume differences between the speakers.	Check the usage environment and cable connections (+/-) of each speaker, and the volume of the subwoofer. We recommend using the same speakers or speakers with specifications that are as similar as possible.

11 Connecting to a network device wirelessly

Connect the unit to a wireless router (access point) or a mobile device by establishing a wireless connection.

Selecting the connection method

Select a connection method according to your network environment.

■ Connecting with a wireless router (access point)

Connect the unit to a wireless router (access point).

You can enjoy Internet radio, AirPlay, or music files stored on media servers (PC/NAS) on the unit.

Internet
Wireless router
Modem
Mobile device (such as iPhone)
The unit

For details on connection, see "Connecting the unit to a wireless network" (p.38).

❗

- You cannot use the wireless network connection simultaneously with the wired (network cable) connection (p.28) or Wireless Direct (p.44).
- If the unit and the wireless router (access point) are too far apart, the unit may not connect to a wireless router (access point). In such case, place them close to each other.

■ Connecting without a wireless router (access point)

Connect a mobile device to the unit directly.

You can use the application for smartphone / tablet "AV CONTROLLER" to control the unit from mobiles devices or enjoy music files stored on mobiles devices on the unit.

Mobile device (such as iPhone)
The unit

For details on connection, see "Connecting a mobile device to the unit directly (Wireless Direct)" (p.44).

❗

- You cannot use Wireless Direct simultaneously with the wired (network cable) connection (p.28) or the wireless network connection (p.38).
- When Wireless Direct is enabled, the following functions are not available.
  – Internet radio
  – Network services
  – Playback of music stored on media servers (PC/NAS)

💡

- For details on "AV CONTROLLER", visit the Yamaha website.

ON SCREEN

Cursor keys
ENTER

Connecting the unit to a wireless network

There are several methods to connect the unit to a wireless network.

Select a connection method according to your environment.

| Do you own iOS devices (iPhone/iPod touch)? | Yes → **A** (p.38) |

No ↓

| Does your wireless router (access point) have a WPS button? | Yes → **B** (p.40) |

No ↓

C (p.41)

■ A: Sharing the iOS device setting

You can easily setup a wireless connection by applying the connection settings on iOS devices (iPhone/iPod touch).

Before proceeding, confirm that your iOS device is connected to a wireless router.

1 Press ⏻ (receiver power) to turn on the unit.

2 Turn on the TV and switch the TV input to display video from the unit (HDMI OUT jack).

> ❗
> • Operations with TV screen are available only when your TV is connected to the unit via HDMI.

3 Press ON SCREEN.

4 Use the cursor keys to select "Setup" and press ENTER.

5 Use the cursor keys (◁/▷) to select "Network".

6 Use the cursor keys (△/▽) to select "Network Connection" and press ENTER.

7 Use the cursor keys (△/▽) and ENTER to check "Wireless (Wi-Fi)" and select "OK".

> 🔅
> • The checkmark indicates the current setting.

8 Use the cursor keys (△/▽) and ENTER to check "Share Wi-Fi Settings (iOS)" and select "NEXT".

9 **Use the cursor keys (△/▽) and ENTER to select the desired connection method and select "NEXT".**

```
                    Network
        Select method for sharing settings with iOS device.
        ✓ Wireless ( WAC )
          USB Cable


               NEXT      BACK      CANCEL

        Select: ENTER
```

The following connection methods are available.

Wireless (WAC)	You can apply the connection settings on the iOS device to the unit using a wireless connection. For details, see "Sharing the iOS device setting wirelessly". (You need iOS device with iOS 7 or later.)
USB Cable	You can apply the connection settings on the iOS device to the unit using a USB cable. For details, see "Sharing the iOS device setting using a USB cable". (You need iOS device with iOS 5 or later.)

!

• This configuration does not work if the security method of your wireless router (access point) is WEP. In this case, use other connection method.

❑ Sharing the iOS device setting wirelessly

If you select "Wireless (WAC)" as the connection method, perform the network setting sharing operation on your iOS device. (The following procedure is a setup example for iOS 8.)

1 **On the iOS device, select the unit as the AirPlay speaker in the Wi-Fi screen.**

```
   ‹ Settings        Wi-Fi


     Wi-Fi                          ⬤
   ✓ XXXXX                   🔒 �dB ⓘ

   CHOOSE A NETWORK…

     Other…

   SET UP NEW AIRPLAY SPEAKER…

     XXXXXXX XXXXXX               ›
```
The name of the unit

2 **Check the network currently selected and tap "Next".**

```
   Cancel    AirPlay Setup    Next
```
Tap here to start setup
```
   This AirPlay speaker will be set up to join "XXXXX".

   NETWORK

     XXXXX                          ✓
```
The network currently selected
```
   Show Other Networks…


   Speaker Name  XXXXXXX XXXXXX
```

When the sharing process finishes, the unit is automatically connected to the selected network (access point).

Cursor keys
ENTER

ON SCREEN

Cursor keys
ENTER

❑ **Sharing the iOS device setting using a USB cable**

If you select "USB Cable" as the connection method, follow the procedure below to share the iOS device setting with the unit.

1 **Connect the iOS device to the USB jack, and disable the screen lock on the iOS device.**

The unit (front)

2 **Use the cursor keys (◁/▷) to select "NEXT" and press ENTER.**

3 **Tap "Allow" in the message appeared on the iOS device.**

When the connection process finishes, "Completed" appears on the TV screen.

4 **To exit from the menu, press ON SCREEN.**

■ **B: Using the WPS push button configuration**

You can easily set up a wireless connection with one push of the WPS button.

!

• This configuration does not work if the security method of your wireless router (access point) is WEP. In this case, use other connection method.

1 **Press ⏻ (receiver power) to turn on the unit.**

2 **Hold down INFO (WPS) on the front panel for 3 seconds.**

"Press WPS button on Access Point" appears on the front display.

3 **Push the WPS button on the wireless router (access point).**

When the connection process finishes, "Completed" appears on the front display.

If "Not connected" appears, repeat from Step 1 or try another connection method.

■ C: Using other connection methods

If your wireless router (access point) does not support WPS push button configuration method, follow the procedure below to configure the wireless network settings.

1 Press ⏻ (receiver power) to turn on the unit.

2 Turn on the TV and switch the TV input to display video from the unit (HDMI OUT jack).

> ❗
> • Operations with TV screen are available only when your TV is connected to the unit via HDMI.

3 Press ON SCREEN.

4 Use the cursor keys to select "Setup" and press ENTER.

5 Use the cursor keys (◁/▷) to select "Network".

6 Use the cursor keys (△/▽) to select "Network Connection" and press ENTER.

7 Use the cursor keys (△/▽) and ENTER to check "Wireless (Wi-Fi)" and select "OK".

> 🔅
> • The checkmark indicates the current setting.

8 Use the cursor keys (△/▽) and ENTER to select the desired connection method and select "NEXT".

The following connection methods are available.

WPS Button	You can set up a wireless connection with the WPS button while viewing the TV screen. Follow the instructions displayed on the TV screen.
Share Wi-Fi Settings (iOS)	See "Sharing the iOS device setting" (p.38).
Access Point Scan	You can set up a wireless connection by searching for an access point. For details on settings, see "Searching for an access point" (p.42).
Manual Setting	You can set up a wireless connection by entering the required information (such as SSID) manually. For details on settings, see "Setting up the wireless connection manually" (p.42).
PIN Code	You can set up a wireless connection by entering the unit's PIN code into the wireless router (access point). The method is available if the wireless router (access point) supports the WPS PIN code method. For details on settings, see "Using the PIN code" (p.43).

About WPS

WPS (Wi-Fi Protected Setup) is a standard established by the Wi-Fi Alliance, which allows easy establishment of a wireless home network.

ON SCREEN

Cursor keys
ENTER

❏ Searching for an access point

If you select "Access Point Scan" as the connection method, the unit starts searching for access points. After a while, the list of available access points appears on the TV screen.

1 **Use the cursor keys and ENTER to check the desired access point and select "NEXT".**

The wireless connection setting screen appears on the TV.

2 **Use the cursor keys and ENTER to enter the security key and select "NEXT".**

3 **Use the cursor keys (◁/▷) to select "CONNECT" and press ENTER to start the connection process.**

When the connection process finishes, "Completed" appears on the TV screen.

If "Not connected" appears, repeat from Step 1 or try another connection method.

4 **To exit from the menu, press ON SCREEN.**

❏ Setting up the wireless connection manually

If you select "Manual Setting" as the connection method, the wireless connection setting screen appears on the TV.

You need to setup the SSID (network name), encryption method and security key for your network.

1 **Use the cursor keys and ENTER to enter the SSID of the access point and select "NEXT".**

2 **Use the cursor keys (△/▽) and ENTER to check the security method of the access point and select "NEXT".**

Settings
None, WEP, WPA2-PSK (AES), Mixed Mode

ON SCREEN

Cursor keys
ENTER

3 **Use the cursor keys and ENTER to enter the security key and select "NEXT".**

If you select "None" in Step 2, this setting is not available. Proceed to Step 4.

If you select "WEP", enter either 5 or 13 character string, or 10 or 26 hexadecimal digits.

If you select other method, enter either 8 to 63 character string, or 64 hexadecimal digits.

4 **Use the cursor keys (◁/▷) to select "CONNECT" and press ENTER to start the connection process.**

When the connection process finishes, "Completed" appears on the TV screen.

If "Not connected" appears, check that all the information is entered correctly, and repeat from Step 1.

5 **To exit from the menu, press ON SCREEN.**

❑ **Using the PIN code**

If you select "PIN Code" as the connection method, the list of available access points appears on the TV screen.

1 **Use the cursor keys and ENTER to check the desired access point and select "NEXT".**

The PIN code of the unit appears on the TV screen.

2 **Enter the unit's PIN code into the wireless router (access point).**

For details on settings, refer to the instruction manual of the wireless router (access point).

3 **Use the cursor keys (◁/▷) to select "CONNECT" and press ENTER to start the connection process.**

When the connection process finishes, "Completed" appears on the TV screen.

If "Not connected" appears, repeat from Step 1 or try another connection method.

4 **To exit from the menu, press ON SCREEN.**

ON SCREEN

Cursor keys
ENTER

Connecting a mobile device to the unit directly (Wireless Direct)

Follow the procedure below to connect a mobile device to the unit directly.

!

- Wireless Direct connection may be insecure since the communication is not strongly encrypted. The unit may operate by playback operation on wireless devices connected to the unit without permission.

1 Press ⏻ (receiver power) to turn on the unit.

2 Turn on the TV and switch the TV input to display video from the unit (HDMI OUT jack).

!

- Operations with TV screen are available only when your TV is connected to the unit via HDMI.

3 Press ON SCREEN.

4 Use the cursor keys to select "Setup" and press ENTER.

5 Use the cursor keys (◁/▷) to select "Network".

6 Use the cursor keys (△/▽) to select "Network Connection" and press ENTER.

7 Use the cursor keys (△/▽) and ENTER to check "Wireless Direct" and select "OK".

☼

- The checkmark indicates the current setting.

8 Use the cursor keys (△/▽) and ENTER to check the desired security method and select "NEXT".

Settings
None, WPA2-PSK (AES)

!

- If you select "None", the connection may be insecure since the communication is not encrypted.

ON SCREEN

Cursor keys
ENTER

ON SCREEN

Cursor keys ENTER

9 **Use the cursor keys and ENTER to enter the security key and select "NEXT".**

If you select "None" in Step 8, this setting is not available. Proceed to Step 10.

Otherwise, enter either 8 to 63 character string, or 64 hexadecimal digits.

10 **Use the cursor keys (◁/▷) to select "OK" and press ENTER to save the setting.**

The settings made appear on the TV screen.

The SSID and security key information is required for setup of a mobile device.

11 **Configure the Wi-Fi settings of a mobile device.**

For details on settings of your mobile device, refer to the instruction manual of the mobile device.

① Enable the Wi-Fi function on the mobile device.

② Select the SSID displayed in Step 10 from the list of available access points.

③ When you are prompted for a password, enter the security key displayed in Step 10.

12 **To exit from the menu, press ON SCREEN.**

En **45**

PLAYBACK

Basic playback procedure

1 **Turn on the external devices (such as a TV or BD/DVD player) connected to the unit.**

2 **Use the input selection keys to select an input source.**

3 **Start playback on the external device or select a radio station.**

Refer to the instruction manual for the external device.

For details on the following operations, see the corresponding pages.

- Listening to FM/AM radio (RX-AS710) (p.54)
- Listening to DAB radio (RX-AS710D) (p.58)
- Listening to FM radio (RX-AS710D) (p.62)
- Playing back music via *Bluetooth* (p.66)
- Playing back iPod music (p.67)
- Playing back music stored on a USB storage device (p.70)
- Playing back music stored on media servers (PCs/NAS) (p.73)
- Listening to Internet radio (p.77)
- Playing back music with AirPlay (p.80)

4 **Press VOLUME to adjust the volume.**

💡
- To mute the audio output, press MUTE. Press MUTE again to unmute.
- To adjust the treble/bass settings, use the "Option" menu (p.93).

Input selection keys

HDMI OUT

MUTE

VOLUME

ON SCREEN

**Cursor keys
ENTER**

On-screen input selection

① Press ON SCREEN.
② Use the cursor keys to select "Input" and press ENTER.
③ Use the cursor keys to select the desired input source and press ENTER.

Selecting an HDMI output jack

1 **Press HDMI OUT to select an HDMI OUT jack.**

Each time you press the key, the HDMI OUT jack to be used for signal output changes.

HDMI OUT 1	Output the signals at the HDMI OUT jack.
HDMI OUT Off	Does not output the signals at the HDMI OUT jack.

Selecting the input source and favorite settings with one touch (SCENE)

The SCENE function allows you to select the assigned input source, sound program and Compressed Music Enhancer on/off with just one touch.

SCENE

1 Press SCENE.

The input source and settings registered to the corresponding scene are selected. The unit turns on automatically when it is in standby mode.

By default, the following settings are registered for each scene.

SCENE	BD DVD	TV	NET	RADIO
Input	HDMI 1	AUDIO 1	NET RADIO	TUNER
Sound program	MOVIE (Sci-Fi)	STRAIGHT	MUSIC (7ch Stereo)	MUSIC (7ch Stereo)
Compressed Music Enhancer	Off	On	On	On

Configuring scene assignments

1 Perform the following operations to prepare the settings you want to assign to a scene.

- Select an input source (p.46)
- Select a sound program (p.48)
- Enable/disable Compressed Music Enhancer (p.53)

2 Hold down the desired SCENE key until "SET Complete" appears on the front display.

```
SCENE 1                    VOL. -30.8dB
SET Complete
```

- You can also configure scene assignments in the "Scene" menu (p.97).
- The SCENE link playback function allows you to start playback of an external device connected to the unit via HDMI. To enable SCENE link playback, specify the device type in "Device Control" (p.98) in the "Scene" menu.

Selecting the sound mode

The unit is equipped with a variety of sound programs and surround decoders that allow you to enjoy playback sources with your favorite sound mode (such as sound field effect or stereo playback).

❑ Selecting a sound program suitable for movies

• Press MOVIE repeatedly.

This mode lets you enjoy sound field effects optimized for viewing video sources, such as movies, TV programs, and games (p.49).

❑ Selecting a sound program suitable for music or stereo playback

• Press MUSIC repeatedly.

This mode lets you enjoy sound field effects optimized for listening music sources or stereo playback (p.50).

❑ Selecting a surround decoder

• Press SUR.DECODE repeatedly.

This mode lets you enjoy unprocessed multichannel playback from 2-channel sources (p.52).

❑ Switching to the straight decode mode

• Press STRAIGHT.

This mode lets you enjoy unprocessed sounds in original channels (p.52).

❑ Switching to the Pure Direct mode

• Press PURE DIRECT.

This mode lets you enjoy pure high fidelity sound by reducing the electrical noise from other circuitry (p.53).

❑ Enabling Compressed Music Enhancer

• Press ENHANCER.

This mode lets you enjoy compressed music with additional depth and breadth (p.53).

On-screen sound program/surround decoder selection

① Press ON SCREEN.

② Use the cursor keys to select "DSP Program" and press ENTER.

③ Use the cursor keys to select a sound program/surround decoder and press ENTER.

• You can also switch the sound programs and surround decoder by pressing PROGRAM.
• You can change the settings of the surround programs and surround decoders in the "DSP Program" menu (p.99).
• The sound mode can be applied separately to each input source.
• When you play back audio signals with a sampling rate of higher than 96 kHz, the straight decode mode (p.52) is automatically selected.
• You can check which speakers are currently outputting sound by looking at the speaker indicators on the unit's front panel (p.10) or at the "Audio Signal" screen in the "Information" menu (p.118).

PROGRAM

ON SCREEN

Cursor keys
ENTER

MOVIE
MUSIC
SUR.DECODE
STRAIGHT
ENHANCER
PURE DIRECT

Enjoying stereoscopic sound fields (CINEMA DSP 3D)

CINEMA DSP 3D DIGITAL

The unit is equipped with a variety of sound programs that utilize Yamaha's original DSP technology (CINEMA DSP 3D). It allows you to easily create sound fields like actual movie theaters or concert halls in your room and enjoy natural stereoscopic sound fields.

Sound program category

"CINEMA DSP" lights up

```
MUSIC      CINEMADSP   VOL. -30.0dB
Hall in Vienna
```

Sound program

- To use the conventional CINEMA DSP, set "CINEMA DSP 3D Mode" (p.109) in the "Setup" menu to "Off".
- We recommend using presence speakers in order to experience the full effect of the stereoscopic sound fields. However, even when no presence speakers are connected, the unit creates Virtual Presence Speaker (VPS) using the front, center, and surround speakers to produce stereoscopic sound fields.
- If a multichannel source (6.1 channels or more) is input when no surround back speakers are connected, the unit creates Virtual Surround Back Speaker (VSBS) using the surround speakers to add a sense of depth to the rear sound field.
- When VPS or VSBS is working, "VIRTUAL" lights up in the front display.

■ Sound programs suitable for movies (MOVIE)

The following sound programs are optimized for viewing video sources, such as movies, TV programs, and games.

❑ MOVIE THEATER

Standard	This program creates a sound field that emphasizes the surround feeling without disturbing the original acoustic positioning of multichannel audio, such as Dolby Digital and DTS. Its design is based on the concept of the ideal movie theater, in which the audience is surrounded by beautiful reverberations from the left, right, and rear.
Spectacle	This program delivers the scale and grandeur of spectacular movie productions. It delivers an expansive sound space to match the cinemascope wide-screen, and boasts a broad dynamic range, providing everything from small delicate sounds to powerful loud booms.
Sci-Fi	This program clearly reproduces the finely elaborated sound design of the latest Sci-Fi and SFX movies. You can enjoy a variety of cinematographically created virtual spaces reproduced with clear separation between dialogue, sound effects, and background music.
Adventure	This program is ideal for reproducing the sound design of action and adventure movies precisely. The sound field restrains reverberations, but puts emphasis on reproducing a sensation of expansiveness on both sides, powerful space expanded widely to the left and right. The restrained depth creates a clear and powerful space, while also maintaining the articulation of the sounds and the separation of the channels.
Drama	This program features stable reverberations that match a wide range of movie genres, from serious dramas to musicals and comedies. The reverberations are modest, but suitably stereophonic. The sound effects and background music are reproduced with a gentle echo that does not impinge on the articulation of the dialogue. You'll never get tired listening for long periods.
Mono Movie	This program reproduces monaural video sources, such as classic movies, in an atmosphere of a good old movie theater. The program creates a pleasant space with depth, by adding breadth and the appropriate reverberation to the original audio.

❑ ENTERTAINMENT

Sports	This program allows listeners to enjoy the rich vividness of sport broadcasts and light entertainment programs. In sports broadcasts, the commentators' voices are positioned clearly at the center, while the atmosphere inside the stadium is realistically conveyed by the peripheral delivery of the sounds of the fans in a suitable space.
Action Game	This program is suitable for action games, such as car racing and fighting games. The reality of, and emphasis on, various effects makes the player feel like they are right in the middle of the action, allowing for greater concentration. Use this program in combination with Compressed Music Enhancer for a more dynamic and strong sound field.
Roleplaying Game	This program is suitable for role-playing and adventure games. This program adds depth to the sound field for natural and realistic reproduction of background music, special effects, and dialogue from a wide variety of scenes. Use this program in combination with Compressed Music Enhancer for a clearer and more spatial sound field.
Music Video	This program allows you to enjoy videos of pop, rock, and jazz concerts, as if you were there yourself. Immerse yourself in the hot concert atmosphere thanks to the vividness of the singers and solos on stage, a presence sound field that emphasizes the beat of rhythm instruments, and a surround sound field that reproduces the space of a big live hall.

■ Sound programs suitable for music/stereo playback (MUSIC)

The following sound programs are optimized for listening to music sources.

You can also select stereo playback.

❑ CLASSICAL

Hall in Munich	This program simulates a Munich concert hall with approximately 2,500 seats that uses stylish wood for the interior finishing. Fine, beautiful reverberations spread richly, creating a calming atmosphere. The listener's virtual seat is at the center left of the arena.
Hall in Vienna	This program simulates a 1,700-seat, middle-sized concert hall with a shoebox shape that is traditional in Vienna. Pillars and ornate carvings create extremely complex reverberations from all around the audience, producing a very full, rich sound.
Chamber	This program creates a relatively wide space with a high ceiling, like an audience hall in a palace. It offers pleasant reverberations that are suitable for courtly music and chamber music.

❑ LIVE/CLUB

Cellar Club	This program simulates an intimate concert venue with a low ceiling and homey atmosphere. A realistic, live sound field delivers powerful sounds that make you feel as if you are sitting in the front row in front of a small stage.
The Roxy Theatre	This program creates the sound field of a 460-seat rock music concert venue in Los Angeles. The listener's virtual seat is at the center left of the hall.
The Bottom Line	This program creates the sound field at stage front in The Bottom Line, a famous New York jazz club once. The floor can seat 300 people to the left and right in a sound field offering real and vibrant sound.

❑ STEREO

2ch Stereo	Use this program to mix down multichannel sources to 2 channels. When multichannel signals are input, they are down mixed to 2 channels and output from the front speakers (this program does not utilize CINEMA DSP).
7ch Stereo	Use this program to output sound from all speakers. When you play back multichannel sources, the unit mixes down the source to 2 channels, and then outputs the sound from all speakers. This program creates a larger sound field and is ideal for background music at parties.

!

• CINEMA DSP 3D (p.49) and Virtual CINEMA DSP (p.51) do not work when "2ch Stereo" or "7ch Stereo" is selected.

■ Enjoying sound field effects without surround speakers (Virtual CINEMA DSP)

If you select one of the sound programs (except 2ch Stereo and 7ch Stereo) when no surround speakers are connected, the unit utilizes Yamaha's original virtual surround technology to reproduce up to 7-channel surround sound and enable you to enjoy the well-oriented sound field only with the front-side speakers. We recommend using presence speakers in order to enjoy more effective stereoscopic sound field.

• When Virtual CINEMA DSP is working, "VIRTUAL" lights up in the front display.

■ Enjoying surround sound with 5 speakers placed in front (Virtual CINEMA FRONT)

If you have surround speakers but there is no space to place them in the rear of your room, you can place them in the front (p.16) and enjoy multichannel surround sound using Virtual CINEMA FRONT.

When "Layout (Surround)" (p.106) in the "Setup" menu is set to "Front", the unit creates the virtual surround speakers in the rear side to allow you to enjoy multichannel surround sound with the 5 speakers placed in the front.

• When Virtual CINEMA FRONT is working, "VIRTUAL" lights up in the front display.

■ Enjoying surround sound with headphones (SILENT CINEMA)

SILENT ™
CINEMA

You can enjoy surround or sound field effects, like a multichannel speaker system, with stereo headphones by connecting the headphones to the PHONES jack and selecting a sound program or a surround decoder.

Enjoying unprocessed playback

You can play back input sources without any sound field effect processing.

■ Playing back in original channels (straight decode)

When the straight decode mode is enabled, the unit produces stereo sound from the front speakers for 2-channel sources such as CDs, and produces unprocessed multichannel sounds for multichannel sources.

1 Press STRAIGHT.

Each time you press the key, the straight decode mode is enabled or disabled.

```
                              VOL -30.8
                                     dB
        STRAIGHT           L C R
                           SL SW SR
```

!
• If "Layout (Surround)" (p.106) in the "Setup" menu is set to "Front", Virtual CINEMA FRONT (p.51) works when multichannel source is played back.

■ Playing back 2-channel sources in multichannel (surround decoder)

The surround decoder enables unprocessed multichannel playback from 2-channel or multichannel sources.

☼
• Speakers that produce sounds will change depending on your speaker system and the selected decode type (p.100).
• For details on each decoder, see "Glossary" (p.136).

1 Press SUR.DECODE to select a surround decoder.

Each time you press the key, the surround decoder changes.

```
      SUR.DECODE              VOL -30.8
                                     dB
      ⫿⫿PLIIx MOVIE        L C R
                           SL SW SR
```

Decoder	Description
⫿⫿PLIIx Movie	Use the Dolby Pro Logic IIx decoder (or Dolby Pro Logic II decoder) suitable for movies. Sounds will be output from the surround/surround back speakers even when 2-channel source is input.
⫿⫿PLII Movie	
⫿⫿PLIIx Music	Use the Dolby Pro Logic IIx decoder (or Dolby Pro Logic II decoder) suitable for music. Sounds will be output from the surround/surround back speakers even when 2-channel source is input.
⫿⫿PLII Music	
⫿⫿PLIIx Game	Use the Dolby Pro Logic IIx decoder (or Dolby Pro Logic II decoder) suitable for games. Sounds will be output from the surround/surround back speakers even when 2-channel source is input.
⫿⫿PLII Game	
Neo:6 Cinema	Uses the DTS Neo:6 decoder (or DTS-ES Matrix decoder) suitable for movies. Sounds will be output from the surround/surround back speakers.
Neo:6 Music	Uses the DTS Neo:6 decoder (or DTS-ES Matrix decoder) suitable for music. Sounds will be output from the surround/surround back speakers.

!
• You cannot select the Dolby Pro Logic IIx decoders when headphones are connected or when "Surround Back" in the "Setup" menu is set to "None".

SUR.DECODE

STRAIGHT

Enjoying pure high fidelity sound (Pure Direct)

When the Pure Direct mode is enabled, the unit plays back the selected source with the least circuitry in order to reduce the electrical noise from other circuitry (such as the front display). It allows you to enjoy Hi-Fi sound quality.

1 Press PURE DIRECT.

Each time you press the key, the Pure Direct mode is enabled or disabled.

```
                          VOL. -30.8dB
  PURE DIRECT             [LCR]
                          [SL SW SR]
                          [SBL SBR]
```

!

• When the Pure Direct mode is enabled, the following functions are not available.
  – Some settings for the speakers or sound programs
  – Operating the on-screen menu and some items in the "Option" menu
  – Using the multi-zone function
  – Viewing information on the front display (when not in operation)

Enjoying compressed music with enhanced sound (Compressed Music Enhancer)

**compressed music
ENHANCER**

Compressed Music Enhancer adds depth and breadth to the sound, allowing you to enjoy a dynamic sound close to the original sound before it was compressed. This function can be used along with any other sound modes.

1 Press ENHANCER.

Each time you press the key, Compressed Music Enhancer is enabled or disabled.

"ENHANCER" lights up

```
  ENHANCER
  CINEMA DSP              VOL. -30.8dB
  Enhancer On             [LCR]
                          [SL SW SR]
                          [SBL SBR]
```

!

• Compressed Music Enhancer does not work on signals whose sampling rate is over 48 kHz.

☼

• You can also use "Enhancer" (p.94) in the "Option" menu to enable/disable Compressed Music Enhancer.

PURE DIRECT

ENHANCER

TUNER

BAND

TUNING

Numeric keys

Listening to FM/AM radio (RX-AS710)

You can tune into a radio station by specifying its frequency or selecting from registered radio stations.

!

- The radio frequencies differ depending on the country or region where the unit is being used. The explanation of this section uses a display with frequencies used in U.K. and Europe models.
- If you cannot obtain good reception on the radio, adjust the direction of the FM/AM antennas.

Setting the frequency steps

(Asia and General models only)

At the factory, the frequency step setting is set to 50 kHz for FM and 9 kHz for AM. Depending on your country or region, set the frequency steps to 100 kHz for FM and 10 kHz for AM.

1 **Set the unit to standby mode.**

2 **When holding down STRAIGHT on the front panel, press ⏻ (power).**

⏻ (power)

STRAIGHT   PROGRAM

3 **Press PROGRAM repeatedly to select "TU".**

4 **Press STRAIGHT to select "FM100/AM10".**

5 **Press ⏻ (power) to set the unit to standby mode and turn it on again.**

Selecting a frequency for reception

1 **Press TUNER to select "TUNER" as the input source.**

2 **Press BAND to select a band (FM or AM).**

3 **Use the following keys to set a frequency.**

TUNING: Increase/decrease the frequency. Hold down the key for about a second to search stations automatically.

Numeric keys: Enter a frequency directly. For example, to select 98.50 MHz, press "9", "8", "5" and "0" (or ENT).

"TUNED" lights up when a signal is received from a radio station.

"STEREO" also lights up when a stereo signal is received.

!

- "Wrong Station!" appears when you enter a frequency that is out of reception range.

☼

- You can switch between "Stereo" (stereo) and "Mono" (monaural) for FM radio reception in "FM Mode" (p.94) in the "Option" menu. When the signal reception for an FM radio station is unstable, switching to monaural may improve it.

Registering favorite radio stations (presets)

You can register up to 40 radio stations as presets. Once you have registered stations, you can easily tune into them by selecting their preset numbers.

💡

• You can automatically register FM radio stations that have strong signals by using "Auto Preset" (p.57).

■ Registering a radio station

Select a radio station manually and register it to a preset number.

1 **Follow "Selecting a frequency for reception" (p.54) to tune into the desired radio station.**

2 **Hold down MEMORY for more than 2 seconds.**

The first time that you do register a station, the selected radio station will be registered to the preset number "01". Thereafter, each radio station you select will be registered to the next empty (unused) preset number after the most recently registered number.

```
MEMORY        STEREO TUNED      VOL. -30.0dB
01:FM 98.50MHz   LCR SL SW SR SBL SB SBR
```
Preset number

💡

• To select a preset number for registering, press MEMORY once after tuning into the desired radio station, press PRESET to select a preset number, and then press MEMORY again.

```
FM 9850       STEREO TUNED      VOL. -30.0dB
02:Empty        LCR SL SW SR SBL SB SBR
```
"Empty" (not in use) or the frequency currently registered

■ Selecting a preset station

Tune into a registered radio station by selecting its preset number.

1 **Press TUNER to select "TUNER" as the input source.**

2 **Press PRESET repeatedly to select the desired radio station.**

You can also enter a preset number (01 to 40) directly by using the numeric keys after pressing PRESET once.

```
PRESET        STEREO TUNED      VOL. -30.0dB
01:FM 98.50MHz   LCR SL SW SR SBL SB SBR
```

❗

• "No Presets" appears when no radio stations are registered.
• "Wrong Num." appears when an invalid number is entered.
• "Empty" appears when a preset number not in use is entered.

💡

• To clear preset stations, use "Clear Preset" or "Clear All Preset" (p.57).

TUNER

BAND
PRESET
TUNING

Numeric keys
MEMORY
ENT

Radio Data System tuning

(U.K. and Europe models only)

Radio Data System is a data transmission system used by FM stations in many countries. The unit can receive various types of Radio Data System data, such as "Program Service", "Program Type," "Radio Text" and "Clock Time", when it is tuned into a Radio Data System broadcasting station.

■ Displaying the Radio Data System information

1 Tune into the desired Radio Data System broadcasting station.

> 💡
> - We recommend using "Auto Preset" to tune into the Radio Data System broadcasting stations (p.57).

2 Press INFO.
Each time you press the key, the displayed item changes.

```
INFO          STEREO TUNED      -30.0
Program Type         VOL   LCR  dB
                          SL SW SR
                          SBL SBR
```

Item name

About 3 seconds later, the corresponding information for the displayed item appears.

```
FM 98.50      STEREO TUNED      -30.0
CLASSICS             VOL   LCR  dB
                          SL SW SR
                          SBL SBR
```

Information

Program Service	Program service name
Program Type	Current program type
Radio Text	Information on the current program
Clock Time	Current time
DSP Program	Sound mode name
Audio Decoder	Decoder name
Frequency	Frequency

> ❗
> - "Program Service", "Program Type", "Radio Text", and "Clock Time" are not displayed if the radio station does not provide the Radio Data System service.

■ Receiving traffic information automatically

When "TUNER" is selected as the input source, the unit automatically receives traffic information. To enable this function, follow the procedure below to set the traffic information station.

1 When "TUNER" is selected as the input source, press OPTION.

2 Use the cursor keys to select "Traffic Program" (TrafficProgram) and press ENTER.

The traffic information station search will start in 5 seconds. Press ENTER again to start the search immediately.

> 💡
> - To search upward/downward from the current frequency, press the cursor keys ($\triangle/\triangledown$) while "READY" is displayed.
> - To cancel the search, press RETURN.
> - Texts in parentheses denote indicators on the front display.

The following screen appears for about 3 seconds when the search finishes.

```
FINISH        STEREO TUNED      -30.0
TP FM101.30MHz       VOL   LCR  dB
                          SL SW SR
                          SBL SBR
```

Traffic information station (frequency)

> ❗
> - "TP Not Found" appears for about 3 seconds when no traffic information stations are found.

TUNER
OPTION
Menu operation keys
Cursor keys
ENTER
RETURN
PRESET
INFO
Numeric keys

Operating the radio on the TV

You can view the radio information or select a radio station on the TV.

1 Press TUNER to select "TUNER" as the input source.

The playback screen is displayed on the TV.

■ Playback screen

❶ Radio station information

Displays the information of the selected radio station such as the selected band (FM/AM) and frequency.

(U.K. and Europe models only)
When tuning into a Radio Data System broadcasting station (p.56), the Radio Data System information ("Program Service", "Program Type," "Radio Text" and "Clock Time") is also displayed.

❷ TUNED/STEREO indicators

"TUNED" lights up when a signal is received from a radio station.
"STEREO" lights up when a stereo signal is received.

❸ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
Browse	Moves to the browse screen (preset station list).
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

■ Browse screen

❶ Preset station list

Displays the list of preset stations. Use the cursor keys to select a preset station and press ENTER to tune into it.

❷ Preset number

❸ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Submenu	Function
Utility	Memory	Registers the current station to the preset number selected in the list.
	Auto Preset	Automatically registers FM radio stations with strong signals (up to 40 stations).
	Clear Preset	Clear the preset station selected in the list.
	Clear All Preset	Clear all the preset stations.
1 Page Up		Moves to the previous/next page of the list.
1 Page Down		
Now Playing		Moves to the playback screen.
Screen Off		Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

!

• (U.K. and Europe models only)
Only Radio Data System broadcasting stations are stored automatically by "Auto Preset".

TUNER

Menu operation keys
Cursor keys
ENTER

Listening to DAB radio (RX-AS710D)

DAB (Digital Audio Broadcasting) uses digital signals for clearer sound and more stable reception compared to analog signals. The unit can also receive DAB+ (an upgraded version of DAB) that allows for more stations using MPEG-4 audio codec (AAC+), which has a more efficient transmission method.

> **!**
> • The unit supports Band III (174 to 240 MHz) only.
> • Be sure to check the DAB coverage in your area in that not all areas are currently being covered. For a list of nationwide DAB statuses and worldwide DAB frequencies, check WorldDMB online at
> http://www.worlddab.org/.

> **☆**
> • For details on the antenna connection, see "Connecting the radio antennas" (p.27).

Preparing the DAB tuning

Before tuning into DAB radio stations, follow the procedure below to perform an initial scan.

1 Press TUNER to select "TUNER" as the input source.

2 Press BAND to select the DAB band.

The following message appears on the front panel if you have not performed an initial scan yet.

```
SCAN                VOL -30.0 dB
[ENTER] to Start
```

3 Press ENTER to start an initial scan.

```
SCAN                VOL -30.0 dB
>>>——————— 30%
```

When the initial scan finishes, the unit automatically tunes into the first DAB radio station as stored in station order.

```
DAB                 VOL -30.0 dB
BBC Radio 4
```

> **☆**
> • If no DAB radio stations are found by an initial scan, the message in Step 1 appears again. Press ENTER to start an initial scan again.
> • You can check reception strength of each DAB channel label (p.61).
> • To perform an initial scan again after some DAB radio stations are stored, select "Init Scan" (p.59) in the "Option" menu. If you perform an initial scan again, the DAB radio stations currently registered to the preset numbers will be cleared.

Selecting a DAB radio station for reception

You can select a DAB radio station from the stations stored by the initial scan.

1 Press TUNER to select "TUNER" as the input source.

2 Press BAND to select the DAB band.

3 Press TUNING repeatedly to select a DAB radio station.

```
DAB                 VOL -30.0 dB
Daily Service
```

> **!**
> • "Off Air" appears when the selected DAB radio station is currently not available.
> • When the unit is receiving a secondary station, "2" appears next to "DAB".

Secondary station

```
DAB  2              VOL -30.0 dB
BBC National
```

TUNER

BAND

PRESET

MEMORY

💡

- You can watch videos input from external devices while listening to radio by selecting the video input jack in "Video Out" (p.94) in the "Option" menu.

Registering favorite DAB radio stations (presets)

You can register up to 40 DAB radio stations as presets. Once you have registered stations, you can easily tune into them by selecting their preset numbers.

💡

- You can register up to 40 favorite radio stations each for DAB and FM bands.

■ Registering a DAB radio station as presets

Select a DAB radio station and register it to a preset number.

1 **Follow "Selecting a DAB radio station for reception" (p.58) to tune into the desired DAB radio station.**

2 **Hold down MEMORY for more than 2 seconds.**

The first time that you do register a station, the selected radio station will be registered to the preset number "01". Thereafter, each radio station you select will be registered to the next empty (unused) preset number after the most recently registered number.

Preset number

💡

- To select a preset number for registering, press MEMORY once after tuning into the desired DAB radio station, press PRESET to select a preset number, and then press MEMORY again.

"Empty" (not in use) or "Overwrite?" (in use)

■ Selecting a preset DAB radio station

Tune into a registered DAB radio station by selecting its preset number.

1 **Press TUNER to select "TUNER" as the input source.**

2 **Press BAND to select the DAB band.**

**3** **Press PRESET repeatedly to select the desired DAB radio station.**

You can also enter a preset number (01 to 40) directly by using the numeric keys after pressing PRESET once.

⚠️

- "No Presets" appears when no DAB radio stations are registered.
- "Wrong Num." appears when an invalid number is entered.
- "Empty" appears when a preset number not in use is entered.

💡

- To clear preset stations, use "Clear Preset" or "Clear All Preset" (p.65).

En **59**

Displaying the DAB information

The unit can receive various types of DAB information when it is tuned into a DAB radio station.

1 **Tune into the desired DAB radio station.**

2 **Press INFO.**

Each time you press the key, the displayed item changes.

```
INFO           VOL -30.0dB
Program Type
```

Item name

About 3 seconds later, the corresponding information for the displayed item appears.

```
DAB            VOL -30.0dB
Classic Music
```

Information

Service Label	Station name
DLS (Dynamic Label Segment)	Information on the current station
Ensemble Label	Ensemble name
Program Type	Station genre
Date And Time	Current date and time
Audio Mode	Audio mode (monaural/stereo) and bit rate
CH Label/Freq.	Channel label and frequency
Signal Quality	Signal reception quality (0 [none] to 100 [best])
DSP Program	Sound mode name
Audio Decoder	Decoder name

!

• Some information may not be available depending on the selected DAB radio station.

INFO

Checking reception strength of each DAB channel label

You can check reception strength of each DAB channel label (0 [none] to 100 [best]).

1 Press TUNER to select "TUNER" as the input source.

2 Press BAND to select the DAB band.

3 Press OPTION.

4 Use the cursor keys to select "Tune Aid" and press ENTER.

5 Use the cursor keys (◁/▷) to select the desired DAB channel label.

```
TUNAID                    VOL. -30.0dB
◀ 5A  Level: 80▶  L C R
                        SL SW SR
```

DAB channel label   Reception strength

6 To exit from the menu, press OPTION.

■ DAB frequency information

The unit supports Band III (174 to 240 MHz) only.

Frequency	Channel label	Frequency	Channel label
174.928 MHz	5A	208.064 MHz	9D
176.640 MHz	5B	209.936 MHz	10A
178.352 MHz	5C	211.648 MHz	10B
180.064 MHz	5D	213.360 MHz	10C
181.936 MHz	6A	215.072 MHz	10D
183.648 MHz	6B	216.928 MHz	11A
185.360 MHz	6C	218.640 MHz	11B
187.072 MHz	6D	220.352 MHz	11C
188.928 MHz	7A	222.064 MHz	11D
190.640 MHz	7B	223.936 MHz	12A
192.352 MHz	7C	225.648 MHz	12B
194.064 MHz	7D	227.360 MHz	12C
195.936 MHz	8A	229.072 MHz	12D
197.648 MHz	8B	230.784 MHz	13A
199.360 MHz	8C	232.496 MHz	13B
201.072 MHz	8D	234.208 MHz	13C
202.928 MHz	9A	235.776 MHz	13D
204.640 MHz	9B	237.488 MHz	13E
206.352 MHz	9C	239.200 MHz	13F

TUNER

OPTION

Cursor keys
ENTER

BAND

Listening to FM radio (RX-AS710D)

You can tune into a radio station by specifying its frequency or selecting from registered radio stations.

❗
• If you cannot obtain good reception on the radio, adjust the direction of the DAB/FM antenna.

Selecting a frequency for reception

1 **Press TUNER to select "TUNER" as the input source.**

2 **Press BAND to select the FM band.**

> FM 87.50MHz
> VOL -30.0 dB

3 **Use the following keys to set a frequency.**

TUNING: Increase/decrease the frequency. Hold down the key for about a second to search stations automatically.

Numeric keys: Enter a frequency directly. For example, to select 98.50 MHz, press "9", "8", "5" and "0" (or ENT).

> STEREO TUNED
> FM 98.50MHz
> VOL -30.0 dB

"TUNED" lights up when a signal is received from a radio station.

"STEREO" also lights up when a stereo signal is received.

❗
• "Wrong Station!" appears when you enter a frequency that is out of reception range.

💡
• You can switch between "Stereo" (stereo) and "Mono" (monaural) for FM radio reception in "FM Mode" (p.94) in the "Option" menu. When the signal reception for an FM radio station is unstable, switching to monaural may improve it.

TUNER

BAND

TUNING

Numeric keys

Registering favorite FM radio stations (presets)

You can register up to 40 FM radio stations as presets. Once you have registered stations, you can easily tune into them by selecting their preset numbers.

☀️
• You can automatically register FM radio stations that have strong signals by using "Auto Preset" (p.65).

■ Registering a radio station

Select a radio station manually and register it to a preset number.

1 Follow "Selecting a frequency for reception" (p.62) to tune into the desired radio station.

2 Hold down MEMORY for more than 2 seconds.

The first time that you do register a station, the selected radio station will be registered to the preset number "01". Thereafter, each radio station you select will be registered to the next empty (unused) preset number after the most recently registered number.

```
MEMORY            STEREO TUNED
                        VOL. -30.0dB
01:FM 98.50MHz    LCR
                  SL SW SR
                  SBL SB SBR
```
Preset number

☀️
• To select a preset number for registering, press MEMORY once after tuning into the desired radio station, press PRESET to select a preset number, and then press MEMORY again.

```
FM 9850           STEREO TUNED
                        VOL. -30.0dB
02:Empty          LCR
                  SL SW SR
                  SBL SB SBR
```
"Empty" (not in use) or the frequency currently registered

■ Selecting a preset station

Tune into a registered radio station by selecting its preset number.

1 Press TUNER to select "TUNER" as the input source.

2 Press BAND to select the FM band.

3 Press PRESET repeatedly to select the desired radio station.

You can also enter a preset number (01 to 40) directly by using the numeric keys after pressing PRESET once.

```
PRESET            STEREO TUNED
                        VOL. -30.0dB
01:FM 98.50MHz    LCR
                  SL SW SR
                  SBL SB SBR
```

❗
• "No Presets" appears when no radio stations are registered.
• "Wrong Num." appears when an invalid number is entered.
• "Empty" appears when a preset number not in use is entered.

☀️
• To clear preset stations, use "Clear Preset" or "Clear All Preset" (p.65).

TUNER
BAND
PRESET
TUNING
Numeric keys
MEMORY
ENT

Radio Data System tuning

Radio Data System is a data transmission system used by FM stations in many countries. The unit can receive various types of Radio Data System data, such as "Program Service", "Program Type," "Radio Text" and "Clock Time", when it is tuned into a Radio Data System broadcasting station.

■ Displaying the Radio Data System information

1 **Tune into the desired Radio Data System broadcasting station.**

- We recommend using "Auto Preset" to tune into the Radio Data System broadcasting stations (p.65).

2 **Press INFO.**
Each time you press the key, the displayed item changes.

Item name

About 3 seconds later, the corresponding information for the displayed item appears.

Information

Program Service	Program service name
Program Type	Current program type
Radio Text	Information on the current program
Clock Time	Current time
DSP Program	Sound mode name
Audio Decoder	Decoder name
Frequency	Frequency

- "Program Service", "Program Type", "Radio Text", and "Clock Time" are not displayed if the radio station does not provide the Radio Data System service.

Operating the radio on the TV

You can view the radio information or select a radio station on the TV.

1 Press TUNER to select "TUNER" as the input source.

The playback screen is displayed on the TV.

■ Playback screen

❶ Radio station information

Displays the information of the selected radio station such as the selected band (DAB/FM) and frequency.

When tuning into a Radio Data System broadcasting station (p.56), the Radio Data System information ("Program Service", "Program Type," "Radio Text" and "Clock Time") is also displayed.

❷ TUNED/STEREO indicators

"TUNED" lights up when a signal is received from a radio station.
"STEREO" lights up when a stereo radio signal is received.

❸ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
Browse	Moves to the browse screen (preset station list).
Screen Off	Closes the screen display and shows the background. Press of the menu operation keys to redisplay it.

■ Browse screen

❶ Preset station list

Displays the list of preset stations. Use the cursor keys to select a preset station and press ENTER to tune into it.

❷ Preset number

❸ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Submenu	Function
Utility	Memory	Registers the current station to the preset number selected in the list.
	Auto Preset	Automatically registers FM radio stations with strong signals (up to 40 stations).
	Clear Preset	Clear the preset station selected in the list.
	Clear All Preset	Clear all the preset stations.
1 Page Up		Moves to the previous/next page of the list.
1 Page Down		
Now Playing		Moves to the playback screen.
Screen Off		Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

> ❗
> • Only Radio Data System broadcasting stations are stored automatically by "Auto Preset".

TUNER

Menu operation keys
Cursor keys
ENTER

Playing back music via *Bluetooth*

You can play back music files stored on a *Bluetooth* device (such as smartphones) on the unit.

BLUETOOTH

External device operation keys

The unit

Bluetooth device
(such as smartphones)

!
• To use the *Bluetooth* function, set "Bluetooth" (p.114) in the "Setup" menu to "On".

☼
• For details on supported *Bluetooth* devices, see "Supported devices and file formats" (p.138).

Playing back *Bluetooth* device music on the unit

Follow the procedure below to establish a *Bluetooth* connection between a *Bluetooth* device (such as smartphones) and the unit, and play back music stored the *Bluetooth* device on the unit.

!
• The unit does not support video playback via *Bluetooth*.

1 **Press BLUETOOTH to select "Bluetooth" as the input source.**

2 **On the *Bluetooth* device, select the unit (network name of the unit) from the available device list.**

A connection between the *Bluetooth* device and the unit will be made.

If the pass key is required, enter the number "0000".

3 **On the *Bluetooth* device, select a song and start playback.**

The playback screen (artist name, album name and song title) is displayed on the TV.

☼
• If the unit detects the *Bluetooth* device previously connected, the unit automatically connects to the *Bluetooth* device after Step 1. To establish another *Bluetooth* connection, first terminate the current *Bluetooth* connection.

• To terminate the *Bluetooth* connection, perform one of the following operations.

– Perform the disconnect operation on the *Bluetooth* device.

– Select an input source other than "Bluetooth" on the unit.

– Select "Disconnect" in "Audio Receive" (p.104) in the "Setup" menu.

• You can use the external device operation keys (►, ■, ❙❙, ❙◄◄, ►►❙) on the remote control to control playback.

Playing back iPod music

You can play back iPod music on the unit using a USB cable supplied with the iPod.

> 💡
> • For details on playable iPod devices, see "Supported devices and file formats" (p.138).

> ❗
> • The unit does not support a USB connection for iPad. To play back iPad music on the unit, use AirPlay (p.80).

Connecting an iPod

Connect your iPod to the unit with the USB cable supplied with the iPod.

1 Connect the USB cable to the iPod.

2 Connect the USB cable to the USB jack.

The unit (front)

> 💡
> • The iPod charges while it is connected to the unit. If you set the unit to standby mode while the iPod is charging, the iPod continues to charge up to 4 hours. If "Network Standby" (p.113) in the "Setup" menu is set to "On", it continues to charge without limit.

> ❗
> • Disconnect the iPod from the USB jack when it is not in use.

Playback of iPod content

Follow the procedure below to operate the iPod contents and start playback.

You can control the iPod with the menu displayed on the TV screen.

1 Press USB to select "USB" as the input source.

The browse screen is displayed on the TV.

> 💡
> • If playback is ongoing on your iPod, the playback screen is displayed.

2 Use the cursor keys to select an item and press ENTER.

If a song is selected, playback starts and the playback screen is displayed.

> 💡
> • To return to the previous screen, press RETURN.
> • To operate the iPod manually to select content or control playback, switch to the simple play mode (p.69).

USB

Cursor keys
ENTER
RETURN

■ Browse screen

❶ Status indicators

Display the current shuffle/repeat settings (p.69) and playback status (such as play/pause).

❷ List name

❸ Contents list

Displays the list of iPod content. Use the cursor keys to select an item and press ENTER to confirm the selection.

❹ Item number/total

❺ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
1 Page Up	Moves to the previous/next page of the list.
1 Page Down	
10 Pages Up	Moves 10 pages forward/backward.
10 Pages Down	
Return	Returns to the higher-level list.
Now Playing	Moves to the playback screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

■ Playback screen

❶ Status indicators

Display the current shuffle/repeat settings (p.69) and playback status (such as play/pause).

❷ Playback information

Displays the artist name, album name, song title, and elapsed/remaining time.
Use the cursor keys to select scrollable information.

❸ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
Browse	Moves to the browse screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

ℹ️
• You can use the external device operation keys on the remote control to control playback.

Menu operation keys
Cursor keys
ENTER

External device operation keys

■ Operating the iPod itself (simple play)

1 **Press MODE to switch to the simple play mode.**

The TV menu screen turns off and iPod operations are enabled.

To display the TV menu screen, press MODE again.

2 **Operate your iPod itself to start playback.**

OPTION

Cursor keys
ENTER
RETURN

MODE

■ Shuffle/repeat settings

You can configure the shuffle/repeat settings of your iPod.

❗
• During simple play, configure the shuffle/repeat settings directly on your iPod or press MODE to display the TV menu screen and then follow the procedure below.

1 **When "USB" is selected as the input source, press OPTION.**

2 **Use the cursor keys to select "Shuffle" (Shuffle) or "Repeat" (Repeat) and press ENTER.**

💡
• To return to the previous screen during menu operations, press RETURN.
• Texts in parentheses denote indicators on the front display.

3 **Use the cursor keys ($\triangleleft/\triangleright$) to select a setting.**

Item	Setting	Function
Shuffle (Shuffle)	Off (Off)	Turns off the shuffle function.
	Songs (Songs)	Plays back songs in random order. "⤨" appears in the TV screen.
	Albums (Albums)	Plays back albums in random order. "⤨" appears in the TV screen.
Repeat (Repeat)	Off (Off)	Turns off the repeat function.
	One (One)	Plays back the current song repeatedly. "⟳" appears in the TV screen.
	All (All)	Plays back all songs repeatedly. "⟳" appears in the TV screen.

4 **To exit from the menu, press OPTION.**

Playing back music stored on a USB storage device

You can play back music files stored on a USB storage device on the unit.

The unit supports USB mass storage class devices (FAT16 or FAT32 format).

- For details on playable file formats, see "Supported devices and file formats" (p.138).

Connecting a USB storage device

1 Connect the USB storage device to the USB jack.

The unit (front)

USB storage device

USB
Connected   VOL -30.8 dB

- If the USB storage device contains many files, it may take time to load the them. In this case, "Loading..." appears in the front display.

- Stop playback of the USB storage device before disconnect it from the USB jack.

- Connect a USB storage device directly to the USB jack of the unit. Do not use extension cables.

Playback of USB storage device contents

Follow the procedure below to operate the USB storage device contents and start playback.

You can control the USB memory device with the menu displayed on the TV screen.

1 Press USB to select "USB" as the input source.

The browse screen is displayed on the TV.

USB
Top
Folder01
Folder02
Folder03
Folder04
Folder05
1 / 5

- If playback is ongoing on your USB storage device, the playback screen is displayed.

USB

2 Use the cursor keys to select an item and press ENTER.

If a song is selected, playback starts and the playback screen is displayed.

Menu operation keys
Cursor keys
ENTER
RETURN

> 💡
> • To return to the previous screen, press RETURN.
> • Files not supported by the unit cannot be selected.
> • If the unit detects a series of unsupported files (such as images and hidden files) during playback, playback stops automatically.
> • You can register your favorite items as shortcuts and access them directly by selecting the shortcut numbers (p.87).

■ Browse screen

❶ Status indicators

Display the current shuffle/repeat settings (p.72) and playback status (such as play/pause).

❷ List name

❸ Contents list

Displays the list of USB storage device contents. Use the cursor keys to select an item and press ENTER to confirm the selection.

❹ Item number/total

❺ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
1 Page Up	Moves to the previous/next page of the list.
1 Page Down	
10 Pages Up	Moves 10 pages forward/backward.
10 Pages Down	
Return	Returns to the higher-level list.
Now Playing	Moves to the playback screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

■ Playback screen

❶ **Status indicators**

Display the current shuffle/repeat settings (p.72) and playback status (such as play/pause).

❷ **Playback information**

Displays the artist name, album name, song title, and elapsed time. Use the cursor keys to select scrollable information.

❸ **Operation menu**

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
Browse	Moves to the browse screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

💡

- You can use the external device operation keys (▶, ■, ❚❚, ◄◄, ▶▶) on the remote control to control playback.

OPTION

Menu operation keys
Cursor keys
ENTER
RETURN

External device
operation keys

■ Shuffle/repeat settings

You can configure the shuffle/repeat settings for playback of USB storage device contents.

1 When "USB" is selected as the input source, press OPTION.

2 Use the cursor keys to select "Shuffle" (Shuffle) or "Repeat" (Repeat) and press ENTER.

💡

- To return to the previous screen during menu operations, press RETURN.
- Texts in parentheses denote indicators on the front display.

3 Use the cursor keys (◁/▷) to select a setting.

Item	Setting	Function
Shuffle (Shuffle)	Off (Off)	Turns off the shuffle function.
	On (On)	Plays back songs in the current album (folder) in random order. "⤭" appears on the TV screen.
Repeat (Repeat)	Off (Off)	Turns off the repeat function.
	One (One)	Plays back the current song repeatedly. "⟲" appears on the TV screen.
	All (All)	Plays back all songs in the current album (folder) repeatedly. "⟳" appears on the TV screen.

4 To exit from the menu, press OPTION.

Playing back music stored on media servers (PCs/NAS)

You can play back music files stored on your PC or DLNA-compatible NAS on the unit.

🛇

- To use this function, the unit and your PC must be connected to the same router (p.28). You can check whether the network parameters (such as the IP address) are properly assigned to the unit in "Network" (p.119) in the "Information" menu.
- The audio may be interrupted while using the wireless network connection. In this case, use the wired network connection.

💡

- For details on playable file formats, see "Supported devices and file formats" (p.138).

Media sharing setup

To play back music files stored on your PC or DLNA-compatible NAS, first you need to configure the media sharing setting on each music server.

■ For a PC with Windows Media Player installed

❑ For Windows Media Player 12

1 Start Windows Media Player 12 on your PC.

2 Select "Stream", then "Turn on media streaming".

3 Click "Turn on media streaming".

4 Select "Allowed" from the drop-down list next to the unit's model name.

5 Click "OK" to exit.

❑ For Windows Media Player 11

1 Start Windows Media Player 11 on your PC.

2 Select "Library", then "Media Sharing".

3 Check the "Share my media to" box, select the unit's icon, and click "Allow".

4 Click "OK" to exit.

💡

- For details on media sharing settings, refer to Windows Media Player help.

■ For a PC or a NAS with other DLNA server software installed

Refer to the instruction manual for the device or software and configure the media sharing settings.

Playback of PC music contents

Follow the procedure below to operate the PC music contents and start playback.

You can control the PC/NAS with the menu displayed on the TV screen.

1 Press NET repeatedly to select "SERVER" as the input source.

The browse screen is displayed on the TV.

☼
- If playback of a music file selected from the unit is ongoing on your PC, the playback screen is displayed.

2 Use the cursor keys to select a music server and press ENTER.

3 Use the cursor keys to select an item and press ENTER.

If a song is selected, playback starts and the playback screen is displayed.

☼
- To return to the previous screen, press RETURN.
- Files not supported by the unit cannot be selected.
- If the unit detects a series of unsupported files (such as images and hidden files) during playback, playback stops automatically.
- You can register your favorite items as shortcuts and access them directly by selecting the shortcut numbers (p.87).

Menu operation keys
Cursor keys
ENTER

External device operation keys

■ Browse screen

❶ Status indicators

Display the current shuffle/repeat settings (p.76) and playback status (such as play/pause).

❷ List name

❸ Contents list

Displays the list of PC content. Use the cursor keys to select an item and press ENTER to confirm the selection.

❹ Item number/total

❺ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
1 Page Up	Moves to the previous/next page of the list.
1 Page Down	
10 Pages Up	Moves 10 pages forward/backward.
10 Pages Down	
Return	Returns to the higher-level list.
Now Playing	Moves to the playback screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

■ Playback screen

❶ Status indicators

Display the current shuffle/repeat settings (p.76) and playback status (such as play/pause).

❷ Playback information

Displays the artist name, album name, song title, and elapsed time.
Use the cursor keys to select scrollable information.

❸ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
Browse	Moves to the browse screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

- You can use the external device operation keys on the remote control to control playback (some functions may not work depending on the PC/NAS).
- You can also use a DLNA-compatible Digital Media Controller (DMC) to control playback. For details, see "DMC Control" (p.97).

■ Shuffle/repeat settings

You can configure the shuffle/repeat settings for the playback of PC music content.

1 **When "SERVER" is selected as the input source, press OPTION.**

2 **Use the cursor keys to select "Shuffle" (Shuffle) or "Repeat" (Repeat) and press ENTER.**

- To return to the previous screen during menu operations, press RETURN.
- Text in parentheses denotes indicators on the front display.

3 **Use the cursor keys (◁ / ▷) to select a setting.**

OPTION

Cursor keys
ENTER
RETURN

Item	Setting	Function
Shuffle (Shuffle)	Off (Off)	Turns off the shuffle function.
	On (On)	Plays back songs in the current album (folder) in random order. "⤨" appears on the TV screen.
Repeat (Repeat)	Off (Off)	Turns off the repeat function.
	One (One)	Plays back the current song repeatedly. "⟳" appears on the TV screen.
	All (All)	Plays back all songs in the current album (folder) repeatedly. "⟲" appears on the TV screen.

4 **To exit from the menu, press OPTION.**

Listening to Internet radio

You can listen to Internet radio stations from all over the world.

!

- To use this function, the unit must be connected to the Internet (p.28). You can check whether the network parameters (such as the IP address) are properly assigned to the unit in "Network" (p.119) in the "Information" menu.
- You may not be able to receive some Internet radio stations.
- The unit uses the vTuner Internet radio station database service.
- This service may be discontinued without notice.

Playback of Internet radio

1 **Press NET repeatedly to select "NET RADIO" as the input source.**

The browse screen is displayed on the TV.

2 **Use the cursor keys to select an item and press ENTER.**

If an Internet radio station is selected, playback starts and the playback screen is displayed.

🔅

- To return to the previous screen, press RETURN.
- You can register your favorite items as shortcuts and access them directly by selecting the shortcut numbers (p.87).

NET

Cursor keys
ENTER
RETURN

■ Browse screen

**❶ Playback indicator**

❷ List name

❸ Contents list

Displays the list of Internet radio content. Use the cursor keys to select an item and press ENTER to confirm the selection.

❹ Item number/total

❺ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
Bookmark On (Bookmark Off)	Adds/removes the station selected in the list to/from the "Bookmarks" folder (p.79).
1 Page Up	Moves to the previous/next page of the list.
1 Page Down	
10 Pages Up	Moves 10 pages forward/backward.
10 Pages Down	
Return	Returns to the higher-level list.
Now Playing	Moves to the playback screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

■ Playback screen

❶ Playback indicator

❷ Playback information

Displays the station name, album name, song title, and elapsed time. Use the cursor keys (△/▽) to select scrollable information.

❸ Operation menu

Press the cursor key (▷) and then use the cursor keys (△/▽) to select an item. Press ENTER to confirm the selection.

Menu	Function
Bookmark On	Adds the current station to the "Bookmarks" folder (p.79).
Browse	Moves to the browse screen.
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

- You can use the external device operation key (■) on the remote control to stop playback.
- Some information may not be available depending on the station.

Menu operation keys
Cursor keys
ENTER

External device operation keys

Registering favorite Internet radio stations (bookmarks)

By registering your favorite Internet radio stations to "Bookmarks", you can quickly access to them from the "Bookmarks" folder in the browse screen.

■ Registering the station on the browse/playback screen

1 **Select the desired Internet radio station in the browse screen or start playback of it to display the playback screen.**

2 **Press the cursor key (▷) to select "Bookmark On" and press ENTER.**

The selected station is added to the "Bookmarks" folder.

- To remove stations from the "Bookmarks" folder, select the station in the "Bookmarks" folder and then "Bookmark Off".

■ Registering the station on the vTuner website

1 **Select any of Internet radio stations on the unit.**

This operation is necessary to register the radio station for the first time.

2 **Check the vTuner ID of the unit.**

You can find the vTuner ID in "Network" (p.119) in the "Information" menu.

3 **Access the vTuner website (http://yradio.vtuner.com/) with the web browser on your PC and enter the vTuner ID.**

You can switch the language.

Enter the vTuner ID in this area.

- To use this feature, you need to create your personal account. Create your account using your e-mail address.

4 **Register your favorite radio stations.**

Click the "Add" icon (❤+) next to the station name.

- To remove the station from the "My__Favorites" folder, select "My__Favorites" in the Home screen, and then click the "Remove" icon (❤–) next to the station name.

Cursor keys
ENTER

Playing back music with AirPlay

The AirPlay function allows you to play back iTunes/iPod music on the unit via network.

iTunes

PC

(wired or wireless)   Router

The unit

(wired or wireless)

iPhone/iPad/
iPod touch

!

• To use this function, the unit and your PC or iPod must be connected to the same router. You can check whether the network parameters (such as the IP address) are properly assigned to the unit in "Network" (p.119) in the "Information" menu.

• When using a multiple SSID router, access to the unit might be restricted depending on the SSID to connect. Connect the iPod to the SSID which can access the unit.

☼

• For details on supported iPod devices, see "Supported devices and file formats" (p.138).

• You can restrict access to the unit using the AirPlay password (p.90).

Playback of iTunes/iPod music contents

Follow the procedure below to play back iTunes/iPod music contents on the unit.

1 **Turn on the unit, and start iTunes on the PC or display the playback screen on the iPod.**

If the iTunes/iPod recognizes the unit, the AirPlay icon ( ) appears.

iTunes (example)   iPod iOS7/iOS8 (example)   iPod iOS6 (example)

AirDrop   AirPlay

!

• If the icon does not appear, check whether the unit and PC/iPod are connected to the router properly.

2 **On the iTunes/iPod, click (tap) the AirPlay icon and select the unit (network name of the unit) as the audio output device.**

iTunes (example)   iPod (example)

☐ My Computer   iPod touch
✓ Yamaha XXXXX   Yamaha XXXXXX ✓
Multiple Speakers...

Network name of the unit

3 **Select a song and start playback.**

The unit automatically selects "AirPlay" as the input source and starts playback.

The playback screen is displayed on the TV.

!

• The playback screen is available only when your TV is connected to the unit via HDMI.

Menu operation keys
Cursor keys
ENTER

External device
operation keys

- You can turn on the unit automatically when starting playback on iTunes or iPod by setting "Network Standby" (p.113) in the "Setup" menu to "On".
- You can edit the network name (the unit's name on the network) displayed on iTunes/iPod in "Network Name" (p.114) in the "Setup" menu.
- If you select the other input source on the unit during playback, playback on the iTunes/iPod stops automatically.
- You can adjust the unit's volume from the iTunes/iPod during playback. To disable volume controls from iTunes/iPod, set "Volume Interlock" (p.97) in the "Input" menu to "Off".

Caution

- When you use iTunes/iPod controls to adjust volume, the volume may be unexpectedly loud. This could result in damage to the unit or speakers. If the volume suddenly increases during playback, stop playback on the iTunes/iPod immediately.

■ Playback screen

❶ **Playback indicator**

❷ **Playback information**

Displays the artist name, album name, song title, and elapsed/remaining time.
Use the cursor keys (△/▽) to select scrollable information.

❸ **Operation menu**

Press the cursor key (▷) to select an item. Press ENTER to confirm the selection.

| Menu	Function
Screen Off	Closes the screen display and shows the background. Press one of the menu operation keys to redisplay it.

- You can use the external device operation keys (▶, ■, ▐▐, ◀◀, ▶▶) on the remote control to control playback.

Playing back music in multiple rooms (multi-zone)

The multi-zone function allows you to play back different input sources in the room where the unit is installed (Main zone) and in another room (Zone2).

For example, while you are watching TV in the living room (Main zone), another person can listen to radio in the study room (Zone2).

Living room (Main zone)

Study room (Zone2)

!

• Analog audio sources (including radio), and *Bluetooth*, USB, and network sources can be output to Zone2. To listen to the playback of an external device in Zone2, you need to connect the device to the AUDIO jacks (AV 3–4 jacks) of the unit. The party mode (p.86) allows you to play back the same audio output in Main zone as Zone2, whatever the input audio signal type.

Preparing Zone2

Connect the device that will be used in Zone2 to the unit. The connection method varies depending on the amplifier being used (the unit or an external amplifier).

Caution

• Remove the unit's power cable from the AC wall outlet before connecting speakers or an external amplifier.
• Ensure that the core wires of the speaker cable do not touch one another or come into contact with the unit's metal parts. Doing so may damage the unit or the speakers. If the speaker cables short circuit, "Check SP Wires" will appear on the front display when the unit is turned on.

■ Using the unit's internal amplifier

Connect the speakers placed in Zone2 to the unit with speaker cables.

To utilize the EXTRA SP terminals for Zone2 speakers, set "Power Amp Assign" (p.105) in the "Setup" menu to "5ch +1ZONE" after connecting the power cable to an AC wall outlet.

The unit (rear)

Main zone

Zone2

!
• When using the EXTRA SP terminals for Zone2 speakers, you cannot use the front presence speakers, the surround back speakers or the bi-amp function.

■ Using an external amplifier

Connect the external amplifier (with volume control) placed in Zone2 to the unit with a stereo pin cable.

The unit (rear)

ZONE2 OUT jacks

External amplifier
Audio input
(analog stereo)

Main zone

Zone2

■ Operating the unit from Zone2 (remote connection)

You can operate the unit or external devices from Zone2 using the remote control supplied with each device if you connect an infrared signal receiver/emitter to the unit's REMOTE IN/OUT jacks.

REMOTE IN/OUT jacks

The unit (rear)

Infrared signal transmitter

Infrared signal receiver

External device
(such as a CD player)

Remote control
(supplied with each device)

Zone2

Main zone

Remote connections between Yamaha products

An infrared signal transmitter is not required if you are using Yamaha products that support remote connections, as the unit does. You can transmit remote control signals by connecting the REMOTE IN/OUT jacks with monaural mini-jack cables and an infrared signal receiver.

REMOTE IN/OUT jacks   REMOTE IN/OUT jacks

Infrared signal receiver

Yamaha products
(up to six, including the unit)

Remote control

Zone2

Controlling Zone2

1 **Set MAIN/ZONE2 to "ZONE2".**

2 **Press ⏻ (receiver power).**

Each time you press the key, Zone2 output is enabled or disabled.

When Zone2 output is enabled, "ZONE2" lights up in the front display.

3 **Use the following keys to select an input source.**

AV 3–4: AV 3–4 (AUDIO) jacks

TUNER: FM/AM radio (RX-AS710), DAB/FM radio (RX-AS710D)

BLUETOOTH: *Bluetooth* connection (the unit as a *Bluetooth* receiver)

USB: USB jack (on the front panel)

NET: NETWORK sources (press repeatedly to select a desired network source)

AUX: AUX (AUDIO) jack (on the front panel)

PHONO: PHONO jacks

> ❗
> • You cannot select *Bluetooth*, USB and network sources exclusively for each zone. For example, if you select "SERVER" for Zone2 when "USB" is selected for the main zone, the input source for the main zone also switches to "SERVER".

4 **Start playback on the external device or select a radio station.**

Refer to the instruction manual for the external device.

For details on the following operations, see the corresponding pages.

• Listening to FM/AM radio (RX-AS710) (p.54)
• Listening to DAB radio (RX-AS710D) (p.58)
• Listening to FM radio (RX-AS710D) (p.62)
• Playing back music via *Bluetooth* (p.66)
• Playing back iPod music (p.67)
• Playing back music stored on a USB storage device (p.70)
• Playing back music stored on media servers (PCs/NAS) (p.73)
• Listening to Internet radio (p.77)
• Playing back music with AirPlay (p.80)

> ❗
> • The on-screen operations are not available for Zone2. Use the front display or web control (p.88) to control Zone2.
> • AirPlay is available in Zone2 only when AirPlay playback is ongoing in the main zone.

> 🔆
> • To set the sleep timer (120 min, 90 min, 60 min, 30 min, off), press SLEEP repeatedly. The Zone2 output will be disabled after a specified period of time.
> • To adjust the Zone2 volume, press VOLUME or MUTE (when using the unit's internal amplifier). When using an external amplifier, use the volume control on it.
> • The Zone 2 input automatically switches in conjunction with the input source selected in the main zone when "Main Zone Sync" is selected as the Zone 2 input with the web control (p.88) or AV CONTROLLER (p.8).
> • To play back DSD audio in Zone2, select "Main Zone Sync" as the Zone2 input or use the party mode (p.86).

Caution

• To avoid unexpected noise, never play back DTS-CDs in Zone2.

Labels on remote (left column):
AV 3–4
TUNER
BLUETOOTH
USB
NET
AUX
PHONO
MAIN/ZONE2
MUTE
VOLUME
SLEEP

PARTY

■ Enjoying the same source in multiple rooms (party mode)

The party mode allows you to play back in Zone2 the same music that is being played back in the main zone. During the party mode, stereo playback is automatically selected for all zones. Utilize this function when you want to use main zone music as background music for a house party.

1 Press PARTY.

Each time you press the key, the party mode is turned on or off.

When the party mode is turned on, "PARTY" lights up in the front display.

!

• If the party mode does not work on Zone2, set "Party Mode Set" (p.115) in the "Setup" menu to "Enable" (default).

Useful functions

Registering favorite items (shortcut)

You can register up to 40 favorite USB and network contents as shortcuts and access them directly by selecting the shortcut numbers.

☼
- You can also use the "Bookmarks" feature to register Internet radio stations.
- Only the input source will be registered for Bluetooth and AirPlay. Individual contents cannot be registered.

■ Registering an item

Select a desired item and register it to a shortcut number.

1 Play back a song or a radio station to be registered.

2 Press MEMORY.

```
MEMORY        STEREO TUNED
01:Empty            VOL. -30.0dB
```

Shortcut number (flashes)

☼
- To change a shortcut number to which the item will be registered, use numeric keys to select the shortcut number after step 2.

```
FM 98.50      STEREO TUNED
02:Empty            VOL. -30.0dB
```

"Empty" (not in use) or item currently registered

3 To confirm the registration, press MEMORY.

■ Recalling a registered item

Recall a registered item by selecting the shortcut number.

1 Press BLUETOOTH, USB or NET.

2 Use the numeric keys to enter a shortcut number (01 to 40).

You can also use PRESET on the front panel to select a shortcut.

```
RECALL        STEREO TUNED
01:Empty            VOL. -30.0dB
```

❗
- "No Presets" appears when no items are registered.
- "Empty" appears when a preset number not in use is entered.
- The registered item cannot be recalled in the following cases.
  – The USB storage device which contains the registered item is not connected to the unit.
  – The PC/NAS which contains the registered item is turned off or not connected to the network.
  – The registered network content is temporarily unavailable or out of service.
  – The registered item (file) has been deleted or moved to another location.
  – A *Bluetooth* connection cannot be established.
- When you register music files stored on a USB storage device or a PC/NAS, the unit memorizes the relative position of the music files in the folder. If you have added or deleted any music files to or from the folder, the unit may not recall the music file correctly. In such cases, register the items again.

BLUETOOTH USB NET

PRESET

Numeric keys MEMORY

Controlling the unit from a web browser (web control)

You can control the unit with the web control screen displayed in a web browser.

Web browser

PC   (wired or wireless)   Router   (wired or wireless)   The unit

Web control   Web control

!

- To use this function, the unit and your PC must be connected to the same router.
- Some security software installed on your PC may block the access of the unit to your PC. In these cases, configure the security software appropriately.
- To display the web control screen or turn on the unit from the web control when the unit is in standby mode, set "Network Standby" (p.90) to "On".
- We recommend using one of the following web browsers.
  – Internet Explorer 9.x, 10.x or 11.x
  – Safari 7.x

1 **Start the web browser.**

2 **Enter the IP address of the unit in the address bar of the web browser.**

(Example)

http://192.168.1.21/

- You can check the IP address of the unit in "Network" (p.119) in the "Information" menu.
- You can bookmark the unit's IP address in the browser or create a shortcut link (p.90) to access the web control screen quickly in the future. However, if you are using a DHCP server, the IP address of the unit may change each time the unit is turned on.
- If you have enabled the MAC address filter (p.113), you need to specify the MAC address of your PC to allow the PC to access the unit. For information on how to check the MAC address of your PC, refer to its instruction manual.
- If you are using Windows 8, we recommend you start Internet Explorer in the following way.
  – Select "Desktop" in the Start screen and click the Internet Explorer icon at the bottom left of the screen.
- By using the application for smartphone/tablet "AV CONTROLLER", you can control the unit from an iPhone, iPad, iPod touch or Android devices (p.8).

■ Top menu screen

① CONTROL

Moves to the control screen for the selected zone.

② STATUS

Turns on/off the power for each zone or displays the input source and volume set for each zone.

③ SETTINGS

Moves to the settings screen.

④ PARTY MODE

Turns on/off the party mode (p.86).

⑤ SYSTEM POWER

Turns on/off the power for all zones.

⑥ MAIN VOLUME

Adjusts the volume or mutes the audio output for the main zone. You can also select the increments used for volume adjustment.

⑦ RELOAD

Reloads the current status of the unit.

■ Control screen

① PLAY INFO

Selects an input source or controls playback for the selected zone.

② TOP MENU

Moves to the top menu screen.

③ SCENE

Selects a scene for the selected zone.

④ POWER

Turns on/off the power for the selected zone.

⑤ VOLUME

Adjusts the volume or mutes the audio output for the selected zone. You can also select the increments used for volume adjustment.

⑥ RELOAD

Reloads the current status of the unit.

!

• Multi-zone volume adjustment is not available when an external amplifier is used.

■ Settings screen

① Rename

Edits the network name (the unit's name on the network) (p.114) or the name of each zone (p.115). Click "APPLY" to apply the changes to the unit.

Network

Selects the network connection method (p.112) or configures the network parameters (such as IP address) (p.113). Click "APPLY" to apply the changes to the unit.

AirPlay Password

Sets the password to restrict access to the unit via AirPlay (p.80). Click "APPLY" to apply the changes to the unit.

MAC Filter

Sets the MAC address filter (p.113) to limit access to the unit from the network devices. Click "APPLY" to apply the changes to the unit.

Auto Reload

Enables/disables automatic reloading. When "Auto Reload" is "On" (enabled), the web control screen reloads the status of the unit every 5 seconds.

Network Standby

Enables/disables the network standby function (p.113).

Backup/Recovery

Creates a backup of the unit's settings on the PC or restores the settings from the backup.

Firmware Update

Updates the firmware of the unit by using the firmware you have downloaded on the PC. Follow the on-screen instructions to start the firmware update.

Create Link

Creates a shortcut link to the desired control screen.

Tips

Displays tips for use of the web control.

Licenses

Displays the licenses of the software used in the unit.

② BACK

Moves to the top menu screen.

③ RELOAD

Reloads the current status of the unit.

> **Note**
>
> - If the network settings are changed, you may need to restart the browser or regain access to the unit.
> - When using the MAC address filter, make sure you specify the MAC addresses of your network devices correctly. Otherwise, the unit will be inaccessible from your network devices such as PCs and other external devices.
> - Do not operate the unit during the recovery process, as this may result in the incorrect recovery of the settings. When the recovery finishes, click "OK" to set the unit to standby mode.
> - The backup does not contain user information (such as user account and password) or unit-specific information (such as MAC address and IP address).
> - Some characters entered with a PC may not appear correctly on the unit.

Viewing the current status

Switching information on the front display

1 Press INFO.

Each time you press the key, the displayed item changes.

```
INFO                    VOL -30.0 dB
Audio Decoder          [LCR SW]
```
Item name

About 3 seconds later, the corresponding information for the displayed item appears.

```
HDMI 1                  VOL -30.0 dB
DDPLIIx MOVIE          [LCR SW]
```
Information

💡
• Available items vary depending on the selected input source. The displayed item can also be applied separately to each input source group.

Input source group	Item
HDMI 1–6 AUX AV 1–4 AUDIO 1–2	Input (input source name), DSP Program (sound mode name), Audio Decoder (decoder name*)
TUNER (AM/FM)	Frequency (frequency), DSP Program (sound mode name), Audio Decoder (decoder name*) * (U.K. and Europe models only) Radio Data System data is also available when the unit is tuned into a Radio Data System broadcasting station (p.56).
TUNER (DAB)	See "Displaying the DAB information" (p.60) for details.

Input source group	Item
Bluetooth USB SERVER AirPlay	Song (song title), Artist (artist name), Album (album name), DSP Program (sound mode name), Audio Decoder (decoder name*) * During simple playback of iPod: Input (input source name), DSP Program (sound mode name), Audio Decoder (decoder name*)
NET RADIO	Song (song title), Album (album name), Station (station name), DSP Program (sound mode name), Audio Decoder (decoder name*)
PHONO	Input (input source name), DSP Program (sound mode name), Audio Decoder (decoder name*)

* The name of the audio decoder currently activated is displayed. If no audio decoder is activated, "Decoder Off" appears.

Viewing the status information on the TV

1 Press DISPLAY.

The following information is displayed on the TV.

Compressed Music Enhancer status

Input source/Party mode status

Volume/YPAO Volume status

Audio format/Decoder

Sound mode

CINEMA DSP status

2 To close the information display, press DISPLAY.

DISPLAY

INFO

Configuring playback settings for different playback sources (Option menu)

You can configure separate playback settings for different playback sources. This menu is available on the front panel (or on the TV screen), allowing you to easily configure settings during playback.

1 **Press OPTION.**

Front display

TV screen

2 **Use the cursor keys to select an item and press ENTER.**

- To return to the previous screen during menu operations, press RETURN.

3 **Use the cursor keys (◁/▷) to select a setting.**

4 **To exit from the menu, press OPTION.**

Option menu items

- Available items vary depending on the selected input source.
- Text in parentheses denotes indicators on the front display.
- Default settings are underlined.

Item		Function	Page
Tone Control (Tone Control)		Adjusts the high-frequency range and low-frequency range of sounds.	93
YPAO Volume (YPAO Volume)	YPAO Volume (YPAO Vol.)	Enables/disables YPAO Volume.	93
	Adaptive DRC (A.DRC)	Sets whether the dynamic range (from maximum to minimum) is automatically adjusted when the volume is adjusted.	93
Dialogue (Dialog)	Dialogue Level (Dialog Lvl)	Adjusts the volume of dialogue sounds.	93
	Dialogue Lift (Dialog Lift)	Adjusts the perceived height of dialogue sounds.	93
Subwoofer/Bass (Subwoofer/Bass)	Subwoofer Trim (SW.Trim)	Fine-adjusts the subwoofer volume.	94
	Extra Bass (Extra Bass)	Enables/disables Extra Bass.	94
Enhancer (Enhancer)		Enables/disables Compressed Music Enhancer.	94
Video Processing (Video Process.)		Enables/disables the video signal processing settings configured in the "Setup" menu.	94
Input Settings (Input Settings)	Input Trim (In.Trim)	Corrects volume differences between input sources.	94
	Video Out (V.Out)	Selects a video to be output with the audio input source.	94
FM Mode (FM Mode)		Switches between stereo and monaural for FM radio reception.	94
Init Scan (Init Scan)		(RX-AS710D only) Performs an initial scan for DAB radio reception.	58
Tune Aid (Tune Aid)		(RX-AS710D only) Checks reception strength of each DAB channel label.	61
Traffic Program (TrafficProgram)		(RX-AS710 U.K. and Europe models only) Automatically searches for a traffic information station.	56

Item	Function	Page
Shuffle **(Shuffle)**	Configures the shuffle setting for the iPod (p.69), USB storage device (p.72), or media server (p.76).	—
Repeat **(Repeat)**	Configures the repeat setting for the iPod (p.69), USB storage device (p.72), or media server (p.76).	—

■ Tone Control (Tone Control)

Adjusts the high-frequency range (Treble) and low-frequency range (Bass) of sounds.

Choices

Treble (Treble), Bass (Bass)

Setting range

-6.0 dB to Bypass (Bypass) to +6.0 dB, *0.5 dB increments

> **!**
> • If you set an extreme value, sounds may not match those from other channels.

■ YPAO Volume (YPAO Volume)

Enables/disables YPAO Volume or Adaptive DRC.

YPAO Volume (YPAO Vol.)

Enables/disables YPAO Volume. When YPAO Volume is enabled, the high- and low-frequency levels are automatically adjusted according to the volume so that you can enjoy natural sounds even at low volume.

Settings

Off (Off)	Disables YPAO Volume.
On (On)	Enables YPAO Volume.

> **☀**
> • YPAO Volume works effectively after the measurement results of "Auto Setup" have been already saved (p.32).
> • We recommend enabling both YPAO Volume and Adaptive DRC when you are listening at lower volumes or at night.

Adaptive DRC (A.DRC)

Sets whether the dynamic range (from maximum to minimum) is automatically adjusted when the volume level is adjusted. When it is set to "On", it is useful for listening to playback at a low volume at night.

Settings

Off (Off)	The dynamic range is not automatically adjusted.
On (On)	Automatically adjusts the dynamic range when YPAO Volume is enabled.

If "On" is selected, the dynamic range becomes narrow at a low volume and wide at a high volume.

■ Dialogue (Dialog)

Adjusts the volume or perceive height of dialogue sounds.

Dialogue Level (Dialog Lvl)

Adjusts the volume of dialogue sounds. If dialogue sounds cannot be heard clearly, you can turn up its volume by increasing this setting.

Setting range

0 to 3

Dialogue Lift (Dialog Lift)

Adjusts the perceived height of dialogue sounds. If the dialogue sounds as if it is coming from below the TV screen, you can raise its perceived height by increasing this setting.

> **☀**
> • This setting is available only when one of the following conditions is met.
> – One of the sound programs (except for 2ch Stereo and 7ch Stereo) is selected when presence speakers are used.
> – Virtual Presence Speaker (VPS) (p.49) is working.
> (You may hear dialogue sounds from the surround speakers depending on the listening position.)

Setting range

0 to 5 (The bigger the value the higher the position)

Ideal position

■ Subwoofer/Bass (Subwoofer/Bass)

Adjust the subwoofer volume or bass sound.

Subwoofer Trim (SW.Trim)

Fine-adjusts the subwoofer volume.

Setting range

-6.0 dB to 0.0 dB to +6.0 dB (0.5 dB increments)

Extra Bass (Extra Bass)

Enables/disables Extra Bass. When Extra Bass is enabled, you can enjoy enhanced bass sounds, regardless of the size of the front speakers and the presence or absence of the subwoofer.

Settings

Off (Off)	Disables Extra Bass.
On (On)	Enables Extra Bass.

■ Enhancer (Enhancer)

Enables/disables Compressed Music Enhancer (p.53).

- This setting is applied separately to each input source.
- You can also use ENHANCER on the remote control to enable/disable Compressed Music Enhancer (p.53).

Settings

Off (Off)	Disables Compressed Music Enhancer.
On (On)	Enables Compressed Music Enhancer.

Default

TUNER, Bluetooth, USB, (network sources): On (On)
Others: Off (Off)

■ Video Processing (Video Process.)

Enables/disables the video signal processing (resolution and aspect ratio) settings configured in "Processing" (p.110) in the "Setup" menu.

Settings

Direct (Direct)	Disables the video signal processing.
Processing (Processing)	Enables the video signal processing.

■ Input Settings (Input Settings)

Configures the input settings.

- This setting is applied separately to each input source.

Input Trim (In.Trim)

Corrects volume differences between input sources. If you are bothered by volume differences when switching between input sources, use this function to correct it.

Setting range

-6.0 dB to 0.0 dB to +6.0 dB (0.5 dB increments)

Video Out (V.Out)

Selects a video to be output with the audio input source.

Settings

Off (Off)	Does not output video.
HDMI 1–6 (HDMI 1–6), AV 1–4 (AV 1–4)	Outputs video input through the corresponding video input jacks.

■ FM Mode (FM Mode)

Switches between stereo and monaural for FM radio reception.

Settings

Stereo (Stereo)	Receives FM radio in stereo sounds.
Mono (Mono)	Receives FM radio in monaural sounds.

CONFIGURATIONS

Configuring input sources (Input menu)

You can change the input source settings using the TV screen.

1 Press ON SCREEN.

2 Use the cursor keys to select "Input" and press ENTER.

3 Use the cursor keys (◁/▷) to select an input source to be configured and press the cursor key (△).

The input source of the unit also changes.

• You can still switch the input source by using cursor keys (◁/▷) after Step 3.

4 Use the cursor keys (△/▽) to select an item and press ENTER.

• To return to the previous screen during menu operations, press RETURN.

5 Use the cursor keys to select a setting and press ENTER.

6 To exit from the menu, press ON SCREEN.

Input menu items

• Available items vary depending on the selected input source.
• Default settings are underlined.

Item	Function	Page
Rename/Icon Select	Changes the input source name and icon.	96
Audio In	Combines the video jack of the selected input source with an audio jack of others.	96
Decoder Mode	Sets the format of digital audio playback to DTS.	96
Volume Interlock	Enables/disables volume controls from iTunes/iPod via AirPlay.	97
DMC Control	Selects whether to allow a DLNA-compatible Digital Media Controller (DMC) to control playback.	97

■ Rename/Icon Select

Changes the input source name and icon displayed on the front display or TV screen.

Input sources
HDMI 1–6, AUX, AV 1–4, AUDIO 1–2, USB, PHONO

■ Setup procedure

1 Use the cursor keys (◁/▷) to select a template and press the cursor key (▽).

> ⚠
> • You cannot change the template or icon for "USB" when an iPod is connected.

2 Use the cursor keys (◁/▷) to select an icon and press the cursor key (▽).

3 Press ENTER to enter the name edit screen.

4 Use the cursor keys and ENTER to rename and select "ENTER" to confirm the entry.

> 💡
> • To clear the entry, select "CLEAR".

5 Use the cursor keys to select "OK" and press ENTER.

> 💡
> • To restore the default setting, select "RESET".

6 To exit from the menu, press ON SCREEN.

■ Audio In

Combines the video jack of the selected input source with an audio jack of others. For example, use this function in the following cases.

• Connecting a playback device that supports HDMI video output, but not HDMI audio output

• Connecting a playback device that has component video jacks and analog stereo jacks (such as game consoles)

Input sources
HDMI 1–6, AV 1–2

■ Setup procedure

(To input audio through a digital optical jack)

Select "AV1" or "AUDIO1" and connect the device to the unit's corresponding audio jacks with a digital optical cable.

(To input audio through a digital coaxial jack)

Select "AV2" or "AUDIO2" and connect the device to the unit's corresponding audio jacks with a digital coaxial cable.

(To input audio through analog audio jacks)

Select "AV3" or "AV4", and connect the device to the unit's corresponding audio jacks with a stereo pin cable.

■ Decoder Mode

Sets the format of digital audio playback to "DTS".

For example, if the unit does not detect DTS audio and outputs noise, set "Decoder Mode" to "DTS".

Input sources
HDMI 1–6, AV 1–2, AUDIO 1–2

Settings

Auto	Automatically selects an audio format to match the input audio signal.
DTS	Selects DTS only. (Other audio signals are not reproduced.)

■ Volume Interlock

Enables/disables volume controls from iTunes/iPod via AirPlay.

Input sources
AirPlay

Settings

Off	Disables volume controls from iTunes/iPod.
Limited	Enables volume controls from iTunes/iPod within the limited range (-80 dB to -20 dB and mute).
Full	Enables volume controls from iTunes/iPod in the full range (-80 dB to +16.5 dB and mute).

■ DMC Control

Selects whether to allow DLNA-compatible Digital Media Controller (DMC) to control playback.

Input source
SERVER

Settings

Disable	Does not allow DMCs to control playback.
Enable	Allows DMCs to control playback.

🔅

• A Digital Media Controller (DMC) is a device that can control other network devices through the network. When this function is enabled, you can control playback of the unit from DMCs (such as Windows Media Player 12) on the same network.

Configuring the SCENE function (Scene menu)

You can change the settings of the SCENE function (p.47) using the TV screen.

1 Press ON SCREEN.

2 Use the cursor keys to select "Scene" and press ENTER.

3 Use the cursor keys (◁/▷) to select a scene to be configured and press the cursor key (△).

🔅

• You can still switch the scene by using cursor keys (◁/▷) after Step 3.

4 Use the cursor keys (△/▽) to select an item and press ENTER.

5 Use the cursor keys and ENTER to change the setting.

6 To exit from the menu, press ON SCREEN.

Scene menu items

Item	Function	Page
Save	Registers the current settings in the selected scene.	98
Load	Loads the settings registered for the selected scene. You can also configure the SCENE link playback setting or view the scene assignments.	98
Rename/Icon Select	Changes the scene name and icon.	99
Reset	Restores the default settings for the selected scene.	99

■ Save

Registers the unit's current settings (input source, sound program/surround decoder, and Compressed Music Enhancer on/off) in the selected scene.

☀️
- If you have changed the input assignment for a scene, you also need to change the external device assigned to the corresponding SCENE key (p.47).

■ Load

Loads the settings registered for the selected scene.

Select "DETAIL" to configure the SCENE link playback setting or view the scene assignments.

Device Control

Recalls a selected scene and starts its playback on an external device connected to the unit via HDMI. (SCENE link playback)

Settings

Off	Disables the SCENE link playback function.
HDMI Control	Enables SCENE link playback using HDMI Control signals. Select this if an HDMI Control-compatible device (such as a BD/DVD player) is connected to the unit via HDMI. It also turns on the TV if it supports HDMI Control.

Default
SCENE1 (BD/DVD), SCENE2 (TV): HDMI Control
SCENE3 (NET), SCENE4 (RADIO): Off

❗
- To control playback of an HDMI Control-compatible device by SCENE link playback, you need to set "HDMI Control" in the "Setup" menu to "On" and perform the HDMI Control link setup (p.141).

Detail

Displays the assignments of the selected scene.

Input	Input source to be used
Mode	Sound program/surround decoder to be used
Enhancer	Compressed Music Enhancer on/off

■ Rename/Icon Select

Changes the scene name and icon displayed on the front display or TV screen.

■ Setup procedure

1 Use the cursor keys (◁/▷) to select an icon and press the cursor key (▽).

2 Press ENTER to enter the name edit screen.

3 Use the cursor keys and ENTER to rename and select "ENTER" to confirm the entry.

💡
• To clear the entry, select "CLEAR".

4 Use the cursor keys to select "OK" and press ENTER.

💡
• To restore the default setting, select "RESET".

5 To exit from the menu, press ON SCREEN.

■ Reset

Restores the default settings (p.47) for the selected scene.

Configuring sound programs/surround decoders (DSP Program menu)

You can change the settings of the sound programs and surround decoders using the TV screen.

1 Press ON SCREEN.

2 Use the cursor keys to select "DSP Program" and press ENTER.

3 Use the cursor keys (◁/▷) to select a sound program to be configured and press the cursor key (△).

💡
• You can still switch the sound program by using cursor keys (◁/▷) after Step 3.

4 **Use the cursor keys (△/▽) to select an item and press ENTER.**

```
DSP Program : The Roxy Theatre
DSP Level                          0 dB
Initial Delay                     15 ms
Room Size                          1.0
Liveness                             5
Reverb Time                      1.6 s
Reverb Delay                    120 ms
Reverb Level                       7 %
Reset
Back: RETURN                     4 / 8
              The Roxy Theatre
```

• To return to the previous screen during menu operations, press RETURN.

• To restore the default settings for the selected sound program, select "Reset".

5 **Use the cursor keys to select a setting and press ENTER.**

6 **To exit from the menu, press ON SCREEN.**

DSP Program menu items

• Available items vary depending on the selected sound program or surround decoder.

• Default settings are underlined.

■ Settings for sound programs

Item	Function	Settings
Decode Type	Selects a surround decoder to be used in combination with the selected sound program.	❑PLIIx Movie (❑PLII Movie), ❑PLIIx Music* (❑PLII Music*), ❑PLIIx Game* (❑PLII Game*), Neo:6 Cinema, Neo:6 Music* (* Available only when "SURROUND DECODER" is selected)
DSP Level	Adjusts the sound field effect level.	-6 dB to 0 dB to +3 dB Higher to enhance the sound field effect, and lower to reduce it.
Initial Delay	Adjusts the delay between the direct sound and presence sound field generation.	1 ms to 99 ms Higher to enhance the delay effect, and lower to reduce it.
Surround Initial Delay	Adjusts the delay between the direct sound and surround sound field generation.	1 ms to 49 ms Higher to enhance the delay effect, and lower to reduce it.
Surround Back Initial Delay	Adjusts the delay between the direct sound and surround back sound field generation.	
Room Size	Adjusts the broadening effect of the presence sound field.	0.1 to 2.0 Higher to enhance the broadening effect, and lower to reduce it.
Surround Room Size	Adjusts the broadening effect of the surround sound field.	
Surround Back Room Size	Adjusts the broadening effect of the surround back sound field.	
Liveness	Adjusts the loss of the presence sound field.	0 to 10 Higher to enhance the reflectivity, and lower to reduce it.
Surround Liveness	Adjusts the loss of the surround sound field.	
Surround Back Liveness	Adjusts the loss of the surround back sound field.	

Item	Function	Settings
Reverb Time	Adjust the decay time of the rear reverberant sound.	1.0 s to 5.0 s Higher to enrich the reverberant sound and lower to have clear sound.
Reverb Delay	Adjusts the delay between the direct sound and reverberant sound generation.	0 ms to 250 ms Higher to enhance the delay effect, and lower to reduce it.
Reverb Level	Adjusts the volume of the reverberant sound.	0% to 100% Higher to strengthen the reverberant sound, and lower to weaken it.

The following items are available when you select "2ch Stereo" or "7ch Stereo".

Sound program	Item	Function	Settings
2ch Stereo	**Direct**	Selects whether to automatically bypass the DSP circuit when an analog audio source is played back.	<u>Auto</u>, Off
7ch Stereo	**Level**	Adjusts the entire volume.	-5 to <u>0</u> to +5
	Front / Rear Balance	Adjusts the front and rear volume balance.	-5 to <u>0</u> to +5 Higher to enhance the front side, and lower to enhance the rear side.
	Left / Right Balance	Adjusts the left and right volume balance.	-5 to <u>0</u> to +5 Higher to enhance the right side, and lower to enhance the left side.
	Height Balance	Adjust the height volume balance using the presence speakers.	0 to <u>5</u> to 10 Higher to enhance the upside, and lower to enhance the downside. (The presence speakers do not produce sounds when "Height Balance" is set to "0".)
	Monaural Mix	Enables/disables monaural sound output.	<u>Off</u>, On

💡

- Available items in "7ch Stereo" vary depending on the speaker system being used.

■ **Settings for decoders**

The following items are available when you set "Decode Type" of "SURROUND DECODER" to "⊡PLIIx Music" or "Neo:6 Music".

Decode Type	Item	Function	Settings
⊡PLIIx Music	**Panorama**	Adjusts the broadening effect of the front sound field.	<u>Off</u>, On Select "On" to wrap front left/right channel sounds around the field and generate a spacious sound field in combination with the surround sound field.
	Center Width	Adjusts the broadening effect of the center sound field.	0 to <u>3</u> to 7 Higher to enhance the broadening effect, and lower to reduce it (closer to center).
	Dimension	Adjusts the difference in level between the front and surround sound fields.	-3 to <u>0</u> to +3 Higher to strengthen the front sound field and lower to strengthen the surround sound field.
Neo:6 Music	**Center Image**	Adjusts the center orientation level (broadening effect) of the front sound field.	0.0 to <u>0.3</u> to 1.0 Higher to strengthen the center orientation level (less broadening effect) and lower to weaken (more broadening effect).

Configuring various functions (Setup menu)

You can configure the unit's various function with the menu displayed on the TV screen.

1 Press ON SCREEN.

2 Use the cursor keys to select "Setup" and press ENTER.

3 Use the cursor keys (◁/▷) to select a menu.

4 Use the cursor keys (△/▽) to select an item and press ENTER.

- To return to the previous screen during menu operations, press RETURN.

5 Use the cursor keys to select a setting and press ENTER.

6 To exit from the menu, press ON SCREEN.

Setup menu items

Menu	Item			Function	Page
Speaker	**Auto Setup**			Automatically optimizes the speaker settings (YPAO).	32
	Manual Setup	**Power Amp Assign**		Selects a speaker system.	105
		Configuration	**Front**	Selects the size of the front speakers.	105
			Center	Selects whether or not a center speaker is connected and its size.	105
			Surround	Selects whether or not surround speakers are connected and their size.	105
			Surround Back	Selects whether or not surround back speakers are connected and their size.	106
			Front Presence	Selects whether or not front presence speakers are connected and their size.	106
			Subwoofer	Selects whether or not a subwoofer is connected and its phase.	106
			Layout	Selects the layouts of the surround speakers and front presence speakers.	106
			Bass Cross Over	Sets the lower limit of the low-frequency component that can be output from speakers whose size is set to "Small".	106
		Distance		Sets the distance between each speaker and listening position.	107
		Level		Adjusts the volume of each speaker.	107
		Parametric EQ		Adjusts the tone with an equalizer.	107
		Test Tone		Enables/disables the test tone output.	108
Sound	**Lipsync**	**Delay Enable**		Enables/disables the Lipsync adjustment for each input source.	108
		Auto/Manual Select		Selects the method to adjust the delay between video and audio output.	108
		Adjustment		Adjusts the delay between video and audio output manually.	109
	Dynamic Range			Selects the dynamic range adjustment method for bitstream audio (Dolby Digital and DTS signals) playback.	109
	Max Volume			Sets the maximum volume to prevent excessive loudness.	109
	Initial Volume			Sets the initial volume for when this receiver is turned on.	109
	Adaptive DSP Level			Selects whether to automatically adjust the CINEMA DSP effect level when the volume is adjusted.	109
	CINEMA DSP 3D Mode			Enables/disables CINEMA DSP 3D.	109
	Virtual Surround Back Speaker			Selects whether to create Virtual Surround Back Speaker (VSBS) using the surround speakers.	109
Video	**Video Mode**			Enables/disables the video signal processing (resolution and aspect ratio).	110
HDMI	**HDMI Control**			Enables/disables HDMI Control. You can also configure the relevant settings (such as ARC and TV audio input).	111
	Audio Output			Selects a device to output audio.	112
	Standby Through			Select whether to output videos/audio (input through HDMI jacks) to the TV when the unit is in standby mode.	112

Menu	Item		Function	Page
Network	**Network Connection**		Selects the network connection method.	112
	IP Address		Configures the network parameters (such as IP address).	113
	Network Standby		Selects whether to enable/disable the function that turns on the unit from other network devices.	113
	MAC Address Filter		Sets the MAC address filter to limit access to the unit from other network devices.	113
	Network Name		Edits the network name (the unit's name on the network) displayed on other network devices.	114
Bluetooth	**Bluetooth**		Enables/disables the *Bluetooth* functions.	114
	Audio Receive	**Disconnect**	Terminates the *Bluetooth* connection between the *Bluetooth* device (such as smartphones) and the unit.	66
	Bluetooth Standby		Selects whether to enable/disable the function that turns on the unit from *Bluetooth* devices (*Bluetooth* standby).	114
Multi Zone	**Main Zone Set**	**Zone Rename**	Changes the zone name (for main zone) displayed on the TV screen.	115
	Zone2 Set	**Max Volume**	Sets the Zone2 maximum volume to prevent excessive loudness in the second zone.	115
		Initial Volume	Sets the Zone2 initial volume for when the unit is turned on.	115
		Zone Rename	Changes the zone name (for Zone2) displayed on the TV screen.	115
	Party Mode Set		Enables/disables switching to the party mode.	115
Function	**Display Set**	**Dimmer (Front Display)**	Adjusts the brightness of the front display.	116
		Short Message	Selects whether to display short messages on the TV screen when the unit is operated.	116
		Wallpaper	Selects the image to be used as wallpaper on the TV.	116
	Trigger Output	**Trigger Mode**	Specifies the condition for the TRIGGER OUT jack to function.	116
		Target Zone	Specifies the zone with which the TRIGGER OUT jack functions are synchronized.	117
	Memory Guard		Prevents accidental changes to the settings.	117
ECO	**Auto Power Standby**		Sets the amount of time for the auto-standby function.	117
	ECO Mode		Enables/disables the eco mode (power saving mode).	117
Language			Select an on-screen menu language.	118

Speaker (Manual Setup)

Configures the speaker settings manually.

💡
• Default settings are underlined.

■ Power Amp Assign

Selects a speaker system.

In addition to the 5.1- or 7.1-channel speaker system, various speaker configurations are possible using the front presence speakers, Zone2 speakers, or bi-amp connection.

Settings

Basic	Select this option when you use a normal speaker system (not using Presence speakers, Zone2 speakers or a bi-amp connection).
Presence	Select this option when you use Presence speakers (p.18).
5ch +1ZONE	Select this option when you use Zone2 speakers (p.83) in addition to the speaker system in the main zone.
5ch BI-AMP	Select this option when you connect front speakers that support bi-amp connections (p.20).

■ Configuration

Configures the output characteristics of the speakers.

💡
• When you configure the speaker size, select "Large" if the woofer diameter of your speaker is 16 cm (6-1/4") or larger or "Small" if it is smaller than 16 cm (6-1/4").
• You can configure the crossover frequency of the speakers whose sizes are set to "Small". For details, refer to "Bass Cross Over" (p.106).

Front

Selects the size of the front speakers.

Settings

Large	Select this option for large speakers. The front speakers will produce all of the front channel frequency components.
Small	Select this option for small speakers. The subwoofer will produce front channel low-frequency components.

💡
• "Front" is automatically set to "Large" when "Subwoofer" is set to "None".

Center

Selects whether or not a center speaker is connected and its size.

Settings

Large	Select this option for large speakers. The center speaker will produce all of the center channel frequency components.
Small	Select this option for small speakers. The subwoofer or front speakers will produce center channel low-frequency components.
None	Select this option when no center speaker is connected. The front speakers will produce center channel audio.

Surround

Selects whether or not surround speakers are connected and their sizes.

Settings

Large	Select this option for large speakers. The surround speakers will produce all of the surround channel frequency components.
Small	Select this option for small speakers. The subwoofer or front speakers will produce surround channel low-frequency components.
None	Select this option when no surround speakers are connected. The front speakers will produce surround channel audio. Virtual CINEMA DSP works when you select a sound program.

Surround Back

Selects whether or not surround back speakers are connected and their sizes.

Settings

Large x1	Select this option when one large speaker is connected. The surround back speaker will produce all of the surround back channel frequency components.
Large x2	Select this option when two large speakers are connected. The surround back speakers will produce all of the surround back channel frequency components.
Small x1	Select this option when one small speaker is connected. The subwoofer or front speakers will produce surround back channel low-frequency components.
Small x2	Select this option when two small speakers are connected. The subwoofer or front speakers will produce surround back channel low-frequency components.
None	Select this option when no surround back speakers are connected. The surround speakers will produce surround back channel audio.

• This setting is not available in the following cases:
  – "Power Amp Assign" is set to anything other than "Basic".
  – "Surround" is set to "None"
  – "Layout (Surround)" is set to "Front"

Front Presence

Selects whether or not presence speakers are connected.

Settings

Use	Select this option when presence speakers are connected.
None	Select this option when no presence speakers are connected.

• This setting is available only when "Power Amp Assign" is set to "Presence".

Subwoofer

Selects whether or not a subwoofer is connected and its phase.

Settings

Use	Normal	Select this option when a subwoofer is connected (phase not reversed). The subwoofer will produce LFE (low-frequency effect) channel audio and low-frequency components from other channels.
	Reverse	Select this option when a subwoofer is connected (phase reversed). The subwoofer will produce LFE (low-frequency effect) channel audio and low-frequency components from other channels.
None		Select this option when no subwoofer is connected. The front speakers will produce LFE (low-frequency effect) channel audio and low-frequency components from other channels.

• When the bass sound is lacking or unclear, switch the subwoofer phase.

Layout

Selects the layouts of the surround speakers and front presence speakers.

Surround

Selects a surround speaker layout when surround speakers are used.

Settings

Rear	Select this option when surround speakers are placed on the rear side of the room.
Front	Select this option when surround speakers are placed on the front side of the room. Virtual CINEMA FRONT (p.51) works in this case.

• This setting is not available when "Configuration (Surround)" is set to "None".

Bass Cross Over

Sets the lower limit of the low-frequency components that can be output from a speaker whose size is set to "Small". A frequency sound lower than the specified value will be produced from the subwoofer or front speakers

Settings

40 Hz, 60 Hz, 80 Hz, 90 Hz, 100 Hz, 110 Hz, 120 Hz, 160 Hz, 200 Hz

• If the volume and crossover frequency are adjustable on your subwoofer, set the volume to half and crossover frequency to maximum.

■ Distance

Sets the distance between each speaker and listening position so that sounds from the speakers reach the listening position at the same time. First, select the unit of distance from "Meter" or "Feet".

Choices

Front L, Front R, Center, Surround L, Surround R, Surround Back L, Surround Back R, Front Presence L, Front Presence R, Subwoofer

Setting range

0.30 m to 3.00 m to 24.00 m (1.0 ft to 10.0 ft to 80.0 ft), *0.05 m (0.2 ft) increments

■ Level

Adjusts the volume of each speaker.

Choices

Front L, Front R, Center, Surround L, Surround R, Surround Back L, Surround Back R, Front Presence L, Front Presence R, Subwoofer

Setting range

-10.0 dB to 0.0 dB to +10.0 dB (0.5 dB increments)

■ Parametric EQ

Adjusts the tone with an equalizer.

Settings

Manual	Select this option when you want to adjust the equalizer manually. For details, see "Manual equalizer adjustment".
YPAO:Flat	Adjusts individual speakers to achieve the same characteristics.
YPAO:Front	Adjusts individual speakers to achieve the same characteristics as the front speakers.
YPAO:Natural	Adjusts all speakers to achieve a natural sound.
Through	Does not use the equalizer.

• "YPAO:Flat", "YPAO:Front", and "YPAO:Natural" are available only when the measurement results of "Auto Setup" have already been saved (p.32). Press ENTER again to view the measurement results.

■ Manual equalizer adjustment

1 Set "Parametric EQ" to "Manual" and press ENTER.

2 Press ENTER again to enter the edit screen.

3 Use the cursor keys to select a speaker and press ENTER.

• To restore the default settings for all speakers, select "PEQ Data Clear" and then "OK".

• To copy the parametric equalizer values acquired with "Auto Setup" (p.32) to the "Manual" fields for fine adjustment, select "PEQ Data Copy" and then an equalizer type.

4 Use the cursor keys (◁/▷) to select a center frequency from the 7 preset bands and the cursor keys (△/▽) to adjust the gain.

Setting range

Gain: -20.0 dB to +6.0 dB

5 To fine-adjust the center frequency or Q factor (bandwidth), press ENTER repeatedly to select an item.

Frequency: Use the cursor keys (◁/▷) to adjust the center frequency of the selected band and the cursor keys (△/▽) to adjust the gain.

Q: Use the cursor keys (◁/▷) to adjust the Q factor (bandwidth) of the selected band and the cursor keys (△/▽) to adjust the gain.

Setting range

Center frequency: 31.3 HZ to 16.0 kHz
Q factor: 0.500 to 10.080

6 To exit from the menu, press ON SCREEN.

■ Test Tone

Enables/disables the test tone output. Test tone output helps you to adjust the speaker balance or equalizer while confirming its effect.

Settings

Off	Does not output test tones.
On	Outputs test tones automatically when you adjust the speaker balance or equalizer.

Sound

Configures the audio output settings.

■ Lipsync

Adjusts the delay between video and audio output.

Delay Enable

Enables/disables the Lipsync adjustment for each input source.

Choices
HDMI 1–6, AV 1–4, AUX, AUDIO 1–2

Settings

Disable	Disable the Lipsync adjustment for the selected input source.
Enable	Enables the Lipsync adjustment for the selected input source.

Auto/Manual Select

Selects the method to adjust the delay between video and audio output.

Setting range

Auto	Adjusts the delay between video and audio output automatically when a TV that supports an automatic lipsync function is connected to the unit via HDMI. If necessary, you can fine-adjust the audio output timing in "Adjustment".
Manual	Select this option when you want to adjust the delay between video and audio output manually. Adjust the audio output timing in "Adjustment".

🔅
- Even if "Auto/Manual Select" is set to "Auto", the automatic adjustment does not work depending on the TV connected to the unit. In this case, adjust the delay manually in "Adjustment".

Adjustment

Adjusts the delay between video and audio output manually when "Auto/Manual Select" is set to "Manual". You can fine-adjust the audio output timing when "Auto/Manual Select" is set to "Auto".

Setting range

0 ms to 500 ms (1 ms increments)

• "Offset" shows the difference between automatic adjustment and fine adjustment.

■ Dynamic Range

Selects the dynamic range adjustment method for bitstream audio (Dolby Digital and DTS signals) playback.

Settings

Maximum	Produces audio without adjusting the dynamic range.
Standard	Optimizes the dynamic range for regular home use.
Minimum/Auto	Sets the dynamic range for clear sound even at night or at low volumes. When playing back Dolby TrueHD signals, the dynamic range is automatically adjusted based on the input signal information.

■ Max Volume

Sets the maximum volume to prevent excessive loudness.

Setting range

-30.0 dB to +15.0 dB (5.0 dB increments), +16.5 dB

■ Initial Volume

Sets the initial volume when the receiver is turned on.

Settings

Off	Sets the level to the volume level of the unit when it last entered standby mode.
On	Sets at Mute or the specified volume level (-80 dB to +16.5 dB, 0.5 dB increments). (This setting works only when the initial volume is set lower than "Max Volume".)

■ Adaptive DSP Level

Selects whether to automatically adjust the CINEMA DSP effect level when the volume is adjusted.

Settings

Off	Does not adjust the effect level automatically.
On	Adjusts the effect level automatically.

■ CINEMA DSP 3D Mode

Enables/disables CINEMA DSP 3D (p.49). If this function is set to "On", CINEMA DSP 3D functions with the selected sound programs (except 2ch Stereo and 7ch Stereo).

Settings

Off	Disables CINEMA DSP 3D.
On	Enables CINEMA DSP 3D.

■ Virtual Surround Back Speaker

Selects whether to create Virtual Surround Back Speaker (VSBS) using the surround speakers. When VSBS is enabled, the unit creates VSBS when no surround back speakers are connected.

Settings

Off	Disables Virtual Surround Back Speaker (VSBS).
On	Enables Virtual Surround Back Speaker (VSBS).

• VSBS is effective only when 6.1- or 7.1-channel content is played back.

Video

Configures the video output settings.

■ Video Mode

Enables/disables the video signal processing (resolution and aspect ratio).

Settings

Direct	Disables the video signal processing.
Processing	Enables the video signal processing. Select a resolution and an aspect ratio in "Resolution" and "Aspect".

- When "Video Mode" is set to "Direct", the unit transmits video signals with the least circuitry in order to reduce video output delay.
- When "Video Mode" is set to "Processing" and the resolution is being converted, short messages are not displayed on the TV screen.

Resolution

Selects a resolution to output HDMI video signals when "Video Mode" is set to "Processing".

Settings

Through	Does not convert the resolution.
Auto	Selects a resolution automatically in accordance with TV resolution.
480p/576p, 720p, 1080i, 1080p, 4K	Output video signals with a selected resolution. (Only the resolutions supported by your TV are selectable.)

- If you need to select a resolution that is not supported by your TV, set "MON.CHK" (p.122) in the "ADVANCED SETUP" menu to "SKIP" and try again. (Note that the output video may not be displayed on your TV normally.)

Aspect

Selects an aspect ratio to output HDMI video signals when "Video Mode" is set to "Processing".

Settings

Through	Does not convert the aspect ratio.
16:9 Normal	Outputs 4:3 video signals to a 16:9 TV with black bands on either side of the screen.

- This setting functions only when 480i/576i or 480p/576p signals are converted into 720p, 1080i, 1080p, or 2160p (4K) signals.

HDMI

Configures the HDMI settings.

■ HDMI Control

Enables/disables HDMI Control (p.141).

Settings

Off	Disables HDMI Control.
On	Enables HDMI Control. Configure the settings in "TV Audio Input", "ARC" and "Standby Sync".

> **!**
> • To use HDMI control, you need to perform the HDMI Control link setup (p.141) after connecting HDMI Control-compatible devices.

TV Audio Input

Selects an audio input jack of the unit to be used for TV audio input when "HDMI Control" is set to "On". The unit's input source automatically switches to TV audio when the TV input is switched to its built-in tuner.

Settings
AV 1–4, AUDIO 1–2

Default
AUDIO1

> **!**
> • When using ARC to input TV audio to the unit, you cannot use the input jacks selected here for connecting an external device because the input will be used for TV audio input.

ARC

Enables/disables ARC (p.142) when "HDMI Control" is set to "On".

Settings

Off	Disables ARC.
On	Enables ARC.

> **!**
> • You do not need to change this setting normally. In case noises are produced from the speakers connected to the unit because TV audio signals input to the unit via ARC are not supported by the unit, set "ARC" to "Off" and use the TV's speakers.

Standby Sync

Select whether to use HDMI control to link the standby behavior of the TV and the unit when "HDMI Control" is set to "On".

Settings

Off	Does not set the unit to standby mode when the TV is turned off.
On	Sets the unit to standby mode when the TV is turned off.
Auto	Sets the unit to standby mode when the TV is turned off only when the unit is receiving TV audio or HDMI signals.

■ Audio Output

Selects a device to output audio.

🔅

• This setting is available only when "HDMI Control" is set to "Off".

Amp

Enables/disables the audio output from the speakers connected to the unit.

Settings

Off	Disables the audio output from the speakers.
On	Enables the audio output from the speakers.

HDMI OUT (TV)

Enables/disables the audio output from a TV connected to the HDMI OUT jack.

Settings

Off	Disables the audio output from the TV.
On	Enables the audio output from the TV.

■ Standby Through

Select whether to output videos/audio (input through HDMI jacks) to the TV when the unit is in standby mode. If this function is set to "On" or "Auto", you can use the input selection keys (HDMI) to select an HDMI input even when the unit is in standby mode (the standby indicator on the unit blinks).

Settings

Off	(This setting is available only when "HDMI Control" is set to "Off".) Does not output videos/audio to the TV.
On	Outputs videos/audio to the TV. (The unit consumes more power than when "Off" is selected.)
Auto	Outputs videos/audio to the TV. If no signals are detected, the unit is set to the power saving mode.

Network

Configures the network settings.

■ Network Connection

Selects the network connection method.

Settings

Wired	Select this option when you want to connect the unit to a network with a commercially-available network cable (p.28)
Wireless (Wi-Fi)	Select this option when you want to connect the unit to a network via the wireless router (access point). For details on settings, see "Connecting the unit to a wireless network" (p.38).
Wireless Direct	Select this option when you want to connect a mobile device to the unit directly. For details on settings, see "Connecting a mobile device to the unit directly (Wireless Direct)" (p.44).

■ IP Address

Configures the network parameters (such as IP address).

DHCP

Select whether to use a DHCP server.

Settings

Off	Does not use a DHCP server. Configure the network parameters manually. For details, see "Manual network settings".
On	Uses a DHCP server to automatically obtain the unit's network parameters (such as IP address).

■ Manual network settings

1 Set "DHCP" to "Off".

2 Use the cursor keys (△/▽) to select a parameter type and press ENTER.

IP Address	Specifies an IP address.
Subnet Mask	Specifies a subnet mask.
Default Gateway	Specifies the IP address of the default gateway.
DNS Server (P)	Specifies the IP address of the primary DNS server.
DNS Server (S)	Specifies the IP address of the secondary DNS server.

3 Use the cursor keys (◁/▷) to move the edit position and the cursor keys (△/▽) to select a value.

4 To confirm the setting, press ENTER.

5 To configure another network parameter, repeat steps 2 to 4.

6 To save the changes, use the cursor keys to select "OK" and press ENTER.

7 To exit from the menu, press ON SCREEN.

■ Network Standby

Selects whether the unit can be turned on from other network devices (network standby).

Settings

Off	Disables the network standby function.
On	Enables the network standby function. (The unit consumes more power than when "Off" is selected.)
Auto	Enables the network standby function. (If "Network Connection" is set to "Wired", the unit is set to the power saving mode when the network cable is disconnected.)

■ MAC Address Filter

Sets the MAC address filter to limit access to the unit from other network devices.

Filter

Enables/disables the MAC address filter.

Settings

Off	Disables the MAC address filter.
On	Enables the MAC address filter. In "MAC Address 1–10", specify the MAC addresses of the network devices that will be permitted access to the unit.

- AirPlay (p.80) and DMC (p.97) operations are not subject to the MAC address filter.

MAC Address 1–10

Specifies the MAC addresses (up to 10) of the network devices that will be permitted access to the unit when "Filter" is set to "On".

■ Procedure

1 Use the cursor keys (△/▽) to select "MAC Address 1–5" or "MAC Address 6–10" and press ENTER.

2 Use the cursor keys (△/▽) to select an MAC address number and press ENTER.

3 Use the cursor keys (◁/▷) to move the edit position and the cursor keys (△/▽) to select a value.

4 To confirm the setting, press ENTER.

5 To save the changes, use the cursor keys to select "OK" and press ENTER.

6 To exit from the menu, press ON SCREEN.

■ Network Name

Edits the network name (the unit's name on the network) displayed on other network devices.

■ Procedure

1 Press ENTER to enter the name edit screen.

2 Use the cursor keys and ENTER to rename and select "ENTER" to confirm the entry.

💡
• To clear the entry, select "CLEAR".

3 Use the cursor keys to select "OK" and press ENTER.

💡
• To restore the default setting, select "RESET".

4 To exit from the menu, press ON SCREEN.

Bluetooth

Configures the *Bluetooth* settings.

■ Bluetooth

Enables/disables the *Bluetooth* function (p.66).

Settings

Off	Disables the *Bluetooth* function.
On	Enables the *Bluetooth* function.

■ Bluetooth Standby

Selects whether to enable/disable the function that turns on the unit from *Bluetooth* devices (*Bluetooth* standby). If this function is set to "On", the unit automatically turns on when a connect operation is performed on the *Bluetooth* device.

Settings

Off	Disables the *Bluetooth* standby function.
On	Enables the *Bluetooth* standby function. (The unit consumes more power than when "Off" is selected.)

💡
• This setting is not available when "Network Standby" (p.113) is set to "Off".

Multi Zone

Configures the multi zone settings.

■ Main Zone Set

Configures the main zone setting.

Zone Rename

Changes the zone name (for main zone) displayed on the TV screen.

■ Procedure

1 **Press ENTER to enter the name edit screen.**

2 **Use the cursor keys and ENTER to rename and select "ENTER" to confirm the entry.**

> 🔅
> • To clear the entry, select "CLEAR".

3 **Use the cursor keys to select "OK" and press ENTER.**

> 🔅
> • To restore the default setting, select "RESET".

4 **To exit from the menu, press ON SCREEN.**

■ Zone2 Set

Configures the Zone2 settings.

Max Volume

Sets the Zone2 maximum volume to prevent excessive loudness.

Setting range
-30.0 dB to +15.0 dB (5.0 dB increments), +16.5 dB

> 🔅
> • This setting is available only when "Power Amp Assign" (p.105) is set to "5ch +1ZONE".

Initial Volume

Sets the Zone2 initial volume for when the unit is turned on.

Settings

Off	Sets the level at the volume level of the unit when it last entered standby mode.
On	Sets at Mute or the specified volume level (-80 dB to +16.5 dB, 0.5 dB increments). (This setting works only when the initial volume is set lower than "Max Volume".)

> 🔅
> • This setting is available only when "Power Amp Assign" (p.105) is set to "5ch +1ZONE".

Zone Rename

Changes the zone name (for Zone2) displayed on the TV screen.

You can change the zone name in the same manner as "Zone Rename" in "Main Zone Set" (p.115).

■ Party Mode Set

Enables/disables switching to the party mode (p.86).

Choice
Target: Zone 2

Settings

Disable	Disables switching to the party mode.
Enable	Enables switching to the party mode. You can turn on/off the party mode by pressing PARTY on the remote control.

Function

Configures the functions that make the unit easier to use.

■ Display Set

Configures the settings related to the front display and TV screen display.

Dimmer (Front Display)

Adjusts the brightness of the front display.

Setting range

-4 to 0 (higher to brighten)

> [!]
> • The front display may become dark when "ECO Mode" (p.117) is set to "On".

Short Message

Selects whether to display short messages on the TV screen when the unit is operated (such as input selection and volume adjustment).

Settings

On	Displays short messages on the TV screen.
Off	Does not display short messages on the TV screen.

Wallpaper

Selects the image to be used as wallpaper on the TV.

Settings

Piano	Displays the piano image on the TV screen when there is no video signal.
Gray	Displays a gray background on the TV screen when there is no video signal.

■ Trigger Output

Sets the TRIGGER OUT jack to function in sync with the power status of each zone or input switching.

Trigger Mode

Specifies the condition for the TRIGGER OUT jack to function.

Settings

Power	The TRIGGER OUT jack functions in sync with the power status of the zone specified with "Target Zone."
Source	The TRIGGER OUT jack functions in sync with the input switching in the zone specified with "Target Zone." An electronic signal is transmitted according to the setting made in "Source."
Manual	Select this to manually switch the output level for electronic signal transmission with "Manual."

Source

Specifies the output level of the electronic signal transmitted with each input, switching when "Trigger Mode" is set to "Source".

Choices

HDMI 1–6, AV 1–4, AUX, AUDIO 1–2, TUNER, PHONO, (network sources), Bluetooth, USB

Settings

Low	Stops the electronic signal transmission when you switch to the input source specified in this option.
High	Transmits the electronic signal when you switch to the input source specified in this option.

Manual

Switches the output level for electronic signal transmission manually when "Trigger Mode" is set to "Manual". This setting can also be used to confirm proper function of the external device connected via the TRIGGER OUT jack.

Choices

Low	Stops the electronic signal transmission.
High	Transmits the electronic signal.

Target Zone

Specifies the zone with which the TRIGGER OUT jack functions are synchronized.

Settings

Main	When "Trigger Mode" is set to "Power," electronic signal transmission is synchronized with the power status of the main zone. When "Trigger Mode" is set to "Source," electronic signal transmission is synchronized with the input switching in the main zone.
Zone2	When "Trigger Mode" is set to "Power," electronic signal transmission is synchronized with the power status of Zone2. When "Trigger Mode" is set to "Source," electronic signal transmission is synchronized with the input switching in Zone2.
All	When "Trigger Mode" is set to "Power," electronic signal transmission is synchronized with the power status of the main zone or Zone2. When "Trigger Mode" is set to "Source," electronic signal transmission is synchronized with the input switching in the main zone or Zone2.

■ Memory Guard

Prevents accidental changes to the settings.

Settings

Off	Does not protect the settings.
On	Protects the settings until "Off" is selected.

☼
• When "Memory Guard" is set to "On", the lock icon (🔒) is displayed on the menu screen.

Icon

ECO

Configures the power supply settings.

■ Auto Power Standby

Sets the amount of time for the auto-standby function. If you do not operate the unit or if no input signals are detected for the specified time, the unit will automatically go into standby mode.

Settings

Off	Does not set the unit to standby mode automatically.
20 Minutes	Sets the unit to standby mode when you have not operated the unit and no input signals are detected for 20 minutes.
2 Hours, 4 Hours, 8 Hours, 12 Hours	Sets the unit to standby mode when you have not operated the unit for the specified time. For example, when "2 Hours" is selected, the unit will switch to standby mode if you do not operate it for 2 hours.

Default
U.K. and Europe models: 20 Minutes
Other models: Off

☼
• Just before the unit enters standby mode, "AutoPowerStdby" appears and then countdown starts in the front display.

■ ECO Mode

Enables/disables the eco (power saving) mode.
When the eco mode is enabled, you can reduce the unit's power consumption.

Settings

Off	Disables the eco mode.
On	Enables the eco mode.

❗
• The new setting will take effect after the unit is restarted.
• When "ECO Mode" is set to "On", the front panel display may become dark.
• If you want to play audio at high volume, set "ECO Mode" to "Off".

Language

Select an on-screen menu language.

Settings

English	English
日本語	Japanese
Français	French
Deutsch	German
Español	Spanish
Русский	Russian
Italiano	Italian
中文	Chinese

☀️

• The information on the front display is provided in English only.

Viewing information about the unit (Information menu)

You can view information about the unit using the TV screen.

1 **Press ON SCREEN.**

2 **Use the cursor keys to select "Information" and press ENTER.**

3 **Use the cursor keys (◁/▷) to select an information type.**

4 **To exit from the menu, press ON SCREEN.**

Types of information

■ Audio Signal

Displays information about the current audio signal.

Input	Format	Audio format of the input signal
	Channel	The number of source channels in the input signal (front/surround/LFE) For example, "5.1 (3/2/0.1)" means 5.1ch in total (3 front channels, 2 surround channels, and LFE).
	Sampling	The number of samples per second of the input digital signal
	Bitrate	The amount of data per second of the input bitstream signal
	Dialogue	The dialogue normalization level of the input bitstream signal
Output		The speaker terminals from which signals are output

- Even when the unit is set to output bitstream signals directly, the signal may be converted depending on the specifications and settings of the playback device.

■ Video Signal

Displays information about the current video signal.

HDMI Signal	Presence or absence of HDMI signal input/output
HDMI Resolution	Resolutions of input signal (analog or HDMI) and output signal (HDMI)
Analog Resolution	Resolutions of input signal (analog)

■ HDMI Monitor

Displays information about the TVs connected to the HDMI OUT jack.

Interface	TV interface
Video Resolution	Resolutions supported by the TV

■ Network

Displays the network information on the unit.

(When using wired or wireless [Wi-Fi] network connection)

IP Address	IP address
Subnet Mask	Subnet mask
Default Gateway	The IP address of the default gateway
DNS Server (P)	The IP address of the primary DNS server
DNS Server (S)	The IP address of the secondary DNS server
MAC Address (Ethernet)	MAC address
MAC Address (Wi-Fi)	
vTuner ID	vTuner ID
Network Name	Network name (the unit's name on the network)
Wired/Wireless	The status of the wired or wireless connection
SSID	(When using wireless [Wi-Fi] network connection) The SSID of the wireless network

(When using Wireless Direct)

SSID	The SSID of the wireless network
Security	Security method
Security Key	Security key
IP Address	IP address
Subnet Mask	Subnet mask
MAC Address (Wi-Fi)	MAC address
Network Connection	"Wireless Direct" indication

■ System

Displays the system information on the unit.

Remote ID	The unit's remote control ID setting (p.121)
TV Format	The unit's video signal type (p.121)
Speaker Impedance	The speaker impedance setting of the unit (p.121)
Tuner Freq. Step	(Asia and General models only) The FM/AM tuning frequency setting of the unit (p.121)
System ID	System ID number
Firmware Version	The version of firmware installed on the unit

- If the unit detects a newer firmware over the network, "!" (exclamation mark) appears at the upper right of the "Information" and "System" icons, and the corresponding message will be displayed in this screen. You can update the unit's firmware by pressing ENTER in this screen and following the procedure in "Updating the unit's firmware via the network" (p.124).

■ Multi Zone

Displays information about Zone2.

Input	The input source selected for Zone2
Volume	The volume setting for Zone2

Configuring the system settings (ADVANCED SETUP menu)

Configure the system settings of the unit while viewing the front display.

1 **Set the unit to standby mode.**

2 **While holding down STRAIGHT on the front panel, press ⏻ (power).**

⏻ (power)

STRAIGHT   PROGRAM

3 **Press PROGRAM to select an item.**

4 **Press STRAIGHT to select a setting.**

5 **Press ⏻ (power) to set the unit to standby mode and turn it on again.**

The new settings take effect.

ADVANCED SETUP menu items

- Default settings are underlined.

Item	Function	Page
SP IMP.	Changes the speaker impedance setting.	121
REMOTE ID	Selects the unit's remote control ID.	121
TU	(Asia and General models only) Changes the FM/AM tuning frequency setting.	121
TV FORMAT	Switches the video signal type.	121
MON.CHK	Removes the limitation on HDMI video output.	122
4K MODE	Selects the HDMI 4K signal format.	122
INIT	Restores the default settings.	122

Item	Function	Page
UPDATE	Updates the firmware.	123
VERSION	Checks the version of firmware currently installed on the unit.	123

Changing the speaker impedance setting (SP IMP.)

```
SP IMP.··8ΩMIN
```

Change the unit's speaker impedance settings depending on the impedance of the speakers connected.

Settings

6 Ω MIN	Select this option when you connect 6-ohm speakers to the unit. You can also use 4-ohm speakers as the front speakers.
8 Ω MIN	Select this option when you connect 8-ohm or higher speakers to the unit.

Selecting the remote control ID (REMOTE ID)

```
REMOTE ID··ID1
```

Change the unit's remote control ID so that it matches the remote control's ID (default: ID1). When using multiple Yamaha AV receivers, you can set each remote control with a unique remote control ID for its corresponding receiver.

Settings
ID1, ID2

■ **Changing the remote control ID of the remote control**

1 **To select ID1, hold down the cursor key (◁) and SCENE (BD/DVD) together for 3 seconds.**
To select ID2, hold down the cursor key (◁) and SCENE (TV) together for 3 seconds.

Changing the FM/AM tuning frequency setting (TU)

(Asia and General models only)

```
TU····FM50/AM9
```

Change the FM/AM tuning frequency setting of the unit depending on your country or region.

Settings

FM100/AM10	Select this when you want to adjust the FM frequency by 100-kHz steps and AM by 10-kHz steps.
FM50/AM9	Select this when you want to adjust the FM frequency by 50-kHz steps and AM by 9-kHz steps.

Switching the video signal type (TV FORMAT)

```
TV FORMAT·NTSC
```

Switch the video signal type of the unit so that it matches to the format of your TV.

Settings
NTSC, PAL

Default
Canada, Korea and General models: NTSC
Other models: PAL

Removing the limitation on HDMI video output (MON.CHK)

```
MON.CHK••••YES
```

The unit automatically detects resolutions supported by a TV connected to the HDMI OUT jack.

Disable the monitor check function if you want to specify a resolution in "Resolution" (p.110) when the unit cannot detect the TV's resolution or when you want to specify a different resolution than the detected resolution.

Settings

YES	Enables the monitor check function. (Outputs video signals with a resolution supported by the TV only.)
SKIP	Disables the monitor check function. (Outputs video signals with a specified resolution regardless of compatibility with the TV.)

!

- Reset to "YES" if the unit becomes inoperable because video from the unit cannot be displayed on the TV after "MON.CHK" has been set to "SKIP".

Selecting the HDMI 4K signal format (4K MODE)

```
4K MODE•MODE 2
```

Selects the format of signals input/output at the unit when HDMI 4K (60 Hz/50 Hz) compatible TV and playback device are connected to the unit.

Settings

MODE 1	Inputs/outputs 4K (60 Hz/50 Hz) signals in 4:4:4, 4:2:2 or 4:2:0 format. Depending on the connected device or HDMI cables, video may not be displayed correctly. In this case, select "MODE 2".
MODE 2	Inputs/outputs 4K (60 Hz/50 Hz) signals in 4:2:0 format.

- When "MODE 1" is selected, use a high-speed HDMI cable that supports 18 Gbps.

Restoring the default settings (INIT)

```
INIT••••CANCEL
```

Restores the default settings for the unit.

Choices

VIDEO	Restores the default settings for video configurations.
ALL	Restores the default settings for the unit.
CANCEL	Does not perform an initialization.

Updating the firmware (UPDATE)

```
UPDATE·····USB
```

New firmware that provides additional features or product improvements will be released as needed. Updates can be downloaded from the Yamaha website. If the unit is connected to the Internet, you can download the firmware via the network. For details, refer to the information supplied with updates.

■ Firmware update procedure

Do not perform this procedure unless firmware update is necessary. Also, make sure you read the information supplied with updates before updating the firmware.

1 **Press STRAIGHT repeatedly to select "USB" or "NETWORK" and press INFO to start firmware update.**

Choices

USB	Update the firmware using a USB memory device.
NETWORK	Update the firmware via the network.

- If the unit detects newer firmware over the network, the corresponding message will be displayed after ON SCREEN is pressed. In this case, you can also update the unit's firmware by following the procedure in "Updating the unit's firmware via the network" (p.124).

Checking the firmware version (VERSION)

```
VERSION··xx.xx
```

Check the version of firmware currently installed on the unit.

- You can also check the firmware version in "System" (p.120) in the "Information" menu.
- It may take a while until the firmware version is displayed.

Updating the unit's firmware via the network

New firmware that provides additional features or product improvements will be released as needed. If the unit is connected to the Internet, you can download the firmware via the network and update it.

> **Note**
> - Do not operate the unit or disconnect the power cable or network cable during firmware update. Firmware update takes about 20 minutes or more (depending on your Internet connection speed).
> - If the unit is connected to the wireless network, network update may not be possible depending on the condition of the wireless connection. In this case, update the firmware using the USB memory device (p.123).
> - For details on update, visit the Yamaha website.

☼
- You can also update the firmware using the USB memory device from the "ADVANCED SETUP" menu (p.123).

A firmware update is available if the following message is displayed after ON SCREEN is pressed.

AV Receiver

New firmware available.
It takes about 20 minutes to update the firmware.
This screen will disappear once the update begins, so please check the status on the front panel display.

Press the "START" button to update now, or the "CLOSE" button to update later.
(You can also start the update from the "Information – System" screen.)

< Note >
Do not disconnect the power cable or network cable during the update.

START   CLOSE

1 **Read the on-screen description.**

2 **To start the firmware update, use the cursor keys to select "START" and press ENTER.**

The on-screen display turns off.

3 **If "Update Success Please Power Off!" appears on the front display, press ⏻ (power) on the front panel.**

The firmware update is complete.

☼
- If you want to update the firmware later, select "CLOSE" in Step 2. "!" (exclamation mark) appears at the upper right of the "Information" and "System" icons, and a message will be displayed in the "System" screen (p.120). You can update the unit's firmware by pressing ENTER in the "System" screen.

Information icon — Information

Remote ID | ID1
TV Format | NTSC
Speaker Impedance | 8Ω min
System ID |
Firmware Version |

Message — New firmware available.
Press ENTER to go to the update screen.

System Icon

Cursor keys
ENTER

APPENDIX

Frequently asked questions

The new speaker system does not provide an ideal sound balance...

If you have changed speakers or have a new speaker system, use "Auto Setup" to optimize the speaker settings again (p.32). If you want to adjust the speaker settings manually, use "Manual Setup" in the "Setup" menu (p.105).

Since we have small children, we want to set limitations on the volume control...

If a small child accidentally operates the controls on the main unit or remote control, the volume may suddenly increase. This may also cause injury or damage the unit or speakers. We recommend using "Max Volume" in the "Setup" menu to set the maximum volume level for the unit in advance (p.109). You can also set the maximum volume for Zone2 (p.115).

I am occasionally startled by a sudden loud sound when turning on the unit...

By default, the volume level when the unit last entered standby mode is automatically applied. If you want to fix the volume, use "Initial Volume" in the "Setup" menu to set the volume to be applied when the receiver is turned on (p.109). You can also set the initial volume for Zone2 (p.115).

We are bothered by volume differences when switching between input sources…

You can correct volume differences between input sources by utilizing "Input Trim" in the "Option" menu (p.94).

I made HDMI connections but HDMI Control does not work at all...

To use HDMI Control, you need to perform the HDMI Control link setup (p.141). After connecting HDMI Control-compatible devices (such as BD/DVD players) to the unit, enable HDMI Control on each device and perform the HDMI Control link setup. This setup is required every time you add a new HDMI Control-compatible device to your system. For information on how HDMI Control works between your TV and playback devices, refer to the instruction manuals for each device.

I want to turn off the on-screen messages displayed during operations...

By default, short messages are displayed on the TV screen when the unit is operated (such as input selection and volume adjustment). If the short messages bother you when you are watching movies or sports, configure "Short Message" (p.116) in the "Setup" menu to turn off the short messages.

I want to prevent accidental changes to the settings...

You can protect the settings configured on the unit (such as speaker settings) by utilizing "Memory Guard" in the "Setup" menu (p.117).

The unit's remote control is simultaneously controlling another Yamaha product as well as the unit...

When using multiple Yamaha products, the remote control may work on another Yamaha product or another remote control may work on the unit. If this happens, register different remote control IDs for the devices that you want to control with each remote control (p.121).

I want to enjoy videos/audio played back on the video device even when the unit is in standby mode…

If you have connected a video device to the unit with HDMI, you can output videos/audio played back on the video device to the TV even when the unit is in standby mode. To use this function, set "Standby Through" (p.112) in the "Setup" menu to "On" or "Auto". You can also switch the input source using the remote control of the unit when this function is enabled.

Troubleshooting

Refer to the table below when the unit does not function properly.

If the problem you are experiencing is not listed below or if the instructions below do not help, turn off the unit, disconnect the power cable, and contact the nearest authorized Yamaha dealer or service center.

First, check the following:

① **The power cables of the unit, TV and playback devices (such as BD/DVD players) are connected to AC wall outlets securely.**

② **The unit, subwoofer, TV and playback devices (such as BD/DVD players) are turned on.**

③ **The connectors of each cable are securely inserted in to jacks on each device.**

Power, system and remote control

Problem	Cause	Remedy
The power does not turn on.	The protection circuitry has been activated three times consecutively. When the unit is in this condition, the standby indicator on the unit blinks if you try to turn on the power.	As a safety precaution, capability to turn on the power is disabled. Contact your nearest Yamaha dealer or service center to request repair.
The power does not turn off.	The internal microcomputer has frozen, due to an external electric shock (such as lightning or excessive static electricity) or to a drop in the power supply voltage.	Hold down ⏻ (power) on the front panel for more than 10 seconds to initialize and reboot the unit. (If the problem persists, disconnect the power cable from the AC wall outlet and plug it again.)
The power turns off (standby mode) immediately.	The unit was turned on while a speaker cable was shorted.	Twist the bare wires of each speaker cable firmly and reconnect to the unit and speakers (p.19).
The unit enters standby mode automatically.	The sleep timer worked.	Turn on the unit and start playback again.
	The auto-standby function kicked in because the unit was not used for the specified time.	To disable the auto-standby function, set "Auto Power Standby" in the "Setup" menu to "Off" (p.117).
	The speaker impedance setting is incorrect.	Set the speaker impedance to match your speakers (p.121).
	The protection circuitry has been activated because of a short circuit.	Twist the bare wires of each speaker cable firmly and reconnect to the unit and speakers (p.19).
The unit is not reacting.	The internal microcomputer is frozen, due to an external electric shock (such as lightning or excessive static electricity) or to a drop in the power supply voltage.	Hold down ⏻ (power) on the front panel for more than 10 seconds to initialize and reboot the unit. (If the problem persists, disconnect the power cable from the AC wall outlet and plug it again.)

Problem	Cause	Remedy
The unit cannot be controlled using the remote control.	The unit is out of the operating range.	Use the remote control within the operating range (p.5).
	The batteries are weak.	Replace with new batteries.
	The unit's remote control sensor is exposed to direct sunlight or strong lighting.	Adjust the lighting angle, or reposition the unit.
	The remote control IDs of the unit and the remote control are not identical.	Change the remote control ID of the unit or the remote control (p.121).

Audio

Problem	Cause	Remedy
No sound.	Another input source is selected.	Select an appropriate input source with the input selection keys.
	Signals that the unit cannot reproduce are being input.	Some digital audio formats cannot be played back on the unit. To check the audio format of the input signal, use "Audio Signal" in the "Information" menu (p.119).
	The cable connecting the unit and playback device is defective.	If there is no problem with the connection, replace with another cable.
The volume cannot be increased.	The maximum volume is set.	Use "Max Volume" in the "Setup" menu to adjust the maximum volume (p.109).
	A device connected to the output jacks of the unit is not turned on.	Turn on all devices connected to the output jacks of the unit.
No sound is coming from a specific speaker.	The playback source does not contain a signal for the channel.	To check it, use "Audio Signal" in the "Information" menu (p.119).
	The currently selected sound program/decoder does not use the speaker.	To check it, use "Test Tone" in the "Setup" menu (p.108).
	Audio output of the speaker is disabled.	Perform "Auto Setup" (p.32) or use "Configuration" in the "Setup" menu to change the speaker settings (p.105).
	The volume of the speaker is set too low.	Perform "Auto Setup" (p.32) or use "Level" in the "Setup" menu to adjust the speaker volume (p.107).
	The speaker cable connecting the unit and the speaker is defective.	If there is no problem with the connection, replace with another speaker cable.
	The speaker is malfunctioning.	To check it, replace with another speaker. If the problem persists, the unit may be malfunctioning.
No sound is coming from the subwoofer.	The playback source does not contain LFE or low-frequency signals.	To check if the subwoofer is working properly, use "Test Tone" in the "Setup" menu (p.108).
	Subwoofer output is disabled.	Perform "Auto Setup" (p.32) or set "Subwoofer" in the "Setup" menu to "Use" (p.106).
	The volume of the subwoofer is too low.	Adjust the volume on the subwoofer.
	The subwoofer has been turned off by its auto-standby function.	Disable the auto-standby function of the subwoofer or adjust its sensitivity level.

Problem	Cause	Remedy
No sound from the playback device (connected to the unit with HDMI).	The TV does not support HDCP (High-bandwidth Digital Content Protection).	Refer to the instruction manuals for the TV and check the TV's specifications.
	The unit is set not to output audio input through HDMI jacks from the SPEAKERS terminals.	In "Audio Output" in the "Setup" menu, set "Amp" to "On" (p.112).
	The number of devices connected to the HDMI OUT jack exceeds the limit.	Disconnect some of the HDMI devices.
No sound from the TV (when HDMI Control is used).	The TV is set to output audio from the TV speakers.	Change the audio output setting on your TV so that the TV audio is output from the speakers connected to the unit.
	A TV that does not support ARC is connected to the unit only with an HDMI cable.	Use a digital optical cable to make an audio connection (p.22).
	(If the TV is connected to the unit with an audio cable) The TV audio input setting does not match the actual connection.	Use "TV Audio Input" in the "Setup" menu to select the correct audio input jack (p.111).
	(If you are trying to use ARC) ARC is disabled on the unit or TV.	Set "ARC" in the "Setup" menu to "On" (p.111). Also, enable ARC on the TV.
Only the front speakers work on multichannel audio.	The playback device is set to output 2-channel audio (such as PCM) only.	To check it, use "Audio Signal" in the "Information" menu (p.119). If necessary, change the digital audio output setting on the playback device.
Noise/hum is heard.	The unit is too close to another digital or radio frequency device.	Move the unit further away from the device.
	The cable connecting the unit and playback device is defective.	If there is no problem with the connection, replace with another cable.
The sound is distorted.	The volume of the unit is too high.	Turn down the volume. If "ECO Mode" is set to "On", set it to "Off" (p.117).
	A device connected to the unit's output jacks is not turned on.	Turn on all devices connected to the unit's output jacks.

Video

Problem	Cause	Remedy
No video.	Another input source is selected on the unit.	Select an appropriate input source with the input selection keys.
	Another input source is selected on the TV.	Switch the TV input to display the video from the unit.
	The video signal output from the unit is not supported by the TV.	Set "MON.CHK" in the "ADVANCED SETUP" menu to "YES" (p.122).
	The cable connecting the unit and TV (or playback device) is defective.	If there is no problem with the connection, replace with another cable.
No video from the playback device (connected to the unit with HDMI).	The input video signal (resolution) is not supported by the unit.	To check the information about the current video signal (resolution), use "Video Signal" in the "Information" menu (p.119). For information about video signals supported by the unit, see "HDMI signal compatibility" (p.143).
	The TV does not support HDCP (High-bandwidth Digital Content Protection).	Refer to the instruction manuals for the TV and check the TV's specifications. If you want to play back contents that require HDCP 2.2-compatible devices, both the TV and playback device must support HDCP 2.2.
	The playback device that supports HDCP 2.2 is connected to other than the HDMI 1–3 jack.	To play back contents that require HDCP 2.2-compatible devices, connect the playback device to the HDMI 1–3 jack (p.23).
	The number of devices connected to the HDMI OUT jack is over the limit.	Disconnect some of the HDMI devices.
The menu of the unit is not displayed on the TV.	The TV is not connected to the unit via HDMI.	You can display the menu of the unit on the TV only when they are connected with an HDMI cable. If necessary, use an HDMI cable to connect them (p.22).
	Another input source is selected on the TV.	Switch the TV input to display the video from the unit (HDMI OUT jack).

FM/AM radio (AM radio feature is available only on RX-AS710.)

Problem	Cause	Remedy
FM radio reception is weak or noisy.	There is multi-path interference.	Adjust the FM antenna height or orientation, or place it in a different location.
	Your area is too far from the FM station transmitter.	Set "FM Mode" in the "Option" menu to "Mono" to select monaural FM radio reception (p.94).
		Use an outdoor FM antenna. We recommend using a sensitive multi-element antenna.
AM radio reception is weak or noisy.	The noises may be caused by fluorescent lamps, motors, thermostats, or other electrical equipment.	It is difficult to completely eliminate noise. It may be reduced by using an outdoor AM antenna.

Problem	Cause	Remedy
Radio stations cannot be selected automatically.	Your area is too far from the FM station transmitter.	Select the station manually (p.54).
		Use an outdoor antenna. We recommend using a sensitive multi-element antenna.
	The AM radio signal is weak.	Adjust the AM antenna orientation.
		Select the station manually (p.54).
		Use an outdoor AM antenna. Connect it to the ANTENNA (AM) jack together with the supplied AM antenna.
AM radio stations cannot be registered as presets.	Auto Preset has been used.	Auto Preset is for registering FM radio stations only. Register AM radio stations manually (p.55).

DAB radio (RX-AS710D)

Problem	Cause	Remedy
No DAB radio reception.	An initial scan has not been performed.	Perform an initial scan to receive DAB radio (p.58).
No DAB radio reception even after performing an initial scan.	Reception strength of DAB radio is poor.	Check reception strength in "Tune Aid" in the "Option" menu (p.61), and adjust the antenna height or orientation, or place it in a different location.
	There is no DAB coverage in your area.	Check with your dealer or WorldDMB online at "http://www.worlddab.org" for a listing of the DAB coverage in your area.
DAB radio reception is weak or noisy.	There is multi-path interference.	Check reception strength in "Tune Aid" in the "Option" menu (p.61), and adjust the antenna height or orientation, or place it in a different location.
	Your area is too far from the DAB station transmitter.	Use an outdoor antenna. We recommend using a sensitive multi-element antenna.
DAB information is not available or is inaccurate.	The selected DAB radio station may be temporarily out of service or may not provide information.	Contact the DAB broadcaster.
No DAB radio sound.	The selected DAB radio station may be temporarily out of service.	Try the station later or select another station.

Bluetooth

Problem	Cause	Remedy
A *Bluetooth* connection cannot be established.	The *Bluetooth* function of the unit is disabled.	Enable the *Bluetooth* function (p.114).
	Another *Bluetooth* device is already connected to the unit.	Terminate the current *Bluetooth* connection and then establish a new connection (p.66).
	The unit and the *Bluetooth* device are too far apart.	Move the *Bluetooth* device closer to the unit.
	There is a device (such as microwave oven and wireless LAN) that outputs signals in the 2.4 GHz frequency band nearby.	Move the unit away from those devices.
	The *Bluetooth* device does not support A2DP.	Use a *Bluetooth* device that supports A2DP.
	The connection information registered on the *Bluetooth* device is not working for some reason.	Delete the connection information on the *Bluetooth* device, and then establish a connection between the *Bluetooth* device and the unit again (p.66).
No sound is produced, or the sound is interrupted during playback.	The volume of the *Bluetooth* device is set too low.	Turn up the volume of the *Bluetooth* device.
	The *Bluetooth* device is not set to send audio signals to the unit.	Switch the audio output of the *Bluetooth* device to the unit.
	The *Bluetooth* connection has been terminated.	Establish a *Bluetooth* connection between the *Bluetooth* device and the unit again (p.66).
	The unit and the *Bluetooth* device are too far apart.	Move the *Bluetooth* device closer to the unit.
	There is a device (such as microwave oven and wireless LAN) that outputs signals in the 2.4 GHz frequency band nearby.	Move the unit away from those devices.

USB and network

Problem	Cause	Remedy
The unit does not detect the USB device.	The USB device is not connected to the USB jack securely.	Turn off the unit, reconnect your USB device, and turn the unit on again.
	The file system of the USB device is not FAT16 or FAT32.	Use a USB device with FAT16 or FAT32 format.
Folders and files in the USB device cannot be viewed.	The data in the USB device is protected by the encryption.	Use a USB device without an encryption function.
The network feature does not function.	The network parameters (IP address) have not been obtained properly.	Enable the DHCP server function on your router and set "DHCP" in the "Setup" menu to "On" on the unit (p.113). If you want to configure the network parameters manually, check that you are using an IP address which is not used by other network devices in your network (p.113).
The unit cannot connect to the Internet via a wireless router (access point).	The wireless router (access point) is turned off.	Turn on the wireless router.
	The unit and the wireless router (access point) are too far apart.	Place the unit and the wireless router (access point) closer to each other.
	There is an obstacle between the unit and the wireless router (access point).	Move the unit and the wireless router (access point) in a location where there are no obstacles between them.
Wireless network is not found.	Microwave ovens or other wireless devices in your neighborhood might disturb the wireless communication.	Turn off these devices.
	Access to the network is restricted by the firewall settings of the wireless router (access point).	Check the firewall setting of the wireless router (access point).
The unit does not detect the PC.	The media sharing setting is not correct.	Configure the sharing setting and select the unit as a device to which music contents are shared (p.73).
	Some security software installed on your PC is blocking the access of the unit to your PC.	Check the settings of security software installed on your PC.
	The unit and PC are not in the same network.	Check the network connections and your router settings, and then connect the unit and the PC to the same network.
	The MAC address filter is enabled on the unit.	In "MAC Address Filter" in the "Setup" menu, disable the MAC address filter or specify the MAC address of your PC to allow it to access to the unit (p.113).
The files in the PC cannot be viewed or played back.	The files are not supported by the unit or the media server.	Use the file format supported by both the unit and the media server. For information about the file formats supported by the unit, see "Playing back music stored on media servers (PCs/NAS)" (p.73).
The Internet radio cannot be played.	The selected Internet radio station is currently not available.	There may be a network problem at the radio station, or the service may have been stopped. Try the station later or select another station.
	The selected Internet radio station is currently broadcasting silence.	Some Internet radio stations broadcast silence at certain of times of the day. Try the station later or select another station.
	Access to the network is restricted by the firewall settings of your network devices (such as the router).	Check the firewall settings of your network devices. The Internet radio can be played only when it passes through the port designated by each radio station. The port number varies depending on the radio station.
The iPod does not recognize the unit when using AirPlay.	The unit is connected to a multiple SSID router.	Access to the unit might be restricted by the network separation function on the router. Connect the iPod to the SSID which can access the unit.

Problem	Cause	Remedy
The application for smartphone/tablet "AV CONTROLLER" does not detect the unit.	The unit and smartphone/tablet are not in the same network.	Check the network connections and your router settings, and then connect the unit and smartphone/tablet to the same network.
	The MAC address filter is enabled on the unit.	In "MAC Address Filter" in the "Setup" menu, disable the MAC address filter or specify the MAC address of your smartphone/tablet to allow it to access to the unit (p.113).
Firmware update via the network is failed.	It may not be possible depending on the condition of the network.	Update the firmware via the network again or use a USB memory device (p.123).

Error indications on the front display

Message	Cause	Remedy
Access denied	Access to the PC is denied.	Configure the sharing settings and select the unit as a device to which music contents are shared (p.73).
Access error	The unit cannot access the USB device.	Turn off the unit and reconnect your USB device. If the problem persists, try another USB device.
	The unit cannot access the iPod.	Turn off the iPod and turn it on again.
	The connected iPod is not supported by the unit.	Use an iPod supported by the unit (p.67).
	There is a problem with the signal path from the network to the unit.	Make sure your router and modem are turned on.
		Check the connection between the unit and your router (or hub) (p.28).
Check SP Wires	The speaker cables short circuit.	Twist the bare wires of the cables firmly and connect to the unit and speakers properly.
Internal Error	An internal error has occurred.	Contact the nearest authorized Yamaha dealer or service center.
No content	There are no playable files in the selected folder.	Select a folder that contains files supported by the unit.
No device	The unit cannot detect the USB device.	Turn off the unit and reconnect your USB device. If the problem persists, try another USB device.
	The unit cannot detect the iPod.	Turn off the iPod and then turn it on again.
Please wait	The unit is preparing for connecting to the network.	Wait until the message disappears. If the message stays more than 3 minutes, turn off the unit and turn it on again.
RemID Mismatch	The remote control IDs of the unit and the remote control are not identical.	Change the remote control ID of the unit or the remote control (p.121).
Unable to play	The unit cannot play back the songs stored on the iPod for some reason.	Check the song data. If it cannot be played on the iPod itself, the song data or storage area may be defective.
	The unit cannot play back the songs stored on the PC for some reason.	Check if the format of files you are trying to play is supported by the unit. For information about the formats supported by the unit, see "Playing back music stored on media servers (PCs/NAS)" (p.73). If the unit supports the file format, but still cannot play back any files, the network may be overloaded with heavy traffic.
USB Overloaded	An overcurrent is flowing through the USB device.	Turn off the unit and reconnect your USB device. If the problem persists, try another USB device.
Version error	Firmware update is failed.	Update the firmware again.

Ideal speaker layout

Use this diagram as a guide. You do not need to adjust the speaker layout to the following diagram exactly.

FPL

0.5 to 1 m
(1.6 to 3.3 ft)

FPR

0.5 to 1 m
(1.6 to 3.3 ft)

1.8 m
(5.9 ft)

FL

FR

1.8 m
(5.9 ft)

SW

C

SW

Turn it slightly inward to
reduce wall reflections.

Turn it slightly inward to
reduce wall reflections.

SL

SR

10° to 30°

10° to 30°

SBL

SBR

0.3 m (1 ft) or more

FL	Front speaker (L)
FR	Front speaker (R)
C	Center speaker
SL	Surround speaker (L)
SR	Surround speaker (R)
SBL	Surround back speaker (L)
SBR	Surround back speaker (R)
FPL	Presence speaker (L)
FPR	Presence speaker (R)
SW	Subwoofer

Glossary

Audio information

■ Audio decoding format

Dolby Digital

Dolby Digital is a compressed digital audio format developed by Dolby Laboratories, Inc. that supports 5.1-channel audio. This technology is used for audio on most DVD discs.

Dolby Digital EX

Dolby Digital EX creates total 6.1-channel audio from 5.1-channel sources that are recorded with Dolby Digital Surround EX. This decoder adds a surround back sound to the original 5.1-channel sound.

Dolby Digital Plus

Dolby Digital Plus is a compressed digital audio format developed by Dolby Laboratories, Inc. that supports 7.1-channel audio. Dolby Digital Plus remains fully compatible with the existing multichannel audio systems that support Dolby Digital. This technology is used for audio on BD (Blu-ray discs).

Dolby Pro Logic II

Dolby Pro Logic II enables 5-channel playback from 2-channel sources. There are three modes available: "Music mode" for music sources, "Movie mode" for movie sources, and "Game mode" for game sources.

Dolby Pro Logic IIx

Dolby Pro Logic IIx enables 7-channel playback from 2-channel or multichannel sources. There are three modes available: "Music mode" for music sources, "Movie mode" for movie sources and "Game mode" for game sources (for 2-channel sources only).

Dolby TrueHD

Dolby TrueHD is an advanced lossless audio format developed by Dolby Laboratories, Inc. to offer a high-definition home theater experience with the quality of the studio master. Dolby TrueHD can carry up to eight channels of 96 kHz/24-bit audio (up to six channels of 192 kHz/24-bit audio) simultaneously. This technology is used for audio on BD (Blu-ray discs).

DSD (Direct Stream Digital)

DSD (Direct Stream Digital) technology stores audio signals on digital storage media, such as SACD (Super Audio CDs). The signals are stored at a high-frequency sampling rate (such as 2.8224 MHz and 5.6448 MHz). The highest frequency response is equal to or higher than 100 kHz, with a dynamic range of 120 dB. This technology offers better audio quality than that used for CDs.

DTS 96/24

DTS 96/24 is a compressed digital audio format that supports 5.1-channel and 96 kHz/24-bit audio. This format remains fully compatible with the existing multichannel audio systems that support DTS Digital Surround. This technology is used for music DVDs, etc.

DTS Digital Surround

DTS Digital Surround is a compressed digital audio format developed by DTS, Inc. that supports 5.1-channel audio. This technology is used for audio on most DVD discs.

DTS-ES

DTS-ES creates total 6.1-channel audio from 5.1-channel sources that are recorded with DTS-ES. This decoder adds a surround back sound to the original 5.1-channel sound. In the DTS-ES Matrix 6.1 format, a surround back sound is recorded in the surround channels, and in the DTS-ES Discrete 6.1 format, a discrete surround back channel is recorded.

DTS Express

DTS Express is a compressed digital audio format that supports 5.1-channel audio and allows a higher compression rate than the DTS Digital Surround format developed by DTS, Inc. This technology is developed for audio streaming services on the Internet and secondary audio on BD (Blu-ray discs).

DTS-HD High Resolution Audio

DTS-HD High Resolution Audio is a compressed digital audio format developed by DTS, Inc. that supports 7.1-channel and 96 kHz/24-bit audio. DTS-HD High Resolution Audio remains fully compatible with the existing multichannel audio systems that support DTS Digital Surround. This technology is used for audio on BD (Blu-ray discs).

DTS-HD Master Audio

DTS-HD Master Audio is an advanced lossless audio format developed to offer a high-definition home theater experience with the quality of the studio master by DTS, Inc. DTS-HD Master Audio can carry up to eight channels of 96 kHz/24-bit audio (up to six channels of 192 kHz/24-bit audio) simultaneously. This technology is used for audio on BD (Blu-ray discs).

DTS Neo:6

DTS Neo:6 enables 6-channel playback from 2-channel sources. There are two modes available: "Music mode" for music sources and "Cinema mode" for movie sources. This technology provides discrete full-bandwidth matrix channels of surround sound.

FLAC

FLAC is a file format for lossless audio data compression. FLAC is inferior to lossy compressed audio formats in compression rate but provides higher audio quality.

MP3

One of the compressed digital audio format used by MPEG. With psychoacoustic technologies, this compression method achieves a high compression rate. Reportedly, it is capable of compressing data quantity by about 1/10 maintaining a certain level of audio quality.

MPEG-4 AAC

An MPEG-4 audio standard. It is used for mobile telephones, portable audio players, and audio streaming services on Internet because it allows a high compression rate of data while maintaining better audio quality than MP3.

PCM (Pulse Code Modulation)

PCM is a signal format under which an analog audio signal is digitized, recorded, and transmitted. This technology is the basis of all other audio format. This technology is used as a lossless audio format called Linear PCM for audio on a variety of media, including CDs and BD (Blu-ray discs).

Sampling frequency/Quantization bit

Sampling frequency and quantization bits indicate the quantity of information when an analog audio signal is digitized. These values are noted as in the following example: "48 kHz/24-bit".

• Sampling frequency
Sampling frequency (the number of times the signal is sampled per second) is called the sampling rate. When the sampling frequency is higher, the range of frequencies that can be played back are wider.

• Quantization bit
The number of quantization bits indicate the degree of accuracy when converting the sound level into a numeric value. When the number of quantized bits is higher, the expression of the sound level is more accurate.

WAV

Windows standard audio file format, which defines the method of recording the digital data obtained by converting audio signals. By default, the PCM method (no compression) is used, but you can also use other compression methods.

WMA (Windows Media Audio)

One of the compressed digital audio formats developed by Microsoft Corporation. With psychoacoustic technologies, this compression method achieves a high compression rate. Reportedly, it is capable of compressing data quantity by about 1/20 maintaining a certain level of audio quality.

■ Others

Bi-amplification connection (Bi-amp)

A bi-amplification connection uses two amplifiers for a speaker. When you use the bi-amplification connection, the unit drives the tweeter and woofer in a speaker with the discrete amplifiers. As a consequence, the tweeter and woofer provide clear audio signal without the interference.

LFE (Low Frequency Effects) 0.1 channel

This channel reproduces low-frequency bass signals and has a frequency range from 20 Hz to 120 Hz. This channel is added to the channels for all bands with Dolby Digital or DTS to enhance low frequency audio effects. This channel is labeled 0.1 because it is limited to only low frequency audio.

Lip sync

Video output sometimes lags behind audio output due to the complexity of signal processing caused by an increase in video signal capacity. Lip sync is a technique for automatically correcting the timing lag between audio and video output.

HDMI and video information

Component video signal

With the component video signal system, the video signal is separated into the Y signal for luminance and the Pb and Pr signals for chrominance. Color can be reproduced more faithfully with this system because each of these signals is independent.

Composite video signal

With the composite video signal system, color, brightness, and synchronization data signals are combined and transmitted with a single cable.

Deep Color

Deep Color is a technology that HDMI specification supports. Deep Color increases the number of available colors within the boundaries defined by the RGB or YCbCr color space. Conventional color systems process the color using 8 bits. Deep Color processes the color with 10, 12, or 16 bits. This technology allows HDTVs and other displays to increase from millions of colors to billions of colors and eliminate on-screen color banding for smooth tonal transitions and subtle gradations between colors.

HDCP

HDCP (High-bandwidth Digital Content Protection) is a digital copy protection form that prevents copying of digital contents as it travels across connections (such as HDMI).

HDMI

HDMI (High-Definition Multimedia Interface) is the world-wide standard interface for digital audio/video signal transmission. This interface transmits both digital audio and digital video signals using a single cable without any loss. HDMI complies with HDCP (High-bandwidth Digital Content Protection) and provides a secure audio/video interface. For further information on HDMI, visit the HDMI website at "http://www.hdmi.org/".

x.v.Color

"x.v.Color" is a technology that the HDMI specification supports. It is a more extensive color space than sRGB and allows the expression of colors that were not hitherto possible. While remaining compatible with the color gamut of sRGB standards, "x.v.Color" expands the color space, and thus can produce more vivid, natural images.

Network information

SSID

SSID (Service Set Identifier) is a name that identifies a particular wireless LAN access point.

Wi-Fi

Wi-Fi (Wireless Fidelity) is a technology that allows an electronic device to exchange data or connect to the Internet wirelessly using radio waves. Wi-Fi offers the advantage of eliminating the complexity of making connections with network cables by using wireless connection. Only products that complete Wi-Fi Alliance interoperability tests can carry the "Wi-Fi Certified" trademark.

WPS

WPS (Wi-Fi Protected Setup) is a standard established by the Wi-Fi Alliance, which allows easy establishment of a wireless home network.

Yamaha technologies

CINEMA DSP (Digital Sound Field Processor)

Since the Dolby Surround and DTS systems were originally designed for use in movie theaters, their effect is best experienced in a theater that has many speakers designed for acoustic effects. Since home conditions (such as room size, wall material, and number of speakers) can differ so widely, it is inevitable that there are differences in the sound that you hear. Based on a wealth of actually measured data, CINEMA DSP, Yamaha's original DSP technology provides the audiovisual experience of a movie theater in your own home.

CINEMA DSP 3D

The actually measured sound field data contain the information of the height of the sound images. CINEMA DSP 3D mode achieves the reproduction of the accurate height of the sound images so that it creates the accurate and intensive 3D sound fields in a listening room.

Compressed Music Enhancer

The Compressed Music Enhancer feature compensates for missing harmonics in compression music formats (such as MP3). As a result, this technology provides improved performance for the overall sound system.

SILENT CINEMA

Yamaha has developed a natural, realistic sound effect DSP algorithm for headphones. Parameters for headphones have been set for each sound program, so that accurate representations of all the sound programs can be enjoyed on headphones.

Virtual CINEMA DSP

Virtual CINEMA DSP allows the system to virtually reproduce the sound field of the surround speakers with front left and right speakers. Even if the surround speakers are not connected, the unit creates the realistic sound field in a listening room.

Virtual CINEMA FRONT

Virtual CINEMA FRONT allows the system to virtually reproduce the sound field of the surround speakers with front surround speakers. Even if the surround speakers placed in the front, the unit creates the realistic sound field in a listening room.

Virtual Presence Speaker (VPS)

Virtual Presence Speaker allows the system to virtually reproduce the height of the 3D sound field without front presence speakers. Even if the front presence speakers are not connected, the unit creates the 3D sound field in your room.

Virtual Surround Back Speaker (VSBS)

Virtual Surround Back Speaker allows the system to virtually reproduce the sound field of the surround back speakers. Even if the surround back speakers are not connected, the unit adds a sense of depth to the rear sound filed of CINEMA DSP.

Supported devices and file formats

■ Supported devices

❑ *Bluetooth* device

- The unit supports *Bluetooth* devices that support A2DP or AVRCP.
- A *Bluetooth* device may not be detected by the unit or some feature may not be compatible, depending on the model.

❑ USB devices

- The unit supports USB mass storage class devices (e.g., flash memories or portable audio players) using FAT16 or FAT32 format.
- Do not connect devices other than USB mass storage class devices (such as USB chargers or USB hubs), PCs, card readers, an external HDD, etc.
- USB devices with encryption cannot be used.
- Some features may not be compatible, depending on the model or manufacturer of the USB storage device.

❑ iPod

> **Made for.**
>
> iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, iPhone 4s, iPhone 4, iPhone 3GS, iPhone 3G
> iPod touch (2nd, 3rd, 4th and 5th generation)
> iPod nano (2nd, 3rd, 4th, 5th, 6th and 7th generation)
> (as of July 2015)

- An iPod may not be detected by the unit or some features may not be compatible, depending on the model or software version of the iPod.

❑ AirPlay

AirPlay works with iPhone, iPad, and iPod touch with iOS 4.3.3 or later, Mac with OS X Mountain Lion or later, and Mac and PC with iTunes 10.2.2 or later.
(as of April 2015)

■ File formats

❑ USB/PC (NAS)

File	Sampling frequency (kHz)	Quantization bitrate (bit)	Bitrate	The number of channels	Gapless playback
WAV *	32/44.1/48/88.2/96/176.4/192	16/24	—	2	✔
MP3	32/44.1/48	—	8 to 320	2	—
WMA	32/44.1/48	—	8 to 320	2	—
MPEG-4 AAC	32/44.1/48	—	8 to 320	2	—
FLAC	32/44.1/48/88.2/96/176.4/192	16/24	—	2	✔
ALAC	32/44.1/48/88.2/96	16/24	—	2	✔
AIFF	32/44.1/48/88.2/96/176.4/192	16/24	—	2	✔
DSD	2.8 MHz/5.6 MHz	1	—	2	—

* Linear PCM format only

> **!**
>
> • To play back FLAC files stored on a PC or NAS, you need to install server software that supports sharing of FLAC files via DLNA on your PC or use a NAS that supports FLAC files.
>
> • Digital Rights Management (DRM) contents cannot be played back.

Video signal flow

Video signals input from a video device to the unit are output to a TV as shown below.

■ Video conversion table

💡
- You can select the resolution and the aspect ratio applied to HDMI-output video processing in "Video Mode" (p.110) in the "Setup" menu.
- The unit does not convert 480-line and 576-line video signals interchangeably.

	Resolution	HDMI out					
		480i/576i	480p/576p	720p	1080i	1080p	4K
HDMI in	480i/576i	→	→	→	→	→	→
	480p/576p		→	→	→	→	→
	720p			→	→	→	→
	1080i			→	→	→	→
	1080p/50, 60 Hz			→	→	→	→
	1080p/24 Hz					→	→
	4K						→
COMPONENT VIDEO in	480i/576i	→	→	→	→	→	→
	480p/576p						
	720p						
	1080i						
VIDEO in	480i/576i	→	→	→	→	→	→

→ : Available

Information on HDMI

HDMI Control

HDMI Control allows you to operate external devices via HDMI. If you connect a TV that supports HDMI Control to the unit with an HDMI cable, you can control the unit (such as power and volume) with TV remote control operations. You can also control playback devices (such as HDMI Control-compatible BD/DVD players) connected to the unit with an HDMI cable.

For details on connections, see "Connecting a TV" (p.22) and "Connecting video devices (such as BD/DVD players)" (p.23).

Operations available from the TV's remote control

- Standby synchronization
- Volume control including mute
- Switching to input audio from the TV when the TV input is switched to its built-in tuner
- Switching to input video/audio from the selected playback device
- Switching between audio output devices (the unit or TV speaker)

(Example)

HDMI Control   HDMI Control

Playback device   The unit turns off
also turns off   (standby)

Turn off the TV

Operations available from the unit's remote control

- Starting playback on the playback device and turning on the TV with a scene selection (p.47)
- Switching the TV input to display the on-screen menu (when ON SCREEN is pressed)
- Controlling the playback device (playback and menu operations) using the external device operation keys

(Example)

HDMI Control   HDMI Control

Playback starts   Turns on and displays
                      video from the playback
                      device

Press SCENE (BD/DVD)

To use HDMI Control, you need to perform the following HDMI Control link setup after connecting the TV and playback devices.

For details on settings and operating your TV, refer to the instruction manual for the TV.

⚠️

- This setup is required every time you add a new HDMI Control-compatible device to your system.

1 Turn on the unit, TV, and playback devices.

2 Configure the settings of the unit.
① Switch the TV input to display video from the unit.
② Press ON SCREEN.

ON SCREEN
Cursor keys
ENTER

③ Use the cursor keys to select "Setup" and press ENTER.

Setup

④ Use the cursor keys (◁/▷) to select "HDMI".

⑤ Use the cursor keys (△/▽) to select "HDMI Control" and press ENTER.

⑥ Use the cursor keys to select "On".

⑦ Press ON SCREEN.

3 **Enable HDMI Control on the TV and playback devices (such as HDMI Control-compatible BD/DVD players).**

4 **Turn off the main power of the TV and then turn off the unit and playback devices.**

5 **Turn on the unit and playback devices and then turn on the TV.**

6 **Switch the TV input to display the video from the unit.**

7 **Check the followings.**

On the unit: The input to which the playback device is connected is selected. If not, select the input source manually.

On the TV: The video from the playback device is displayed.

8 **Check that the unit is properly synchronized with the TV by turning off the TV or adjusting the TV volume with the TV remote control.**

!

• If HDMI Control does not work properly, try unplugging the TV in Step 2 and plugging in the TV again in Step 3. It may solve the problem. Also, HDMI Control may not work if the number of connected devices exceeds the limit. In this case, disable HDMI Control on the devices not in use.

• If the unit is not synchronized to the TV's power operations, check the priority of the audio output setting on the TV.

• We recommend using TV and playback devices from the same manufacturer so that HDMI Control works more effectively.

• We do not assure the operation of all HDMI Control-compatible devices.

Audio Return Channel (ARC)

ARC allows you to input TV audio to the unit with the HDMI cable which transmits video signal to the TV.

Check the following after the HDMI Control settings.

1 **Select a TV program with the TV remote control.**

2 **Check that the input source of the unit will be automatically switched to "AUDIO 1" and the TV audio will be played back on the unit.**

If you cannot hear the TV audio, check the following:

– "ARC" (p.111) in the "Setup" menu is set to "On".

– The HDMI cable is connected to the ARC-compatible HDMI jack (HDMI jack marked "ARC") on the TV.

Some HDMI jack on the TV is not compatible with ARC. For details, refer to the instruction manual for the TV.

!

• If the audio is interrupted while using ARC, set "ARC" (p.111) in the "Setup" menu to "Off" and use a digital optical cable to input TV audio to the unit (p.23).

• When using ARC, connect a TV with an HDMI cable that supports ARC.

☀

• "AUDIO 1" is set as TV audio input at the factory. If you have connected any external device to the AUDIO 1 jacks, use "TV Audio Input" (p.111) in the "Setup" menu to change the TV audio input assignment. To use the SCENE function (p.47), you also need to change the input assignment for SCENE (TV).

HDMI signal compatibility

Audio signals

Audio signal type	Audio signal format	Compatible media (example)
2ch Linear PCM	2ch, 32 to 192 kHz, 16/20/24 bit	CD, DVD-Video, DVD-Audio
Multichannel Linear PCM	8ch, 32 to 192 kHz, 16/20/24 bit	DVD-Audio, BD (Blu-ray disc), HD DVD
DSD	2 to 5.1ch, 2.8224 MHz, 1 bit	SACD
Bitstream	Dolby Digital, DTS	DVD-Video
Bitstream (High definition audio)	Dolby TrueHD, Dolby Digital Plus, DTS-HD Master Audio, DTS-HD High Resolution Audio, DTS Express	BD (Blu-ray disc), HD DVD

Video signals

The unit is compatible with the video signals of the following resolutions:

- VGA
- 480i/60 Hz
- 576i/50 Hz
- 480p/60 Hz
- 576p/50 Hz
- 720p/60 Hz, 50 Hz
- 1080i/60 Hz, 50 Hz
- 1080p/60 Hz, 50 Hz, 30 Hz, 25 Hz, 24 Hz
- 4K/60 Hz, 50Hz, 30 Hz, 25 Hz, 24 Hz

!

- When CPPM copy-protected DVD-Audio is played back, video/audio signals may not be output, depending on the type of the DVD player.
- The unit is not compatible with HDCP-incompatible HDMI or DVI devices. For details, refer to the instruction manual for each device.
- To decode audio bitstream signals on the unit, set the input source device appropriately so that the device outputs the bitstream audio signals directly (does not decode the bitstream signals on the playback device). For details, refer to the instruction manual for the playback device.

Reference diagram (rear panel)

(RX-AS710 Europe model)

💡

• The area around the video/audio output jacks is marked in white on the actual product to prevent improper connections.

Trademarks

DOLBY AUDIO

Manufactured under license from Dolby Laboratories. Dolby, Pro Logic, Surround EX and the double-D symbol are trademarks of Dolby Laboratories.

dts-HD Master Audio

For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Licensing Limited. DTS, DTS-HD, the Symbol, & DTS and the Symbol together are registered trademarks, and DTS-HD Master Audio is a trademark of DTS, Inc. © DTS, Inc. All Rights Reserved.

Made for iPod iPhone   AirPlay

"Made for iPod" and "Made for iPhone" mean that an electronic accessory has been designed to connect specifically to iPod or iPhone, respectively, and has been certified by the developer to meet Apple performance standards.
Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.
Please note that the use of this accessory with iPod or iPhone may affect wireless performance.

iTunes, AirPlay, iPhone, iPod, iPod nano, iPod touch, and Safari are trademarks of Apple Inc., registered in the U.S. and other countries.

App Store is a service mark of Apple Inc.

Bluetooth

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Yamaha Corporation is under license.

Bluetooth protocol stack (Blue SDK)

Copyright 1999-2014 OpenSynergy GmbH
All rights reserved. All unpublished rights reserved.

DAB Digital Audio Broadcasting   **DAB+** Digital Audio Broadcasting

(For RX-AS710D)
The unit supports DAB/DAB+ tuning.

Network

This receiver supports network connections.

HDMI
HIGH DEFINITION MULTIMEDIA INTERFACE

HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

x.v.Color™

"x.v.Color" is a trademark of Sony Corporation.

dlna CERTIFIED™

DLNA™ and DLNA CERTIFIED™ are trademarks or registered trademarks of Digital Living Network Alliance. All rights reserved. Unauthorized use is strictly prohibited.

Windows™

Windows is a registered trademark of Microsoft Corporation in the United States and other countries.

Internet Explorer, Windows Media Audio and Windows Media Player are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Android™   Google Play™

Android and Google Play are trademarks of Google Inc.

Blu-ray is a trademark of the Blu-ray Disc Association.

Wi-Fi CERTIFIED   Wi-Fi PROTECTED SETUP

The Wi-Fi CERTIFIED™ Logo is a certification mark of Wi-Fi Alliance®.
The Wi-Fi Protected Setup™ Identifier Mark is a certification mark of Wi-Fi Alliance®.

SILENT CINEMA ™

"SILENT CINEMA" is a trademark of Yamaha Corporation.

Google Noto Fonts

Copyright © 2012 Google Inc. All rights reserved.
Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License.
You may obtain a copy of the License at
　http://www.apache.org/licenses/LICENSE-2.0
Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and limitations under the License.

Explanations regarding GPL

This product utilizes GPL/LGPL open-source software in some sections. You have the right to obtain, duplicate, modify, and redistribute this open-source code only. For information on GPL/LGPL open source software, how to obtain it, and the GPL/LGPL license, refer to the Yamaha Corporation website (http://download.yamaha.com/sourcecodes/musiccast/).

Specifications

Input jacks

- Analog Audio
  Audio x 4 (AV 3–4, PHONO, AUX)

- Digital Audio (Supported frequencies: 32 kHz to 96 kHz)
  Optical x 2 (AUDIO 1, AV 1)
  Coaxial x 2 (AUDIO 2, AV 2)

- Video
  Composite x 2 (AV 3–4)
  Component x 2 (AV 1–2)

- HDMI Input
  HDMI x 6 (HDMI 1–6)

- Other
  USB x 1 (USB2.0)
  NETWORK x 1 (100Base-TX/10Base-T)

Output jacks

- Analog Audio
  - Speaker Out x 7 (FRONT L/R, CENTER, SURROUND L/R, EXTRA SP L/R[*])
    * Note: Assignment is possible [ZONE2, PRESENCE, SURROUND BACK, BI-AMP (FRONT L/R)]
  - Subwoofer Out x 2 (SUBWOOFER 1–2, mono)
  - ZONE2 OUT x 1
  - Headphone x 1

- HDMI Output
  HDMI OUT x 1

Other jacks

- YPAO MIC x 1

- REMOTE IN x 1

- REMOTE OUT x 1

- TRIGGER OUT x 1

HDMI

- HDMI features: Deep Color, "x.v.Color," Auto Lip Sync, ARC (Audio Return Channel), 3D, 4K Ultra HD

- Video Format (Repeater Mode)
  - VGA
  - 480i/60 Hz
  - 576i/50 Hz
  - 480p/60 Hz
  - 576p/50 Hz
  - 720p/60 Hz, 50 Hz
  - 1080i/60 Hz, 50 Hz
  - 1080p/60 Hz, 50 Hz, 30 Hz, 25 Hz, 24 Hz
  - 4K/60 Hz, 50Hz, 30 Hz, 25 Hz, 24 Hz

- Audio Format
  - Dolby TrueHD
  - Dolby Digital Plus
  - Dolby Digital
  - DTS-HD Master Audio
  - DTS-HD High Resolution Audio
  - DTS Express
  - DTS
  - DSD 2-ch to 6-ch
  - PCM 2-ch to 8-ch (Max. 192 kHz/24-bit)

- Content Protection: HDCP compatible (HDMI 1–3: HDCP 2.2 compatible)

- Link Function: CEC supported

TUNER

- Analog Tuner
  [RX-AS710 U.K. and Europe models]
  FM/AM with Radio Data System x 1 (TUNER)
  [RX-AS710 Other models]
  FM/AM x 1 (TUNER)
  [RX-AS710D U.K. and Europe models]
  DAB/FM with Radio Data System x 1 (TUNER)
  [RX-AS710D Australia model]
  DAB/FM x 1 (TUNER)

USB

- Capable of iPod, Mass Storage Class USB Memory

- Current Supply Capacity: 1 A

Bluetooth

- Sink Function
  Source Device to AVR (ex. Smartphone/Tablet)

- Capable of Play/Stop Operation from Sink Device

- Bluetooth Version ....Ver. 2.1+EDR

- Supported Profile ....A2DP, AVRCP

- Supported Codec ....SBC, AAC

- Wireless Output..Bluetooth Class 2

- Maximum Communication Distance ....10 m (33 ft)

Network

- PC Client Function

- Compatible with DLNA ver. 1.5

- AirPlay supported

- Internet Radio

- WiFi function
  - Capable of WPS by PIN Method and Push-Button-Method
  - Capable of sharing with iOS devices by wireless connection and USB connection
  - Capable of Direct Connection with Mobile Device
  - Available Security Method: WEP, WPA2-PSK (AES), Mixed Mode
  - Radio Frequency Band: 2.4GHz
  - Wireless Network Standard: IEEE 802.11 b/g/n

Compatible Decoding Formats

- Decoding Format
  - Dolby TrueHD, Dolby Digital Plus
  - Dolby Digital, Dolby Digital EX
  - DTS-HD Master Audio, DTS-HD High Resolution Audio, DTS Express
  - DTS 96/24, DTS-ES Matrix 6.1, DTS-ES Discrete 6.1
  - DTS Digital Surround
- Post Decoding Format
  - Dolby Pro Logic II Music, Dolby Pro Logic II Movie, Dolby Pro Logic II Game
  - Dolby Pro Logic IIx Music, Dolby Pro Logic IIx Movie, Dolby Pro Logic IIx Game
  - DTS Neo:6 Music, DTS Neo:6 Cinema

Audio Section

- Rated Output Power (2-channel driven)
  (20 Hz to 20 kHz, 0.07% THD, 8 Ω)
  Front L/R ....60 W+60 W
  (1 kHz, 0.9% THD, 8 Ω)
  Front L/R ....70 W+70 W
  Center .... 70 W
  Surround L/R..70 W+70 W
  Surround Back L/R ....70 W+70 W

- Rated Output Power (1-channel driven)
  (1 kHz, 0.9% THD, 8 Ω)
  Front L/R ....80 W/ch
  Center ....80 W/ch
  Surround L/R ....80 W/ch
  Surround Back L/R ....80 W/ch
  (1 kHz, 0.9% THD, 4 Ω)
  Front L/R ....130 W/ch

- Maximum Effective Output Power
  (1 kHz, 10% THD, 6 Ω)
  Front L/R ....125 W/ch
  Center..125 W/ch
  Surround L/R ....125 W/ch
  Surround Back L/R ....125 W/ch
  (1 kHz, 10% THD, 8 Ω)
  Front L/R ....100 W/ch
  Center..100 W/ch
  Surround L/R ....100 W/ch
  Surround Back L/R ....100 W/ch

- Dynamic Power (IHF)
  Front L/R (8/6/4/2 Ω).....................................90/110/140/160 W

- Damping Factor
  Front L/R, 1 kHz, 8 Ω... 100 or more

- Input Sensitivity / Input Impedance
  PHONO (1 kHz, 100 W/8 Ω)................................3.5 mV/47 kΩ
  AV 3 etc. (1 kHz, 100 W/8 Ω).............................. 200 mV/47 kΩ

- Maximum Input Signal
  PHONO (1 kHz, 0.1% THD) ....60 mV
  AV 3 etc. (1 kHz, 0.5% THD, Effect On) ....2.3 V

- Output Level / Output Impedance
  SUBWOOFER/PRE OUT... 1 V/1.2 kΩ
  ZONE2 OUT .... 200 mV/1.2 kΩ

- Headphone Impedance ....16 Ω or more

- Frequency Response
  AV 3 etc. to Front (10 Hz to 100 kHz)..........................+0/-3 dB

- RIAA Equalization Deviation
  PHONO ....0±0.5 dB

- Total Harmonic Distortion
  PHONO to Speaker Out (FRONT) (1 kHz, 10 V)
  .... 0.02% or less
  AV 3 etc. to Front (Pure Direct)
  (20 Hz to 20 kHz, 30 W, 8 Ω) .... 0.06% or less

- Signal to Noise Ratio (IHF-A Network)
  PHONO (Input Shorted 35 mV, Speaker Out [FRONT])
  .... 96 dB or more
  AV 3 etc. (Pure Direct) (Input 1 kΩ Shorted (2V), Speaker Out)
  .... 108 dB or more

- Residual Noise (IHF-A Network)
  Front L/R (Speaker Out).................................... 150 μV or less

- Channel Separation
  PHONO (Input Shorted, 1 kHz/10 kHz) ...60 dB/55 dB or more
  AV 3 etc. (Input 1 kΩ Shorted, 1 kHz/10 kHz)
  ....70 dB/50 dB or more

- Volume Control
  Range..MUTE, -80 dB to +16.5 dB
  Step...0.5 dB

- Tone Control Characteristics
  Bass Boost/Cut ....±6 dB/0.5 dB Step at 50 Hz
  Bass Turnover ....350 Hz
  Treble Boost/Cut.......................... ±6 dB/0.5 dB Step at 20 kHz
  Treble Turnover ....3.5 kHz

- Filter Characteristics
  (fc=40/60/80/90/100/110/120/160/200 Hz)
  H.P.F. (Front, Center, Surround, Surround Back).......12 dB/oct.
  L.P.F. (Subwoofer) ....24 dB/oct.

Video Section

- Video Signal Type ....NTSC/PAL/SECAM

- Video Signal Level
  Composite...1 Vp-p/75 Ω
  Component
  Y ....1 Vp-p/75 Ω
  Pb/Pr ....0.7 Vp-p/75 Ω

- Video Maximum Input Level........................... 1.5 Vp-p or more

FM Section

- Tuning Range

  [Canada model]...................................87.5 MHz to 107.9 MHz

  [Asia and General models]

  ....87.5/87.50 MHz to 108.0/108.00 MHz

  [Other models]................................87.50 MHz to 108.00 MHz

- 50 dB Quiet Sensitivity (IHF, 1 kHz, 100% MOD.)

  Mono... 3 μV (20.8 dBf)

- Signal to Noise Ratio (IHF)

  Mono...65 dB

  Stereo ....64 dB

- Harmonic Distortion (IHF, 1 kHz)

  Mono... 0.5%

  Stereo 0.6%

- Antenna Input ....75 Ω unbalanced

AM Section (RX-AS710)

- Tuning Range

  [Canada model].. 530 kHz to 1710 kHz

  [Asia and General models]...... 530/531 kHz to 1710/1611 kHz

  [Other models].. 531 kHz to 1611 kHz

DAB Section (RX-AS710D)

- Tuning Range ....174 MHz to 240 MHz (Band III)

- Support Audio Format

  ....MPEG 1 Layer II/MPEG 4 HE AAC v2 (AAC+)

- Antenna ....75 Ω unbalanced

General

- Power Supply

  [Canada model].. AC 120 V, 60 Hz

  [General model]............ AC 110 to 120/220 to 240 V, 50/60 Hz

  [Korea model].. AC 220 V, 60 Hz

  [Australia model] .... AC 240 V, 50 Hz

  [U.K. and Europe models]............................. AC 230 V, 50 Hz

  [Asia model] .... AC 220 to 240 V, 50/60 Hz

- Power Consumption

  [Canada model] ....190 W

  [Asia and General models] ....170 W

  [Other models] ....190 W

- Standby Power Consumption

  HDMI Control Off, Standby Through Off, Network Standby Off

  ....0.1 W

  HDMI Control On, Standby Through On (No Signals),

  Network Standby Off ....0.9 W

  HDMI Control Off, Standby Through Off, Network Standby On,

  Bluetooth Standby Off

  Wired ....2.0 W

  Wireless (Wi-Fi)..1.9 W

  Wireless Direct ....2.1 W

  HDMI Control Off, Standby Through Off, Network Standby On

  (Wired), Bluetooth Standby On ....1.8 W

  HDMI Control On, Standby Through On (No Signals),

  Network Standby On (Wireless Direct), Bluetooth Standby On

  ....2.4 W

- Maximum Power Consumption

  [Asia and General models] ....500 W

- Dimensions (W x H x D)

  .... 435 x 111 x 377 mm (17-1/8" × 4-3/8" × 14-7/8")
  * Including legs and protrusions

- Reference Dimensions (W x H x D) (with wireless antenna upright)

  .... 435 x 181 x 377 mm (17-1/8" × 7-1/8" × 14-7/8")
  * Including legs and protrusions

- Weight

  [RX-AS710]...9.2 kg (20.3 lbs)

  [RX-AS710D] ....9.2 kg (20.3 lbs)

* Specifications are subject to change without notice.

Index

YAMAHA