Web applications

Juan Luis Gorricho

Creating a web application

- New Project / Java Web / Web Application
- Choose project name / server / context path
- No frameworks
- Run the created web application project by default

Project scheme

- Web pages folder containing all html, jsp and auxiliary files to display web content.
- Configuration file:
  - web.xml
- Source packages folder containing all source code including Servlet files.

web.xml example

```
<?xml version="1.0" encoding="UTF-8"?>
<web-app version="2.5" xmlns="http://java.sun.com/xml/ns/javaee" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
    instance" xsi:schemaLocation="http://java.sun.com/xml/ns/javaee http://java.sun.com/xml/ns/javaee/web-
    app_2_5.xsd">

    <listener>
        <description>ServletContextListener</description>
        <listener-class>util.ContextListener</listener-class>
    </listener>

    <servlet>
        <servlet-name>controller</servlet-name>
        <servlet-class>web.ControllerServlet</servlet-class>
    </servlet>

    <servlet-mapping>
        <servlet-name>controller</servlet-name>
        <url-pattern>*.do</url-pattern>
    </servlet-mapping>

    <session-config>
        <session-timeout>
            10
        </session-timeout>
    </session-config>

    <welcome-file-list>
        <welcome-file>index.jsp</welcome-file>
    </welcome-file-list>

</web-app>
```

Creating our first Servlet

- Create a new package at source packages
- Create a new Servlet at the new package
- Allow add information to deployment descriptor
- Deploy the web application on the application server
- Check out the Servlet execution from an Internet browser typing the appropriate URL

Exercises

- Add a counter field and show how it is increased independently of the browser you access from
- Obtain the HttpSession and show its session ID on two different browsers, check out the time-out at web.xml
- Add a query string with a couple of parameters and retrieve them with the req.getParameter()