Distributed Systems and Internet technologies

PUSH FUNCTIONALITY

Juan Luis Gorricho

EXERCISE

- Modify the programming of **MessagesActivity** to avoid the polling strategy requesting new messages.
- You must use the WebSockets library as you learned in the interactive services unit.
- For the Android app. you have to use the library: tyrus-standalone-client-1.3.3, as summarized on the following slides.

PROGRAMMING WITH WEBSOCKETS

- Snippet of code for Android client:

```
private void connectToServer(){
    try {
      ClientManager client = ClientManager.createClient();

      client.connectToServer(new MyEndPoint(),
        ClientEndpointConfig.Builder.create().build(),
        URI.create("ws://10.0.2.2:8080/WhatsAppServer/push"));
    }
    catch (Exception e) {
      Log.e("WebSocketService", e.toString());
    }
  }
```

PROGRAMMING WITH WEBSOCKETS

```
public class MyEndPoint extends Endpoint {
    @Override
    public void onOpen(Session session, EndpointConfig EndpointConfig) {
        session.addMessageHandler(new MessageHandler.Whole<String>() {
        @Override
        public void onMessage(String message) { ... } });
        ...
    }
    @Override
    public void onError(Session session, Throwable t) {
      ...
    }
    @Override
    public void onClose(Session session, CloseReason closeReason) {
      ...
    }
  }
```