

LIROS D-Pro 01505

LIROS Heat-Stretch-System guarantees optimal breaking loads and stretch characteristics of this line. Excellent chafing resistance, light weight, and easy spliceability make this line irreplaceable in all sorts of applications on racing boats of any size. Perfect as a replacement for steel cabling in technical applications.

- *working stretch < 1%*
- *very high breaking load with small diameter and very low weight*
- *first choice for any application under extreme loads*
- *very spliceable*
- *highly UV stable and chafe resistant*
- *LIROS Heat-Stretch-System*

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
1	195	0,9	100
1,5	230	1,3	100
2	410	1,8	100
2,5	580	3,5	100
3	950	4,6	100
4	1300	7	100
5	2600	13	100
6	4300	23	100
8	5300	35	100
9	7500	49	100
10	9000	60	100
12	11900	72	100
14	14500	95	100
16	19200	131	100

Material Coated Dyneema® SK78

Construction 12-plaited, heat-set and coated


Dyneema®


LIROS HSS Heat Stretch System


LIROS LCS LIROS Coating System


Not certified for lifting loads and personal security!


Colours



010 Blue


059 Yellow


086 Green


171 Red


205 Silver


228 White


674 Deep Black



LIROS Speed Vision 01572

LIROS Speed Vision closes the gap between conventional polyester halyards and high-quality superior halyard-material of Dyneema. Due to the elaborate construction this rope is very handy and easy to splice. LIROS Speed Vision is perfectly suitable for the use as a low-priced halyard, control line or sheet.

- *working stretch < 3%*
- *robust and handy construction*
- *easy to splice*
- *LIROS Heat-Stretch-System*

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
8	1600	43	200
10	2500	65	200
12	3500	100	200

Dyneema®

LIROS HSS Heat Stretch System

Cover
Polyester

Construction
24-plaited

Core
Dyneema® / Polypropylene

Colours


229 White-Blue


303 White-Neon Orange


404 White-Silver