

David Alcázar Sánchez, DAW 2

Instalación Apache Tomcat en Linux

Vamos a instalar Apache-Tomcat en un sistema operativo Linux y a realizar su configuración inicial para poder desplegar aplicaciones a posteriori. Haremos la instalación de manera manual.

La versión más estable es Tomcat 9 con la versión JDK 8. Lo primero que haremos es ver si java está instalado y, en caso de que sí, ver qué versión tenemos:

```
(kali㉿kali)-[~]
$ java -version
openjdk version "21.0.8" 2025-07-15
OpenJDK Runtime Environment (build 21.0.8+9-Debian-1)
OpenJDK 64-Bit Server VM (build 21.0.8+9-Debian-1, mixed mode, sharing)

(kali㉿kali)-[~]
$ javac -version
Command 'javac' not found, did you mean:
  command 'javacc' from deb javacc
Try: sudo apt install <deb name>
```

He intentado hacerlo con java 8, pero no he conseguido instalarlo, así que lo voy a hacer con java 11:

```
(kali㉿kali)-[~]
$ javac -version
javac 11.0.25-ea
```

Seleccionamos las versiones que acabamos de instalar:

```
(kali㉿kali)-[~]
$ sudo update-alternatives --config java
There are 2 choices for the alternative java (providing /usr/bin/java).

  Selection    Path                                          Priority  Status
* 0            /usr/lib/jvm/java-21-openjdk-amd64/bin/java  2111     auto mode
  1            /usr/lib/jvm/java-11-openjdk-amd64/bin/java  1111     manual mode
  2            /usr/lib/jvm/java-21-openjdk-amd64/bin/java  2111     manual mode

Press <enter> to keep the current choice[*], or type selection number: 1
update-alternatives: using /usr/lib/jvm/java-11-openjdk-amd64/bin/java to provide /usr/bin/java (java) in manual mode

(kali㉿kali)-[~]
$ sudo update-alternatives --config javac
There is 1 choice for the alternative javac (providing /usr/bin/javac).

  Selection    Path                                          Priority  Status
* 0            /usr/lib/jvm/java-11-openjdk-amd64/bin/javac  1111     auto mode
  1            /usr/lib/jvm/java-11-openjdk-amd64/bin/javac  1111     manual mode

Press <enter> to keep the current choice[*], or type selection number: 1
```

Creamos un directorio para guardar Tomcat 9 en el directorio opt y posteriormente descargamos Tomcat 9 (versión estable):

```

kali@kali:~$ sudo mkdir /opt/tomcat9
kali@kali:~$ cd /tmp
kali@kali:~/tmp$ wget https://archive.apache.org/dist/tomcat/tomcat-9/v9.0.83/bin/apache-tomcat-9.0.83.tar.gz
--2026-02-01 15:55:27-- https://archive.apache.org/dist/tomcat/tomcat-9/v9.0.83/bin/apache-tomcat-9.0.83.tar.gz
Resolving archive.apache.org (archive.apache.org)... 65.108.204.189, 2a01:499:1a:a084::2
Connecting to archive.apache.org (archive.apache.org)|65.108.204.189|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 11801705 (11M) [application/x-gzip]
Saving to: 'apache-tomcat-9.0.83.tar.gz'

apache-tomcat-9.0.83.tar.gz                               100%[=====] 11.25M  16.0MB/s   in 0.7s

2026-02-01 15:55:28 (16.0 MB/s) - 'apache-tomcat-9.0.83.tar.gz' saved [11801705/11801705]

kali@kali:~/tmp$

```

Descomprimos Tomcat en /opt/tomcat9:

```
(kali㉿kali)-[/tmp]
$ sudo tar -xzf apache-tomcat-9.0.83.tar.gz -C /opt/tomcat9 --strip-components=1
(kali㉿kali)-[/tmp]
$
```

Damos permisos de ejecución a Tomcat:

```
(kali㉿kali)-[/tmp]
$ ls -l /opt/tomcat9/bin
ls: cannot open directory '/opt/tomcat9/bin': Permission denied

(kali㉿kali)-[/tmp]
$ sudo /opt/tomcat9/bin/startup.sh
Using CATALINA_BASE:   /opt/tomcat9
Using CATALINA_HOME:   /opt/tomcat9
Using CATALINA_TMPDIR: /opt/tomcat9/temp
Using JRE_HOME:        /usr
Using CLASSPATH:        /opt/tomcat9/bin/bootstrap.jar:/opt/tomcat9/bin/tomcat-juli.jar
Using CATALINA_OPTS:
Tomcat started.

(kali㉿kali)-[/tmp]
$
```

Comprobamos que Apache-Tomcat está ejecutando correctamente accediendo a “<http://localhost:8080>”:

The image shows a Kali Linux terminal window on the left and a web browser window on the right. The terminal window displays the output of the command `dpkg-query -f='${Package} ${Version} ${Architecture}\n'`, showing that Tomcat 9.0.83 has been successfully installed. The web browser window shows the Apache Tomcat 9.0.83 welcome page, which includes a congratulatory message, recommended reading links, a developer quick start section, and links to documentation and getting help.

Por último, comprobamos que no hay errores en la configuración de Tomcat con el siguiente comando:

```
(kali㉿kali)-[/tmp]
$ /opt/tomcat9/bin/configtest.sh
zsh: permission denied: /opt/tomcat9/bin/configtest.sh

(kali㉿kali)-[/tmp]
$ sudo /opt/tomcat9/bin/startup.sh
Using CATALINA_BASE:   /opt/tomcat9
Using CATALINA_HOME:   /opt/tomcat9
Using CATALINA_TMPDIR: /opt/tomcat9/temp
Using JRE_HOME:        /usr
Using CLASSPATH:       /opt/tomcat9/bin/bootstrap.jar:/opt/tomcat9/bin/tomcat-juli.jar
Using CATALINA_OPTS:
Tomcat started.
```

En mi caso tengo que usar sudo para ejecutar los scripts de Tomcat porque la instalación la he realizado en el directorio /opt, que pertenece al usuario root.