9

11 12 13

14 15 18

20 21 22

19

23 24

25

26 27 28 29 30 31 32

33 34 35 36 37

38 41 42 43

44

45

46

47

48

49

50

51

53

54

55

56

57

58

ABSTRACT

Anonymous Author(s)

Towards system development processes for robotic applications

The number of robotic applications that are being developed is increasing exponentially both in industry and academia. However, those applications do not have common system development process, what leads to the necessity of starting projects from scratch for most of the robot developers.

In this PhD project, we aim to produce a set of processes and architectural models and methods to be used by developers in order to improve reusability and modularity in robotic applications. In order to validate our results we make use of a set of service robots that will be employed for different case studies.

ACM Reference format:

Anonymous Author(s). 2018. Towards system development processes for robotic applications . In Proceedings of 40th International Conference on Software Engineering, Gothenburg, Sweden, May 27-June 3, 2018 (ICSE 2018),

DOI: 10.1145/nnnnnnn.nnnnnnn

1 INTRODUCTION

Service robots are invading human lives. They are increasingly used in environments such as houses, airports, hospitals, and offices for performing navigation, transportation, and manipulation tasks. The World Robotic Survey [4] estimated 35 million indoor service robots to be sold by 2018, accumulating a sales value of \$12 billion since 2015. The global sales of household and personal robots is expected to grow by 23.5% per year [7]. This increase is accompanied with huge progress in robot technology, especially in image processing, planning, control, and collaboration. Software engineering is key to sustaining this new technology.

A robot typically performs specialized tasks; however, some tasks are highly complex and require a team of robots, whose capabilities (e.g., perception, manipulation, and actuation) are coordinated and supervised. Such teams also need to adapt to changes, such as of the environment, of the desired tasks, or of the robot (e.g., hardware failures). These demands drive the complexity of robot control software relying on appropriate software architectures. To tackle this complexity, we need to rethink design processes [5] by properly managing system integration and raising the abstraction levels, addressing qualities like evolvability [6], configurability [3], scalability, power consumption, and dependability.

Figure 1 depicts an overview of the work being developed for this project. There is an evident difference between two different approaches in robotic practices, that is when the robotic application

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

ICSE 2018, Gothenburg, Sweden

© 2018 ACM. 978-x-xxxx-xxxx-x/YY/MM...\$15.00

DOI: 10.1145/nnnnnnn.nnnnnnn




Figure 1: Overview of this PhD project.

puts to work an unique robot or a team of them. This division also splits the research schedule of this project in terms of time, as explained in the following. The "Single robot" subdivision of the overview represents the work already achieved and work in progress to be achieved in the near future. This subdivision contains the block of the Software Architecture, which is at the same time contained in the Software Platform block. The last mentioned block represents an additional layer for integrating the tools developed by researchers. Our platform must also be able to be customized by means of configuration facilities, which provide the required tools for configuring the basic platform both at design and run-time.

On the other hand, the future work that will be tackled once the single robot contents are already addresses is group in the subdivision of "Multi robot". The main expected outcome of this subdivision is to achieve the orchestration of a deployed team of potentially heterogeneous robots. In order to do so, issues as Emergent properties [1, 2] and selecting the most suitable Collaborative

Research Questions. In this project we divide robot applications between single-robot and multi-robot approaches. For this reason, we state the following research questions:

- RQ1 Which are the software engineering practices for single and multi-robotic systems?
- RQ2 Which are the applicable strategies to manage an heterogeneous robotic application?

Contributions.

Organization. In Section ??, we introduce different works with a similar scope and position our research. Section ?? describes the research approach of the current work. Then, the next sections present the current state of our work in Section ??, future work and planned directions in Section ?? and it concludes with Section ?? with final remarks.

REFERENCES

[1] Francesco Luca De Angelis and Giovanna Di Marzo Serugendo. 2015. Logic Fragments: A Coordination Model Based on Logic Inference. Springer International Publishing, Cham, 35–48. https://doi.org/10.1007/978-3-319-19282-6_3

- [2] Francesco Luca De Angelis and Giovanna Di Marzo Serugendo. 2016. Logic Fragments: Coordinating Entities with Logic Programs. Springer International Publishing, Cham, 589–604. https://doi.org/10.1007/978-3-319-47166-2_41
- [3] Nadia Gamez and Lidia Fuentes. 2013. Architectural evolution of FamiWare using cardinality-based feature models. *Information and Software Technology* 55, 3 (2013), 563–580.
- [4] IFR. 2016. World Robotic Survey. https://ifr.org/ifr-press-releases/news/world-robotics-survey-service-robots-are-conquering-the-world-. (2016).
- [5] E. A. Lee. 2008. Cyber Physical Systems: Design Challenges. In ISORC.
- [6] Jennifer Pérez, Nour Ali, Jose A. Carsí, Isidro Ramos, Bárbara Álvarez, Pedro Sánchez, and Juan A. Pastor. 2008. Integrating aspects in software architectures: PRISMA applied to robotic tele-operated systems. *Information and Software Technology* 50, 9 (2008), 969 990. https://doi.org/10.1016/j.infsof.2007.08.007
- [7] Colleen Sheng. 2016. Global Domestic Service Robots Market âĂŞ-Size and Trends to 2020. https://www.alliedmarketresearch.com/ robotics-technology-market. (2016).