

Review: "A Combined Approach to Improving Image Quality Using Bicubic Interpolation and a Lanczos Filter"

D. R. Bodashevskiy, K. R. Potapova, L. B. Vovk, K. O. Radchenko, M. V. Nalyvaichuk (2023) · Tavriiskiy Naukovyi Visnyk, No. 5 · Igor Sikorsky Kyiv Polytechnic Institute

1. Introduction

The paper proposes a hybrid method of image upscaling and compares it with classical interpolation. Its starting point is practical: bicubic interpolation and the Lanczos filter are both reliable at moderate magnification but lose detail at larger factors, while the neural approaches that handle this well demand resources many projects cannot spare. The authors look for a middle path, maximising PSNR at an acceptable processing time.

2. Methodology

The hybrid is defined plainly: the image is upscaled twice, once with bicubic interpolation and once with the Lanczos filter, and the output is the pixel-wise arithmetic mean of the two results. Evaluation follows the degrade-and-restore protocol. A photograph of 5184×3456 pixels is reduced by factors of 2, 4 and 8; each reduced version is upscaled back to the original resolution by nearest neighbour, bilinear and bicubic interpolation and by the hybrid; and every reconstruction is compared with the original through PSNR, with execution time recorded alongside.

3. Results

The hybrid attains the highest PSNR at every scale factor: 42.12, 40.30 and 36.83 dB, against 41.95, 40.28 and 36.73 dB for bicubic interpolation, with bilinear and nearest neighbour further behind. The ranking is consistent, but the margins are narrow — 0.17, 0.02 and 0.10 dB — while the processing time grows from 0.15 s to 0.94 s, roughly sixfold.

4. Key Insights

Insight 1. Averaging the outputs of two linear resampling filters is the same as applying one filter whose kernel is the average of the two. The hybrid is therefore not a new class of method but a new linear kernel, sitting between bicubic and Lanczos in frequency response, which explains why its result falls between them rather than beyond them. Reasoning about an operation through its kernel rather than its implementation is a habit worth carrying into any work with signals.

Insight 2. The conclusion rests on one metric and one image. PSNR measures mean squared error, while the properties the paper argues for — edge sharpness and preserved detail — are the ones it does not capture, so a structural measure could reorder the methods. I take from this the habit of confirming a claim with a second metric grounded in a different principle.

Insight 3. Quality and cost belong in one judgement. Six times the computation for a tenth of a decibel is a trade few applications would accept, and reporting the two figures in separate tables lets a marginal gain read as a clear win.

5. Conclusion

The contribution is a clear and reproducible comparison of classical upscaling methods with a simple hybrid, described in enough detail to repeat. Its weakness is the evidentiary base: one photograph, one metric and no measure of variability, supporting differences of hundredths of a decibel. Standard benchmark sets, a structural similarity measure reported next to PSNR, and an explicit statement of the filter used to downscale the inputs would make the claimed advantage convincing.