WIMA MKP-X2

Metallized Polypropylene (PP) RFI-Capacitors Class X2 PCM 7.5 mm to 27.5 mm

Special Features

- **Reliable self-healing**
- **High degree of interference suppression due to good attenuation and low ESR**
- **According to RoHS 2011/65/EU**

Typical Applications

Class X2 RFI applications to meet EMC regulations

- **Capacitors connected to the mains between phase and neutral or phase conductors**
- **Installation category II in accordance with IEC 60664, pulse peak voltage ⩽ 2.5 kV**

Construction

Dielectric:
Polypropylene (PP) film
Capacitor electrodes:
Vacuum-deposited
Internal construction:



Encapsulation:
Solvent-resistant, flame-retardant plastic case with epoxy resin seal, UL 94 V-0
Terminations:
Tinned wire.
Marking:
Colour: Red. Marking: Black.

Electrical Data

Capacitance range: 1000 pF to 2.2 µF
Rated voltage: 275 VAC
Continuous DC voltage* (general guide): ⩽ 560 V
Capacitance tolerances: ±20%, ±10%
Operating temperature range: –55° C to +105° C
Climatic test category: 55/105/56/B in accordance with IEC
Insulation resistance at +20° C:
C ⩽ 0.33 µF: ⩾ 15 x 10^3 MΩ
C > 0.33 µF: ⩾ 5000 sec (MΩ x µF)
Measuring voltage: 100 V/1 min.
Dissipation factors at + 20° C: tan δ

at f	C ⩽ 0.1 µF	0.1 µF < C ⩽ 1.0 µF	C > 1.0 µF
1 kHz	⩽ 10 x 10^{-4}	⩽ 20 x 10^{-4}	⩽ 30 x 10^{-4}
10 kHz	⩽ 20 x 10^{-4}	⩽ 60 x 10^{-4}	–
100 kHz	⩽ 90 x 10^{-4}	–	–

Test specifications:
In accordance with IEC 60384-14
Maximum pulse rise time:
100 V/µsec for pulses equal to a voltage amplitude with $\sqrt{2}$ x 275 VAC = 390 V according to IEC 60384-14
Test voltage:
C ⩽ 1.0 µF: 2260 VDC, 2 sec.
C > 1.0 µF: 1800 VDC, 2 sec.
Reliability:
Operational life > 300 000 hours
Failure rate < 2 fit (0.5 x U_r and 40° C)

Approvals:

Country	Authority	Specification	Symbol	Approval-No.
Germany	VDE	IEC 60384-14/3	10	40003472
USA/Canada	UL	UL 1414 (250 VAC) C 22.2 No. 1 (250 VAC)	c US 250~	E 134915
USA/Canada	UL	UL 1283 (305 VAC) C 22.2 No. 8 (305 VAC)	c US 305~	E 100438

Mechanical Tests

Pull test on pins: 10 N in direction of pins according to IEC 60068-2-21
Vibration: 6 hours at 10 ... 2000 Hz and 0.75 mm displacement amplitude or 10 g in accordance with IEC 60068-2-6
Low air density: 1kPa = 10 mbar in accordance with IEC 60068-2-13
Bump test: 4000 bumps at 390 m/sec^2 in accordance with IEC 60068-2-29

* If safety-approved EMI suppression capacitors are operated with a DC voltage being above the specified AC voltage rating the given approvals are no longer valid (IEC 60384-14).

Furthermore the permissible pulse rise time du/dt ($F_{max.}$) will be subject to a reduction according to

$F_{max.} = F_r \times \sqrt{2} \times UAC / UDC$

if the DC operating voltage UDC is higher than $\sqrt{2}$ x UAC

Packing

Available taped and reeled up to and including case size 15 x 26 x 31.5 / PCM 27.5 mm.

Detailed taping information and graphs at the end of the catalogue.

For further details and graphs please refer to Technical Information.

Continuation

General Data

Capacitance	275 VAC*					305 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
1000 pF	4	9	10	**7.5**	MKX21W11002C00_____					
1500 „	4	9	10	**7.5**	MKX21W11502C00_____					
2200 „	4	9	10	**7.5**	MKX21W12202C00_____					
3300 „	4	9	10	**7.5**	MKX21W13302C00_____					
4700 „	4	9	10	**7.5**	MKX21W14702C00_____					
6800 „	4	9	10	**7.5**	MKX21W16802C00_____					
0.01 µF	4	9	10	**7.5**	MKX21W21002C00_____					
	5	11	13	10	MKX21W21003F00_____					
0.015 „	4	9	10	**7.5**	MKX21W21502C00_____	5	11	13	10	MKX2AW21503F00_____
	5	11	13	10	MKX21W21503F00_____					
0.022 „	4	9	10	**7.5**	MKX21W22202C00_____	5	11	13	10	MKX2AW22203F00_____
	5	11	13	10	MKX21W22203F00_____					
0.033 „	5	10.5	10.3	**7.5**	MKX21W23302E00_____	5	10.5	10.3	**7.5**	MKX2AW23302E00_____
	5	11	13	10	MKX21W23303F00_____	5	11	13	10	MKX2AW23303F00_____
0.047 „	5.7	12.5	10.3	**7.5**	MKX21W24702F00_____	5.7	12.5	10.3	**7.5**	MKX2AW24702F00_____
	6	12.5	13	10	MKX21W24703H00_____	6	12.5	13	10	MKX2AW24703H00_____
0.068 „	6	12.5	13	10	MKX21W26803H00_____	6	12.5	13	10	MKX2AW26803H00_____
0.1 µF	8	12	13	10	MKX21W31003I00_____	8	12	13	10	MKX2AW31003I00_____
	5	11	18	15	MKX21W31004B00_____	5	11	18	15	MKX2AW31004B00_____
	6	12.5	18	15	MKX21W31004C00_____	6	12.5	18	15	MKX2AW31004C00_____
0.15 „	6	12.5	18	15	MKX21W31504C00_____	6	12.5	18	15	MKX2AW31504C00_____
	7	14	18	15	MKX21W31504D00_____	7	14	18	15	MKX2AW31504D00_____
0.22 „	9	14	18	15	MKX21W32204H00_____	8	15	18	15	MKX2AW32204F00_____
	8	15	18	15	MKX21W32204F00_____					
0.33 „	11	14	18	15	MKX21W33304M00_____	9	16	18	15	MKX2AW33304J00_____
	9	16	18	15	MKX21W33304J00_____					
0.47 „	8.5	18.5	26.5	22.5	MKX21W34705F00_____	8.5	18.5	26.5	22.5	MKX2AW34705F00_____
	10.5	19	26.5	22.5	MKX21W34705G00_____	10.5	19	26.5	22.5	MKX2AW34705G00_____
0.68 „	10.5	19	26.5	22.5	MKX21W36805G00_____	10.5	19	26.5	22.5	MKX2AW36805G00_____
	11	21	26.5	22.5	MKX21W36805I00_____	11	21	26.5	22.5	MKX2AW36805I00_____
1.0 µF	11	21	26.5	22.5	MKX21W41005I00_____	11	21	26.5	22.5	MKX2AW41005I00_____
	13	24	31.5	27.5	MKX21W41006D00_____	13	24	31.5	27.5	MKX2AW41006D00_____
1.5 „	15	26	31.5	27.5	MKX21W41506F00_____	15	26	31.5	27.5	MKX2AW41506F00_____
2.2 „	17	29	31.5	27.5	MKX21W42206G00_____					

* f = 50/60 Hz

** PCM = Printed circuit module = pin spacing

Certified for 250 VAC in accordance with UL/CSA.

Dims. in mm.



d = 0.6 ø if PCM < 15
d = 0.8 ø if PCM ≥ 15

Part number completion:	
Tolerance:	20 % = M
	10 % = K
Packing:	bulk = S
Pin length:	6-2 = SD

Taped version see page 144.

Recommendation for Processing and Application of Through-Hole Capacitors

Soldering Process

Internal temperature of the capacitor must be kept as follows:

Polyester:	preheating:	$T_{max.} \leqslant 125°$ C
	soldering:	$T_{max.} \leqslant 135°$ C
Polypropylene:	preheating:	$T_{max.} \leqslant 100°$ C
	soldering:	$T_{max.} \leqslant 110°$ C

Single wave soldering
Soldering bath temperature: T < 260° C
Dwell time: t < 5 sec

Double wave soldering
Soldering bath temperature: T < 260° C
Dwell time: Σt < 5 sec

Due to different soldering processes and heat requirements the graphs are to be regarded as a recommendation only.

Wave soldering



Typical temperature/time graph for double wave soldering

WIMA Quality and Environmental Philosophy

ISO 9001:2008 Certification

ISO 9001:2008 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2008 of our factories by the VDE inspectorate certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

WIMA WPCS

The WIMA Process Control System (WPCS) is a quality surveillance and optimization system developed by WIMA. WPCS is a major part of the quality-oriented WIMA production. Points of application of WPCS during production process:

- **incoming material inspection**
- **metallization**
- **film inspection**
- **schoopage**
- **pre-healing**
- **pin attachment**
- **cast resin preparation/ encapsulation**
- **100% final inspection**
- **AQL check**

WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

- **Lead**
- **PCB**
- **CFC**
- **Hydrocarbon chloride**
- **Chromium 6+**
- **PBB/PBDE**
- **Arsenic**
- **Cadmium**
- **Mercury**
- **etc.**

We merely use pure, recyclable materials for packing our components, such as:

- **carton**
- **cardboard**
- **adhesive tape made of paper**
- **polystyrene**

We almost completely refrain from using packing materials such as:

- **foamed polystyrene (Styropor®)**
- **adhesive tapes made of plastic**
- **metal clips**

RoHS Compliance

According to the RoHS Directive 2011/65/EU certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refraind from using such substances since years already.

Tape for lead-free WIMA capacitors

DIN EN ISO 14001:2004

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2004 to optimize the production processes with regard to energy and resources.

11.13

Typical Dimensions for Taping Configuration



Diagram 1:
PCM 2.5/5/7.5mm



Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5*mm
*PCM 27.5 taping possible with two feed holes between components

Designation	Symbol	Dimensions for Radial Taping						
		PCM 2.5 taping	**PCM 5 taping**	**PCM 7.5 taping**	**PCM 10 taping***	**PCM 15 taping***	**PCM 22.5 taping**	**PCM 27.5 taping**
Carrier tape width	W	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5
Hold-down tape width	W_0	6.0 for hot-sealing adhesive tape	6.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape
Hole position	W_1	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5
Hold-down tape position	W_2	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.
Feed hole diameter	D_0	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2
Pitch of component	P	12.7 ±1.0	12.7 ±1.0	12.7 ±1.0	25.4 ±1.0	25.4 ±1.0	38.1 ±1.5	*38.1 ±1.5 or 50.8 ±1.5
Feed hole pitch	P_0	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch
Feed hole centre to pin	P_1	5.1 ±0.5	3.85 ±0.7	2.6 ±0.7	7.7 ±0.7	5.2 ±0.7	7.8 ±0.7	5.3 ±0.7
Hole centre to component centre	P_2	6.35 ±1.3	6.35 ±1.3	6.35 ±1.3	12.7 ±1.3	12.7 ±1.3	19.05 ±1.3	19.05 ±1.3
Feed hole centre to bottom edge of the component	H	16.5 ±0.3 18.5 ±0.5	16.5 ±0.3 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5
Feed hole centre to top edge of the component	H_1	$H+H_{component} < H_1$ 32.25 max.	$H+H_{component} < H_1$ 32.25 max.	$H+H_{component} < H_1$ 24.5 to 31.5	$H+H_{component} < H_1$ 25.0 to 31.5	$H+H_{component} < H_1$ 26.0 to 37.0	$H+H_{component} < H_1$ 30.0 to 43.0	$H+H_{component} < H_1$ 35.0 to 45.0
Pin spacing at upper edge of carrier tape	F	2.5 ±0.5	5.0 $^{+0.8}_{-0.2}$	7.5 ±0.8	10.0 ±0.8	15 ±0.8	22.5 ±0.8	27.5 ±0.8
Pin diameter	d	0.4 ±0.05	0.5 ±0.05	•0.5 ±0.05 or 0.6 $^{+0.06}_{-0.05}$	•0.5 ±0.05 or 0.6 $^{+0.06}_{-0.05}$	0.8 $^{+0.08}_{-0.05}$	0.8 $^{+0.08}_{-0.05}$	0.8 $^{+0.08}_{-0.05}$
Component alignment	Δh	± 2.0 max.	± 2.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.
Total tape thickness	t	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2
Package (see also page 145)		ROLL/AMMO		AMMO				
		REEL ø 360 max. ø 30 ±1 B 52 ±2 / 58 ±2 } depending on comp. dimensions		REEL ø 360 max. ø 30 ±1 B 52 ±2 / 58 ±2 / 66 ±2 or REEL ø 500 max. ø 25 ±1 B 54 ±2 / 60 ±2 / 68 ±2 } depending on PCM and component dimensions				
Unit		see details page 146.						

Dims in mm.

• Diameter of pins see General Data.

Please clarify customer-specific deviations with the manufacturer.

* PCM 10 and PCM 15 can be crimped to PCM 7.5.
Position of components according to PCM 7.5 (sketch 1). P_0 = 12.7 or 15.0 is possible

11.13

Types of Tape Packaging of Capacitors for Automatic Radial Insertion

ROLL Packaging



AMMO Packaging



REEL Packaging



BAR CODE (Labelling)

Labelling of package units in plain text and with alphanumerical Bar Code

Scanner decoding of

- WIMA supplier number
- Customer's P/O number
- Customer's part number
- WIMA confirmation number
- WIMA part number
- Lot number
- Date code
- Quantity

In addition part description of

– article
– capacitance value
– rated voltage
– dimensions
– capacitance tolerance
– packing

as well as gross weight and customer's name are indicated in plain text.



BARCODE „Code 39"

Packing Quantities for Capacitors with Radial Pins in PCM 2.5 mm to 22.5 mm

PCM	Size				pcs. per packing unit											
					bulk	ROLL		REEL				AMMO				
								ø 360		ø 500		340 × 340		490 × 370		
						H16.5	H18.5	H16.5	H18.5	H16.5	H18.5	H16.5	H18.5	H16.5	H18.5	
	W	H	L	Codes	S	N	O	F	I	H	J	A	C	B	D	
2.5 mm	2.5	7	4.6	**0B**	5000	2200		2500		–		2800		–		
	3	7.5	4.6	**0C**	5000	2000		2300		–		2300		–		
	3.8	8.5	4.6	**0D**	5000	1500		1800		–		1800		–		
	4.6	9	4.6	**0E**	5000	1200		1500		–		1500		–		
	5.5	10	4.6	**0F**	5000	900		1200		–		1200		–		
5 mm	2.5	6.5	7.2	**1A**	5000	2200		2500		–		2800		–		
	3	7.5	7.2	**1B**	5000	2000		2300		–		2300		–		
	3.5	8.5	7.2	**1C**	5000	1600		2000		–		2000		–		
	4.5	6	7.2	**1D**	6000	1300		1500		–		1500		–		
	4.5	9.5	7.2	**1E**	4000	1300		1500		–		1500		–		
	5	10	7.2	**1F**	3500	1100		1400		–		1400		–		
	5.5	7	7.2	**1G**	4000	1000		1200		–		1200		–		
	5.5	11.5	7.2	**1H**	2500	1000		1200		–		1200		–		
	6.5	8	7.2	**1I**	2500	800		1000		–		1000		–		
	7.2	8.5	7.2	**1J**	2500	700		1000		–		1000		–		
	7.2	13	7.2	**1K**	2000	700		950		–		1000		–		
	8.5	10	7.2	**1L**	2000	600		800		–		800		–		
	8.5	14	7.2	**1M**	1500	600		800		–		800		–		
	11	16	7.2	**1N**	1000	500		600		–		400		–		
7.5 mm	2.5	7	10	**2A**	5000	–		2500		4400		2500		–		
	3	8.5	10	**2B**	5000	–		2200		4300		2300		4150		
	4	9	10	**2C**	4000	–		1700		3200		1700		3100		
	4.5	9.5	10.3	**2D**	3500	–		1500		2900		1400		2800		
	5	10.5	10.3	**2E**	3000	–		1300		2500		1300		–		
	5.7	12.5	10.3	**2F**	2000	–		1000		2200		1100		–		
	7.2	12.5	10.3	**2G**	1500	–		900		1800		1000		–		
10 mm	3	9	13	**3A**	3000	–		1100		2200		–		1900		
	4	8.5	13.5	**FA**	3000	–		900		1600		–		1450		
	4	9	13	**3C**	3000	–		900		1600		–		1450		
	4	9.5	13	**3D**	3000	–		900		1600		–		1400		
	5	10	13.5	**FB**	2000	–		700		1300		–		1200		
	5	11	13	**3F**	3000	–		700		1300		–		1200		
	6	12	13	**3G**	2400	–		550		1100		–		1000		
	6	12.5	13	**3H**	2400	–		550		1100		–		1000		
	8	12	13	**3I**	2000	–		400		800		–		740		
15 mm	5	11	18	**4B**	2400	–		600		1200		–		1150		
	5	13	19	**FC**	1000	–		600		1200		–		1200		
	6	12.5	18	**4C**	2000	–		500		1000		–		1000		
	6	14	19	**FD**	1000	–		500		1000		–		1000		
	7	14	18	**4D**	1600	–		450		900		–		850		
	7	15	19	**FE**	1000	–		450		900		–		850		
	8	15	18	**4F**	1200	–		400		800		–		740		
	8	17	19	**FF**	500	–		400		800		–		740		
	9	14	18	**4H**	1200	–		350		700		–		650		
	9	16	18	**4J**	900	–		350		700		–		650		
	10	18	19	**FG**	500	–		300		650		–		590		
	11	14	18	**4M**	1000	–		300		600		–		540		
22.5 mm	5	14	26.5	**5A**	1200	–		–		800		–		770		
	6	15	26.5	**5B**	1000	–		–		700		–		640		
	7	16.5	26.5	**5D**	760	–		–		600		–		550		
	8	20	28	**FH**	500	–		–		500		–		480		
	8.5	18.5	26.5	**5F**	500	–		–		480		–		450		
	10	22	28	**FI**	540*	–		–		420		–		380		
	10.5	19	26.5	**5G**	680*	–		–		400		–		360		
	10.5	20.5	26.5	**5H**	680*	–		–		400		–		360		
	11	21	26.5	**5I**	680*	–		–		380		–		350		
	12	24	28	**FJ**	450*	–		–		350		–		310		

* TPS (Tray-Packing-System). Plate versions may have different packing units. Samples and pre-production needs on request.

Moulded versions.

Packing Quantities for Capacitors with Radial Pins in PCM 27.5 mm to 52.5 mm

PCM	Size				bulk	pcs. per packing unit									
						ROLL		REEL				AMMO			
								ø 360		ø 500		340 × 340		490 × 370	
						H16.5	H18.5	H16.5	H18.5	H16.5	H18.5	H16.5	H18.5	H16.5	H18.5
	W	H	L	Codes	S	N	O	F	I	H	J	A	C	B	D
27.5 mm	9	19	31.5	**6A**	640*	–		–		460/340*		–		420	
	11	21	31.5	**6B**	544*	–		–		380/280*		–		350	
	13	24	31.5	**6D**	448*	–		–		300		–		290	
	13	25	33	**FK**	336*	–		–		–		–		–	
	15	26	31.5	**6F**	384*	–		–		270		–		250	
	15	26	33	**FL**	288*	–		–		–		–		–	
	17	29	31.5	**6G**	176*	–		–		–		–		–	
	17	34.5	31.5	**6I**	176*	–		–		–		–		–	
	20	32	33	**FM**	216*	–		–		–		–		–	
	20	39.5	31.5	**6J**	144*	–		–		–		–		–	
37.5 mm	9	19	41.5	**7A**	480*	–		–		–		–		–	
	11	22	41.5	**7B**	408*	–		–		–		–		–	
	13	24	41.5	**7C**	252*	–		–		–		–		–	
	15	26	41.5	**7D**	144*	–		–		–		–		–	
	17	29	41.5	**7E**	132*	–		–		–		–		–	
	19	32	41.5	**7F**	108*	–		–		–		–		–	
	20	39.5	41.5	**7G**	108*	–		–		–		–		–	
	24	45.5	41.5	**7H**	84*	–		–		–		–		–	
	31	46	41.5	**7I**	72*	–		–		–		–		–	
	35	50	41.5	**7J**	35*	–		–		–		–		–	
	40	55	41.5	**7K**	28*	–		–		–		–		–	
48.5 mm	19	31	56	**8D**	50*	–		–		–		–		–	
	23	34	56	**8E**	72*	–		–		–		–		–	
	27	37.5	56	**8H**	60*	–		–		–		–		–	
	33	48	56	**8J**	48*	–		–		–		–		–	
	37	54	56	**8L**	25*	–		–		–		–		–	
52.5 mm	35	50	57	**9F**	25*	–		–		–		–		–	
	45	55	57	**9H**	20*	–		–		–		–		–	
	45	65	57	**9J**	20*	–		–		–		–		–	

* for 2-inch transport pitches.

* TPS (Tray-Packing-System). Plate versions may have different packing units. Samples and pre-production needs on request.

Moulded versions.

WIMA Part Number System

A WIMA part number consists of 18 digits and is composed as follows:

Field 1 - 4: Type description
Field 5 - 6: Rated voltage
Field 7 - 10: Capacitance
Field 11 - 12: Size and PCM
Field 13 - 14: Version code (e.g. Snubber versions)
Field 15: Capacitance tolerance
Field 16: Packing
Field 17 - 18: Pin length (untaped)

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
M	**K**	**S**	**2**	**C**	**0**	**2**	**1**	**0**	**0**	**1**	**A**	**0**	**0**	**M**	**S**	**S**	**D**
MKS 2				63 VDC		0.01 µF				2.5 x 6.5 x 7.2		-		20%	bulk	6 -2	

Type description:

SMD-PET	= SMDT
SMD-PPS	= SMDI
FKP 02	= FKP0
MKS 02	= MKS0
FKS 2	= FKS2
FKP 2	= FKP2
MKS 2	= MKS2
MKP 2	= MKP2
FKS 3	= FKS3
FKP 3	= FKP3
MKS 4	= MKS4
MKP 4	= MKP4
MKP 10	= MKP1
FKP 4	= FKP4
FKP 1	= FKP1
MKP-X2	= MKX2
MKP-X2 R	= MKXR
MKP-Y2	= MKY2
MP 3-X2	= MPX2
MP 3-X1	= MPX1
MP 3-Y2	= MPY2
MP 3R-Y2	= MPRY
Snubber MKP	= SNMP
Snubber FKP	= SNFP
GTO MKP	= GTOM
DC-LINK MKP 3	= DCP3
DC-LINK MKP 4	= DCP4
DC-LINK MKP 4S	= DCPS
DC-LINK MKP 5	= DCP5
DC-LINK MKP 6	= DCP6
DC-LINK HC	= DCH_
DC-LINK HY	= DCHY
SuperCap S	= SCSS
SuperCap H	= SCSH
SuperCap M	= SCM_

Rated voltage:

2.7 VDC	= AI
12 VDC	= AN
16 VDC	= A0
32 VDC	= AH
48 VDC	= AQ
50 VDC	= B0
56 VDC	= B1
63 VDC	= C0
64 VDC	= CA
100 VDC	= D0
125 VDC	= DA
250 VDC	= F0
400 VDC	= G0
450 VDC	= H0
600 VDC	= I0
630 VDC	= J0
700 VDC	= K0
800 VDC	= L0
850 VDC	= M0
900 VDC	= N0
1000 VDC	= O1
1100 VDC	= P0
1200 VDC	= Q0
1250 VDC	= R0
1500 VDC	= S0
1600 VDC	= T0
2000 VDC	= U0
2500 VDC	= V0
3000 VDC	= W0
4000 VDC	= X0
6000 VDC	= Y0
250 VAC	= 0W
275 VAC	= 1W
300 VAC	= 2W
400 VAC	= 3W
440 VAC	= 4W
500 VAC	= 5W

Capacitance:

22 pF	= 0022
47 pF	= 0047
100 pF	= 0100
150 pF	= 0150
220 pF	= 0220
330 pF	= 0330
470 pF	= 0470
680 pF	= 0680
1000 pF	= 1100
1500 pF	= 1150
2200 pF	= 1220
3300 pF	= 1330
4700 pF	= 1470
6800 pF	= 1680
0.01 µF	= 2100
0.022 µF	= 2220
0.047 µF	= 2470
0.1 µF	= 3100
0.22 µF	= 3220
0.47 µF	= 3470
1 µF	= 4100
2.2 µF	= 4220
4.7 µF	= 4470
10 µF	= 5100
22 µF	= 5220
47 µF	= 5470
100 µF	= 6100
220 µF	= 6220
1 F	= A010
2.5 F	= A025
50 F	= A500
100 F	= B100
125 F	= B125
500 F	= B500
1200 F	= C120
...	

Size:

4.8 x 3.3 x 3 Size 1812	= KA
4.8 x 3.3 x 4 Size 1812	= KB
5.7 x 5.1 x 3.5 Size 2220	= QA
5.7 x 5.1 x 4.5 Size 2220	= QB
7.2 x 6.1 x 3 Size 2824	= TA
7.2 x 6.1 x 5 Size 2824	= TB
10.2 x 7.6 x 5 Size 4030	= VA
12.7 x 10.2 x 6 Size 5040	= XA
15.3 x 13.7 x 7 Size 6054	= YA
2.5 x 7 x 4.6 PCM 2.5	= 0B
3 x 7.5 x 4.6 PCM 2.5	= 0C
2.5 x 6.5 x 7.2 PCM 5	= 1A
3 x 7.5 x 7.2 PCM 5	= 1B
2.5 x 7 x 10 PCM 7.5	= 2A
3 x 8.5 x 10 PCM 7.5	= 2B
3 x 9 x 13 PCM 10	= 3A
4 x 9 x 13 PCM 10	= 3C
5 x 11 x 18 PCM 15	= 4B
6 x 12.5 x 18 PCM 15	= 4C
5 x 14 x 26.5 PCM 22.5	= 5A
6 x 15 x 26.5 PCM 22.5	= 5B
9 x 19 x 31.5 PCM 27.5	= 6A
11 x 21 x 31.5 PCM 27.5	= 6B
9 x 19 x 41.5 PCM 37.5	= 7A
11 x 22 x 41.5 PCM 37.5	= 7B
94 x 49 x 182 DCH_	= H0
94 x 77 x 182 DCH_	= H1
...	

Version code:

Standard	= 00
Version A1	= 1A
Version A1.1.1	= 1B
Version A2	= 2A
...	

Tolerance:

20%	= M
10%	= K
5%	= J
2.5%	= H
1%	= E
...	

Packing:

AMMO H16.5 340 x 340	= A
AMMO H16.5 490 x 370	= B
AMMO H18.5 340 x 340	= C
AMMO H18.5 490 x 370	= D
REEL H16.5 360	= F
REEL H16.5 500	= H
REEL H18.5 360	= I
REEL H18.5 500	= J
ROLL H16.5	= N
ROLL H18.5	= O
BLISTER W12 180	= P
BLISTER W12 330	= Q
BLISTER W16 330	= R
BLISTER W24 330	= T
Bulk/TPS Standard	= S
...	

Pin length (untaped)

3.5 ±0.5	= C9
6 -2	= SD
16 ±1	= P1
...	

The data on this page is not complete and serves only to explain the part number system. Part number information is listed on the pages of the respective WIMA range.

11.13