```
.venv) (base) Sergio@SERHIIs-MacBook-Pro homework_buggy % pytest -v
tests/test_iot_manual_scenarios.py
============================================ test session starts
============================================
platform darwin -- Python 3.9.12, pytest-8.4.2, pluggy-1.6.0 -- /Users/Sergio/
Documents/QA_Embedded/Gate/Task7/HomeWork/homework_buggy/.venv/bin/
python
cachedir: .pytest_cache
metadata: {'Python': '3.9.12', 'Platform': 'macOS-10.16-x86_64-i386-64bit',
'Packages': {'pytest': '8.4.2','pluggy': '1.6.0'}, 'Plugins': {'metadata': '3.1.1',
'html': '4.2.0'}, 'JAVA_HOME': '/Library/Java/JavaVirtualMachines/jdk-21.jdk/
Contents/Home'}
rootdir: /Users/Sergio/Documents/QA_Embedded/Gate/Task7/HomeWork/
homework_buggy
plugins: metadata-3.1.1, html-4.2.0
collected 22 items

tests/test_iot_manual_scenarios.py::test_tc18_buffer_cmd_vs_status[5]
PASSED                      [  4%]
tests/test_iot_manual_scenarios.py::test_tc18_buffer_cmd_vs_status[8]
PASSED                      [  9%]
tests/test_iot_manual_scenarios.py::test_tc18_buffer_cmd_vs_status[12]
PASSED                     [ 13%]
tests/test_iot_manual_scenarios.py::test_tc19_double_net_down PASSED
[ 18%]
tests/test_iot_manual_scenarios.py::test_tc20_net_up_when_connected
PASSED                       [ 22%]
tests/test_iot_manual_scenarios.py::test_tc21_net_down_mid_flush FAILED
[ 27%]
tests/test_iot_manual_scenarios.py::test_tc22_send_during_flush FAILED
[ 31%]
tests/test_iot_manual_scenarios.py::test_tc23_rapid_toggle PASSED
[ 36%]
tests/test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[-5] FAILED
[ 40%]
tests/test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[1.5] FAILED
[ 45%]
tests/test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[abc]
FAILED                      [ 50%]
tests/test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[10 20]
PASSED                      [ 54%]
tests/
test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[99999999999]
PASSED                [ 59%]
tests/test_iot_manual_scenarios.py::test_tc25_messy_input[] PASSED
[ 63%]
tests/test_iot_manual_scenarios.py::test_tc25_messy_input[   ] PASSED
```

```
[ 68%]
tests/test_iot_manual_scenarios.py::test_tc25_messy_input[status ] PASSED
[ 72%]
tests/test_iot_manual_scenarios.py::test_tc25_messy_input[ STATUS] PASSED
[ 77%]
tests/test_iot_manual_scenarios.py::test_tc25_messy_input[RESET  STATS]
PASSED                    [ 81%]
tests/
test_iot_manual_scenarios.py::test_tc25_messy_input[AAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAA] PASSED [ 86%]
tests/test_iot_manual_scenarios.py::test_tc25_messy_input[NET\tDOWN]
PASSED                     [ 90%]
tests/test_iot_manual_scenarios.py::test_tc26_reset_stats_keeps_buffer
PASSED                     [ 95%]
tests/test_iot_manual_scenarios.py::test_tc27_long_outage SKIPPED (set
RUN_SLOW=1 to run the lon...) [100%]

================================================== FAILURES
==================================================
_____________________________________ test_tc21_net_down_mid_flush
_____________________________________

node = <test_iot_manual_scenarios.Node object at 0x7fd55c72ce20>

    def test_tc21_net_down_mid_flush(node):
        ids = node.offline_send(8); mark = len(node.log)
        node.raw(b"NET UP\nNET DOWN\n"); node.pump(1.5)
        node.cmd("NET UP", 8)
        pub = published(node.log[mark:])
        dup = {i for i in pub if pub.count(i) > 1}
>       assert not dup, f"published more than once: {sorted(dup)}"
E       AssertionError: published more than once: [26, 27, 28, 29, 30, 31, 32, 33]
E       assert not {26, 27, 28, 29, 30, 31, ...}

tests/test_iot_manual_scenarios.py:126: AssertionError
_____________________________________ test_tc22_send_during_flush
_____________________________________

node = <test_iot_manual_scenarios.Node object at 0x7fd55c72ce20>

    def test_tc22_send_during_flush(node):
        ids = node.offline_send(8); mark = len(node.log)
```

```
        node.raw(b"NET UP\nSEND\n"); node.pump(6)
        pub = published(node.log[mark:])
        dup = {i for i in pub if pub.count(i) > 1}
>       assert not dup, f"published more than once: {sorted(dup)}"
E       AssertionError: published more than once: [34, 35, 36, 37, 38, 39, 40, 41]
E       assert not {34, 35, 36, 37, 38, 39, ...}

tests/test_iot_manual_scenarios.py:137: AssertionError
_____________________________________________ test_tc24_stress_invalid_args[-5]
_____________________________________________

node = <test_iot_manual_scenarios.Node object at 0x7fd55c72ce20>, arg =
'-5'

    @pytest.mark.parametrize("arg", ["-5", "1.5", "abc", "10 20",
"99999999999"])
    def test_tc24_stress_invalid_args(node, arg):
        out = node.cmd(f"STRESS {arg}", 4)
        assert not rebooted(out), "node rebooted"
        st = node.status(); assert st["heap"] > 0
        if arg in ("-5", "1.5", "abc"):
>           assert any("ERROR" in l for _, l in out) or st["sent"] == 0, \
              f"invalid number accepted: sent={st['sent']}"
E           AssertionError: invalid number accepted: sent=1
E           assert (False or 1 == 0)
E            +  where False = any(<generator object
test_tc24_stress_invalid_args.<locals>.<genexpr> at 0x7fd55c89ca50>)

tests/test_iot_manual_scenarios.py:160: AssertionError
_____________________________________________ test_tc24_stress_invalid_args[1.5]
_____________________________________________

node = <test_iot_manual_scenarios.Node object at 0x7fd55c72ce20>, arg =
'1.5'

    @pytest.mark.parametrize("arg", ["-5", "1.5", "abc", "10 20",
"99999999999"])
    def test_tc24_stress_invalid_args(node, arg):
        out = node.cmd(f"STRESS {arg}", 4)
        assert not rebooted(out), "node rebooted"
        st = node.status(); assert st["heap"] > 0
        if arg in ("-5", "1.5", "abc"):
>           assert any("ERROR" in l for _, l in out) or st["sent"] == 0, \
              f"invalid number accepted: sent={st['sent']}"
E           AssertionError: invalid number accepted: sent=1
E           assert (False or 1 == 0)
E            +  where False = any(<generator object
```

```
test_tc24_stress_invalid_args.<locals>.<genexpr> at 0x7fd55c9210b0>)

tests/test_iot_manual_scenarios.py:160: AssertionError
_____ test_tc24_stress_invalid_args[abc] _____

node = <test_iot_manual_scenarios.Node object at 0x7fd55c72ce20>, arg =
'abc'

    @pytest.mark.parametrize("arg", ["-5", "1.5", "abc", "10 20",
"99999999999"])
    def test_tc24_stress_invalid_args(node, arg):
        out = node.cmd(f"STRESS {arg}", 4)
        assert not rebooted(out), "node rebooted"
        st = node.status(); assert st["heap"] > 0
        if arg in ("-5", "1.5", "abc"):
>           assert any("ERROR" in l for _, l in out) or st["sent"] == 0, \
              f"invalid number accepted: sent={st['sent']}"
E           AssertionError: invalid number accepted: sent=1
E           assert (False or 1 == 0)
E            +  where False = any(<generator object
test_tc24_stress_invalid_args.<locals>.<genexpr> at 0x7fd55c89c820>)

tests/test_iot_manual_scenarios.py:160: AssertionError
========== short test summary info ==========
FAILED tests/test_iot_manual_scenarios.py::test_tc21_net_down_mid_flush -
AssertionError: published more than once: [26, 27, 28, 29, 30, 31, 32, 33]
FAILED tests/test_iot_manual_scenarios.py::test_tc22_send_during_flush -
AssertionError: published more than once: [34, 35, 36, 37, 38, 39, 40, 41]
FAILED tests/test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[-5]
- AssertionError: invalid number accepted: sent=1
FAILED tests/test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[1.5]
- AssertionError: invalid number accepted: sent=1
FAILED tests/
test_iot_manual_scenarios.py::test_tc24_stress_invalid_args[abc] -
AssertionError: invalid number accepted: sent=1
========== 5 failed, 16 passed, 1 skipped in 264.84s
(0:04:24) ==========
(.venv) (base) Sergio@SERHIIs-MacBook-Pro homework_buggy %
```