COMENERGY
Heat Exchanger & Units

CONDENSING UNITS

Bitzer Compressor Units





- Bitzer semi-hermetic piston compressor
- Wide application range (high/medium/low temperature)
- Premium domestic refrigeration components
- Customizable accessories
- Multi-refrigerant compatibility (with oil change)

Bitzer Series-M/H Temp

Model	Compressor			Condenser					S (Inch)	D (Inch)	Overall Dimension L*W*H(mm	Power Supply
	Model	HP	Capacity (w)	Fan Oty*Dia(mm)	Air Flow (m3/h)	Power of (w)	Poles	KW				
CEM9HP	4CES-9Y	10	18520	4x350	4x3110	4x145						
CEM10HP	4VES-10Y	10	19180	4x350	4x3110	4x145	4	23.7	1-1/8"	5/8"	1270x850x970	
CEM12HP	4TES-12Y	12	23300	4x400	4x3900	4x190	4	28.9	1-3/8"	5/8"	1270x850x1170	
CEM15HP	4PES-15Y	15	26350	4x400	4x3900	4x190	4	35.5	1-5/8"	7/8"	1270x850x1420	
CEM20HP	4NES-20Y	20	31700	4x500	4x6900	4x380	4	51.3	1-5/8"	7/8"	1270x950x1370	*220V* 3PH/60HZ
CEM25HP	4HE-25Y	25	41900	3x500	3x6900	3x380	4	65.7	2-1/8"	7/8"	2060x890x1970	
CEM30HP	4GE-30Y	30	48000	3x550	3x8500	3x650	4	76.8	2-1/8"	7/8"	2360x890x1970	
CEM35HP	4FE-35Y	35	58000	3x630	3x13000	3x860	4	87.9	2-1/8"	7/8"	2660x890x1970	
CEM40HP	6GE-40Y	40	69900	3x630	3x13000	3x860	4	109.8	2-1/8"	7/8"	2660x1110x2100	
CEM50HP	6FE-50Y	50	85100	3x710	3x15600	3x1100	4	148.5	2-1/8"	1-1/8"	2860x1110x2100	

Data sheet based on: E.T -5° C/ C.T 50°C/Return air temperature 20'C/R404A