

更改单No.	更改单和序号ECN	更改单 MARK	描述 DESCRIPTION	日期 DATE	签字 APP	已审核 CHK
2017/07/15	2017/07/15	2017/07/15	新图	2017/07/15	2017/07/15	2017/07/15
1	ESN_111332	①	螺母安装改为卡套安装	2012.5.30	2012.5.30	2012.5.30
13	ESN_124269	⑤	三通阀连接方式更改: 三通阀增加侧角; 更改为参考尺寸	2012.7.14	2012.7.14	2012.7.14

技术要求

- ① 1. 线性和角度尺寸的未注公差按GB/T1804-c级。
- 2. 装配前O形圈表面涂适量锂基润滑脂, 钢球表面均匀涂上防锈油。
- 3. 密封性能: 介质: 空气 测试压力: 100kPa 工作温度: 25℃±5℃
泄漏量: 1.5mL/min (max)
- 4. 表面喷漆防腐蚀处理, 漆料为黑色底漆。
- 5. 各接头采用堵头防护。
- 6. 手动抽油泵每完成一个工作冲程, 最小排量为0.35L。
- ② 7. 手动抽油泵总成重量为2.3kg。
- 8. 手动抽油泵客户零件号: 13057165; 泵体客户零件号: 13057166; 三通阀客户零件号: 13057167。

Technic Specification

- ③ 1. Undefined size tolerance according to GB/T 1804-c.
- 2. The O-ring shall be spreaded with lithium base grease before installing, the steel ball shall be spreaded with preservation oil.
- 3. The sealing performance:
Medium: Air Test pressure: 100kPa
Test temperature: 25℃±5℃ Leakage: 1.5mL/min (max)
- 4. The surface shall be treat with anticorrosion black of priming.
- 5. All tie-ins of the valve must be protected with plug .
- 6. The minimum delivery of the hand pump is 0.35L at each strokes.
- ④ 7. The weight of assenbly is 2.3kg.
- 8. Assembly customer part number: 13057165; pump customer part numeber: 13057166; valve customer part numeber: 13057167.

序号No.	代号 Code	名称 Name	数量 Quantity	材料 Material	备注 Remark
14		O形圈 O-ring	1	80X3.55G GB/T 3452.1	
13	3841115-12	圆柱销 pin	1	45 GB/T 699	
12	HK0607C-01	缸体 pump body	1	ADC12 JIS H5302	
11	HK0607C-05	缸体支板 support board	1	t3 Q235A	
10	3841115-02	曲柄轴 brace shaft	1	Q235A GB/T 699	
9	HK0607C-02	缸盖 cover	1	ADC12 JIS H5032	
8	3841115-03	短连杆板套 short pole cover	1	Q235A GB/T 699	
7	3841115-10	长连杆板套 long pole cover	2	Q235A GB/T 699	
6		开口挡圈 peg ring	2	GB/T 896 6	
5		活塞销 piston pin	1	45 GB/T 119	
4		I六角螺母 nut	4	M6 GB/T 6170	
3		弹簧垫圈 spring gasket	4	GB/T 93 6	
2		平垫圈 plane gasket 6x12x1	6	GB/T 95	
1	3841115-16	六角头螺栓 bolt	4	M6X22 GB/T 5782	
14		O形圈 O-ring	1	80X3.55G GB/T 3452.1	
13	3841115-12	圆柱销 pin	1	45 GB/T 699	
12	HK0607C-01	缸体 pump body	1	ADC12 JIS H5302	
11	HK0607C-05	缸体支板 support board	1	t3 Q235A	
10	3841115-02	曲柄轴 brace shaft	1	Q235A GB/T 699	
9	HK0607C-02	缸盖 cover	1	ADC12 JIS H5032	
8	3841115-03	短连杆板套 short pole cover	1	Q235A GB/T 699	
7	3841115-10	长连杆板套 long pole cover	2	Q235A GB/T 699	
6		开口挡圈 peg ring	2	GB/T 896 6	
5		活塞销 piston pin	1	45 GB/T 119	
4		I六角螺母 nut	4	M6 GB/T 6170	
3		弹簧垫圈 spring gasket	4	GB/T 93 6	
2		平垫圈 plane gasket 6x12x1	6	GB/T 95	
1	3841115-16	六角头螺栓 bolt	4	M6X22 GB/T 5782	

序号No.	代号 Code	名称 Name	数量 Quantity	材料 Material	备注 Remark
31	13057166	泵体 pump	1		
30		O形圈 O-ring	1	15.6X1.78 NBR-70 parker2-016	
29		螺母 nut	1	M20X1.5 06Cr19Ni10 GB/T 6173	
28	HK0607C-03	接头 tie-in	1	06Cr19Ni10	
27	SYB3936316-22	螺纹堵盖 screw stopper	2	PE	
26	13057167	三通阀 valve	1		
25		I六角螺母 nut	1	M12 GB/T 6170	
24	3841115.2	摇臂部件 rocker shaft	1		
23		O形圈 O-ring	2	14X2.65 G GB/T 3452.1	
22	3841115-11	摇臂轴 rocker shaft	1	Q235A GB/T 699	
21		开口销 pin	1	2X10 GB/T 91	
20		销轴 pin shaft	1	6X24 GB/T 882	
19		钢球 steel ball	2	SØ19 GB/T 308	
18	3841115.1	活塞部件 piston	1		
17	3841115-08	Y形密封圈 Y sealing ring	4	橡胶复合 RP (黑色)	
16	HK0607C-04	缸体夹板 splint	1	t3 Q235A	
15	3841115-06	连杆板 connection board	2	t3 Q235A GB/T 699	

