

Projective geometry and Panoramic image

Image Processing, Analysis and Classification

Sergio Marín Sánchez

Tuesday 2nd April, 2024



POLITÉCNICA

UNIVERSIDAD
POLÍTÉCNICA
DE MADRID



Table of Contents

- ▶ Introduction
- ▶ Perspective
- ▶ Homographies
- ▶ Panoramic image
- ▶ Use case: Dental images
- ▶ References



Introduction

3D world → 2D content

An image is just a flat representation of the 3D world.



Even though we lose the depth component the image maintain the perspective.



Introduction

3D world → 2D content

Images are useful to store memories, but also we can extract information from them. For instance, we may want to know how tall is this bottle.





Introduction

3D world → 2D content

We need to represent the images in such a way that both humans and computers are able to deal with them. Thus matrix representation of images is defined. We can define an image $I \in M_{h,w} (\mathbb{Z}^n)$ as:

$$I = \begin{pmatrix} p_{1,1} & p_{1,2} & \dots & p_{1,w} \\ p_{2,1} & p_{2,2} & \dots & p_{2,w} \\ \vdots & \vdots & \ddots & \vdots \\ p_{h,1} & p_{h,2} & \dots & p_{h,w} \end{pmatrix}_{h \times w}$$

Where each p_{ij} is a vector in \mathbb{Z}^n , n varies depending on the number of color channels.



Introduction

3D world → 2D content

Here we can see how the image is codified as we have defined before:







Table of Contents

- ▶ Introduction
- ▶ Perspective
- ▶ Homographies
- ▶ Panoramic image
- ▶ Use case: Dental images
- ▶ References

Perspective

We can use angles to represent the perspective of a point in the image if we know the focal distance f of the camera.



$$\alpha = \arctan \frac{u}{f}$$



Perspective

Use case: Locate the place from where a photo was taken

We can use this information to locate where a photo was taken.







Perspective

Use case: Locate the place from where a photo was taken


We only need to use some trigonometry.





Perspective

Use case: Locate the place from where a photo was taken



Perspective

Use case: Locate the place from where a photo was taken

The precision is quite accurate even though the methods are not so precise.







Table of Contents

- ▶ Introduction
- ▶ Perspective
- ▶ Homographies
- ▶ Panoramic image
- ▶ Use case: Dental images
- ▶ References

Homographies

“The homograph is a mapping between two perspective images of a planar surface in a scene” [1]





Homographies

An homography is just a matrix that convert some points into others.

$$\lambda \begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} H_{1,1} & H_{1,2} & H_{1,3} \\ H_{2,1} & H_{2,2} & H_{2,3} \\ H_{3,1} & H_{3,2} & H_{3,3} \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$



Homographies

Use case: How far was this shot?

By using homographies we can remove the perspective from an image, and after that we can measure in the image.





Homographies

Use case: How far was this shot?

By using homographies we can remove the perspective from an image.






Homographies

Use case: How far was this shot?


We can establish measurements in the image.



Homographies

Use case: How far was this shot?

Using trigonometry, as before, we can estimate the shot distance.



Homographies

Use case: How far was this shot?

Using trigonometry, as before, we can estimate the shot distance.





Table of Contents

- ▶ Introduction
- ▶ Perspective
- ▶ Homographies
- ▶ Panoramic image
- ▶ Use case: Dental images
- ▶ References

Panoramic image

Panoramic image reconstruction uses the techniques explained before.

Rotating camera, arbitrary world





Figure: Panoramic image reconstruction [2]



Panoramic image

The key points have to be automatically calculated.




Figure: Stereo images and related disparity map [1]



Panoramic image

We can use techniques explain during the lessons (Key point feature extraction), such as SIFT, FAST, etc.




Figure: Key points from practical exercise



Panoramic image

If the key points are good enough selected, the results could be quite accurate.




(a) Original images before the mosaic [1]



(b) Two images stitched together [1]

Panoramic image

This technique can also be used in the reconstruction of non-planar images. [3]





Panoramic image

Another example with a 360° image. [4]






Table of Contents

- ▶ Introduction
- ▶ Perspective
- ▶ Homographies
- ▶ Panoramic image
- ▶ Use case: Dental images
- ▶ References

Use case: Dental images

Problem description

In the context of dental health, as teeth are bones, the dentist needs to take X-rays.




Figure: Some teeth hide others [5]

Use case: Dental images

Proposed solution


Yun *et al.* [5] came up with a solution based on the contents of this subject.



Use case: Dental images

Thresholding

They use histograms to establish a threshold value.






Use case: Dental images

Morphological processing

With the threshold calculated before, they managed to create a mask.






Use case: Dental images

Morphological processing

With the threshold calculated before, they managed to create a mask.



Also perform Gaussian filtering



Use case: Dental images

Arch approximation

Dental arch approximation using the following formula:


$$I_0(i,j) = S \cdot \log \left(\sum_{n=1}^N e^{\frac{P_n(i,j)}{S}} \right)$$



Use case: Dental images

Arch approximation


Dental arch approximations are quite accurate:



Use case: Dental images

Panoramic images generation

Using homographies and the arch estimation in each tooth, they are able to reconstruct a panoramic image of the whole teething.






Use case: Dental images

Applications

Using techniques similar as the ones seen during the lessons, dentists can obtain automatic tooth identification.



Use case: Dental images

Known problems

One future path of this method is dealing with mental objects.






Table of Contents

- ▶ Introduction
- ▶ Perspective
- ▶ Homographies
- ▶ Panoramic image
- ▶ Use case: Dental images
- ▶ References



References

- [1] D. Gledhill, G. Y. Tian, D. Taylor, and D. Clarke, "Panoramic imaging—a review," *Computers & Graphics*, vol. 27, no. 3, pp. 435–445, Jun. 1, 2003. DOI: 10.1016/S0097-8493(03)00038-4.
- [2] "OpenCV: Basic concepts of the homography explained with code," (), [Online]. Available: https://docs.opencv.org/4.x/d9/dab/tutorial_homography.html (visited on 04/01/2024).
- [3] H. Yong, J. Huang, W. Xiang, X. Hua, and L. Zhang, "Panoramic background image generation for PTZ cameras," *IEEE Transactions on Image Processing*, vol. 28, no. 7, pp. 3162–3176, Jul. 2019. DOI: 10.1109/TIP.2019.2894940.



References

- [4] Y. Duan, C. Han, X. Tao, B. Geng, Y. Du, and J. Lu, "Panoramic image generation: From 2-d sketch to spherical image," *IEEE Journal of Selected Topics in Signal Processing*, vol. 14, no. 1, pp. 194–208, Jan. 2020, Conference Name: IEEE Journal of Selected Topics in Signal Processing. DOI: [10.1109/JSTSP.2020.2968772](https://doi.org/10.1109/JSTSP.2020.2968772).
- [5] Z. Yun, S. Yang, E. Huang, L. Zhao, W. Yang, and Q. Feng, "Automatic reconstruction method for high-contrast panoramic image from dental cone-beam CT data," *Computer Methods and Programs in Biomedicine*, vol. 175, pp. 205–214, Jul. 1, 2019. DOI: [10.1016/j.cmpb.2019.04.024](https://doi.org/10.1016/j.cmpb.2019.04.024).
- [6] Q. Yan, Y. Xu, X. Yang, and T. Nguyen, "HEASK: Robust homography estimation based on appearance similarity and keypoint correspondences," *Pattern Recognition*, vol. 47, no. 1, pp. 368–387, Jan. 2014. DOI: [10.1016/j.patcog.2013.05.007](https://doi.org/10.1016/j.patcog.2013.05.007).



References

- [7] K. Mahajan, M. Sharma, and L. Vig, “Character keypoint-based homography estimation in scanned documents for efficient information extraction,” in *2019 International Conference on Document Analysis and Recognition Workshops (ICDARW)*, Sydney, Australia: IEEE, Sep. 2019, pp. 25–30. DOI: [10.1109/ICDARW.2019.90060](https://doi.org/10.1109/ICDARW.2019.90060).
- [8] A. Konrad, C. Eising, G. Sistu, J. McDonald, R. Villing, and S. Yogamani, “FisheyeSuperPoint: Keypoint detection and description network for fisheye images,”, 2021, Publisher: [object Object] Version Number: 2. DOI: [10.48550/ARXIV.2103.00191](https://doi.org/10.48550/ARXIV.2103.00191).