Re-ranking RAG on the GDPR: Failure Modes and Analysis

Shubhadeep Mandal | 2025201056 | 19 October 2026

Adding a cross-encoder re-ranker put the correct GDPR passage into the LLM's context for 6 of 13 hand-labelled stress-test questions where the bi-encoder alone missed it, and broke 1. It costs about 83 ms per query, under 1% of end-to-end time.

Setup

Both pipelines run over the GDPR (Regulation (EU) 2016/679, 88 pages), split into 305 chunks of 220 words with a 40-word overlap. The bi-encoder is `all-MiniLM-L6-v2` with a FAISS index, the cross-encoder `ms-marco-MiniLM-L-6-v2`, and both pipelines answer with `gemini-3.7-flash`. The test set is 13 questions, each labelled with its gold chunk(s) and grouped by the failure it probes. Timings are averaged over 5 runs per query on a CUDA GPU.




Figure 1: The two pipelines share the index and the first-stage search. Pipeline 2 adds one step: the cross-encoder re-scores the bi-encoder's top 10 and passes its own top 3 to the LLM.

1 Failure mode analysis

Re-ranking restored the gold passage in every required category; one question got worse. Table 1 shows one representative case per failure type. Five more (erasure, dismissal of the data protection officer (DPO), data portability, child consent, a control) had the gold in the top 3 under both pipelines and are left out.

Category	Query	Gold passage (chunk)	Why the bi-encoder stumbles	Outcome
Keyword trap	Does a startup with 10 staff have to maintain records of processing?	Art. 30(5), "fewer than 250 persons" (193)	"Records of processing" matches Recital 82 word for word; the answer says "250 persons", never "startup" or "staff"	Restored
Keyword trap	How long can personal data be stored?	Art. 5(1)(e), storage limitation (146)	Gold never enters the top 10, so the re-ranker has nothing to promote	Both miss
Exception	Must every company appoint a data protection officer?	Art. 37(1), when a DPO is mandatory (205)	Finds Art. 37(4), the general "may designate" rule, and misses the conditions	Restored
Exception	Does a controller always have to notify affected individuals about a data breach?	Art. 34(3), when notice is not required (197, 198)	Gets the general duty (Recital 86) but not the "except when" list	Restored
Negation	Is processing someone's religious beliefs or health information prohibited?	Art. 9(1), the prohibition (153)	"Prohibited" blurs with recitals on derogations; gold sits at rank 10	Restored
Buried	What is the maximum fine for breaching the basic principles of processing?	Art. 83(5), 20 M EUR or 4% (291, 292)	Returns the neighbouring 10 M EUR / 2% tier, Art. 83(4)	Restored
Degraded	Can the Commission ask the Board to examine a matter affecting more than one Member State?	Art. 64(2) (264)	Bi-encoder had it at rank 2; the cross-encoder pushed it to 8	Degraded

Table 1: Representative stress-test questions, one or two per failure type.

Failure hunt and standard retrieval metrics

To check that the hand-picked questions were not cherry-picked, `gemini-3.6-flash` wrote 100 more: an ordinary question and a **wording trap** (borrowing a phrase from the most similar other passage) for each of 50 passages. On ordinary questions re-ranking restored 8 and degraded 2; on wording traps it restored 2 and degraded 5, because the cross-encoder can be pulled toward the passage the phrase came from. 30 of 100 were missed by both pipelines: if the gold is not in the bi-encoder's top 10, re-ranking cannot help.

	13 hand-labelled		100 generated	
Metric	**Baseline**	**Re-ranked**	**Baseline**	**Re-ranked**
Hit@1	0.23	**0.46**	0.34	**0.42**
Hit@3 / Recall@3 (gold reaches the LLM)	0.46	**0.85**	0.60	**0.63**
Hit@10	0.92	0.92	0.77	0.77
MRR@10	0.40	**0.64**	0.50	**0.55**
Precision@3	0.18	**0.31**	0.22	**0.24**
nDCG@10	0.47	**0.64**	0.53	**0.57**

Table 2: Retrieval metrics. Hit@10 cannot change: the re-ranker reorders the same 10 candidates.

Hit@k counts a hit when any gold chunk is in the top k; MRR uses the first gold chunk; Precision@3 and nDCG@10 use every gold chunk (binary relevance). Precision@3 stays low because most questions have only one gold chunk, so 0.33 is its ceiling for them. The hand-labelled set was built to stress the baseline, so the hunt's smaller gain (Hit@3 +3 points) is closer to everyday use. Answer-level metrics (faithfulness, answer relevance) were not scored automatically; Section 3 compares answers by hand.

2 Architecture comparison

A bi-encoder encodes the query and each passage separately and compares two vectors. A cross-encoder reads them as one sequence, so every query token can attend to every passage token.




Figure 2: (a) The bi-encoder compresses each text into one 384-d vector on its own, so relevance is a single dot product. (b) The cross-encoder reads the pair as one sequence and outputs a relevance score directly.

The bi-encoder answers "is this passage about the same thing?"; the cross-encoder answers "does this passage answer this question?". Squeezing a passage into one vector means a passage that shares the query's words or topic scores close to the right one, and "not" or "except" barely moves the vector. That is why the cross-encoder pulled Art. 9(1) up from rank 10: it is the sentence that says processing is *prohibited*, while the recitals ranked above it only discuss the topic. The price is speed: the bi-encoder's passage vectors are built once, while the cross-encoder must run one full pass for every candidate at query time.

3 Qualitative and rank shift analysis




Figure 3: Re-ranking lifted the gold chunk into the top 3 for 6 questions; one fell from rank 2 to 8. The biggest lifts came from deep in the list: Art. 9(1) rose 10 → 2 and the 20 M EUR fine tier 7 → 1.

The baseline never invented a rule outright. Its failures were quieter: it said the context did not cover the question, stated a general rule without its exception, or quoted the wrong tier, each time because the chunk with the deciding clause sat outside the top 3. The research and breach questions failed like the DPO question (rule without its exception), so Table 3 omits them.

Query	Answer 1 (baseline)	Answer 2 (re-ranked)	Baseline failure
Startup with 10 staff: records of processing?	"Not possible to answer"; quotes only Recital 82's general duty	Generally exempt under Art. 30(5) (fewer than 250 persons), unless the processing is risky, not occasional or covers special categories	Omitted the deciding exemption; no answer
Must every company appoint a DPO?	No; cites only Art. 37(4) "may designate"	No; lists the three mandatory cases of Art. 37(1)(a)–(c)	Omitted the conditions that make it mandatory
Religious beliefs or health data prohibited?	Says the context does not list them as prohibited	Yes; Art. 9(1) prohibits it, with the Art. 9(2) exceptions	Misstated the rule: denied a prohibition that exists
Maximum fine for breaching basic principles?	"Not explicitly stated"; gives the 10 M EUR / 2% tier of Art. 83(4)	20 M EUR or 4% of worldwide turnover, Art. 83(5)(a)	Wrong tier on offer; no answer
Commission asks the Board? *(degraded)*	Yes; quotes Art. 64(2)	"Not explicitly stated"; text cuts off	Reverse: re-ranking dropped the gold chunk

Table 3: Answer 1 vs Answer 2 for representative queries.

Because the prompt tells the model to answer only from the context, a dropped chunk produces a cautious "not stated" rather than a confident error, in either pipeline.

4 Latency profiling

Re-ranking makes retrieval 7.5× slower (12.7 → 95.4 ms) but adds only 0.9% to the end-to-end time, because LLM generation takes about 9.2 s either way.

Stage (mean, ms)	Pipeline 1 (baseline)	Pipeline 2 (re-ranked)
Bi-encoder: embed query + FAISS search	12.73 (top 3)	12.73 (top 10)
Cross-encoder: score 10 pairs	—	82.62
Retrieval total	**12.73**	**95.35**
LLM generation (`gemini-3.7-flash`)	9,223.5	9,223.5
End-to-end	**9,236.23**	**9,318.85**

Medians are within 1 ms of the means. Generation time ranged from 5.5 to 18.2 s per answer, driven by answer

length rather than the pipeline. On the CPU (8 threads) the 10-pair re-rank takes about 1 s, still small next to generation.

5 Scaling: why not cross-encode everything?

A cross-encoder over the whole collection costs one transformer pass per passage for every query, and nothing can be computed ahead of time. Scanning this 305-chunk regulation takes 2.65 s; a million passages would take 2.4 hours per question.

Collection size (chunks)	Cross-encoder full scan	Two-stage: re-rank top 10
305 (this GDPR, measured)	2.65 s	82.62 ms
100,000	870 s (14.5 min)	82.62 ms
1,000,000	8,700 s (2.4 h)	82.62 ms
10,000,000	87,001 s (24.2 h)	82.62 ms

- **No precomputation.** The score depends on query and passage together, so nothing can be cached or indexed. Bi-encoder vectors are built once; a FAISS search stays in milliseconds at millions of vectors.
- **Cost grows with the collection.** A full scan is linear in N (8.7 ms per pair); the two-stage design costs a fixed $k = 10$ pairs.
- **Precision only matters at the top.** The bi-encoder only has to get the answer into the top 10 (recall); the cross-encoder spends its expensive attention ordering those 10 (precision).

The catch is that the re-ranker can only promote what the bi-encoder found (30 of 100 hunt questions missed in both). A larger pool ($k = 20$–50) or hybrid BM25 + vector retrieval would target those, at a cost that grows with k, not N.

Conclusion

On a legal text where the deciding clause often sits beside a general rule (an exemption, a higher fine tier, a prohibition), a cross-encoder re-ranker is worth its 83 ms: it turned 6 incomplete or wrong answers into correct, cited ones. It is not free of failure: wording traps can mislead it, and it cannot recover passages the bi-encoder never retrieves. Widening the first-stage candidate pool is the next lever.

Code

Notebook, saved results, this report and the live app: `https://github.com/Seronic2001/retrieve-ten-keep-three`