P3449-B01 Jetson Nano Developer Kit Carrier Board TABLE OF CONTENTS Description Page Description Table of Contents Block Diagram Power Tree SODIMM connector 1/3 SODIMM connector 2/3 SODIMM connector 3/3 USB2.0 micro USB3.1 x4 HUB USB3.1 Type-A x2 (A) USB3.1 Type-A x2 (B) 11 DC Jack 3V3 DCDC and 1V8 LDO 13 Power ON/OFF Logic 14 M.2 Key-E Gigabit Ethernet POE HDMI 16 DisplayPort 17 **CAM Connector** 18 40Pin GPIO expansion header 19 Fan, Debug and EEPROM 21 Loop Back Test 22 Mechanical 23 RESERVED P3449 I2C Port Assignments Slave Device BOARDID EEPROM I2C Gen 3: 7'57h RTS5411S USB3.1 HUB CAM I2C : 7'6Ah M.2 KEY-E WIFI/BT I2C Gen 3: TBD **NVIDIA CORPORATION** 2701 SAN TOMAS EXPRESSWAY SANTA CLARA, CA 95050, USA ASSEMBLY Jetson Nano Developer Kit Carrier Board NV_PN 600-13449-0000-400 ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS AND OTHER DOCUMENTS OR INFORMATION (TOGETHER AND SEPARATELY, 'MATERIALS') ARE BEING PROVIDED 'AS IS'. THE MATERIALS MAY PCB REV P3449-B01
BOM REV M CONTAIN KNOWN AND UNKNOWN VIOLATIONS OF INDUSTRY STANDARDS AND SPECIFICATIONS. NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY OF OTHERWISE WITH RESPECT TO THE MATERIALS OR OTHERWISE, AND EXPRESSID, IMPLIED, STATUTORY OF A PARTICULAR PURPOSE, OR ARISING FROM A COURSE OF DEALING, TRADE USAGE, TRADE PRACTICE, OR INDUSTRY STANDARDS. PAGE 1 OF 23
DATE 08-OCT-2022











































