

Celestra cheatsheet – v6.0.1 – <https://github.com/Serrin/Celestra/>

The `celestra` and/or the `CEL` objects contain these functions, except the polyfills. Example: `CEL.qsa("p");`

Core API		Type API	DOM API
VERSION;	noConflict();	type(value);	qsa(selector[,context]).forEach(callback);
constant(value);	asyncConstant(value);	getType(val[,class[,throw=false]]);	qs(selector[,context]);
identity(value);	asyncIdentity(value);	classof(val[,class[,throw=false]]);	domReady(callback);
noop();	asyncNoop();	isSameType(value1,value2);	domClear(element);
T();	asyncT();	isSameClass(value1,value2);	domCreate(type[,properties[,innerHTML]]);
F();	asyncF();	isSameInstance(v1,v2,Constructor);	domCreate(element descriptive object);
BASE16; BASE32; BASE36; BASE58; BASE62;		isDeepStrictEqual(value1,value2);	domToElement(htmlString);
WORDSAFEALPHABET;		isNull(value);	domGetCSS(element[,property]);
toObject(value);		isUndefined(value);	domSetCSS(element,property,value);
extend([deep,]target,source[,sourceN]);		isNil(value);	domSetCSS(element,properties);
deleteOwnProperty(obj,prop[,Throw=false]);		isNumeric(value);	domFadeIn(element[,duration[,display]]);
sizeIn(object);		isChar(value);	domFadeOut(element[,duration]);
pick(object,keys);		isFunction(value);	domFadeToggle(element[,duration[,display]]);
omit(object,keys);		isCallable(value);	domShow(element[,display]);
assoc(object,key,value);		isClass(value);	domHide(element);
createPolyfillMethod(object,prop,value);		isGeneratorFn(value);	domToggle(element[,display]);
createPolyfillProperty(object,prop,value);		isAsyncFn(value);	domIsHidden(element);
		isAsyncGeneratorFn(value);	domScrollToTop(); and domScrollToBottom();
randomBoolean();		isObject(value);	domScrollToElement(element[,top=true]);
randomUUIDv7();		isPlainObject(value)	domSiblings(element);
timestampID([size=21[,alphabet="ABCDEFGHJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789_-"]]);		isProxy(value);	domSiblingsPrev(element);
nanoid([size=21[,alphabet="123456789ABCDEFGHJKLMNPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz"]]);		isElement(value);	domSiblingsLeft(element);
getUrlVars([str=location.search]);		isRegex(value);	domSiblingsNext(element);
obj2string(object);		isArraylike(value);	domSiblingsRight(element);
delay(milisec).then(callback);		isTypedArray(value);	domGetCSSVar(name);
bind(function,context);		isIterator(value);	domSetCSSVar(name,value);
unBind(function);		isIterable(value);	importScript(script1[,scriptN]);
curry(function);		isCoercedObject(object);	importStyle(style1[,styleN]);
compose(function1[,functionN]);		isEmptyValue(value);	setFullscreenOn(selector);
pipe(function1[,functionN]);		isIndex(value);	setFullscreenOn(element);
once(function);		toIndex(value);	setFullscreenOff();
		isLength(value);	getFullscreen();
		toLength(value);	form2array(form);
		isPropertyKey(value);	form2string(form);
		toPropertyKey(value);	getDoNotTrack();
		isPrimitive(value);	getLocation(success[,error]);
		toPrimitiveValue(value);	createFile(filename,content[,dType]);

String API	Assertion API	Math API
b64Decode(string); b64Encode(string); strAt(string, index[, newChar]); strCapitalize(string); strCodePoints(string); strDownFirst(string); strFromCodePoints(iterator); strHTMLEscape(string); strHTMLRemoveTags(string); strHTMLUnEscape(string); strPropercase(string); strReverse(string); strSplice(string, index, count[, add]); strTitlecase(string); strTruncate(string); strUpFirst(string);	assert(condition[, message error]); assertTrue(condition[, message error]); assertFalse(condition[, message error]); assertThrows(callback[, message error]); assertFail(message error); assertEqual(value1, value2[, message error]); assertNotEqual(value1, value2[, message error]); assertStrictEqual(value1, value2[, message error]); assertNotStrictEqual(value1, value2[, message error]); assertDeepEqual(value1, value2[, message error]); assertNotDeepEqual(value1, value2[, message error]); assertDeepStrictEqual(value1, value2[, message error]); assertNotDeepStrictEqual(value1, value2[, message error]); assertTypeOf(value, type[, message error]); assertNotTypeOf(value, type[, message error]); assertInstanceOf(value, constructor[, message error]); assertNotInstanceOf(value, constructor[, message error]); assertIsNil(value[, message error]); assertIsNotNil(value[, message error]); assertMatch(string, regexp[, message error]); assertDoesNotMatch(string, regexp[, message error]);	sum(value1[, valueN]); avg(value1[, valueN]); product(value1[, valueN]); clamp(value, min, max); minmax(value, min, max); inRange(value, min, max); signbit(value); randomInt([max]); randomInt(min, max); randomFloat([max]); randomFloat(min, max); isEven(value); isOdd(value); isInt8(value); isInt16(value); isUInt32(value); isUInt8(value); isUInt16(value); isInt32(value); isBigInt64(value); isBigUInt64(value); isFloat16(value); isFloat(value); toInteger(value); toIntegerOrInfinity(value); toInt8(value); toInt16(value); toInt32(value); toUInt8(value); toUInt16(value); toUInt32(value); toBigInt64(value); toBigUInt64(value); toFloat16(value); toFloat32(value);

Collections API		Polyfills
<pre> arrayDeepClone(array); arrayMerge(target, source1[, sourceN]); arrayAdd(array, value); arrayClear(array); arrayRemove(array, value[, all = false]); arrayRemoveBy(array, callback[, all=false]); arrayRange([start=0[, end = 99[, step = 1]]]); iterRange([start=0[, step=1[, end=Infinity]]]); arrayCycle(iterator[, n = 100]); iterCycle(iterator[, n = Infinity]); arrayRepeat(value[, n = 100]); iterRepeat(value[, n = Infinity]); unique(iterator[, resolver]); slice(iterator[, begin=0[, end = Infinity]]); without(iterator, filterIterator); reduce(iterator, callback[, initialValue]); count(iterator, callback); take(iterator[, n = 1]); takeWhile(iterator, callback); takeRight(iterator[, n = 1]); takeRightWhile(iterator, callback); drop(iterator[, n = 1]); dropWhile(iterator, callback); dropRight(iterator[, n = 1]); dropRightWhile(iterator, callback); isSuperset(superCollection, subCollection); setDifference(set1, set2); setIntersection(set1, set2); setSymmetricDifference(set1, set2); setUnion(iterator1[, iteratorN]); </pre>	<pre> forEach(iterator, callback); map(iterator, callback); enumerate(iterator[, offset = 0]); size(iterator); every(iterator, callback); some(iterator, callback); none(iterator, callback); includes(iterator, value); contains(iterator, value); find(iterator, callback); findLast(iterator, callback); filter(iterator, callback); reject(iterator, callback); partition(iterator, callback); zip(iterator1[, iteratorN]); unzip(iterator); zipObj(iterator1, iterator1); shuffle(iterator); min(value1[, valueN]); max(value1[, valueN]); sort(iterator[, numbers = false]); reverse(iterator); item(iterator, index); nth(iterator, index); first(iterator); head(iterator); last(iterator); initial(iterator); tail(iterator); flat(iterator); concat(iterator1[, iteratorN]); join(iterator[, separator = ", "]); </pre>	<pre> Array.fromAsync(); Array.prototype.toReversed(); Array.prototype.toSorted(); Array.prototype.toSpliced(); Array.prototype.with(); crypto.randomUUID(); Error.isError(); globalThis; Map.groupBy(); Math.sumPrecise(); Object.groupBy(); Object.hasOwn(); TypedArray.prototype.toReversed(); TypedArray.prototype.toSorted(); TypedArray.prototype.with(); globalThis.AsyncFunction(); globalThis.AsyncGeneratorFunction(); globalThis.GeneratorFunction(); </pre>

AJAX and CORS API

```
getText(url, success);  
getJSON(url, success);  
ajax(Options object);
```

Options object properties (* = default value):

Property	Value
url	string
data	string
contentType	*"ajax"/"cors"
type	*"get"/"post"
success	function
error	function
format	*"text"/"json"/"xml"
user	string
password	string

Cookie API

```
getCookie([name]);  
  
hasCookie(name);  
  
setCookie(Options object: properties are the same as the parameters);  
setCookie(name,value[,hours=8760[,path="/"[,domain[,secure[,SameSite="Lax"[,HttpOnly]]]]]);  
  
removeCookie(Options object: properties are the same as the parameters);  
removeCookie(name[,path="/"[,domain[,secure[,SameSite="Lax"[,HttpOnly]]]]]);  
  
clearCookies(Options object: properties are the same as the parameters);  
clearCookies([path="/"[,domain[,sec[,SameSite="Lax"[,HttpOnly]]]]]);
```

Celestra for Node.js and Deno: <i>celestra.node.mjs</i>		
How to import	Removed functions in the <i>celestra.node.mjs</i>	
<pre>// import the defaultExport object import defaultExport from "./celestra.node.mjs"; globalThis.celestra = defaultExport; globalThis.CEL = defaultExport; // import with default with name import { default as celestra } from "./celestra.node.mjs"; globalThis.celestra = celestra; globalThis.CEL = celestra; // import all into a new celestra object import * as celestra from "./celestra.node.mjs"; globalThis.celestra = celestra; globalThis.CEL = celestra; // import some functions import { first, classof } from "./celestra.node.mjs"; globalThis.first = first; globalThis.classof = classof; // dynamic import const celestra = await import("./celestra.node.mjs"); globalThis.celestra = celestra; globalThis.CEL = celestra;</pre>	<p>DOM API</p> <pre>qsa(); qs(); domReady(); domClear(); domCreate(); domToElement(); domGetCSS(); domSetCSS(); domFadeIn(); domFadeOut(); domFadeToggle(); domShow(); domHide(); domToggle(); domIsHidden(); domScrollToTop(); domScrollToBottom(); domScrollToElement(); domSiblings(); domSiblingsPrev(); domSiblingsLeft(); domSiblingsNext(); domSiblingsRight();</pre>	<p>DOM API</p> <pre>domGetCSSVar(); domSetCSSVar(); importScript(); importStyle(); setFullscreenOn(); setFullscreenOn(); setFullscreenOff(); getFullscreen(); form2array(form); form2string(form); getDoNotTrack(); getLocation(); createFile(); AJAX and CORS API getText(); getJSON(); ajax(); Cookie API getCookie(); hasCookie(); setCookie(); removeCookie(); clearCookies();</pre>

Removed Polyfills - Available in celestra-polyfills.dev.js and celestra-polyfills.min.js		
v3.1.0	v3.8.0	v5.6.0
Array.from(); Array.of(); Array.prototype.copyWithin(); Array.prototype.fill(); Array.prototype.find(); Array.prototype.findIndex(); Object.create(); String.fromCodePoint(); String.prototype.codePointAt(); String.prototype.endsWith(); String.prototype.startsWith(); Math.acosh(); Math.asinh(); Math.atanh(); Math.cbrt(); Math.clz32(); Math.cosh(); Math.expm1(); Math.fround(); Math.hypot(); Math.imul(); Math.log1p(); Math.log10(); Math.log2(); Math.sign(); Math.sinh(); Math.tanh(); Math.trunc(); Number.EPSILON; Number.isNaN(); isNaN(); Number.isInteger(); Number.isFinite(); Number.isSafeInteger(); Number.parseInt(); Number.parseFloat();	Array.prototype.values(); Array.prototype.includes(); ChildNode.after(); ChildNode.before(); ChildNode.remove(); ChildNode.replaceWith(); Element.prototype.closest(); Element.prototype.getAttributeNames(); Element.prototype.matches(); Element.prototype.toggleAttribute(); ParentNode.append(); ParentNode.prepend(); String.prototype[Symbol.iterator](); String.prototype.includes(); String.prototype.repeat(); NodeList.prototype.forEach(); Object.assign(); Object.entries(); Object.getOwnPropertyDescriptors(); Object.values(); RegExp.prototype.flags; window.screenLeft; window.screenTop;	Array.prototype.at(); Array.prototype.findLast(); Array.prototype.findLastIndex(); Array.prototype.flat(); Array.prototype.flatMap(); Number.MIN_SAFE_INTEGER; Number.MAX_SAFE_INTEGER; Object.fromEntries(); Object.is(); String.prototype.at(); String.prototype.matchAll(); String.prototype.padStart(); String.prototype.padEnd(); String.prototype.replaceAll(); String.prototype.trimStart(); String.prototype.trimLeft(); String.prototype.trimEnd(); String.prototype.trimRight(); Typedarray.prototype.at(); TypedArray.prototype.findLast(); TypedArray.prototype.findLastIndex(); <div>v5.9.0</div> BigInt.prototype.toJSON();