Celestra cheatsheet – v6.5.0 – https://github.com/Serrin/Celestra/

Core API

```
constant(value);
identity(value);
noop();
T();
F();
```

```
asyncConstant(value);
asyncIdentity(value);
asyncNoop();
asyncT();
asyncF();
```

```
VERSION;
eq(value1, value2);
gt(value1, value2);
gte(value1, value2);
lt(value1, value2);
lte(value1, value2);
```

```
BASE16;
BASE32;
BASE36;
BASE58;
BASE62;
WORDSAFEALPHABET;
```

```
extend([deep,]target,source1[,sourceN]);
deleteOwnProperty(obj,prop[,Throw=false]);
sizeIn(object);
pick(object,keys);
omit(object,keys);
assoc(object,key,value);
delay(milisec).then(callback);
bind(function,context);
unBind(function);
curry(function);
compose(function1[,functionN]);
pipe(function1[,functionN]);
once(function);
tap(function): function(value);
randomBoolean();
randomUUIDv7(v4=false);
timestampID([size=21[,alphabet="123456789A
BCDEFGHJKLMNPQRSTUVWXYZabcdefghijkmnopqrst
uvwxyz"]]);
nanoid([size=21[,alphabet="A-Za-z0-
9_-"]]);
createPolyfillMethod(object,prop,value);
createPolyfillProperty(object,prop,value);
getUrlVars([str=location.search]);
obj2string(object);
assert(condition[,message|error]);
```

Type API

```
typeOf(value);
is(val[,expectedType[,Throw=false]]);
isTypedCollection(iter,expectedType,
Throw=false);
isSameType(value1,value2);
isSameInstance(v1,v2,Contructor);
isDeepStrictEqual(value1,value2);
isCoercedObject(object);
isEmptyValue(value);
isNull(value);
isUndefined(value);
isNullish(value);
isNonNullable(value);
isNonNullablePrimitive(value);
isNumeric(value);
isChar(value);
isPlainObject(value);
isFunction(val); and isCallable(val);
isGeneratorFunction(value);
isAsyncFunction(value);
isAsyncGeneratorFunction(value);
isArrowFunction(value);
isProxy(value);
isElement(value);
isRegexp(value);
isArraylike(value);
isTypedArray(value);
isIterator(val); and isIterable(val);
isAsyncIterator(value);
isAsyncIterable(value);
isPropertyKey(value);
toPropertyKey(value);
isPrimitive(value);
toPrimitive(value);
isObject(value); and toObject(value);
isIndex(value);  and toIndex(value);
isLength(value); and toLength(value);
toSafeString(value);
```

DOM API

```
qsa(selector[,context]).forEach(callback);
qs(selector[,context]);
domReady(callback);
domClear(element);
domCreate(type[,properties[,innerHTML]]);
domCreate(element descriptive object);
domToElement(htmlString);
domGetCSS(element[,property]);
domSetCSS(element,property,value);
domSetCSS(element,properties);
domFadeIn(element[,duration[,display]]);
domFadeOut(element[,duration]);
domFadeToggle(elem[,duration[,display]]);
domShow(element[,display]);
domHide(element);
domToggle(element[,display]);
domIsHidden(element);
domScrollToTop();
domScrollToBottom();
domScrollToElement(element[,top=true]);
domSiblings(element);
domSiblingsPrev(element);
domSiblingsLeft(element);
domSiblingsNext(element);
domSiblingsRight(element);
domGetCSSVar(name);
domSetCSSVar(name,value);
importScript(script1[,scriptN]);
importStyle(style1[,styleN]);
setFullscreenOn(selector);
setFullscreenOn(element);
setFullscreenOff();
getFullscreen();
form2array(form);
form2string(form);
getDoNotTrack();
getLocation(success[,error]);
createFile(filename,content[,dType]);
```

String API	Math API	

b64Decode(string);
b64Encode(string);
 	
strCodePoints(string);
strFromCodePoints(iterator);
 	
strAt(string,index[,newChar]);
 	
strCount(string, substring);
 	
strSplice(string,index,count[,add]);
 	
strTruncate(string);
 	
strReverse(string);
 	
strUpFirst(string);
strDownFirst(string);
strCapitalize(string);
strPropercase(string);
strTitlecase(string);
 	
strHTMLEscape(string);
strHTMLRemoveTags(string);
strHTMLUnEscape(string);
	sum(value1[,valueN]);
	avg(value1[,valueN]);
	product(value1[,valueN]);
	
	clamp(value,min,max);
	minmax(value,min,max);
	
	inRange(value,min,max);
	
	signbit(value);
	
	randomInt([max]);
	randomInt(min,max);
	
	randomFloat([max]);
	randomFloat(min,max);
	
	add(value1,value2);
	sub(value1,value2);
	mul(value1,value2);
	div(value1,value2);
	
	divMod(value1,value2);
	mod(value1,value2);
		isEven(value);
		isOdd(value);
		isInt8(value);
		isInt16(value);
		isUInt32(value);
		isUInt8(value);
		isUInt16(value);
		isInt32(value);
		isBigInt64(value);
		isBigUInt64(value);
		isFloat16(value);
		isFloat(value);
		
		toInteger(value);
		toIntegerOrInfinity(value);
		toInt8(value);
		toInt16(value);
		toInt32(value);
		toUInt8(value);
		toUInt16(value);
		toUInt32(value;
		toBigInt64(value);
		toBigUInt64(value);
		toFloat16(value);
		toFloat32(value);

Cookie API

getCookie([name]);
hasCookie(name);
setCookie(name,value[,hours=8760[,path="/"[,domain[,secure[,SameSite="Lax"[,HttpOnly]]]]]]);
setCookie(Options object: properties are the same as the parameters);
removeCookie(name[,path="/"[,domain[,secure[,SameSite="Lax"[,HttpOnly]]]]]);
removeCookie(Options object: properties are the same as the parameters);
clearCookies([path="/"[,domain[,sec[,SameSite="Lax"[,HttpOnly]]]]]);
clearCookies(Options object: properties are the same as the parameters);

Collections API		Polyfills

castArray(value);
compact(iterator);
arrayDeepClone(array);
arrayMerge(target,source1[,sourceN]);
arrayAdd(array,value);
arrayClear(array);
arrayRemove(array,value[,all = false]);
arrayRemoveBy(array,callback[,all=false]);
 	
arrayRange([start=0[,end = 99[,step = 1]]]);
iterRange([start=0[,step=1[,end=Infinity]]]);
 	
arrayCycle(iterator[,n = 100]);
iterCycle(iterator[,n = Infinity]);
 	
arrayRepeat(value[,n = 100]);
iterRepeat(value[,n = Infinity]);
 	
unique(iterator[,resolver]);
slice(iterator[,begin=0[,end = Infinity]]);
withOut(iterator,filterIterator);
reduce(iterator,callback[,initialvalue]);
count(iterator,callback);
 	
take(iterator[,n = 1]);
takeWhile(iterator,callback);
takeRight(iterator[,n = 1]);
takeRightWhile(iterator,callback);
drop(iterator[,n = 1]);
dropWhile(iterator,callback);
dropRight(iterator[,n = 1]);
dropRightWhile(iterator,callback);
 	
isSuperset(superCollection,subCollection);
setDifference(set1,set2);
setIntersection(set1,set2);
setSymmetricDifference(set1,set2);
setUnion(iterator1[,iteratorN]);
	forEach(iterator,callback);
	map(iterator,callback);
	enumerate(iterator[,offset = 0]);
	size(iterator);
	
	every(iterator,callback);
	some(iterator,callback);
	none(iterator,callback);
	
	includes(collection,value[,comparator]
	);
	find(iterator,callback);
	findLast(iterator,callback);
	filter(iterator,callback);
	reject(iterator,callback);
	partition(iterator,callback);
	
	zip(iterator1[,iteratorN]);
	unzip(iterator);
	zipObj(iterator1,iterator1);
	shuffle(iterator);
	
	min(value1[,valueN]);
	max(value1[,valueN]);
	sort(iterator[,numbers = false]);
	reverse(iterator);
	
	item(iterator,index);
	nth(iterator,index);
	first(iterator);
	head(iterator);
	last(iterator);
	initial(iterator);
	tail(iterator);
	
	flat(iterator);
	concat(iterator1[,iteratorN]);
	join(iterator[,separator = ","]);
		crypto.randomUUID();
		
		Error.isError();
		
		globalThis;
		
		Math.sumPrecise();
		
		globalThis.AsyncFunction();
		
		globalthis.AsyncGeneratorFunction();
		
		globalThis.GeneratorFunction();

How to import	
Celestra for browser: *celestra.browser.js*	**Celestra for Node.js and Deno: *celestra.node.mjs***

<script type="module">
// import the defaultExport object
import defaultExport from "./celestra.browser.js";
globalThis.celestra = defaultExport;
globalThis.CEL = defaultExport;
</script>
 	
<script type="module">
// import with default with name
import { default as celestra } from "./celestra.browser.js";
globalThis.celestra = celestra;
globalThis.CEL = celestra;
</script>
 	
<script type="module">
// import all into a new celestra object
import * as celestra from "./celestra.browser.js";
globalThis.celestra = celestra;
globalThis.CEL = celestra;
</script>
 	
<script type="module">
// import some functions
import { first, map } from "./celestra.browser.js";
globalThis.first = first;
globalThis.map = map;
</script>
 	
<script type="module">
// dynamic import
const celestra = await import("./celestra.browser.js");
globalThis.celestra = celestra;
globalThis.CEL = celestra;
</script>
	// import the defaultExport object
	
	import defaultExport from "./celestra.node.mjs";
	globalThis.celestra = defaultExport;
	globalThis.CEL = defaultExport;
	
	// import with default with name
	
	import { default as celestra } from "./celestra.node.mjs";
	globalThis.celestra = celestra;
	globalThis.CEL = celestra;
	
	// import all into a new celestra object
	
	import * as celestra from "./celestra.node.mjs";
	globalThis.celestra = celestra;
	globalThis.CEL = celestra;
	
	// import some functions
	
	import { first, map } from "./celestra.node.mjs";
	globalThis.first = first;
	globalThis.map = map;
	
	// dynamic import
	
	const celestra = await import("./celestra.node.mjs");
	globalThis.celestra = celestra;
	globalThis.CEL = celestra;

	Removed APIs in the *celestra.node.mjs*
	DOM API | Cookie API

Removed Polyfills – Available in celestra-polyfills.dev.js and celestra-polyfills.min.js		
v3.1.0	**v3.8.0**	**v5.6.0**
Array.from(); Array.of(); Array.prototype.copyWithin(); Array.prototype.fill(); Array.prototype.find(); Array.prototype.findIndex(); Object.create(); String.fromCodePoint(); String.prototype.codePointAt(); String.prototype.endsWith(); String.prototype.startsWith(); Math.acosh(); Math.asinh(); Math.atanh(); Math.cbrt(); Math.clz32(); Math.cosh(); Math.expm1(); Math.fround(); Math.hypot(); Math.imul(); Math.log1p(); Math.log10(); Math.log2(); Math.sign(); Math.sinh(); Math.tanh(); Math.trunc(); Number.EPSILON; Number.isNaN(); isNaN(); Number.isInteger(); Number.isFinite(); Number.isSafeInteger(); Number.parseInt(); Number.parseFloat();	Array.prototype.values(); Array.prototype.includes(); ChildNode.after(); ChildNode.before(); ChildNode.remove(); ChildNode.replaceWith(); Element.prototype.closest(); Element.prototype.getAttributeNames(); Element.prototype.matches(); Element.prototype.toggleAttribute(); ParentNode.append(); ParentNode.prepend(); String.prototype[Symbol.iterator](); String.prototype.includes(); String.prototype.repeat(); NodeList.prototype.forEach(); Object.assign(); Object.entries(); Object.getOwnPropertyDescriptors(); Object.values(); RegExp.prototype.flags; window.screenLeft; window.screenTop;	Array.prototype.at(); Array.prototype.findLast(); Array.prototype.findLastIndex(); Array.prototype.flat(); Array.prototype.flatMap(); Number.MIN_SAFE_INTEGER; Number.MAX_SAFE_INTEGER; Object.fromEntries(); Object.is(); String.prototype.at(); String.prototype.matchAll(); String.prototype.padStart(); String.prototype.padEnd(); String.prototype.replaceAll(); String.prototype.trimStart(); String.prototype.trimLeft(); String.prototype.trimEnd(); String.prototype.trimRight(); Typedarray.prototype.at(); TypedArray.prototype.findLast(); TypedArray.prototype.findLastIndex();
		v5.9.0
		BigInt.prototype.toJSON();
		v6.5.0
		Array.fromAsync(); Array.prototype.toReversed(); Array.prototype.toSorted(); Array.prototype.toSpliced(); Array.prototype.with(); Map.groupBy(); *and* Object.groupBy(); Object.hasOwn(); TypedArray.prototype.toReversed(); TypedArray.prototype.toSorted(); TypedArray.prototype.with();