

Assert.js v1.0.0 cheatsheet

<https://github.com/Serrin/assert.js>

```
assert(condition, [message: string | Error]);
assert.ok(condition, [message: string | Error]);

assert.notOk(value, [message: string | Error]);

assert.fail([message: string | Error]);

assert.Equal(actual, expected, [message: string | Error]);
assert.notEqual(actual, expected, [message: string | Error]);

assert.strictEqual(actual, expected, [message: string | Error]);
assert.notStrictEqual(actual, expected, [message: string | Error]);

assert.deepEqual(actual, expected, [message: string | Error]);
assert.notDeepEqual(actual, expected, [message: string | Error]);

assert.throws(fn, [ErrorType|string|RegExp], [message: string | Error]);

await assert.rejects(asyncFnOrPromise, [ErrorType|string|RegExp],
[message: string | Error]);
await assert.doesNotReject(asyncFnOrPromise, [ErrorType|string|RegExp],
[message: string | Error]);

assert.isTrue(value, [message: string | Error]);
assert.isFalse(value, [message: string | Error]);

assert.is(value, expectedType, [message: string | Error]);
assert.isNot(value, expectedType, [message: string | Error]);

assert.isNullish(value, [message: string | Error]);
assert.isNotNullish(value, [message: string | Error]);

assert.match(string, regexp, [message: string | Error]);

assert.stringContains(actual, substring, [message: string | Error]);

assert.stringNotContains(actual, substring, [message: string | Error]);

assert.lt(value1, value2, [message: string | Error]);
assert.lte(value1, value2, [message: string | Error]);

assert.gt(value1, value2, [message: string | Error]);
assert.gte(value1, value2, [message: string | Error]);
```