API

LIGHT UP TOTAL

LTS Platform MasterDataAPI

API Documentation

VERSION	BASE URL	AUTH	DATE
1.0.0	http://localhost:8000	API Key (X-API-Key)	2026-05-12

Table of Contents

Health — 1 endpoints

- GET /health — Health check endpoint

Prefix — 6 endpoints

- GET /api/v1/prefix — Get all prefixes with pagination
- POST /api/v1/prefix — Create a new prefix
- GET /api/v1/prefix/code/{code} — Get prefix by code
- GET /api/v1/prefix/{id} — Get prefix by ID
- PUT /api/v1/prefix/{id} — Update a prefix
- DELETE /api/v1/prefix/{id} — Delete a prefix

Address - Countries — 5 endpoints

- GET /api/v1/address/address/country — Get all countries
- GET /api/v1/address/country/{id} — Get country by ID
- PUT /api/v1/address/country/{id} — Update a country
- DELETE /api/v1/address/country/{id} — Delete a country
- POST /api/v1/address/country — Create a new country

Address - Provinces — 7 endpoints

- GET /api/v1/address/province — Get all provinces with pagination
- POST /api/v1/address/province — Create a new province
- GET /api/v1/address/province/{id} — Get province by ID
- PUT /api/v1/address/province/{id} — Update a province
- DELETE /api/v1/address/province/{id} — Delete a province
- POST /api/v1/address/province/bulk/delete — Bulk delete provinces
- POST /api/v1/address/province/bulk/status — Bulk update province status

Address - Districts — 7 endpoints

- GET /api/v1/address/district — Get all districts with pagination
- POST /api/v1/address/district — Create a new district
- GET /api/v1/address/district/{id} — Get district by ID
- PUT /api/v1/address/district/{id} — Update a district
- DELETE /api/v1/address/district/{id} — Delete a district
- POST /api/v1/address/district/bulk/delete — Bulk delete districts
- POST /api/v1/address/district/bulk/status — Bulk update district status

Address - Sub-districts — 7 endpoints

- GET /api/v1/address/sub-district — Get all sub-districts with pagination
- POST /api/v1/address/sub-district — Create a new sub-district
- GET /api/v1/address/sub-district/{id} — Get sub-district by ID
- PUT /api/v1/address/sub-district/{id} — Update a sub-district
- DELETE /api/v1/address/sub-district/{id} — Delete a sub-district
- POST /api/v1/address/sub-district/bulk/delete — Bulk delete sub-districts
- POST /api/v1/address/sub-district/bulk/status — Bulk update sub-district status

Address - Hierarchy

1 endpoints

- GET /api/v1/address/hierarchy — Get address hierarchy

Organization - Divisions

9 endpoints

- GET /api/v1/organization/division — Get all divisions with pagination
- POST /api/v1/organization/division — Create a new division
- GET /api/v1/organization/division/code/{code} — Get division by code
- GET /api/v1/organization/division/{id} — Get division by ID
- PUT /api/v1/organization/division/{id} — Update a division
- DELETE /api/v1/organization/division/{id} — Delete a division
- POST /api/v1/organization/division/bulk-delete — Bulk delete divisions
- POST /api/v1/organization/division/reorder — Reorder divisions
- POST /api/v1/organization/division/bulk-status — Bulk update division status

Organization - Departments

9 endpoints

- GET /api/v1/organization/department — Get all departments with pagination
- POST /api/v1/organization/department — Create a new department
- GET /api/v1/organization/department/code/{code} — Get department by code
- GET /api/v1/organization/department/{id} — Get department by ID
- PUT /api/v1/organization/department/{id} — Update a department
- DELETE /api/v1/organization/department/{id} — Delete a department
- POST /api/v1/organization/department/bulk-delete — Bulk delete departments
- POST /api/v1/organization/department/reorder — Reorder departments
- POST /api/v1/organization/department/bulk-status — Bulk update department status

Organization - Positions

9 endpoints

- GET /api/v1/organization/position — Get all positions with pagination
- POST /api/v1/organization/position — Create a new position
- GET /api/v1/organization/position/code/{code} — Get position by code
- GET /api/v1/organization/position/{id} — Get position by ID
- PUT /api/v1/organization/position/{id} — Update a position
- DELETE /api/v1/organization/position/{id} — Delete a position
- POST /api/v1/organization/position/bulk-delete — Bulk delete positions

- POST /api/v1/organization/position/reorder — Reorder positions
- POST /api/v1/organization/position/bulk-status — Bulk update position status

File Management

6 endpoints

- GET /api/v1/files/template — Download data import template
- POST /api/v1/files/upload — Upload data file
- POST /api/v1/files/export — Export data
- GET /api/v1/files — Get uploaded files
- GET /api/v1/files/{fileId} — Download a specific file
- DELETE /api/v1/files/{fileId} — Delete a file

Address - Search

1 endpoints

- GET /api/v1/address/search — Search addresses with language support

Entity Type

1 endpoints

- GET /api/v1/entity-type — Get all entity types

System

1 endpoints

- POST /api/v1/system/cache/flush — Flush all caches

Component Schemas

3 schemas

Health

Health check and status endpoints

GET `/health` Health check endpoint

Check if the API server is running properly

RESPONSES

200 Server is healthy

NAME	TYPE	REQUIRED	DESCRIPTION
success	string		
message	string		
version	string		
timestamp	string <date-time>		
uptime	string		

Prefix

Prefix management operations

GET `/api/v1/prefix` Get all prefixes with pagination

Retrieve a paginated list of all prefixes

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`page`	`string`	optional	Page number (1-based, ignored when limit=-1)
`limit`	`string`	optional	Items per page. Use -1 to return all results.
`search`	`string`	optional	Free-text search (split by whitespace, AND logic). Searchable fields: nameTh, nameEn, code
`entityType`	`string`	optional	Filter by entity type
`isActive`	`string`	optional	Filter by active status
`orderField`	`string`	optional	Field to sort by
`orderSort`	`string`	optional	Sort direction

RESPONSES

200 Prefixes retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST `/api/v1/prefix` Create a new prefix

Create a new prefix with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
code	string	required	Prefix code
nameTh	string	required	Prefix name in Thai
nameEn	string	required	Prefix name in English
sortNo	string		Sort order
isActive	string		Whether the prefix is active

RESPONSES

201 Prefix created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 Prefix already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/prefix/code/{code}` Get prefix by code

Retrieve a specific prefix by its code

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{code}`	`string`	required	Prefix code

RESPONSES

200 Prefix retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Prefix not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/prefix/{id}` Get prefix by ID

Retrieve a specific prefix by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Prefix ID

RESPONSES

200 Prefix retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Prefix not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/prefix/{id}` Update a prefix

Update an existing prefix with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Prefix ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`nameTh`	`string`		Prefix name in Thai
`nameEn`	`string`		Prefix name in English
`sortNo`	`string`		Sort order
`isActive`	`string`		Whether the prefix is active

RESPONSES

200 Prefix updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details

NAME	TYPE	REQUIRED	DESCRIPTION
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Prefix not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/prefix/{id}` Delete a prefix

Delete a prefix by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Prefix ID

RESPONSES

200 Prefix deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Prefix not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

Address - Countries

Country management operations

GET `/api/v1/address/address/country` Get all countries

Retrieve a paginated list of all countries

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
search	string	optional	Free-text search (split by whitespace, AND logic). Searchable fields: nameTh, nameEn, countryCode
isActive	string	optional	Filter by active status
orderField	string	optional	Field to sort by
orderSort	string	optional	Sort direction

RESPONSES

200 Countries retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

GET `/api/v1/address/country/{id}` Get country by ID

Retrieve a specific country by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Country ID

RESPONSES

200 Country retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Country not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/address/country/{id}` Update a country

Update an existing country with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Country ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`nameTh`	`string`		Country name in Thai
`nameEn`	`string`		Country name in English
`iso2`	`string`		ISO 3166-1 alpha-2 code
`iso3`	`string`		ISO 3166-1 alpha-3 code
`sortNo`	`string`		Sort order for display
`isActive`	`string`		Active status

RESPONSES

200 Country updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message

NAME	TYPE	REQUIRED	DESCRIPTION
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Country not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/address/country/{id}` Delete a country

Delete a country by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Country ID

RESPONSES

200 Country deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Country not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST `/api/v1/address/country` Create a new country

Create a new country with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
countryCode	string	required	Unique country code
nameTh	string	required	Country name in Thai
nameEn	string		Country name in English
iso2	string		ISO 3166-1 alpha-2 code
iso3	string		ISO 3166-1 alpha-3 code
sortNo	string		Sort order for display
isActive	string		Active status

RESPONSES

201 Country created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details

NAME	TYPE	REQUIRED	DESCRIPTION
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 Country already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

Address - Provinces

Province management operations

GET `/api/v1/address/province` Get all provinces with pagination

Retrieve a paginated list of all provinces

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
search	string	optional	Free-text search (split by whitespace, AND logic). Searchable fields: nameTh, nameEn, code, provinceId
countryId	string	optional	Filter by country ID
isActive	string	optional	Filter by active status
orderField	string	optional	Field to sort by
orderSort	string	optional	Sort direction

RESPONSES

200 Provinces retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

POST `/api/v1/address/province` Create a new province

Create a new province with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
provinceId	string	required	Unique province code
nameTh	string	required	Province name in Thai
nameEn	string		Province name in English
code	string		Province abbreviation or code
countryId	string	required	Country identifier
isActive	string		Active status

RESPONSES

201 Province created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 Province already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/address/province/{id}` Get province by ID

Retrieve a specific province by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Province ID

RESPONSES

200 Province retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Province not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/address/province/{id}` Update a province

Update an existing province with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Province ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`nameTh`	`string`		Province name in Thai
`nameEn`	`string`		Province name in English
`code`	`string`		Province abbreviation or code
`countryId`	`string`		Country identifier
`isActive`	`string`		Active status

RESPONSES

200 Province updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Province not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/address/province/{id}` Delete a province

Delete a province by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Province ID

RESPONSES

200 Province deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Province not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST /api/v1/address/province/bulk/delete — Bulk delete provinces

Delete multiple provinces by their IDs

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	

RESPONSES

200 Bulk delete completed

401 Unauthorized

POST /api/v1/address/province/bulk/status — Bulk update province status

Update active status for multiple provinces

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	
isActive	string	required	

RESPONSES

200 Bulk status update completed

401 Unauthorized

Address - Districts

District management operations

GET `/api/v1/address/district` Get all districts with pagination

Retrieve a paginated list of all districts

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
search	string	optional	Free-text search (split by whitespace, AND logic). Searchable fields: nameTh, nameEn, code, districtId
provinceId	string	optional	Filter by province ID
isActive	string	optional	Filter by active status
orderField	string	optional	Field to sort by
orderSort	string	optional	Sort direction

RESPONSES

200 Districts retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

POST `/api/v1/address/district` Create a new district

Create a new district with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`districtId`	`string`	required	Unique district code
`nameTh`	`string`	required	District name in Thai
`nameEn`	`string`		District name in English
`code`	`string`		District abbreviation or code
`provinceId`	`string`	required	Province ID reference
`isActive`	`string`		Active status

RESPONSES

201 District created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 District already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/address/district/{id}` Get district by ID

Retrieve a specific district by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	District ID

RESPONSES

200 District retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 District not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/address/district/{id}` Update a district

Update an existing district with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	District ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`nameTh`	`string`		District name in Thai
`nameEn`	`string`		District name in English
`code`	`string`		District abbreviation or code
`provinceId`	`string`		Province ID reference
`isActive`	`string`		Active status

RESPONSES

200 District updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 District not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/address/district/{id}` Delete a district

Delete a district by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	District ID

RESPONSES

200 District deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 District not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST /api/v1/address/district/bulk/delete — Bulk delete districts

Delete multiple districts by their IDs

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	

RESPONSES

200 Bulk delete completed

401 Unauthorized

POST /api/v1/address/district/bulk/status — Bulk update district status

Update active status for multiple districts

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	
isActive	string	required	

RESPONSES

200 Bulk status update completed

401 Unauthorized

Address - Sub-districts

Sub-district management operations

GET `/api/v1/address/sub-district` Get all sub-districts with pagination

Retrieve a paginated list of all sub-districts

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
search	string	optional	Free-text search (split by whitespace, AND logic). Searchable fields: nameTh, nameEn, code, subDistrictId, postalCode
districtId	string	optional	Filter by district ID
postalCode	string	optional	Filter by postal code
isActive	string	optional	Filter by active status
orderField	string	optional	Field to sort by
orderSort	string	optional	Sort direction

RESPONSES

200 Sub-districts retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details

NAME	TYPE	REQUIRED	DESCRIPTION
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST `/api/v1/address/sub-district` Create a new sub-district

Create a new sub-district with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
subDistrictId	string	required	Unique sub-district code
nameTh	string	required	Sub-district name in Thai
nameEn	string		Sub-district name in English
code	string		Sub-district abbreviation or code
districtId	string	required	District ID reference
postalCode	string	required	Postal code
isActive	string		Active status

RESPONSES

201 Sub-district created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details

NAME	TYPE	REQUIRED	DESCRIPTION
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 Sub-district already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/address/sub-district/{id}` Get sub-district by ID

Retrieve a specific sub-district by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Sub-district ID

RESPONSES

200 Sub-district retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Sub-district not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/address/sub-district/{id}` Update a sub-district

Update an existing sub-district with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Sub-district ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`nameTh`	`string`		Sub-district name in Thai
`nameEn`	`string`		Sub-district name in English
`code`	`string`		Sub-district abbreviation or code
`districtId`	`string`		District ID reference
`postalCode`	`string`		Postal code
`isActive`	`string`		Active status

RESPONSES

200 Sub-district updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message

NAME	TYPE	REQUIRED	DESCRIPTION
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Sub-district not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/address/sub-district/{id}` Delete a sub-district

Delete a sub-district by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
{id}	string	required	Sub-district ID

RESPONSES

200 Sub-district deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Sub-district not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST /api/v1/address/sub-district/bulk/delete — Bulk delete sub-districts

Delete multiple sub-districts by their IDs

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	

RESPONSES

200 Bulk delete completed

401 Unauthorized

POST /api/v1/address/sub-district/bulk/status — Bulk update sub-district status

Update active status for multiple sub-districts

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	
isActive	string	required	

RESPONSES

200 Bulk status update completed

401 Unauthorized

Address - Hierarchy

Address hierarchy operations

GET `/api/v1/address/hierarchy` Get address hierarchy

Retrieve complete address hierarchy with countries, provinces, districts, and sub-districts

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
countryId	string	optional	Filter by country ID
provinceId	string	optional	Filter by province ID
districtId	string	optional	Filter by district ID

RESPONSES

200 Address hierarchy retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

Organization - Divisions

Division management operations

GET `/api/v1/organization/division` Get all divisions with pagination

Retrieve a paginated list of all divisions

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
search	string	optional	Free-text search (split by whitespace, AND logic). Searchable fields: code, nameTh, nameEn
isActive	string	optional	Filter by active status
orderField	string	optional	Field to sort by
orderSort	string	optional	Sort direction

RESPONSES

200 Divisions retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

POST `/api/v1/organization/division` Create a new division

Create a new division with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
code	string	required	Division code
nameTh	string	required	Division name in Thai
nameEn	string	required	Division name in English
sortNo	string		Sort order
isActive	string		Whether the division is active

RESPONSES

201 Division created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 Division already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/organization/division/code/{code}` Get division by code

Retrieve a specific division by its code

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{code}`	`string`	required	Division code

RESPONSES

200 Division retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Division not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/organization/division/{id}` Get division by ID

Retrieve a specific division by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Division ID

RESPONSES

200 Division retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Division not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/organization/division/{id}` Update a division

Update an existing division with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Division ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`code`	`string`		Division code
`nameTh`	`string`		Division name in Thai
`nameEn`	`string`		Division name in English
`sortNo`	`string`		Sort order
`isActive`	`string`		Whether the division is active

RESPONSES

200 Division updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Division not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/organization/division/{id}` Delete a division

Delete a division by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Division ID

RESPONSES

200 Division deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Division not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST /api/v1/organization/division/bulk-delete — Bulk delete divisions

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	

RESPONSES

200 Divisions deleted successfully

POST /api/v1/organization/division/reorder — Reorder divisions

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
items	string[]	required	

RESPONSES

200 Divisions reordered successfully

POST `/api/v1/organization/division/bulk-status` Bulk update division status

Activate or deactivate multiple divisions

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
ids	`string[]`	required	
isActive	`string`	required	

RESPONSES

200 Division status updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [success, error]	required	Response status indicator
message	`string`	required	Human-readable message describing the result
content	`string`	nullable	Response data payload
errorCode	`string`	nullable	Error code (only present for error responses)
timestamp	`string` <date-time>	nullable	Response timestamp
requestId	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	
message	`string`	required	Error message
errorCode	`string`	required	Error code identifier
content	`string`	nullable	Additional error details
timestamp	`string` <date-time>	nullable	
requestId	`string`	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	

NAME	TYPE	REQUIRED	DESCRIPTION
`message`	`string`	**required**	Error message
`errorCode`	`string`	**required**	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

Organization - Departments

Department management operations

GET `/api/v1/organization/department` Get all departments with pagination

Retrieve a paginated list of all departments

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`page`	`string`	optional	Page number (1-based, ignored when limit=-1)
`limit`	`string`	optional	Items per page. Use -1 to return all results.
`search`	`string`	optional	Free-text search (split by whitespace, AND logic). Searchable fields: code, nameTh, nameEn
`divisionCode`	`string`	optional	Filter by division code
`isActive`	`string`	optional	Filter by active status
`orderField`	`string`	optional	Field to sort by
`orderSort`	`string`	optional	Sort direction

RESPONSES

200 Departments retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

POST `/api/v1/organization/department` Create a new department

Create a new department with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
code	string	required	Department code
nameTh	string	required	Department name in Thai
nameEn	string	required	Department name in English
divisionCode	string	required	Division code this department belongs to
sortNo	string		Sort order
isActive	string		Whether the department is active

RESPONSES

201 Department created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 Department already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/organization/department/code/{code}` Get department by code

Retrieve a specific department by its code

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
{code}	string	required	Department code

RESPONSES

200 Department retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Department not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/organization/department/{id}` Get department by ID

Retrieve a specific department by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Department ID

RESPONSES

200 Department retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Department not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/organization/department/{id}` Update a department

Update an existing department with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Department ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`code`	`string`		Department code
`nameTh`	`string`		Department name in Thai
`nameEn`	`string`		Department name in English
`divisionCode`	`string`		Division code this department belongs to
`sortNo`	`string`		Sort order
`isActive`	`string`		Whether the department is active

RESPONSES

200 Department updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message

NAME	TYPE	REQUIRED	DESCRIPTION
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Department not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/organization/department/{id}` Delete a department

Delete a department by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Department ID

RESPONSES

200 Department deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Department not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST /api/v1/organization/department/bulk-delete — Bulk delete departments

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	

RESPONSES

200 Departments deleted successfully

POST /api/v1/organization/department/reorder — Reorder departments

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
items	string[]	required	

RESPONSES

200 Departments reordered successfully

POST `/api/v1/organization/department/bulk-status` Bulk update department status

Activate or deactivate multiple departments

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
ids	`string[]`	required	
isActive	`string`	required	

RESPONSES

200 Department status updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [success, error]	required	Response status indicator
message	`string`	required	Human-readable message describing the result
content	`string`	nullable	Response data payload
errorCode	`string`	nullable	Error code (only present for error responses)
timestamp	`string` <date-time>	nullable	Response timestamp
requestId	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	
message	`string`	required	Error message
errorCode	`string`	required	Error code identifier
content	`string`	nullable	Additional error details
timestamp	`string` <date-time>	nullable	
requestId	`string`	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	

NAME	TYPE	REQUIRED	DESCRIPTION
`message`	`string`	**required**	Error message
`errorCode`	`string`	**required**	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

Organization - Positions

Position management operations

GET `/api/v1/organization/position` Get all positions with pagination

Retrieve a paginated list of all positions

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
search	string	optional	Free-text search (split by whitespace, AND logic). Searchable fields: code, nameTh, nameEn
departmentCode	string	optional	Filter by department code
isActive	string	optional	Filter by active status
orderField	string	optional	Field to sort by
orderSort	string	optional	Sort direction

RESPONSES

200 Positions retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

POST `/api/v1/organization/position` Create a new position

Create a new position with the provided data

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
code	string	required	Position code
nameTh	string	required	Position name in Thai
nameEn	string	required	Position name in English
departmentCode	string	required	Department code this position belongs to
sortNo	string		Sort order
isActive	string		Whether the position is active

RESPONSES

201 Position created successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

409 Position already exists

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/organization/position/code/{code}` Get position by code

Retrieve a specific position by its code

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{code}`	`string`	required	Position code

RESPONSES

200 Position retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Position not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

GET `/api/v1/organization/position/{id}` Get position by ID

Retrieve a specific position by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Position ID

RESPONSES

200 Position retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Position not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

PUT `/api/v1/organization/position/{id}` Update a position

Update an existing position with the provided data

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Position ID

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`code`	`string`		Position code
`nameTh`	`string`		Position name in Thai
`nameEn`	`string`		Position name in English
`departmentCode`	`string`		Department code this position belongs to
`sortNo`	`string`		Sort order
`isActive`	`string`		Whether the position is active

RESPONSES

200 Position updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message

NAME	TYPE	REQUIRED	DESCRIPTION
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

404 Position not found

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/organization/position/{id}` Delete a position

Delete a position by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{id}`	`string`	required	Position ID

RESPONSES

200 Position deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 Position not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST /api/v1/organization/position/bulk-delete — Bulk delete positions

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
ids	string[]	required	

RESPONSES

200 Positions deleted successfully

POST /api/v1/organization/position/reorder — Reorder positions

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: string

NAME	TYPE	REQUIRED	DESCRIPTION
items	string[]	required	

RESPONSES

200 Positions reordered successfully

POST `/api/v1/organization/position/bulk-status` Bulk update position status

Activate or deactivate multiple positions

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
ids	`string[]`	required	
isActive	`string`	required	

RESPONSES

200 Position status updated successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [success, error]	required	Response status indicator
message	`string`	required	Human-readable message describing the result
content	`string`	nullable	Response data payload
errorCode	`string`	nullable	Error code (only present for error responses)
timestamp	`string` <date-time>	nullable	Response timestamp
requestId	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	
message	`string`	required	Error message
errorCode	`string`	required	Error code identifier
content	`string`	nullable	Additional error details
timestamp	`string` <date-time>	nullable	
requestId	`string`	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	

NAME	TYPE	REQUIRED	DESCRIPTION
`message`	`string`	**required**	Error message
`errorCode`	`string`	**required**	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

File Management

File upload, download, and export operations for data management

GET `/api/v1/files/template` Download data import template

Download a template file for data import (address, organization, prefix, etc.)

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
type	string	optional	Type of data template to download
format	string	optional	File format

RESPONSES

200 Template file downloaded successfully

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

POST `/api/v1/files/upload` Upload data file

Upload a file for data import processing

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: multipart/form-data · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
file	`string` <binary>		File to upload (CSV, Excel)
type	`string` [address, organization, prefix]		Type of data to process (default: `"address"`)

RESPONSES

201 File uploaded and processed successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [success, error]	required	Response status indicator
message	`string`	required	Human-readable message describing the result
content	`string`	nullable	Response data payload
errorCode	`string`	nullable	Error code (only present for error responses)
timestamp	`string` <date-time>	nullable	Response timestamp
requestId	`string`	nullable	Unique request identifier for tracking

400 Bad request

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	
message	`string`	required	Error message
errorCode	`string`	required	Error code identifier
content	`string`	nullable	Additional error details
timestamp	`string` <date-time>	nullable	
requestId	`string`	nullable	

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	required	

NAME	TYPE	REQUIRED	DESCRIPTION
`message`	`string`	**required**	Error message
`errorCode`	`string`	**required**	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

POST `/api/v1/files/export` Export data

Export data in specified format

REQUEST BODY <SPAN CLASS="PARAM-REQUIRED">(REQUIRED)</SPAN>

Content-Type: application/json · Type: `string`

NAME	TYPE	REQUIRED	DESCRIPTION
`type`	`string` [address, organization, prefix]	required	Type to export
`format`	`string` [csv, xlsx, json]		Export format
`filters`	`string`		Optional filters for export
`includeInactive`	`string`		Whether to include inactive records (default: `false`)

RESPONSES

200 Data exported successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

GET `/api/v1/files` Get uploaded files

Retrieve a list of uploaded files

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`page`	`string`	optional	Page number
`limit`	`string`	optional	Items per page
`search`	`string`	optional	Search by filename

RESPONSES

200 Files retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

GET `/api/v1/files/{fileId}` Download a specific file

Downloads a previously uploaded file by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{fileId}`	`string`	required	File ID to download

RESPONSES

200 File download

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 File not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message

NAME	TYPE	REQUIRED	DESCRIPTION
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

DELETE `/api/v1/files/{fileId}` Delete a file

Delete a file by its ID

PATH PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
`{fileId}`	`string`	required	File ID to delete

RESPONSES

200 File deleted successfully

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [success, error]	required	Response status indicator
`message`	`string`	required	Human-readable message describing the result
`content`	`string`	nullable	Response data payload
`errorCode`	`string`	nullable	Error code (only present for error responses)
`timestamp`	`string` <date-time>	nullable	Response timestamp
`requestId`	`string`	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier
`content`	`string`	nullable	Additional error details
`timestamp`	`string` <date-time>	nullable	
`requestId`	`string`	nullable	

404 File not found

NAME	TYPE	REQUIRED	DESCRIPTION
`status`	`string` [error]	required	
`message`	`string`	required	Error message
`errorCode`	`string`	required	Error code identifier

NAME	TYPE	REQUIRED	DESCRIPTION
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

Address - Search

GET `/api/v1/address/search` Search addresses with language support

Search sub-districts with full address hierarchy and computed full address fields

QUERY PARAMETERS

NAME	TYPE	REQUIRED	DESCRIPTION
query	string	optional	Search term for address (searches sub-district, district, province, and country names)
postalCode	string	optional	Filter by postal code
lang	string	optional	Language for response content
page	string	optional	Page number (1-based, ignored when limit=-1)
limit	string	optional	Items per page. Use -1 to return all results.
orderField	string[]	optional	Field(s) to sort by (e.g., nameEn, postalCode). Can be multiple.
orderSort	string[]	optional	Sort direction(s) corresponding to orderField fields (asc/desc). Default is asc.
fresh	string	optional	If true, ignore cache and fetch fresh data from database

RESPONSES

200 Addresses retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
success	string		
data	string[]		
pagination	string		
└ page	string		
└ limit	string		
└ total	string		
└ totalPages	string		
└ hasNext	string		
└ hasPrev	string		
message	string		

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

Entity Type

GET `/api/v1/entity-type` Get all entity types

Returns the list of available entity types with descriptions

RESPONSES

200 Entity types retrieved successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

System

POST `/api/v1/system/cache/flush` Flush all caches

Clears all data from both in-memory cache and Redis database. Use with caution.

RESPONSES

200 Cache flushed successfully

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

401 Unauthorized

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	
requestId	string	nullable	

500 Internal server error

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [error]	required	
message	string	required	Error message
errorCode	string	required	Error code identifier
content	string	nullable	Additional error details
timestamp	string <date-time>	nullable	

NAME	TYPE	REQUIRED	DESCRIPTION
`requestId`	`string`	nullable	

Component Schemas

ApiResponse

Type: `object`

NAME	TYPE	REQUIRED	DESCRIPTION
status	string [success, error]	required	Response status indicator
message	string	required	Human-readable message describing the result
content	string	nullable	Response data payload
errorCode	string	nullable	Error code (only present for error responses)
timestamp	string <date-time>	nullable	Response timestamp
requestId	string	nullable	Unique request identifier for tracking

Pagination

Type: `object`

NAME	TYPE	REQUIRED	DESCRIPTION
page	string	required	Current page number (1-based). Always 1 when limit=-1.
limit	string	required	Items per page. Equals total when limit=-1 (unlimited).
total	string	required	Total number of items
totalPages	string	required	Total number of pages. Always 1 when limit=-1.
hasNext	string	required	Whether there is a next page. Always false when limit=-1.
hasPrev	string	required	Whether there is a previous page. Always false when limit=-1.

ErrorResponse

Type: `object`

NAME	TYPE	REQUIRED	DESCRIPTION
status	`string` [error]	**required**	
message	`string`	**required**	Error message
errorCode	`string`	**required**	Error code identifier
content	`string`	nullable	Additional error details
timestamp	`string` <date-time>	nullable	
requestId	`string`	nullable	