NATIONAL UNIFIED ELECTRONIC RECEIPT SYSTEM

DIGITAL TRANSACTIONS. A STRONGER PHILIPPINES.

NATIONAL UNIFIED ELECTRONIC RECEIPT SYSTEM

Exit, Migration & Data Portability Plan

Continuity • Secure handover • Verified acceptance



PRESERVE



TRANSFER



VALIDATE

STRUCTURED RECORDS | SECURE TRANSFER | CONTROLLED CLOSURE

SOFTWARE VERSION 1.0.0

Plan edition 1.0 | 19 October 2026

Enterprise procedures for merchant exit, system migration and data portability. Includes the current export baseline, implementation gaps, operational checklists and acceptance forms.

NAVIGATION | CLICK A TITLE

Contents

Controlled plan and purpose 4

Executive policy and readiness 5

Exit scenarios and boundaries 6

Controlled exit lifecycle 7

Roles and decision authority 8

Request intake and recipient verification 9

Commercial terms and continued access 10

Core data and relationship inventory 11

Files, settings and scope supplements 12

Implemented portability endpoint 13

Export contents and known limitations 14

Proposed enterprise handover package 15

Package layout and data dictionary 16

NDJSON structure and integrity validation 17

Identity and relationship mapping 18

Financial, tax and sales-category fidelity 19

Document copies, branding and evidence 20

Audit lineage and chain continuity 21

Encryption, credentials and key boundaries 22

Contents / continued

Secure handover and chain of custody 23

Preflight and migration rehearsal 24

Cutover architecture and write ownership 25

Final extract and cutover runbook 26

Reconciliation and acceptance criteria 27

Rollback and failed migration handling 28

Wallet settlement and financial closure 29

Retention, legal holds and disposal 30

Secure disposal and residual copies 31

Access revocation and retained retrieval 32

Hosting migration and location disclosure 33

Service cessation and emergency exit 34

Illustrative exit schedule and support 35

Exit request and scope form 36

Handover and migration acceptance record 37

Retention and disposal record 38

Risk register and completion priorities 39

Validation evidence and source baseline 40

References, approval and revision history 41

Controlled plan and purpose

A structured route from NUERS service exit to verified handover and closure.

Field	Controlled value
System	NUERS - National Unified Electronic Receipt System
Software / plan edition	1.0.0 / 1.0 | 19 October 2026
Document ID	NUERS-EMP-1.0.0-20261019
Audience	Merchant owners, NUERS operations, receiving providers, migration engineers, finance, security, privacy and assurance reviewers
Status	Prepared operating plan. Service commitments, named owners, destination design and execution dates require approval.
Evidence basis	Local portability/export implementation, relevant tests, related NUERS manuals and selected official guidance.
Distribution	Controlled technical and operational reference; no production credentials or customer records included.
Print / version control	A4, duplex, long-edge binding. Mirrored margins. Printed copies become uncontrolled after a newer edition is released.

This plan defines how to preserve usable business records and continuity when a merchant leaves NUERS, changes its connected system, moves to another service provider, or when NUERS changes its hosting arrangement or ceases a service.

> Evidence labels: IMPLEMENTED = visible in reviewed code, not proof of live deployment. TESTED = the stated isolated software test only. PROPOSED = procedure or package requirement not automatically delivered by the current system. UNVERIFIED = evidence not available.

Executive policy and readiness

Portability succeeds when the recipient can use and reconcile the data.

- **Preserve ownership and lawful access:** verify the requester and destination, provide the approved merchant scope, and maintain required retrieval after transactional service ends.
- **Provide usable records:** structured originals, relationships, documents, financial control totals, schema information and retained provenance are part of the agreed handover.
- **Avoid duplicate business events:** migration must not issue new invoices, charge another fee, resend customer receipts or replay government submissions unintentionally.
- **Prove the result:** count, hash, map, import and reconcile before acceptance. Download completion alone is insufficient.
- **Close in stages:** cut over service, settle commercial matters, retain legally required records and dispose only of eligible copies under recorded authority.

Current implementation position

NUERS provides a scoped streaming NDJSON export with a schema label, table-level record counts and SHA-256 values. Selected encrypted business fields are made usable. The reviewed endpoint does not create a complete binary-document archive, a universal destination importer, or an automatic exit/deletion workflow.

> No merchant has been migrated, deactivated or deleted for this document. No production dataset was exported. The plan is ready for review and adaptation to a named destination; successful real migration is not claimed.

Exit scenarios and boundaries

Select the scenario before defining access, transfer and retention.

Scenario	Required scope / distinction
Merchant service exit	Transfer the authorized merchant dataset and required evidence to the merchant or its approved recipient. Preserve other tenants and shared platform secrets.
ERP / POS / e-commerce change	Move connector configuration and source identity mapping. Existing NUERS documents and acceptance history remain authoritative; avoid re-importing them as new sales.
Migration to another ESP or platform	Agree destination schema, tax/document semantics, authority dependencies, retention and independent acceptance. No automatic transfer of accreditation or issuance authority.
NUERS hosting/provider migration	Move full service dependencies under NUERS control, including protected keys and shared services through separate custody. This is broader than a merchant export.
Contract termination or dispute	Separate write/service suspension, data retrieval, settlement, hold and deletion decisions. Provide a verified assisted retrieval path where self-service is unavailable.
Service cessation / provider failure	Activate continuity and emergency exit coordination. Preserve available backups, access, evidence, recipient contacts and authoritative records before infrastructure closure.

A personal-data portability request and a company-wide service exit are related but different. A merchant export may contain multiple individuals' personal information and financial evidence. Its scope, authority and transfer safeguards must be established separately.

> This plan does not authorize an export of another merchant's data, a shared master encryption key, proprietary source code or confidential platform records unrelated to the approved scope.

Controlled exit lifecycle

D01 - Gate each phase with evidence and an accountable decision.



An agreed exit scope becomes an inventory, a verified package, a reconciled destination and a controlled closure record.

The first approved package is used for mapping and rehearsal. A final consistent extract or validated change set is produced at cutover. The recipient must demonstrate usability and financial consistency before the source is released from operational responsibility.

Where the current exporter cannot provide a continuous change feed, use a planned write freeze and complete final extract. Do not assume that an exported_at timestamp identifies every concurrent change or guarantees database/object consistency.

> PROPOSED workflow. The present NDJSON endpoint is one input to the process; it does not automatically execute these stages or certify migration completion.

Roles and decision authority

Assign named primary and alternate owners before execution.

Role	Accountability
Merchant owner / authorized representative	Requests scope; confirms authority and recipient; accepts business records and destination outcomes.
NUERS service owner / exit manager	Coordinates milestones, support, service boundaries, exceptions and final closure approvals.
Data custodian / export operator	Inventories tables/files, captures consistency point, creates verified exports and records custody.
Receiving system owner	Defines schema and import constraints, secures staging, validates the package and signs receipt/acceptance.
Migration engineer	Builds mapping, preserves source IDs, executes idempotent imports and records transformations and exceptions.
Finance / reconciliation reviewer	Validates transaction values, taxes, discounts, wallet ledger, deposits and settlement.
Security / privacy / legal reviewer	Confirms lawful transfer, minimization, recipient identity, encryption, retention, holds and permitted disposal.
Independent acceptance reviewer	Reviews tests, totals, rejected records and cutover evidence independently from the operator who produced them.

Use two-person review for release of sensitive export packages, production cutover and irreversible disposal. Emergency authority must be recorded with its reason, exact scope and retrospective review. A receiver's technical access does not itself prove permission to receive data.

> Contact names, legal entities, support channels and contractual notice periods are intentionally left for the approved exit record. No service commitments are invented in this plan.

Request intake and recipient verification

EX-01 - Confirm who may request, receive and approve the transfer.

Step	Procedure and evidence
1. Register request	Create case ID; identify merchant account, requested datasets, periods/environments, business purpose and target date.
2. Verify authority	Confirm registered ownership or documented delegation. Use approved identity evidence and existing contact channels; do not rely only on a supplied email or company name.
3. Verify recipient	Confirm receiving legal entity, named custodians, destination domain/storage location and independently verified public key or approved secure channel.
4. Define restrictions	Record legal holds, investigations, sensitive personal data, third-party rights and exclusions. Explain each withheld or supplemental dataset.
5. Approve transfer	Record merchant authorization and relevant privacy/security approvals. Bind approval to the exact scope and destination.
6. Establish acceptance	Agree schema, record totals, document formats, rejection thresholds, delivery acknowledgment and completion criteria before export.
7. Maintain access	Provide lawful retrieval through normal or assisted access while protecting suspended accounts from new unauthorized writes.

> Section 18 of the Philippine Data Privacy Act addresses a data subject's right to obtain qualifying electronically processed personal data in a commonly used structured form. It is not a blanket authorization to disclose an entire corporate tenant to any requester. [R1, R2]

Commercial terms and continued access

PROPOSED policy - keep settlement separate from lawful retrieval.

The exit agreement should define the standard export scope, optional migration assistance, notice period, support window, archive access, responsibility for destination import, and any disclosed cost. Resolve outstanding amounts through the contract and applicable law; do not use a technical lockout to defeat a verified right to retrieve retained records.

Topic	Required agreement
Export and assistance	Identify included structured export, private-file supplements and optional engineering services. State the deliverables and acceptance conditions.
Service suspension	Separate write/API issuance from authorized read/export access. Provide an assisted route if a session, owner account or portal is unavailable.
Archive access	State who may retrieve records after cutover, how identity is verified, response process and applicable retention/hold basis.
Wallet and deposit settlement	Agree final cut-off, pending funding treatment, disputes and approved payout/credit process. Do not infer refund entitlement from an export.
Destination responsibility	Receiver owns import mapping, target controls and operational readiness; NUERS supplies agreed evidence and resolves verified export defects.
Closure and deletion	Define eligible copies, retention exceptions, required approvals, backup expiry and evidence of completed disposal.

IMPLEMENTED: the API boundary preserves authorized GET retrieval for suspended merchants while restricting writes. Recovery of identity/access, end-to-end fee-dispute handling and a guaranteed request SLA still require operational procedures and verification.

Core data and relationship inventory

Preserve financial meaning and identifiers, not only table rows.

Data domain	Portable business information	Control totals / relationships
Business identity	Registered seller, TIN, address, authorized business context and historical seller snapshots.	Merchant ID; source seller identity; effective dates.
Sales and documents	Transactions, invoices, receipts, line items, original references, issue dates, status and corrections.	Counts and monetary totals by tenant, period, type and environment; parent-child links.
Tax and discounts	VAT/non-VAT classifications, taxable/exempt/zero-rated bases, statutory categories and manual discounts where recorded.	Tax and discount sums; rates and calculation basis retained.
Customers	Authorized customer profiles, history and document relationships.	Stable customer IDs; snapshot vs current profile distinction.
Wallet / funding	Available balance, ledger, top-ups and adjustments in the entitled export scope.	Opening + credits - debits = closing; sequence, entry hash and ledger head.
Integration intake	Original source system/event/reference, accepted NUERS IDs and request/content identity.	Duplicate/conflict boundaries; transaction and receipt references.
Regulatory / operational evidence	Outbox preparations, delivery evidence, permits/authorizations, review and hold records where available.	Original provider references and evidence status; no invented acknowledgment.

A migration must preserve the source meaning of every financial field. Do not recalculate historical totals using a new price, fee threshold, tax treatment or destination default.

Files, settings and scope supplements

Inventory every dependency required for independent use of the records.

Asset / area	Required handover treatment
Private verification and supporting files	List every in-scope version with logical document ID, type, filename, bytes and verified plaintext hash. Supply authorized usable bytes in an encrypted package.
Customer document attachments	Keep relationships, reason/history and approved access scope. Metadata alone is not the file.
Receipt branding	Preserve dedicated receipt logo, template/settings and render context where required. Business profile image and receipt logo are different assets.
Printed / PDF copies	Supply required document renditions with generation time and hash. Keep structured financial data alongside PDFs for reuse.
Sandbox records	Inventory separately. The reviewed allowlist is not evidence of complete dedicated Sandbox export; obtain and validate a separate scope supplement.
Email and webhook history	Check current receipt-email and merchant callback tables separately. Legacy delivery tables in the allowlist do not prove all newer workflow records are included.
Accounts and credentials	Supply approved identity/role mapping, not passwords, MFA secrets, recovery codes or active API secrets. Re-enroll and issue destination credentials.
Shared platform records	Provide a scoped extract or attestation where necessary; never hand over other tenants or a full shared audit/database dump to one merchant.

PROPOSED supplements must be explicitly inventoried, authorized, produced and verified. The current structured exporter does not automatically package these assets into a complete exit archive.

Implemented portability endpoint

Technical reference for the reviewed source, not a new public integration contract.

Property	Reviewed behavior
Route	GET /api/businesses/{merchant}/portability
Authentication	Authenticated human session through ApiAccess and the API boundary; tenant/role, session and applicable MFA checks. This is not the merchant ingestion API-key route.
Role handling	Controller permits merchant, admin, super_admin and bir roles; a merchant is checked against its accessible business context. Operational authority and lawful recipient scope must still be verified.
Wallet entitlement	Wallet tables are included for super_admin or a user whose accessible merchant context matches; ordinary regulator/admin access is not assumed to include wallet data.
Format	application/x-ndjson; schema label NUERS-portability-1; one header, record lines, terminal manifest.
Response handling	Streamed download; private, no-store cache directive; route throttle is 3 requests per minute in the reviewed route definition.
Audit	Records tenant.portability.exported with schema context before streaming. This event is not proof that the download or destination import completed.
Scoping	Allowlisted direct merchant queries and relationship-scoped child records; several sensitive credential/deduplication fields are excluded.

Use an approved session-driven download or assisted export workflow. Never place a bearer session token, device header value, API key or secret in this PDF, a public URL, command history or recipient package.

Export contents and known limitations

The allowlist is a baseline, not proof of full service portability.


Implemented behavior	Required qualification
Financial and evidence records	Many transaction, invoice, receipt, source, delivery, review, hold and related audit tables are scoped. Confirm inventory against every feature used by the merchant.
Usable selected encrypted fields	Controller decrypts customer profiles/history, selected customer document reasons, top-up references/review notes and internal outbox documents. Other encrypted fields may remain ciphertext.
Private document metadata	Verification/customer/branch document metadata may be present; private_path is excluded for selected tables. Binary file contents are not streamed by this endpoint.
Hash manifest	Table counts and SHA-256 hashes are produced. The manifest is not independently signed or authenticated by a recipient key.
Database transaction	Streaming occurs inside a database transaction; actual consistent-snapshot behavior depends on the deployed engine/isolation. No explicit exported snapshot/log-position contract is provided.
No universal importer	No reviewed route promises automatic import into another vendor, exact round-trip restore or destination acceptance.
No incremental contract	No explicit resumable batch/checkpoint or change-data-capture contract is exposed here. Large exports and final-delta strategy need operational testing.

A stream can fail after HTTP headers and earlier records have been sent. Missing terminal manifest, decryption errors, a false hash_verified value or missing required datasets must prevent the package being marked complete.

> Do not send a shared application encryption key to solve ciphertext portability. Use an authorized tenant-scoped decrypt-and-re-encrypt supplement, with its own inventory and recipient protection.

Proposed enterprise handover package

D02 - Wrap the current export with the evidence and files needed for migration.



The wrapper is a proposed operational deliverable. It is separate from the implemented NUERS-portability-1 NDJSON response.

Use a unique package ID and revision. Bind the approved merchant, environments, date coverage, recipient, source release, consistency point, exclusions and retention restrictions to that package. A corrected package receives a new revision and preserves the previous manifest as superseded evidence.

> Do not describe a partial package as complete. The release checklist must identify included, excluded, unavailable, unreadable and not-applicable items, with a reason and accountable approval for each exception.

Package layout and data dictionary

PROPOSED - Agree this directory structure with the receiving system.

Path / component	Contents and handling
00-control/	Approved scope, README, package revision, file inventory, checksum manifest, delivery/acceptance forms and exclusions.
01-records/tenant.ndjson	Original structured export bytes, preserved unchanged for hash verification.
02-documents/	Authorized usable private files and selected PDF renditions, with version index and plaintext file hashes. Protect the enclosing package.
03-schema/	Table/field dictionary; data types; null rules; enums; units; dates/timezones; foreign-key/relationship mapping.
04-reconciliation/	Record counts and financial totals by merchant, environment, period, document type and sales category; exception register.
05-provenance/	Scoped audit records, source/destination ID map, transformations, provider references and chain-verification context.
06-configuration/	Permitted presentation/settings and operational references. No shared master key or usable sign-in credentials.
07-retention/	Retention/hold schedule, archive owner, authorized retrieval procedure and disposal eligibility decisions.

Use UTF-8 for structured text, preserve identifiers as strings, and define exact decimal or integer monetary representation. CSV is a convenience view, not the authoritative source if nested or typed information would be lost. Protect CSV consumers against formula injection without altering the canonical archive.

> Every delivered file needs a size and hash. Keep a recipient-verifiable manifest outside any optional human-readable summary; authenticate that manifest through an approved signature or independently confirmed secure channel.

NDJSON structure and integrity validation

Preserve exact source bytes before parsing or transformation.

Line type	Current contract
header	type=header; schema=NUERS-portability-1; merchant_id; exported_at; descriptive note. exported_at is not an engine commit marker.
record	type=record; table; record object. The row fields depend on the current database schema and the allowlist.
manifest	type=manifest; tables mapping each table to records and sha256; manifest_sha256. This is the terminal completion record.

Validation sequence

- Save the original byte stream securely. Require a valid header and terminal manifest; reject truncated, malformed or unexpected trailing content.
- For each table, count its record lines and compute SHA-256 over those exact emitted record-line bytes including the terminating LF. Do not parse and reserialize first.
- Compare per-table counts/hashes with the manifest; reject missing, duplicate or unexpected required datasets after applying the approved scope.
- The manifest hash is computed over PHP JSON serialization of the tables object with its original ordering/encoding. Cross-language verification must reproduce those exact bytes; ordinary reformatting can change the hash.
- Check every decryption_error and hash_verified flag. Validate relationship and financial control totals independently of byte hashes.

> A matching hash shows byte consistency against that manifest. It does not establish who produced it, whether the source query was complete, or whether the destination interpreted the records correctly. Keep transport authentication and business reconciliation as separate controls.

Identity and relationship mapping

Preserve source identities and maintain a durable cross-reference.

Source identity	Destination rule
Merchant / tenant ID	Map to one approved destination tenant. Do not use business name or TIN display text alone as a relational key.
Transaction / invoice / receipt ID	Preserve as a source identifier even if the target allocates a different internal ID. Keep a one-to-one map and uniqueness constraints.
Source system + source event + external reference	Retain the complete scoped identity and original canonical/content hash where permitted. Prevent replay as a newly issued sale.
Document number / series	Preserve original numbers, prefixes, business dates, sequence history and status. Do not continue a series unless independently authorized for the target.
Customer ID and snapshot	Map the current customer master separately from immutable buyer/seller snapshots on historical documents.
Parent / correction links	Keep line items, credit/debit notes, original_invoice_id and other corrective relationships attached to the correct original.
Actor and audit subject	Map pseudonymous/source actor IDs without importing authentication secrets. Explain unresolved legacy identities without rewriting audit history.

Maintain a mapping register with source table/key, destination entity/key, transformation version, import batch, result, validation reference and exception ID. Repeated import of the same package must update staging safely or return the original result rather than create duplicates.

> Do not infer missing relationships from similar amounts, names or timestamps. Quarantine unresolved records, obtain evidence and record the mapping decision.

Financial, tax and sales-category fidelity

Historical amounts retain their original calculation and evidence context.

Dimension	Migration requirement
Currency and units	Preserve currency and distinguish PHP decimal amounts from integer centavos. Never multiply or divide implicitly; document conversion per field.
VAT and non-VAT	Retain seller registration snapshot, line tax treatment, VAT rates, taxable/exempt/zero-rated bases and recorded totals. Mixed line treatments must not be flattened.
Statutory sales categories	Preserve senior citizen, PWD, national athletes/coaches and solo parent classifications where recorded, plus the applicable evidence references and discount/VAT treatment.
Manual discounts	Carry line/document discount amounts, percentages or basis, reason and recorded calculation context where available. Do not overwrite statutory discount provenance.
Fees	Preserve charged amount and pricing revision. Destination migration must not charge the same accepted event again or recompute fees under current rules.
Dates and status	Retain original business occurrence/issue dates separately from ingestion/import time; preserve offsets or documented timezone assumptions. Map statuses explicitly.
Corrections and cancellations	Retain original and corrective documents and review evidence. Do not silently erase or mark originals cancelled merely to fit a destination enum.

> Validation compares exported financial totals with the destination; it does not re-adjudicate historical tax eligibility. Where a destination cannot represent a field, retain a searchable source archive and record the limitation for approval.

Document copies, branding and evidence

Make the archive readable without confusing a copy with a new original.

Provide structured financial records and required human-readable copies together. Preserve the original document identity and financial content. A destination-rendered copy must remain linked to the original and must not be represented as newly issued by the destination merely because it uses a different template.

Component	Required control
Encrypted private file	Authorized operator verifies original size/plaintext hash, decrypts within a protected boundary and packages usable bytes encrypted for the recipient.
Version history	Keep previous versions, upload/review chronology and recorded decisions when included in scope. Do not replace historical evidence with only the latest upload.
Receipt logo and profile image	Export the relevant assets independently. Receipt branding is not automatically the business profile picture.
Rendering context	Record template/settings revision and generation time for exported copies. Current branding can differ from an earlier issued visual rendition; disclose this.
Original vs generated PDF	Mark generated copies as such. Preserve any retained original file with its own hash; do not claim exact historical pixel reproduction without an original artifact.
Offline readability	Test opening a representative PDF/image set without a NUERS session. Check page count, fonts, amounts, customer/seller text and links.

> The current NDJSON stream contains metadata and selected usable text, not a complete attachment/PDF archive. File export must follow the existing private access controls and an approved supplemental packaging process.

Audit lineage and chain continuity

Preserve evidence of origin without disclosing other tenants.

Retain the source export unchanged, the package manifest, each transformation version and the source-to-destination map. Record import attempts, rejected rows, operator identity and approvals in a separate migration audit trail. Do not rewrite the original audit events to make them look native to the target.

Evidence	Preservation requirement
Scoped audit subset	The export selects events by relevant subject IDs. A filtered subset of a shared hash chain may contain gaps and is not a self-contained full-chain proof.
Chain context	Preserve existing previous/entry hashes and source sequence/time. Obtain a scoped attestation or appropriate checkpoint/context through controlled review where needed.
Wallet ledger	Validate entry ordering, amounts, previous hash, entry hash, balance and head before import. Preserve the original ledger as read-only evidence.
Delivery evidence	Retain provider references, request/response hashes, authentic acknowledgments and uncertainty states. An internal preparation is not an external acknowledgment.
Import lineage	Record package ID/revision, source key, transformation ID, target key, import time, result and review.
Proof custody	Record who generated, protected, transferred, received and verified each package. Retain receipts independently of temporary download links.

> Do not export the entire shared platform audit log to complete one merchant's chain. Protect other tenants and use an approved evidence method suited to the reviewer's authority.

Encryption, credentials and key boundaries

Portability should remove technical dependency without copying sign-in secrets.

Item	Merchant exit	Whole-service hosting move
Business records	Authorized usable export protected for recipient.	Consistent protected database/object transfer.
Shared APP_KEY / master keys	Never included in a tenant package.	Move only through separate approved custody; test decryption and rollback.
Passwords, MFA and recovery codes	Do not export as migration credentials; re-enroll users at target.	Retain or rotate through a controlled identity plan, with access testing.
Merchant API / webhook secrets	Issue destination-specific replacements; retire old secrets after controlled cutover.	Assess endpoint/signing continuity and rotate only with a tested coordinated plan.
Encrypted business fields	Decrypt/re-encrypt only authorized tenant data; document unreadable fields.	Retain required key versions for all supported backups and records.
Provider credentials / certificates	Re-provision for target authority; no assumption of transferable entitlement.	Separate secret transfer, owner approval, scope and provider constraints.

Use recipient-specific encryption, verified key fingerprints, restricted storage and controlled access expiry. Keep decryption material separate from the package delivery channel. Record key references and release approvals, never usable key values, in the migration register.

> Role access in the source application is necessary but does not replace recipient verification, purpose limitation or approval of a cross-provider/cross-border transfer.

Secure handover and chain of custody

EX-02 - Acknowledge receipt and validate content separately.

Step	Procedure and evidence
1. Stage	Create the package in restricted storage with named custodians; scan/validate files; calculate full-file hashes after finalization.
2. Protect	Encrypt for the verified recipient; authenticate the manifest; record package version, size, protection method and recipient binding.
3. Deliver	Use approved HTTPS/SFTP or controlled object transfer with least privilege, expiry and logging. Avoid ordinary unprotected email attachments or public URLs.
4. Confirm receipt	Recipient acknowledges package ID/version, received bytes/hash, time and storage location. An HTTP download event alone is insufficient.
5. Verify	Recipient verifies integrity, decryptability, completeness and staging access. Any mismatch triggers quarantine and a corrected package revision.
6. Import and reconcile	Run the agreed mapping and business checks. Record rejected rows and exceptions; no production write enablement yet.
7. Accept / close staging	Sign acceptance only after criteria pass. Expire temporary links and remove eligible staging copies under the agreed retention decision.

Interrupted transfer resumes only through a supported safe transfer mechanism. The reviewed NDJSON endpoint does not promise resumable exports; regenerate and reverify a complete package when needed. Avoid mixing bytes from different export attempts.

> A delivery receipt proves possession of bytes. A migration acceptance proves agreed usability and reconciliation. A deletion certificate proves a separately authorized disposal action. Keep all three records distinct.

Preflight and migration rehearsal

EX-03 - Prove the mapping before scheduling the production transition.

Check	Required evidence
Target readiness	Named tenant, storage/region, database/import engine, encryption, access, audit, capacity and operational owner.
Scope baseline	Approved inventory including all used features, documents, Sandbox records, retention restrictions and exclusions.
Schema compatibility	Field dictionary and tested mapping for types, lengths, enums, decimal precision, timestamps, IDs and null values.
Representative rehearsal	Synthetic or specifically authorized isolated data covering normal, high-value, discounted, mixed-tax, corrected and incomplete cases.
Import behavior	Deterministic mappings; duplicate import safely detected; invalid/unknown fields rejected or quarantined without silent truncation.
Negative tests	Truncated stream, wrong hash, missing file, wrong recipient key, foreign tenant, orphan line item and conflicting event ID fail safely.
Performance	Measure export, transfer, decrypt, import, reconciliation and validation at representative volume; record memory/disk and elapsed times.
Release criteria	Agree allowable downtime, zero-loss consistency boundary, rollback owner and destination acceptance checklist.

> No destination importer or real migration was executed for this plan. The previous backup/restore lab does not prove cross-system portability or provide a migration outage estimate.

Cutover architecture and write ownership

D03 - Retain one authoritative writer across the transition.



The destination can be used for rehearsal before cutover, but it must not issue duplicate originals or dispatch restored historical work.

Declare a cutover boundary in both technical and business terms: source commit/checkpoint, last accepted external event, invoice series boundary, wallet balance and delivery reconciliation state. Ensure all participating ERPs/POS systems understand which endpoint is authoritative after that boundary.

> A DNS change alone does not disable source writes. Revoke or restrict old write credentials, stop old workers and verify that cached clients cannot continue creating accepted financial events on the source.

Final extract and cutover runbook

EX-04 - Move from rehearsal evidence to a controlled production transition.

Stage	Action / release gate
1. Approve window	Confirm merchant, receiver, operations, finance and security readiness; communicate impact and rollback decision point.
2. Preserve recovery	Take and verify an appropriate recoverable source backup; record keys/release and ensure legal holds remain intact.
3. Freeze	Pause source intake and mutating jobs as agreed; drain in-flight commits; stop outbound mail/webhook/provider workers. Record unresolved external outcomes.
4. Capture final state	Produce a consistent final export plus required file/configuration supplements. Use a verified change-capture method only if implemented and rehearsed; otherwise a full final extract.
5. Import	Load into controlled destination staging/target; preserve source IDs; suppress issue/send/charge side effects; record import map and exceptions.
6. Reconcile	Compare final counts, hashes, relationships, money, documents, audit context, numbering and pending deliveries with the approved criteria.
7. Accept and switch	Obtain signed acceptance; enable one destination writer; coordinate connector endpoints and new credentials; retain source read/archive access.
8. Observe	Monitor duplicates, rejected events, totals, customer document access and delivery queues. Keep an incident and rollback path active.

> Do not disable the only usable source archive or release decrypting keys for destruction merely because the destination application is reachable.

Reconciliation and acceptance criteria

EX-05 - Apply deterministic checks and document every exception.

Domain	Minimum acceptance criterion
Record completeness	Counts match for each agreed table/type/period/environment; exclusions and unavailable records separately enumerated and approved.
Identity / relationships	Source IDs uniquely mapped; no foreign-tenant rows; no orphan items, receipt links, corrections or customer associations.
Financial control totals	Source and target totals match in exact units for gross/net/tax/discount/fees. No undocumented rounding or duplicated sale/payment recognition.
Wallet / funding	Ledger balances and references reconcile; pending deposits/adjustments/disputes have an owner and resolution plan.
Documents	All required file versions present with matching hashes; representative copies render correctly without an active NUERS session.
Audit / status	Original provenance retained; status mappings approved; external acknowledgments remain authentic and distinguishable from internal preparation.
Environment	Live and Sandbox remain separate; test data cannot affect live balances or reporting.
Operational use	Authorized destination users can search, view, export and support the migrated scope; credentials and tenant restrictions pass.

Default acceptance rule: no unexplained loss, duplicate business identity, money mismatch or missing required document. A documented exception requires the accountable merchant/service owner and relevant finance/security reviewer; it must not be disguised as a passed control.

> Reconcile at aggregate and record level. Matching totals alone can hide offsetting errors or misassigned customers/tenants.

Rollback and failed migration handling

Keep the business authoritative even when the transition fails.

Failure point	Recovery action
Before source freeze	Stop rehearsal/import work; preserve diagnostics; correct mapping or package defects. Source remains authoritative.
After freeze, before destination writes	If the agreed window expires or validation fails, discard/quarantine failed target staging, confirm no external side effects, then resume the source under an approved decision.
After destination begins writing	Pause both sides; preserve all new destination events; reconcile accepted identities, numbers, wallet effects and external sends before reverse synchronization. Never blindly switch to a stale source database.
Corrupt or incomplete package	Reject the package revision, preserve evidence and obtain a complete corrected export. Do not manually patch original bytes and reuse the old manifest.
Recipient compromise	Suspend delivery/access, revoke transfer credentials, preserve evidence, notify approved response owners and assess exposure before resuming.
Unresolvable target limitation	Retain an approved searchable source archive; agree a revised scope or destination. Do not certify complete migration without usable required data.

Rollback is a controlled transition with its own source-of-truth boundary. The exit manager records who decided, why, what was restored, where new data was retained and how duplicate issuance/transmission was prevented.

> The RTO/RPO targets in the separate recovery plan apply only when approved for their defined service scope. Migration downtime must be estimated from its own rehearsals and contractual acceptance.

Wallet settlement and financial closure

An exported balance is evidence, not an executed payout.


Item	Closure procedure
Final balance	Record the cut-off timestamp, ledger sequence/head and available/reserved amounts. Reconcile charges and credits through that boundary.
Pending deposits	Identify submitted, reviewed, credited, rejected and uncertain deposits; match payment evidence and avoid double credit.
Adjustments / disputes	Record unresolved adjustments, refunds, charge disputes and their accountable owner. Preserve notes and evidence under authorized access.
Settlement decision	Apply the contract and approved finance/legal decision for any refund, transfer or retained credit. Communicate calculation and timing to the merchant.
Execution	Use the authorized settlement mechanism; capture external reference and approval. Do not issue a refund simply by changing a database balance.
Post-settlement evidence	Record ledger entries, final reconciliation, receipt of funds if applicable and remaining exceptions.
Destination opening balance	A destination operational wallet is a separate financial arrangement. Do not treat a copied NUERS balance as money received by the new provider.

Preserve historical pricing revisions and recorded fees. Migration/retry of an already accepted event must not create a second NUERS transaction fee. Supplementary documents and payment records must not be counted as a new original sale merely because they are imported.

> No wallet settlement, refund or financial transfer is performed by this documentation task or by the current NDJSON export.

Retention, legal holds and disposal

D04 - Separate service termination from data-disposal authority.



Closing an account, finishing a migration and deleting retained records are distinct decisions with different evidence.

Create an asset-level retention register with purpose/basis, owner, retention trigger, applicable period, hold status, archive location, authorized retrieval and review date. Determine applicable tax/privacy/contract retention with qualified review; do not copy a static dashboard label as the legal rule.

> IMPLEMENTED: document holds and independently reviewed written release references are recorded. Releasing a hold retains originals; the reviewed hold-release response explicitly states that no purge is implemented.

Secure disposal and residual copies

EX-06 - Dispose only after authority, acceptance and retention checks.

Scope	Required treatment
Temporary export/staging	Expire transfer access; delete eligible local/download/staging copies after acceptance and approved retention. Record residual locations.
Active source records	Retain where legally/contractually required or under hold. Any eligible tenant disposal needs a separate scoped authorized procedure and independent verification.
Shared storage	Never wipe a shared database, volume or master key to delete one tenant. Identify tenant-specific copies and dependencies safely.
Backups and replicas	Record retained backup sets and expiry dates. Prevent routine restoration from silently resurrecting disposed data without reapplying the approved disposition ledger.
Keys	Destroy only keys that are eligible and exclusively associated with the disposed scope, with dependencies checked. Shared or still-needed decrypting keys must remain.
Provider-managed media	Obtain contractual disposal evidence or service-specific attestation where appropriate; distinguish logical deletion from physical media sanitization.
Evidence	Record authority, exact assets, method/tool/version, execution time, verifier, failures, retained exceptions and next review.

Select sanitization methods suited to the medium, confidentiality and custody model. NIST SP 800-88 Rev. 2 provides a sanitization-program reference; a successful application delete call by itself is not a media-sanitization certificate. [R3]

> Deletion must not precede verified handover or override a valid hold/retention obligation. This plan does not claim that automated tenant purge or cryptographic erasure is implemented in NUERS.

Access revocation and retained retrieval

Retire operational access without losing required archive access.

Access class	Cutover / closure control
API write keys	Disable old writes at the agreed boundary; verify requests fail safely; keep required read-only retrieval through approved separate access.
Webhook and mail dispatch	Stop historical queue replay; reconcile outstanding outcomes; rotate/revoke old receiver secrets after the final agreed delivery state.
Merchant/team sessions	Review authorized archive users and revoke unnecessary sessions/grants. Re-enroll target MFA and destination roles independently.
Migration operators	Expire temporary access, storage links and destination permissions after acceptance; retain audited break-glass access only if approved.
Provider administration	Remove old administrative/service accounts only after backup, DNS, key and archive dependencies are verified.
Archive retrieval	Publish a controlled request route with identity verification, scope approval, access logging, retention limits and escalation.
Emergency/hold access	Maintain authorized legal/regulatory access as applicable; verify external requester authority and exact scope rather than treating a role label as sufficient.

> Complete revocation tests from an independent session/client. A UI status change does not by itself prove that cached tokens, background workers, transfer links or provider credentials can no longer act.

Hosting migration and location disclosure

PLANNED providers do not establish current data residency or transfer approval.

Provider / location	Planning position and required decision
Dataplugs	Intended candidate; exact facility, country, workload and primary/recovery role remain unassigned.
Contabo	Intended candidate; region, storage role, backup independence and operational ownership must be confirmed.
AWS Singapore / Hong Kong	Candidate regions ap-southeast-1 / ap-east-1; account, resource roles, key locations and replication design remain unassigned.
Current environment	Actual production app/database/object/backup/key/log locations were not inventoried for this PDF. Obtain verified resource-level evidence before migration.
Cross-border transfer	Map each dataset, recipient/subprocessor, destination and protection. Record required assessments, agreements and approvals before moving production data.

A whole-service move requires consistent database and object recovery, release/configuration parity, key custody, network/TLS/DNS changes, identity access, schedulers, callbacks, email and monitoring. It must preserve the original tenant boundaries and existing ledger/sequence/idempotency controls.

The owner previously confirmed these providers/regions are intended future choices, not the deployed arrangement. Do not list them as active copies, guaranteed failover locations or certified residency in a merchant exit statement.

> Personal-data accountability remains relevant when processing is transferred to another party. The applicable controller/processor roles and agreements require review for the specific service and transfer. [R1]

Service cessation and emergency exit

Prepare an exit route before the primary operator or provider becomes unavailable.

- **Trigger:** planned shutdown, contract/provider termination, sustained outage, loss of critical access or a formal decision to discontinue a service.
- **Stabilize:** assign an exit commander, preserve backups/keys/evidence, prevent uncoordinated deletion, identify available authoritative copies and stop unsafe new issuance.
- **Communicate:** notify verified affected merchants with scope, interim retrieval method, support contact, proposed transition dates and known limitations; avoid unsupported guarantees.
- **Recover access:** use approved continuity and key-custody procedures; maintain independent access to contracts, domains, backups and the authorized contact register.
- **Deliver:** prioritize complete recoverable merchant datasets and required records; document missing or unrecoverable scope; obtain recipient acknowledgment and validation.
- **Close responsibly:** maintain required retention and retrieval, resolve provider custody and settlement, then dispose only eligible copies with evidence.

Consider contractual escrow or independent custody for necessary continuity artifacts where justified. The agreement must define release triggers, beneficiaries, scope, key access and testing. No escrow service, insolvency arrangement or automatic fallback operator is claimed to exist.

> Use the NUERS Backup Procedure and Disaster Recovery Plan for technical restoration controls. Its isolated local test results are not evidence that an emergency cross-provider exit has succeeded.

Illustrative exit schedule and support

PROPOSED planning guide - replace with measured and agreed dates.

Phase	Indicative working window	Deliverable / gate
Intake and verification	Days 1-2	Approved requester, recipient, scope and contacts.
Inventory and design	Days 3-5	Data dictionary, assets, holds, gaps and target mapping.
Package and rehearsal	Days 6-10	Verified sample/full package, import tests and exception register.
Final readiness	Days 11-15	Performance estimate, resolved defects, cutover and rollback approval.
Cutover	Agreed maintenance window	Final consistent state, reconciliation, recipient acceptance and single writer.
Observation and closure	Agreed post-cutover period	Stable operation, settlement, archive access, revocation and eligible disposal evidence.

These intervals are neither legal deadlines nor contractual SLAs. Data volume, recipient readiness, provider access, object count, exceptions and retention constraints determine the actual schedule. Assign owners and dates in the exit case; communicate a revised plan when a gate fails.

Communication record

Each update should state case/package ID, completed facts, outstanding gaps, impact on access, next action/owner and next update time. Notify the merchant before a write freeze or credential change and provide precise retry/cutover guidance to connected-system owners.

> Do not promise that settlement, regulator approval, data deletion or an external provider's import will complete by a date not agreed with the responsible party.

Exit request and scope form

Use one controlled case per tenant/service scope.

Field	Required entry
Case / authorization	Case ID; requester; legal entity; merchant/account IDs; authority evidence; approving owner.
Scenario / purpose	Merchant exit, connector change, provider migration or cessation; business purpose; requested completion.
Destination	Receiving entity/system/version; named custodian; verified contact; data location; transfer method/key fingerprint.
Data scope	Environment; periods; document types; customers; taxes/discounts; wallet; attachments; audit/evidence; settings.
Required supplements	Private files; PDFs; Sandbox; current delivery history; branding; decrypted business fields; dictionary.
Restrictions	Holds; retention basis; privacy limitations; third-party data; exclusions and reason.
Acceptance	Counts; totals; file hashes; relationship checks; source-ID mapping; permitted exceptions; approvers.
Service boundary	Freeze/cutover; source write end; destination write start; retained retrieval; observation and rollback.
Commercial / support	Agreed assistance; charges if any; wallet settlement; support/notice terms; escalation.
Sign-off	Merchant authorization; recipient acceptance of scope; NUERS owner; security/privacy and finance where relevant.

> Do not attach usable credentials to this form. Keep any sensitive identity proof or customer-level exception list in a restricted evidence store referenced by case ID.

Handover and migration acceptance record

Record received, verified and accepted as separate states.

Control	Evidence / sign-off field
Package receipt	Package ID/revision; source release; scope; encrypted bytes/hash; received time; recipient identity; custody reference.
Integrity	Header/schema valid; terminal manifest present; table counts/hashes match; package signature/channel verified; decryptability confirmed.
Import	Importer/mapping version; target tenant; started/completed time; inserted/mapped/rejected counts; idempotent-repeat result.
Business validation	Transactions/receipts/items; financial/tax/discount/fee totals; wallet; source IDs; status; Live/Sandbox separation.
Document validation	File/version completeness; plaintext hashes; sample rendering; original/copy distinction; branding context.
Provenance / access	Source audit preserved; mapped lineage; required archive access; target permissions and confidentiality tests.
Exceptions	Exception ID; affected records/value; risk; owner; resolution date; explicit acceptance or rejection.
Cutover decision	Go/no-go; merchant owner; receiving owner; NUERS exit manager; finance/security reviewers; timestamp.
Closure prerequisites	Settlement decision; retained-copy register; revocation tests; disposal approvals; support owner.

> Acceptance wording: "The undersigned accept package [ID/revision] for the specified scope subject only to the recorded exceptions. This confirms agreed migration validation; it does not certify regulatory approval or authorize deletion of retained records."

Retention and disposal record

A completion record must identify what remains and why.

Field	Required evidence
Authority	Case/change ID; owner approval; applicable retention/hold review; eligibility decision and reviewer.
Asset scope	Exact tenant/dataset/file versions; active/staging/replica/backup locations; package and record identifiers.
Retained exceptions	Basis; hold reference; archive owner; access route; review/expiry trigger; dependency on retained keys.
Disposal method	Logical deletion, media sanitization, provider disposal or eligible cryptographic erasure; tool/service/version and scope limitations.
Execution	Operator; start/end UTC/PHT; job/output reference; failures/retries; affected asset count.
Verification	Independent verifier; read/access tests; provider evidence; logs and hashes where appropriate.
Backups	Residual backup sets; scheduled expiry; restrictions; disposition ledger to apply after any restoration.
Certification	Authorized sign-off stating completed scope and exceptions; no claim of physical sanitization without supporting evidence.

Suggested closure statement: "The specified eligible copies were disposed of using the recorded method on [date]. Records listed in the retained-copy register remain protected for the stated purpose/basis. This statement does not cover unlisted recipient copies or unverified provider media."

> This is a reusable record template. No real NUERS records were deleted, no hold was released and no disposal certificate was issued by preparing this PDF.

Risk register and completion priorities

Close product and operational gaps before promising complete portability.

Risk / gap	Required mitigation and accountable role
Missing assets/new workflows	Compare every used feature with the export allowlist; supplement files, Sandbox, branding and current delivery records. Data custodian + application lead.
Ciphertext without usable content	Inventory remaining encrypted fields; produce authorized tenant-scoped usable supplements without shared keys. Security + export operator.
Inconsistent concurrent export	Prove engine snapshot/isolation and object boundary or use a controlled freeze/final full extract. Database + application leads.
Unsigned / incomplete stream	Require terminal manifest, exact hashes and recipient-authenticated packaging. Export operator + receiver.
No validated importer	Build and rehearse destination mapping; test duplicates, money, document rendering and failure cases. Receiving system owner.
Audit subset not full-chain proof	Preserve original hashes and provide scoped verification context/attestation without foreign-tenant disclosure. Assurance + security.
Access or settlement dispute	Maintain verified assisted retrieval and clear settlement/retention decisions. Service owner + finance/legal.
Premature deletion	Separate retention/hold approval, archive acceptance and disposal verification. Data owner + independent reviewer.

Status at issue: these are explicit readiness requirements, not completed remediation claims. Assign dates and evidence in the actual exit project; document any accepted residual risk.

Validation evidence and source baseline

Limited isolated test evidence supports the current export description.

Three existing portability-related feature tests were executed on 19 October 2026 using isolated in-memory SQLite fixtures. Result: **3 tests, 27 assertions passed** under PHPUnit 11.5.55 / PHP 8.5.9, in 0.695 seconds. No production export or third-party migration was performed.

Test / source	What it supports
MerchantWalletTest portability case	Owned wallet data appears; other tenant access is rejected; regulator output excludes wallet entries in that tested scenario.
MerchantCustomerTest portability case	Usable customer profile/history appears; selected identity hash is excluded; foreign tenant access is rejected.
DurableWorkflowTest portability case	Scoped new evidence export and independent hold-release behavior in the tested fixture.
TenantPortability service	Current table allowlist, relational scoping and selected column exclusions.
TenantPortabilityController	NDJSON header/record/manifest behavior, selected decryption, wallet entitlement and pre-stream audit event.
ApiAccess / ApiBoundary / routes	Human session and role/tenant access, applicable MFA, suspended-write restrictions and route throttle.

The tests are not a complete column-level confidentiality audit, large-volume benchmark, all-feature inventory or cross-system round-trip test. Production engine isolation, large exports, file supplementation, recipient transfer and destination acceptance require separate evidence.

> Selected source SHA-256 values, the test execution record and PDF quality checks are retained with this plan's supporting files. Code review does not prove that the same release is deployed online.

References, approval and revision history

Maintain the plan with each material data-model or provider change.

[R1] National Privacy Commission - Republic Act No. 10173. Sections 18 and 21 provide relevant portability/accountability context. Apply the actual scope and lawful basis through qualified review.
privacy.gov.ph/data-privacy-act-/

[R2] National Privacy Commission - Right to data portability. Guidance on the personal-data right and its scope.
privacy.gov.ph/right-to-data-portability/

[R3] NIST SP 800-88 Rev. 2 - Guidelines for Media Sanitization. Reference for the disposal program; not a NUERS sanitization certification.
csrc.nist.gov/pubs/sp/800/88/r2/final

Internal alignment: NUERS Technical Specifications and System Manual 1.0.0; Backup Procedure and Disaster Recovery Plan 1.0.0; reviewed portability/governance source and tests. The supplied ESP presentation lists an exit/migration/data-portability plan as a documentary item; that source alone is not proof of current accreditation or full compliance.

Approval and maintenance

Approval pending: NUERS service owner, data/security/privacy owner, operations lead and finance/legal reviewers as relevant. Each executed migration also requires the merchant and recipient's scope/acceptance approval. Review at least annually and after significant schema, key, storage, provider, legal or service changes.

Edition 1.0 | 19 October 2026: Initial plan for NUERS software 1.0.0. Includes implemented export behavior, explicit gaps, proposed migration/closure procedures, operational forms and limited isolated test evidence.

> Official references checked on 19 October 2026. Proposed timelines and procedures are not contractual or statutory guarantees. No destination migration, accreditation, settlement or secure-disposal certification is asserted.