NATIONAL UNIFIED ELECTRONIC RECEIPT SYSTEM

DIGITAL TRANSACTIONS. A STRONGER PHILIPPINES.

QUALITY ASSURANCE / EXECUTION MANUAL

QA Test Manual

Understand the feature.
Verify the behavior. Record the evidence.

NUERS software 1.0.0 | Manual revision 1.1

Prepared 29 October 2026 | Asia/Manila (PHT)

225 test cases. 20 feature areas.

166 route entries and 20 controlled test datasets

A practical guide for QA testers, product owners, developers and release reviewers. Each feature explains its purpose, workflow and risks. Each test includes setup references, actions and an observable expected result.

Execution status: Not Run
This document defines the testing plan. It does not record completed test results, certify BIR acceptance or establish production readiness.

Internal QA use / controlled synthetic data / evidence-led sign-off

Document control and scope

Control	Value
Document	NUERS Detailed QA Test Manual
Software baseline	NUERS 1.0.0. Record the exact release/build and deployment timestamp for each execution.
Manual revision	1.1 - expanded PDF companion to the QA Master Checklist
Prepared	29 October 2026; timestamps to be recorded in PHT, with UTC where cross-system correlation requires it.
Coverage	225 cases / 20 feature areas / 166 declared frontend routes / 20 test datasets
Current execution	All cases Not Run. No system test was executed as part of preparing this manual.
Audience	QA, security and performance testers; developers; product, finance and release reviewers.
Primary result register	NUERS_QA_Master_Checklist_v1.0.0.xlsx. Use the same test IDs; attach evidence and defects there or in the approved QA tool.

What this manual covers

Functional behavior, permissions and tenant isolation, invoices and receipts, financial correctness, integration outcomes, reporting, user experience, performance and operational recovery. It preserves the product decisions recorded in the QA checklist.

This is not a new legal interpretation of BIR rules. Tax computations, authority scope and regulated document fields must use the approved requirement version and independently reviewed fixtures for the tested release. A passing software test does not itself issue a permit or establish BIR certification.

> **Execution boundary**
> Run changes, simulated attacks, high-volume workloads, delivery faults, restore and failover tests in an authorized isolated environment. Live checks are limited to separately approved smoke scenarios. Do not send test receipts to real customers.

Contents

Document control and scope 2

Contents 3

How to use the manual 5

Priorities, results and release gates 6

Environment and test data preparation 7

Worked example: a fee and retry test 8

01 / Login and sessions 9

02 / 2FA and trusted devices 14

03 / Authorization and tenant isolation 18

04 / Business registry and onboarding 24

05 / Users, branches and terminals 30

06 / Invoice lifecycle and numbering 34

07 / Amounts, tax and discounts 39

08 / E-receipts, PDFs and branding 45

09 / ERP, POS and ecommerce intake 50

10 / Customer email, notifications and webhooks 57

11 / Wallet, deposits and pricing 62

12 / Dashboards and live monitoring 68

13 / Tables, filters and record actions 72

14 / Reports and PDF/CSV exports 76

15 / Compliance operations and evidence 82

16 / BIR EIS preparation and adapter 87

17 / Server management and recovery 93

18 / Scale, resilience and realtime load 99

19 / Common checks for every page 104

20 / Customers, support and additional portals 108

Appendix A / Test data catalogue 112

Appendix B / Complete route inventory 116

Appendix C / Performance and resilience protocol 125

Appendix D / External dependency register 127

Appendix E / Evidence and defect reporting 129

Appendix F / Glossary and scope notes 131

How to use the manual

Start with the feature overview before executing its cases. The purpose explains why the control exists; the expected result is the observable pass condition. Steps can contain several variants: execute and record each applicable variant instead of marking the whole case from one successful attempt.

Recommended execution sequence

1. Record the exact release/build, environment, configuration, tester and requirement/oracle revision. Confirm that the environment is isolated and recoverable.
2. Prepare the test data IDs named by the case. Verify account roles and data ownership independently, especially Merchant A versus Merchant B.
3. Capture the baseline specified by the feature: counts, balances, document identity, state, revision and relevant timestamps.
4. Execute the stated actions and each negative, boundary or concurrency variant. Preserve request/event IDs so UI, API and job evidence can be correlated.
5. Compare the observed result with the expected result and independent oracle. Reconcile the backend record with the UI, receipt, report and ledger where applicable.
6. Record actual result, evidence link, defect ID, tester and execution time. A missing prerequisite is Blocked or Deferred, not Pass.
7. After a fix, retest the failed case and related regressions on the new build. Clean only the authorized synthetic fixtures; preserve audit evidence.

Read a test card

Field	How QA uses it
ID and title	Stable link to the spreadsheet, defect, screenshot and retest. Do not renumber cases.
Priority and phase	Priority controls execution order; phase identifies the required environment or external gate.
Purpose	The business/security/operational reason the test matters.
Preconditions	Named actor and data fixture IDs, in addition to the module setup.
Procedure	Actions to perform. Expand multi-variant instructions in the execution notes.
Expected result	All stated conditions must be observed. Do not infer success from a toast or HTTP 200 alone.
Evidence	Use the module evidence list and the evidence standard in this manual; include before/after proof for state changes.

Priorities, results and release gates

Priority	Meaning
P0	Release-critical security, financial correctness, identity, data integrity or core availability control. Execute first and after relevant fixes.
P1	Important functional, operational and usability coverage. A P1 is not automatically optional; release scope and risk govern disposition.

Result definitions

Result	Required interpretation
Not Run	No execution evidence yet.
In Progress	Execution started; not all assertions or variants have been evaluated.
Pass	Every applicable expected condition passed on the recorded build and environment, with evidence.
Fail	At least one expected condition failed. Record the observed difference and defect.
Blocked	Execution cannot finish because a prerequisite, environment or dependency is unavailable.
Deferred	Explicitly moved outside this release with an approved reason, owner and target phase.
N/A	Feature or variant does not apply to the documented scope; provide reviewer-approved justification.

Entry and exit criteria

Entry: Approved candidate build and scope; isolated environment; accounts and capability matrix; controlled mail/webhook sinks; known data and tax oracles; monitoring; backup/rollback plan and evidence storage.

Exit: All in-scope P0 and P1 cases pass with evidence; no unresolved critical/high security, financial-integrity or data-loss defect; fixes are retested; performance and reconciliation targets are met; external dependencies and exceptions have explicit owner approval.

> **A status is not a substitute for evidence**
> Do not mark an entire module Pass because one screen loads. Document blocked BIR, offsite recovery and real-controller cases separately, and obtain scope approval before excluding them from a release decision.

Environment and test data preparation

Use distinguishable synthetic records. Do not copy production personal information into screenshots or test files. Assign friendly aliases such as Merchant A / Branch A1 and Merchant B / Branch B1, while storing real test IDs in the execution register.

Environment	Permitted use in this plan
Staging	Functional, authorization, data correctness and supported UI/API workflows with controlled identities and delivery endpoints.
Isolated load lab	Million-row, concurrency, rate-limit, saturation and soak tests. Record production-like hardware and configuration differences.
Recovery lab	Synthetic backup, restore, corruption and migration drills on separate targets. Never overwrite the active source database.
External certification	Official BIR contract/authentication scenarios after issued credentials, approved scope and test-channel access exist.
Production smoke	Only approved, bounded checks for a specific deployed build; use the agreed real/synthetic record policy and no unapproved load or destructive actions.

Minimum fixture matrix

1. Two unrelated merchants, two branches each, overlapping visible invoice numbers and clearly different wallet balances. Include owner, restricted staff, Admin and Super Admin accounts.
2. Live and Sandbox records with distinguishable sources and IDs. Include valid, invalid, pending, void/cancelled and duplicate/retry variants.
3. Empty datasets, one record, page-size boundary records, equal timestamps, many-line documents, long names and Unicode/peso characters.
4. Known centavo-accurate financial fixtures, date boundaries around midnight PHT, controlled email recipients and signed-webhook receivers.
5. Approved large synthetic datasets: one million rows in total, separately one million for a single merchant, and a skewed tenant distribution for noisy-neighbor checks.

The Test Data Catalogue at the end defines D01-D20. Capture fixture hashes or version IDs so a developer can reproduce the result. Reset only test-owned mutable data using an approved script; do not delete historical audit evidence to obtain a passing result.

Worked example: a fee and retry test

This example explains the level of detail expected from QA. It illustrates WAL-001 together with API retry coverage; it is not a completed result.

Setup	Controlled value
Merchant / environment	Merchant A / Live-mode fixture in staging
Opening available balance	PHP 100.00
Published fee / minimum	PHP 3.00 / PHP 0.00; record pricing revision
Events	Five distinct eligible finalized sales, each with a unique accepted event ID
Expected fee sum	5 x PHP 3.00 = PHP 15.00
Expected closing balance	PHP 100.00 - PHP 15.00 = PHP 85.00; assuming no other posted entries

Procedure and reconciliation

1. Record the opening ledger, available balance, pricing revision and initial document/transaction counts.
2. Submit five unique eligible sales. Record the five event IDs and the response/outcome of each.
3. Confirm five accepted sales, five posted fee debits and PHP 15.00 total charged. Confirm closing available balance PHP 85.00.
4. Retry one event with the identical supported idempotency/source identity. Confirm the documented replay result and no additional sale, fee or receipt-delivery job.
5. Compare the merchant wallet, admin financial overview and exported statement against the same scope and cutoff.
6. Capture the actual values and differences. If another fixture posted a credit/debit during the run, isolate or reconcile it before assigning a result.

> **Separate the outcomes**
> NUERS acceptance means the sale was accepted into NUERS. Email delivery has its own outcome. BIR transmission and official acceptance have separate evidence and gates; do not infer them from a successful source API response.

01 / Login and sessions

11 test cases / AUTH / All results: Not Run

Feature purpose / Para saan ito

Login identifies the person using NUERS and opens the workspace allowed for that account. Sessions carry that identity between requests, while logout, expiry and password recovery control when access must end or be re-established.

> **Plain-language explanation**
> Para saan: para ang registered at authorized user lamang ang makapasok, sa tamang account at portal, at hindi manatiling accessible ang private data matapos mag-logout o ma-revoke.

Where it is used

Login, Google sign-in, account recovery and every authenticated portal.

Workflow to follow

Identify account -> validate credentials -> complete required MFA -> establish scoped session -> expire or revoke session.

Prepare before testing

Prepare active, suspended and unassigned test accounts. Use controlled Google accounts and a recovery-mail sink. Record the configured session lifetime and permitted role matrix.

Capture baseline: Record the account alias, role, permitted portal, active-session state and expected expiry policy.

Evidence and cross-check

Redacted login result, final URL, account/role shown, relevant HTTP status and before/after session behavior.

Check carefully: Repeat protected requests after logout or expiry; a visible page alone does not prove the server accepted the correct identity.

AUTH-001 / Valid sign-in and correct portal

P0 | Staging | Result: Not Run

Purpose: Routes an authenticated person into the correct workspace without inheriting another account identity or privilege.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Sign in separately as Super Admin, Admin, Merchant A, Merchant B and restricted staff.
2. Open their default portal.

Expected result: Each account opens its permitted portal with the correct identity. No other account data appears.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-002 / Invalid password and inactive account

P0 | Staging | Result: Not Run

Purpose: Prevents incorrect credentials or a disabled account from obtaining access to business data.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Try incorrect credentials, suspended accounts and accounts without an assigned role.

Expected result: Access is denied with a safe message. No session or privilege is granted.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-003 / Registered Google account

P0 | Staging | Result: Not Run

Purpose: Lets an existing registered user use Google sign-in while retaining the same NUERS account and permissions.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Use the controlled Google account already linked to a registered NUERS email.
2. Complete the normal login flow.

Expected result: Login preserves the existing user, role and merchant. No duplicate account is created.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-004 / Unknown Google account

P0 | Staging | Result: Not Run

Purpose: Enforces the requirement that Google sign-in cannot create an unregistered NUERS user automatically.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Use a controlled Google email that is absent from the NUERS database.

Expected result: Login is rejected. No NUERS account is created automatically.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-005 / OAuth integrity and replay

P0 | Isolated lab | Result: Not Run

Purpose: Binds an OAuth response to the original login attempt so a stolen or mismatched response cannot replace an identity.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. In isolated tests, use an invalid state, expired handoff, reused handoff and mismatched Google subject.

Expected result: Each attempt fails. An existing identity cannot be replaced or reassigned.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-006 / Refresh, deep link and browser restart

P1 | Staging | Result: Not Run

Purpose: Keeps normal navigation usable without losing or accidentally broadening the authenticated account context.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Sign in, reload a protected detail URL, open a second tab and restart the browser within the permitted session lifetime.

Expected result: Session behavior follows the configured policy. No infinite loading, role switch or lost authorized destination.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-007 / Logout and revoked session

P0 | Staging | Result: Not Run

Purpose: Makes logout and administrative revocation effective on the server, including previously issued sessions and cached views.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Log out, use browser Back, and repeat an authenticated request with the old session.
2. Repeat after admin revocation.

Expected result: Protected data and mutations are denied after revocation. Cached sensitive data is not exposed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-008 / Expired session during work

P1 | Staging | Result: Not Run

Purpose: Returns the user safely to authentication when access expires, without leaving a form or table stuck loading.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Expire a session while a filter is loading and while a form has unsaved data.

Expected result: Loading ends with a clear sign-in action. No silent save, request loop or exposure of old account data.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-009 / Password recovery

P0 | Staging | Result: Not Run

Purpose: Restores legitimate account access through a time-limited, one-use recovery process.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Request recovery for a test account.
2. Test valid, expired, reused and altered tokens.

Expected result: Only the valid unused token works. Existing security policy is enforced and prior sessions are handled correctly.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-010 / Password change and old sessions

P0 | Staging | Result: Not Run

Purpose: Ensures changing a password stops continued use of the previous credentials and invalidated access proofs.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Change a test password using the required current credentials.
2. Retry old password and old session/handoff.

Expected result: Old credentials and invalidated sessions stop working. The new login succeeds.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUTH-011 / Login abuse and return URL

P1 | Isolated lab | Result: Not Run

Purpose: Limits abusive login attempts and prevents a return URL from redirecting access to an unrelated site.

Preconditions: Actor: All roles. Fixtures: D01, D02. Complete the module setup and baseline first.

Procedure

1. Exceed the configured login limit in the lab.
2. Supply an external return URL.

Expected result: Rate limit is enforced with a recoverable message. Redirects cannot send the session to another site.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

02 / 2FA and trusted devices

8 test cases / MFA / All results: Not Run

Feature purpose / Para saan ito

Multi-factor authentication adds a second proof of identity to sensitive access. Multiple confirmed authenticator devices allow continuity when one device is unavailable without sharing or replacing the existing device secret.

> **Plain-language explanation**
> Para saan: dagdag proteksiyon sa account at ligtas na paggamit ng higit sa isang authenticator device.

Where it is used

Account Security, MFA enrollment and privileged administrative actions.

Workflow to follow

Verify current access -> start enrollment -> confirm fresh OTP -> use confirmed device -> revoke or recover when necessary.

Prepare before testing

Use two test authenticators, a fresh confirmed factor and controlled recovery codes. Keep seeds and recovery codes outside screenshots and the execution register.

Capture baseline: Record confirmed and pending device aliases, primary device and the configured enrollment/device limits.

Evidence and cross-check

Redacted device list, enrollment/revocation outcome, OTP acceptance/rejection and corresponding security audit event.

Check carefully: A device should work only after confirmation; a revoked or expired secret must never regain access through a stale page.

MFA-001 / Enroll first authenticator

P0 | Staging | Result: Not Run

Purpose: Confirms possession of the first authenticator before treating it as an active security factor.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Start enrollment and enter an invalid code, then a valid code.

Expected result: The device is inactive until confirmed. Invalid codes cannot enable MFA.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MFA-002 / Multiple authenticator devices

P0 | Staging | Result: Not Run

Purpose: Supports multiple independent confirmed authenticators without silently replacing the existing device.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Add a second authenticator after the required password and existing-factor checks.
2. Sign in with each device.

Expected result: Both confirmed devices work independently. Enrolling the second does not overwrite the first secret.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MFA-003 / OTP replay and expired code

P0 | Staging | Result: Not Run

Purpose: Prevents an intercepted or previously used OTP from being accepted again.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Reuse an accepted code and try a code outside the permitted time window.

Expected result: Replayed and expired codes are denied without bypassing MFA.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MFA-004 / Revoke device

P0 | Staging | Result: Not Run

Purpose: Allows a lost device to be removed while preserving a valid remaining recovery path.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Revoke a confirmed test device and try it again.
2. If primary, verify the remaining confirmed device.

Expected result: Revoked codes stop working. Another confirmed device remains usable according to policy.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MFA-005 / Ownership of device actions

P0 | Staging | Result: Not Run

Purpose: Prevents one user from enrolling, changing or removing another user security devices.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Use Account A to confirm, rename or revoke Account B device identifiers.

Expected result: All cross-account device actions are denied and reveal no secret.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MFA-006 / Pending setup expiry and cancellation

P1 | Staging | Result: Not Run

Purpose: Ensures abandoned enrollments expire safely without removing an already working device.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Cancel enrollment; start another and let it expire.
2. Attempt confirmation afterward.

Expected result: Cancelled and expired secrets cannot be activated. Active devices are not removed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MFA-007 / Recovery code single use

P0 | Staging | Result: Not Run

Purpose: Provides controlled recovery when an authenticator is unavailable, with no reusable recovery bypass.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Use one recovery code, then repeat it.
2. Test recovery under the documented procedure.

Expected result: A code is consumed once. Recovery does not silently weaken privileged MFA.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MFA-008 / Device list and limits

P1 | Staging | Result: Not Run

Purpose: Keeps device management understandable and bounded while protecting the actual authenticator secrets.

Preconditions: Actor: Account owner / Super Admin. Fixtures: D01, D03. Complete the module setup and baseline first.

Procedure

1. Test duplicate/long device names, configured device cap and last-used metadata.

Expected result: Validation is clear. No secret is returned in lists, exports, logs or browser storage.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

03 / Authorization and tenant isolation

14 test cases / SEC / All results: Not Run

Feature purpose / Para saan ito

Authorization decides what an authenticated person or API key can read or change. Tenant isolation is the boundary separating each merchant, including its files, customers, balances, reports and background jobs.

> **Plain-language explanation**
> Para saan: hindi makikita o mababago ng Merchant A ang data ni Merchant B kahit alam niya ang record ID o URL.

Where it is used

Every private page, API endpoint, download, export, upload and background-job status route.

Workflow to follow

Authenticate -> resolve role and tenant -> apply branch/capability rules -> authorize exact resource -> read or mutate -> record outcome.

Prepare before testing

Create two recognizable synthetic merchants with colliding invoice numbers and different balances. Document allowed capabilities; test both UI and direct requests in the authorized lab.

Capture baseline: Record the resource owner and permitted caller before each attempt. Keep an independent before/after snapshot of the protected test record.

Evidence and cross-check

Redacted request path/method, caller alias, expected owner, status code and proof that foreign content or mutation did not occur.

Check carefully: A denied page is insufficient if a PDF, export, count, cache or direct endpoint still reveals the same private data.

SEC-001 / Cross-merchant reads

P0 | Staging | Result: Not Run

Purpose: Protects the confidentiality of every merchant record even when another merchant knows its identifier.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. As Merchant A, request Merchant B invoice, receipt, transaction, customer and wallet identifiers.

Expected result: 403/404 or scoped empty results. No B data, counts, names or amounts leak.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-002 / Cross-merchant writes

P0 | Staging | Result: Not Run

Purpose: Protects data integrity by stopping unauthorized changes to another merchant records.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. As A, attempt update, cancel, approve, email or delete operations using B identifiers.

Expected result: Denied before mutation. B records and audit attribution remain unchanged.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-003 / PDF and export ownership

P0 | Staging | Result: Not Run

Purpose: Closes download and export paths that could otherwise bypass the normal screen-level access checks.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Request B receipt PDF, report job download, attachment and export URLs with A session.

Expected result: Every file route enforces ownership and authorization independently.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-004 / Branch and terminal restrictions

P0 | Staging | Result: Not Run

Purpose: Keeps delegated staff limited to the branches and terminals assigned to their role.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. As branch-limited staff, change branch/terminal filters and direct identifiers to another branch.

Expected result: Results and permitted writes stay within assigned scope. Filters cannot widen access.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-005 / Role escalation and admin endpoints

P0 | Staging | Result: Not Run

Purpose: Stops privilege escalation through direct API requests or forged administrative fields.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. As merchant and ordinary admin, call restricted endpoints directly and submit role or approval fields.

Expected result: Server denies unauthorized roles and privileged fields. Hiding a button is not the only protection.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-006 / Cached data after account switch

P0 | Staging | Result: Not Run

Purpose: Prevents browser caches and realtime subscriptions from exposing data after switching accounts.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. View A data, log out and log in as B in the same browser.
2. Repeat with two concurrent tabs.

Expected result: A data never flashes or persists in B views, downloads or realtime subscriptions.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-007 / Anonymous private URLs

P0 | Staging | Result: Not Run

Purpose: Ensures knowing a private URL does not substitute for authentication and ownership.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Open private document, attachment, PDF, job and dashboard endpoints without credentials.

Expected result: Denied. Public verification reveals only its explicitly allowed fields.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-008 / CSRF and authentication headers

P0 | Isolated lab | Result: Not Run

Purpose: Prevents another site or ambiguous credential combination from causing an unauthorized mutation.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. For every cookie-authenticated mutation, test missing/invalid CSRF protection.
2. Test conflicting API credentials separately.

Expected result: Unauthorized mutation fails. Authentication ambiguity cannot select a different user or merchant.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-009 / Stored XSS and injection

P0 | Isolated lab | Result: Not Run

Purpose: Ensures user-entered content remains data when displayed, queried, printed, emailed or opened in a spreadsheet.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Use harmless lab payloads in names, descriptions, filters, invoice notes and filenames.
2. Render UI, PDFs, email and CSV.

Expected result: Input is escaped/validated. No script execution, query manipulation or CSV formula execution.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-010 / Unsafe uploads and URLs

P0 | Isolated lab | Result: Not Run

Purpose: Prevents a file or URL field from becoming a route to unsafe files or private network services.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Try wrong MIME, oversized files, traversal names and internal-network URLs in logo/webhook fields.

Expected result: Validation blocks unsupported content and unintended network/file access. Private uploads remain private.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-011 / Secrets and debug output

P0 | Staging | Result: Not Run

Purpose: Keeps operational errors and diagnostic output from revealing secrets or private raw payloads.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Inspect normal/error API responses, browser storage, exported files and redacted logs.

Expected result: No API secret, signing key, database credential, stack trace or encrypted raw customer payload is exposed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-012 / TLS, cookies and security headers

P1 | Staging | Result: Not Run

Purpose: Protects browser/server communication and session handling according to the approved deployment baseline.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Check HTTPS, redirect behavior, session cookie flags and deployed security headers against the approved configuration.

Expected result: Certificate validates; cookies and headers meet the approved baseline. No mixed-content credential transfer.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-013 / Rate limits and safe errors

P0 | Isolated lab | Result: Not Run

Purpose: Returns useful failure reasons without letting a rejected request create a record or disclose sensitive internals.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Exercise documented 401/403/402/409/422/429/5xx outcomes in the lab.

Expected result: Correct contract and actionable safe reason. No unauthorized sale, charge or information leak.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

SEC-014 / Security audit trail

P0 | Staging | Result: Not Run

Purpose: Makes sensitive actions and denied attempts attributable to an actor, target and outcome.

Preconditions: Actor: Security QA / all roles. Fixtures: D01, D04. Complete the module setup and baseline first.

Procedure

1. Perform denied access and privileged changes with test accounts.
2. Review audit evidence.

Expected result: Actor, time, action, target and outcome are attributable without logging secrets.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

04 / Business registry and onboarding

12 test cases / REG / All results: Not Run

Feature purpose / Para saan ito

The business registry connects merchant access to a reviewed business identity. Onboarding collects evidence; profile-change review keeps protected identity details stable until an authorized reviewer accepts a change.

> **Plain-language explanation**
> Para saan: may malinaw na master record ng negosyo at may approval muna sa mahahalagang pagbabago tulad ng registered name at TIN.

Where it is used

Public registration, Registered Businesses, Taxpayer Onboarding, Merchant Profile and Business Details.

Workflow to follow

Register -> verify contact/evidence -> review -> activate -> maintain allowed contact fields -> request review of protected changes.

Prepare before testing

Prepare valid/invalid synthetic identity, location chains, private evidence files and an independent reviewer. Use a separate profile image and invoice logo.

Capture baseline: Record approved identity, proposed identity, review state, owner display and merchant financial overview before changing a field.

Evidence and cross-check

Before/after profile, review request and reviewer decision, private-file access result and registry/owner-directory comparison.

Check carefully: A pending identity change must not silently replace the effective seller identity or the login email used for access.

REG-001 / Business registration and validation

P1 | Staging | Result: Not Run

Purpose: Creates a reviewable business record while preventing incomplete or conflicting registrations.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Submit a valid synthetic registration; repeat with missing identity, malformed TIN and duplicate account data.

Expected result: Valid registration enters the intended review state. Invalid and duplicate submissions are handled clearly.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-002 / Email code and activation

P1 | Staging | Result: Not Run

Purpose: Verifies control of the intended contact channel before activation is accepted.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Use correct, wrong, expired and reused verification/activation links.

Expected result: Only current valid proofs work. Failed verification cannot activate an account.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-003 / Location and RDO mapping

P1 | Staging | Result: Not Run

Purpose: Keeps the registered address and RDO relationship coherent instead of combining incompatible locations.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Choose a complete region/province/city/barangay chain; test incompatible children and unresolved RDO.

Expected result: Stored address is coherent. Unresolved mapping asks for authorized manual review instead of inventing an RDO.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-004 / Verification documents

P0 | Staging | Result: Not Run

Purpose: Allows reviewers to inspect submitted evidence while keeping that evidence private to authorized users.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Upload allowed documents; download as owner/reviewer; attempt another merchant download.

Expected result: Private documents retain correct ownership, type and integrity. Other merchants cannot retrieve them.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-005 / Approve, reject and suspend

P0 | Staging | Result: Not Run

Purpose: Controls business activation and suspension with traceable, non-duplicated decisions.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Review registration with reason/evidence.
2. Repeat each action and try a stale revision.

Expected result: Authorized transition occurs once with history. Suspension consistently restricts applicable actions.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-006 / Directly editable merchant profile fields

P0 | Staging | Result: Not Run

Purpose: Lets merchants maintain routine contact information without requiring identity approval for every edit.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Change contact number, website and business description from merchant profile.

Expected result: Allowed fields update without identity approval. Unrelated identity fields are unchanged.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-007 / Protected identity change request

P0 | Staging | Result: Not Run

Purpose: Keeps the approved legal business identity effective until a reviewer authorizes a proposed change.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Change registered business name, TIN, address or representative through merchant workflow.

Expected result: A review request is created. Current approved identity stays effective until authorized approval.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-008 / Representative and user directory alignment

P0 | Staging | Result: Not Run

Purpose: Keeps the representative shown in business and user views aligned without accidentally changing login ownership.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Approve an authorized representative update.
2. Compare business profile and owner display in user directory.

Expected result: Displayed representative stays aligned. Login identity and permissions do not change accidentally.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-009 / Profile image versus invoice logo

P1 | Staging | Result: Not Run

Purpose: Separates account presentation from the logo printed on customer-facing invoices.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Upload a profile picture, then a different invoice logo.
2. Refresh profile and receipt preview.

Expected result: Profile image needs no identity approval. Receipt uses the separately configured invoice logo.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-010 / Registered-business financial overview

P1 | Staging | Result: Not Run

Purpose: Gives the administrator a complete, scoped view of the selected merchant financial position.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Open each business detail and compare wallet, transaction count/amount, fees, deposits and pending top-ups with fixtures.

Expected result: Figures belong to the selected business and stated environment/period. Pending funds are not available balance.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-011 / Business transaction list and actions

P1 | Staging | Result: Not Run

Purpose: Lets the administrator investigate the transactions behind a business summary and open the corresponding receipt.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Open Transactions from Business Details.
2. Filter, paginate, preview a receipt and export.

Expected result: Merchant scope remains fixed. Actions open the exact record and are clearly labeled without duplicate controls.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REG-012 / Registry search and export

P1 | Staging | Result: Not Run

Purpose: Makes the registry searchable and exportable without losing filter consistency or authorization scope.

Preconditions: Actor: Applicant / Merchant / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Combine name/TIN/type/status/industry/registration dates.
2. Reset; export the result.

Expected result: Counts, rows and exported scope agree. Clear empty/error states and no stale filters.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

05 / Users, branches and terminals

8 test cases / TEAM / All results: Not Run

Feature purpose / Para saan ito

User roles, branches and terminals let a merchant delegate work while restricting the records and operations available to each staff member. Branch identity and device registration also identify the source of a transaction.

> **Plain-language explanation**
> Para saan: makapagbigay ng access sa staff ayon sa trabaho, branch at terminal nang hindi binubuksan ang lahat ng merchant data.

Where it is used

Merchant Users, branch registry and API/POS terminal configuration; administrative branch review.

Workflow to follow

Invite user -> accept membership -> assign capability/branch -> register terminal -> enforce scope -> revoke when needed.

Prepare before testing

Prepare owner and restricted staff accounts across two branches, controlled invitation mailboxes and valid/expired terminal assignments.

Capture baseline: Record membership, role, branch, terminal and review revision before the test.

Evidence and cross-check

Invitation and membership result, permission matrix, scoped query results, terminal assignment and revocation audit.

Check carefully: Changing a browser filter or reusing an old session must not widen a user or terminal beyond the assigned scope.

TEAM-001 / Invite and accept team member

P0 | Staging | Result: Not Run

Purpose: Adds a staff member through an expiring invitation tied to an explicit role and branch.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Invite controlled mailbox with a restricted role and branch.
2. Accept once; reuse and expire the invitation.

Expected result: Exactly one scoped membership is created. Expired/replayed invitations cannot grant access.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

TEAM-002 / Role capabilities

P0 | Staging | Result: Not Run

Purpose: Ensures delegated staff can perform only the work granted to their role.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Run view/create/export/settings actions as each restricted staff role.

Expected result: Only assigned capabilities work, including direct endpoint calls.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

TEAM-003 / Permission revocation

P0 | Staging | Result: Not Run

Purpose: Stops a removed permission from remaining usable through an existing session.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Remove a staff permission or membership while the staff tab is open; retry the action.

Expected result: Revoked access stops server-side immediately according to session policy.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

TEAM-004 / User directory filters and export

P1 | Staging | Result: Not Run

Purpose: Makes user access review accurate across searches, pages and exported records.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Search name/email; combine role, branch and status; export and paginate.

Expected result: No duplicate users, missing owner or out-of-scope accounts. Export follows the filters.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

TEAM-005 / Branch registration and identity

P0 | Staging | Result: Not Run

Purpose: Keeps branch identifiers unique and preserves registered identity after activation.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Create draft and complete branch data.
2. Test duplicate codes and attempt to change a registered immutable code.

Expected result: Allowed draft behavior works; registered identity constraints and review history are preserved.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

TEAM-006 / Branch evidence and approval

P0 | Staging | Result: Not Run

Purpose: Links branch approval to reviewed evidence and detects changes that invalidate the prior review.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Upload private branch evidence; approve as authorized reviewer; change protected identity afterward.

Expected result: Evidence is protected. A material identity change requires the documented re-review.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

TEAM-007 / Terminal assignment

P0 | Staging | Result: Not Run

Purpose: Associates a terminal with the correct active merchant/branch authorization.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Assign a test terminal to an approved merchant branch.
2. Try foreign branch, expired authority and stale revision.

Expected result: Only valid scoped assignment succeeds. Invalid assignment cannot authorize transaction intake.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

TEAM-008 / Inactive branch and connection claims

P1 | Staging | Result: Not Run

Purpose: Prevents inactive branches or unverified merchant claims from enabling unsupported transaction authority.

Preconditions: Actor: Merchant owner / staff / Admin. Fixtures: D01, D05. Complete the module setup and baseline first.

Procedure

1. Suspend a branch.
2. Submit a request or merchant claim that it is connected/BIR approved.

Expected result: Applicable writes stop. API activity alone cannot establish BIR approval or verified connectivity.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

06 / Invoice lifecycle and numbering

12 test cases / INV / All results: Not Run

Feature purpose / Para saan ito

Invoice processing turns a draft or captured source document into a uniquely identified financial record. Numbering, corrections and supplementary documents preserve document history and prevent one business event from being counted twice.

> **Plain-language explanation**
> Para saan: tama at traceable ang invoice number, isang beses lamang ma-issue ang document, at hindi mabago nang tahimik ang issued financial record.

Where it is used

Create Invoice, Invoices and Receipts, electronic invoice center and source-capture API.

Workflow to follow

Prepare draft/source -> validate identity and registration -> reserve eligible number -> commit issued document -> view/copy -> correct through linked workflow.

Prepare before testing

Use active, expired and exhausted test series. Prepare colliding visible numbers across different merchants and record their separate internal IDs.

Capture baseline: Record series counter, document count, source identity, wallet balance and any original-document link.

Evidence and cross-check

Invoice/source IDs, printed number, number allocation before/after, financial record count and applicable wallet entry.

Check carefully: The same event must not become two sales. Issued and voided document history must remain traceable through corrections and reprints.

INV-001 / Draft to issued invoice

P0 | Staging | Result: Not Run

Purpose: Allows review of a draft before creating the final numbered financial document and applicable fee.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Create a draft, add buyer/items, save, reopen and issue using an approved test series.

Expected result: Draft persists. Issuance creates one immutable numbered document and one applicable fee debit.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-002 / Required invoice fields

P0 | Staging | Result: Not Run

Purpose: Stops incomplete invoices before they consume a number, charge the wallet or enter reports.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Omit required seller/buyer/date/item/registration fields one at a time for each supported document type.

Expected result: Clear field validation blocks invalid issuance without advancing the number or debiting wallet.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-003 / Registered series and branch scope

P0 | Staging | Result: Not Run

Purpose: Restricts document numbering to the correct active series, branch and permitted range.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Issue using active, missing, expired, exhausted and wrong-branch series.

Expected result: Only the correct active series issues within its approved range and preserves formatting.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-004 / Concurrent numbering

P0 | Isolated lab | Result: Not Run

Purpose: Avoids duplicate invoice numbers when several users or workers issue documents simultaneously.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Issue multiple documents concurrently in one branch and in separate branches.

Expected result: Unique, ordered series allocation within each scope. No duplicate number or cross-branch collision.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-005 / Rollback does not consume number

P0 | Isolated lab | Result: Not Run

Purpose: Keeps number reservation, financial records and fees consistent when an issue operation fails.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Force failure after number reservation but before transaction commit.
2. Retry the valid issue.

Expected result: No partial financial record or charge. Transactional reservation rolls back consistently.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-006 / Void number is never reused

P0 | Staging | Result: Not Run

Purpose: Preserves the historical identity of a voided invoice rather than recycling its number.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Void an issued test invoice and attempt to reuse its number.

Expected result: Original number/history remain preserved. Reuse is rejected.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-007 / External ERP invoice numbers

P0 | Staging | Result: Not Run

Purpose: Retains the ERP/POS document number as originally recorded while maintaining a separate NUERS reference.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Capture valid source invoice identifiers with leading zeros/prefixes; try invalid format and duplicate identity.

Expected result: Source number is printed unchanged when valid. NUERS reference remains separate; conflicts are not overwritten.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-008 / Same invoice number across merchants

P0 | Staging | Result: Not Run

Purpose: Disambiguates identical visible invoice numbers belonging to different merchants.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Create the same visible number under A and B.
2. Open each from merchant, admin and PDF routes.

Expected result: Lookup resolves the exact authorized merchant/document identity every time.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-009 / Issued document edits and cancellation

P0 | Staging | Result: Not Run

Purpose: Prevents silent rewriting of issued financial history and supports traceable corrections.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Try editing totals/identity after issuance.
2. Use the supported cancel/correction workflow with evidence.

Expected result: Issued financial history is preserved. Changes require the appropriate linked record and audit trail.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-010 / Sales invoice versus payment copy

P1 | Staging | Result: Not Run

Purpose: Separates evidence of payment from the sale so revenue and fees are not counted twice.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Issue an invoice and record its payment or supplementary document.
2. Compare sales totals and fee ledger.

Expected result: Payment copy is linked and not counted as a second sale or charged again.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-011 / Buyer and customer selection

P1 | Staging | Result: Not Run

Purpose: Places the intended customer details on the invoice without creating unintended duplicate customer records.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Select an existing customer, add a new one and switch customers before issue.

Expected result: Correct buyer data is saved. Failed/draft operations do not create unintended duplicate customers.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

INV-012 / Print registration and POS fields

P1 | Staging | Result: Not Run

Purpose: Prints the applicable recorded system/branch registration details without inventing missing authority.

Preconditions: Actor: Merchant issuer / Admin. Fixtures: D04, D06. Complete the module setup and baseline first.

Procedure

1. Preview applicable CAS and POS documents with supplied registration/branch/MIN/MSN evidence.

Expected result: Applicable recorded registration fields appear correctly. Missing evidence is not fabricated.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

07 / Amounts, tax and discounts

14 test cases / CALC / All results: Not Run

Feature purpose / Para saan ito

The calculation layer determines line values, discounts, tax buckets, withholding and payable totals. It must preserve exact centavos and the distinctions between ordinary discounts and reviewed statutory-benefit treatment.

> **Plain-language explanation**
> Para saan: pare-pareho ang computation sa API, dashboard, receipt at report, at tama ang discount at tax classification.

Where it is used

Invoice creation, integration ingestion, statutory sales, withholding memos, receipts and reports.

Workflow to follow

Validate amounts -> classify lines -> apply permitted discount rules -> allocate rounding -> derive tax/withholding -> reconcile document total.

Prepare before testing

Use an independently reviewed calculation oracle. Include VAT-inclusive/exclusive, exempt, zero-rated, benefit-eligible/ineligible and centavo-boundary fixtures.

Capture baseline: Record original line prices, quantities, tax classes, discount mode/reason and expected base/VAT/payable values before submitting.

Evidence and cross-check

Input fixture, independent calculation, persisted line and document totals, receipt/PDF and matching report row.

Check carefully: Displayed totals are not their own oracle. Compare against the approved fixture, and treat any unexplained centavo difference as a defect.

CALC-001 / Basic VAT-inclusive fixture

P0 | Staging | Result: Not Run

Purpose: Establishes a simple known arithmetic baseline against which API, UI and report calculations can be compared.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Issue the approved fixture with one VAT-inclusive PHP 1,120 item.
2. Compare API, UI, PDF and report.

Expected result: Fixture totals: taxable base PHP 1,000; VAT PHP 120; total PHP 1,120. All views reconcile.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-002 / VAT-exclusive, exempt and zero-rated

P0 | Staging | Result: Not Run

Purpose: Keeps each tax classification distinct and handles mixed documents without taxing the same value twice.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Run independently approved fixtures for each classification and a mixed document.

Expected result: Line and document tax buckets match the approved oracle without double-taxing or relabeling sales.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-003 / Manual fixed discount

P0 | Staging | Result: Not Run

Purpose: Applies a fixed ordinary discount consistently to the amount and the resulting tax base.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Apply PHP 112 document discount to the PHP 1,120 inclusive fixture with a reason.

Expected result: Manual discount PHP 112; taxable PHP 900; VAT PHP 108; total PHP 1,008. Reason persists.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-004 / Manual percentage and line discounts

P0 | Staging | Result: Not Run

Purpose: Confirms equivalent supported discount representations produce the same financial outcome.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Run equivalent 10% document and line discounts; also test legacy supported discount input.

Expected result: Equivalent fixtures reconcile. Manual and statutory discount totals remain separately identified.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-005 / Fractional rounding and allocation

P0 | Staging | Result: Not Run

Purpose: Distributes centavo rounding deterministically so line amounts always reconcile to the document.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Allocate a PHP 0.01 discount over three PHP 0.01 non-VAT lines.
2. Test fractional quantities and mixed tax lines.

Expected result: Allocation is deterministic and exact to centavos; line totals sum to the immutable document total.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-006 / Invalid discounts and totals

P0 | Staging | Result: Not Run

Purpose: Prevents invalid discounts or inconsistent declared totals from entering financial records.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Use negative/over-limit discounts, conflicting input modes and a mismatched declared total.

Expected result: Request is rejected before financial writes, numbering, wallet debit or email scheduling.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-007 / Senior citizen sale

P0 | Staging | Result: Not Run

Purpose: Records reviewed senior citizen treatment with the appropriate eligibility evidence and reporting category.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Run approved eligible/ineligible senior citizen fixtures with identity evidence and mixed eligible items.

Expected result: Calculation, evidence, invoice labels and senior sales report match the reviewed business-rule oracle.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-008 / PWD sale

P0 | Staging | Result: Not Run

Purpose: Records reviewed PWD treatment without granting a benefit to unsupported lines or missing evidence.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Run approved eligible/ineligible PWD fixtures and mixed eligible items.

Expected result: Calculation, evidence and PWD report reconcile to issued documents.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-009 / National athlete and coach sale

P0 | Staging | Result: Not Run

Purpose: Applies the reviewed athlete/coach treatment only when the required eligibility conditions are evidenced.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Run athlete and coach fixtures with valid and missing eligibility evidence.

Expected result: Applicable approved rules are used; unsupported eligibility is rejected or sent to required review.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-010 / Solo-parent sale

P0 | Staging | Result: Not Run

Purpose: Applies reviewed solo-parent rules to the supported goods, scope and eligibility period.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Run approved item/scope/eligibility fixtures, including missing evidence and boundary dates.

Expected result: Only supported eligible sales receive the approved treatment; solo-parent report reconciles.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-011 / Manual and statutory discount interaction

P0 | Staging | Result: Not Run

Purpose: Prevents unsupported discount stacking while allowing supported discounts on separately classified lines.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Try overlapping discounts on an ineligible combination; then manual discount on a separate regular line beside a benefit line.

Expected result: Unsupported overlap is rejected. Supported separate-line treatment remains distinctly recorded.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-012 / Withholding and CWT memo

P0 | Staging | Result: Not Run

Purpose: Separates withholding from gross sales and VAT and preserves the original when a memo is recorded.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Use valid structured withholding and invalid/excess withholding.
2. Create a supported linked CWT memo.

Expected result: Gross, VAT, withholding and payable amounts reconcile. Original invoice values are not silently changed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-013 / Service charges and other charges

P1 | Staging | Result: Not Run

Purpose: Includes service and other charges once, under the correct classification.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Use approved fixtures with service/other charges, zero charges and item-level tax classifications.

Expected result: Charges are counted exactly once and displayed consistently in totals and reports.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

CALC-014 / Currency, precision and boundaries

P0 | Staging | Result: Not Run

Purpose: Prevents invalid currency or numeric precision from producing ambiguous or unreconcilable money values.

Preconditions: Actor: Merchant / API tester / finance QA. Fixtures: D07, D08. Complete the module setup and baseline first.

Procedure

1. Try zero where allowed, negative totals, maximum supported values, excess decimals and unsupported currency.

Expected result: Supported PHP values use exact centavos and peso formatting. Unsupported values fail clearly.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

08 / E-receipts, PDFs and branding

10 test cases / RCP / All results: Not Run

Feature purpose / Para saan ito

Receipt views, printable copies and PDFs present the recorded document to merchants, administrators and customers. Branding identifies the merchant while the underlying financial content must remain consistent in every copy.

> **Plain-language explanation**
> Para saan: makita at ma-download ang mismong merchant receipt, gamit ang invoice branding, na pareho ang details at totals sa lahat ng channel.

Where it is used

Admin View Receipt, merchant invoice/receipt details, invoice settings preview, PDF download, print and email attachment.

Workflow to follow

Authorize exact document -> load recorded details -> apply invoice branding -> render preview/PDF -> deliver permitted copy.

Prepare before testing

Use distinct profile/invoice logos and all supported templates. Include long text, Unicode, many items and broken/absent-image fixtures.

Capture baseline: Record the exact source/merchant/document ID, invoice number, line count, totals and configured invoice logo.

Evidence and cross-check

Preview screenshot, PDF or attachment hash, extracted totals, page count and original-record before/after comparison.

Check carefully: The removed Record Evidence/verification/custom-footer section stays absent. Receipt identity, item details and tax totals remain complete.

RCP-001 / Admin receipt viewer

P0 | Staging | Result: Not Run

Purpose: Lets administrators inspect the actual merchant document when investigating a transaction.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Open View Receipt from admin transactions, recent transactions and business transaction list.

Expected result: Exact merchant-branded receipt opens rather than transaction-only metadata.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-002 / Merchant receipt viewer

P0 | Staging | Result: Not Run

Purpose: Lets the merchant review the same financial document used by administrative and delivery views.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Open the same document from merchant invoice/receipt lists and details.

Expected result: Number, date, buyer, items, taxes and total agree with the admin view.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-003 / Removed receipt section globally

P1 | Staging | Result: Not Run

Purpose: Enforces the approved global removal while ensuring essential invoice content is not removed with it.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Inspect standard, minimal and detailed previews; generate PDFs and captured email copies.

Expected result: Record Evidence, verification/QR notice and removed custom footer notes are absent. Items, tax breakdown and totals remain.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-004 / Separate invoice logo

P1 | Staging | Result: Not Run

Purpose: Ensures the invoice-branding setting controls the receipt logo independently of the account picture.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Change invoice branding and compare profile image, preview, PDF and captured email copy.

Expected result: Receipt outputs use the invoice logo and configured colors. Profile image stays independent.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-005 / Logo validation and fallback

P1 | Staging | Result: Not Run

Purpose: Keeps image uploads safe and the document usable when branding is absent or invalid.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Use permitted image types, transparent image, missing image, invalid MIME and oversized upload.

Expected result: Valid image is legible; invalid uploads fail; missing image has an intentional fallback without a broken layout.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-006 / Long and multi-page receipt

P1 | Staging | Result: Not Run

Purpose: Preserves readable complete documents when real-world text and item counts exceed a short sample.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Use many items, long descriptions, Unicode names and long addresses.
2. Generate print/PDF.

Expected result: No clipped columns, missing lines or overlaps. Pagination and totals remain readable.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-007 / PDF integrity and audit

P0 | Staging | Result: Not Run

Purpose: Produces an authorized, valid PDF copy without changing the underlying financial record.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Download through admin and merchant authenticated routes; inspect type and contents; compare record afterward.

Expected result: Valid PDF for the requested document. Viewing/downloading does not change original financial data.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-008 / Print behavior

P1 | Staging | Result: Not Run

Purpose: Provides a usable paper copy with complete financial details and no application controls.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Use browser print and PDF print at supported paper sizes.

Expected result: Only intended document content prints with usable margins, peso symbol and complete totals.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-009 / Renderer failure and retry

P1 | Isolated lab | Result: Not Run

Purpose: Lets a user recover from PDF-service failure without recreating the sale.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. In lab, make PDF service unavailable or exceed a supported limit.
2. Retry after recovery.

Expected result: Clear bounded error; no endless loading, duplicate sale or lost record.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

RCP-010 / Receipt copy security

P0 | Staging | Result: Not Run

Purpose: Protects the receipt-copy endpoint and renderer against unauthorized data and unsafe embedded content.

Preconditions: Actor: Merchant / Admin / recipient. Fixtures: D04, D06, D09. Complete the module setup and baseline first.

Procedure

1. Use expired session, foreign receipt ID and unsafe text/URL content in a test receipt.

Expected result: Access is denied or content is safely rendered; renderer cannot fetch arbitrary private resources.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

09 / ERP, POS and ecommerce intake

18 test cases / API / All results: Not Run

Feature purpose / Para saan ito

The transaction API accepts merchant sales from ERP, POS and ecommerce systems and returns a stable NUERS outcome. Identity, validation, idempotency and atomic processing protect against duplicates, partial batches and wrongly attributed data.

> **Plain-language explanation**
> Para saan: maipasa nang ligtas ang sale sa NUERS at makita sa source system kung successful, rejected o hindi pa tiyak ang resulta.

Where it is used

Merchant integration endpoints, API keys/source profiles, integrating system status UI and failed-attempt monitoring.

Workflow to follow

Authenticate key -> validate merchant/branch/source -> check event identity and funding -> commit atomically -> return outcome -> recover safe retries.

Prepare before testing

Use staging keys, a controlled integration client and unique request/event IDs. Preserve a canonical payload for duplicate/retry tests and a mail sink for delivery checks.

Capture baseline: Record source event ID, payload hash, merchant/branch/environment, document count, wallet balance and pending delivery-job count.

Evidence and cross-check

Redacted request/response, correlation ID, persisted record, wallet debit, source-system status and delivery-job counts.

Check carefully: A client timeout does not prove failure. A request that never reaches NUERS cannot appear as a received transaction until actual evidence arrives.

API-001 / Valid finalized sale

P0 | Staging | Result: Not Run

Purpose: Accepts one properly attributed finalized sale and makes its stable outcome visible across NUERS.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. POST a valid source-capture sale using the active scoped key.
2. Read its status and both dashboards.

Expected result: One accepted source record with stable identifiers, correct totals and one applicable fee.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-002 / Authentication variants

P0 | Staging | Result: Not Run

Purpose: Ensures only an active appropriately scoped integration credential can submit a transaction.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Test missing, invalid, expired, revoked and wrong-scope API keys plus IP restriction mismatch.

Expected result: Request fails with the documented safe status/reason and no sale or wallet change.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-003 / Merchant and branch binding

P0 | Staging | Result: Not Run

Purpose: Prevents an API client from selecting a different owner or branch by changing payload fields.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Put another merchant ID, source profile or branch in a request authenticated with A key.

Expected result: Server derives ownership from authorized key/scope and rejects mismatches.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-004 / Identical retry

P0 | Staging | Result: Not Run

Purpose: Makes an identical retry safe when an integrator is unsure whether the first request completed.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Submit the same event/request identity and identical payload repeatedly.

Expected result: One sale and one fee only. Retry returns the existing outcome and identifiers.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-005 / Changed-payload conflict

P0 | Staging | Result: Not Run

Purpose: Prevents a reused event identity from silently overwriting accepted financial data.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Reuse an accepted identity with a different amount, discount, buyer or source content.

Expected result: Conflict is returned. Original record and wallet remain unchanged.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-006 / Concurrent retries

P0 | Isolated lab | Result: Not Run

Purpose: Avoids duplicate sales, charges and receipt jobs when concurrent retries arrive together.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Send the same valid event concurrently from multiple workers.

Expected result: Exactly one acceptance, fee and customer-email request. Other outcomes are documented retries/conflicts.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-007 / Lost response after commit

P0 | Isolated lab | Result: Not Run

Purpose: Recovers an accepted transaction after the client loses the response without charging again.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. In lab, drop the client response after successful commit.
2. Retry with the same identity.

Expected result: Original acceptance is recovered without a duplicate sale or debit.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-008 / Atomic batch

P0 | Staging | Result: Not Run

Purpose: Keeps all operations in an atomic batch consistent when any required event or funding check fails.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Submit a valid batch, then a batch with one invalid event and one exceeding total wallet funding.

Expected result: Valid batch follows contract. Rejected atomic batch leaves no partial sales, fees, sequence or mail jobs.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-009 / API limits and content validation

P1 | Staging | Result: Not Run

Purpose: Bounds processing cost and rejects unsupported payload formats before partial work occurs.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Test max payload/batch/item limits, malformed JSON, wrong content type and unknown required schema version.

Expected result: Limits and errors match the documented contract without memory exhaustion or partial writes.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-010 / Live and Sandbox isolation

P0 | Staging | Result: Not Run

Purpose: Lets integrators test safely without mixing Sandbox activity into Live funds, sales or customer email.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Use separate keys and try environment overrides.
2. Inspect dashboard, wallet, export and email behavior.

Expected result: Sandbox stays distinct; it does not debit Live wallet, send real customer email or increase Live sales.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-011 / Source authority and registration

P0 | Staging | Result: Not Run

Purpose: Ties source-captured records to an active reviewed source identity and registration scope.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Try active, expired, wrong-merchant and incomplete source profiles.

Expected result: Required source review and registration controls are enforced consistently without forged authority.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-012 / NUERS status in integrating system

P0 | Staging | Result: Not Run

Purpose: Gives the source system an actionable NUERS outcome for each sale instead of an unexplained spinner or generic error.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. In a test ERP/POS/ecommerce, show successful, validation-failed, insufficient-wallet, throttled and uncertain requests.

Expected result: Each sale shows NUERS Success or Error with actionable reason, reference and safe retry behavior.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-013 / BIR status omitted from merchant intake contract

P0 | Staging | Result: Not Run

Purpose: Keeps NUERS transaction status distinct from the deprecated BIR verification field in the merchant intake contract.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Inspect current and supported legacy intake/status responses and integration documentation.

Expected result: No deprecated BIR Not_verified field is presented as the NUERS transaction outcome.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-014 / API status lookup and paging

P1 | Staging | Result: Not Run

Purpose: Lets a client retrieve its own current outcome through bounded, authorized responses.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Read accepted/failed event status with right and foreign keys; page large result sets.

Expected result: Stable bounded responses, correct scope and no payload/credential leakage.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-015 / Invalid attempts visible

P0 | Staging | Result: Not Run

Purpose: Makes received failures discoverable for support without treating a rejection as a successful sale.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Send authenticated invalid payload, insufficient-wallet request and rate-limited request.
2. Open admin failed attempts.

Expected result: Received failure appears with merchant, environment, time and safe reason; it is not counted as an accepted sale.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-016 / Request never reaches NUERS

P1 | Staging | Result: Not Run

Purpose: Distinguishes an unsent local transaction from a request actually received by NUERS.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Disconnect the test integration before transmission.
2. Inspect integration outbox and NUERS dashboard.

Expected result: Integration shows pending/error locally. NUERS does not invent a received transaction it never observed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-017 / Manual discount end to end

P1 | Staging | Result: Not Run

Purpose: Carries manual discount data faithfully through intake, storage, receipt and reporting.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Send fixed and percentage manual discounts through the API, then compare receipt, admin list, report and export.

Expected result: Discount amounts, reasons and totals persist unchanged across every representation.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

API-018 / Contract examples and version parity

P1 | Staging | Result: Not Run

Purpose: Keeps published integration examples and actual API behavior consistent for developers.

Preconditions: Actor: Integration QA. Fixtures: D04, D07, D10. Complete the module setup and baseline first.

Procedure

1. Run valid and invalid examples from website and downloadable API guide against staging.

Expected result: Published request fields, status codes, errors and examples match current behavior and declared version.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

10 / Customer email, notifications and webhooks

10 test cases / MAIL / All results: Not Run

Feature purpose / Para saan ito

Email and notifications communicate receipt copies and operational events to the intended recipient. Webhooks provide machine-readable updates to merchant systems, with signatures and retry rules to support reliable delivery.

> **Plain-language explanation**
> Para saan: awtomatikong maibigay ang e-receipt at tamang alerts, at ma-update ang connected system nang walang duplicate o maling recipient.

Where it is used

Customer receipt-delivery queue, notification center/preferences, SMTP settings and merchant webhooks.

Workflow to follow

Commit event -> enqueue intended delivery -> render/sign -> send -> record delivery outcome -> retry only according to policy.

Prepare before testing

Use a controlled email sink and HTTPS receiver. Simulate accepted, rejected and ambiguous delivery without contacting actual customers.

Capture baseline: Record recipient alias, document/event ID, permitted notification recipients and the existing delivery-job count.

Evidence and cross-check

Delivery ID, redacted recipient, captured payload/attachment hash, signature verification and attempt/retry history.

Check carefully: Mail or callback failure must not repeat the underlying sale. A delivery status must not imply BIR acceptance.

MAIL-001 / Automatic receipt email

P0 | Staging | Result: Not Run

Purpose: Delivers the customer copy automatically when a valid sale supplies an intended email address.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Finalize a valid Live-mode test sale with a controlled customer email using the staging mail sink.

Expected result: One receipt-delivery job for that recipient with the correct merchant document and branding.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-002 / Absent or invalid email

P1 | Staging | Result: Not Run

Purpose: Avoids unwanted delivery jobs for missing addresses and prevents invalid addresses from causing partial processing.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Submit without email, then with malformed email.

Expected result: Absent email does not schedule mail. Invalid email follows the documented validation result with no partial financial write.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-003 / Retry and batch mail deduplication

P0 | Staging | Result: Not Run

Purpose: Prevents retries or failed batches from sending duplicate or nonexistent receipts.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Retry an accepted emailed sale; reject an atomic batch after validation.

Expected result: Retry does not resend automatically; rolled-back batch schedules no receipt mail.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-004 / SMTP failure and uncertainty

P1 | Isolated lab | Result: Not Run

Purpose: Keeps delivery uncertainty separate from the committed financial outcome.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Simulate rejection, timeout and ambiguous SMTP completion.
2. Check sale outcome and delivery history.

Expected result: Sale is not reversed/repeated. Delivery has an accurate retryable/uncertain state and bounded retries.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-005 / Manual resend authorization

P0 | Staging | Result: Not Run

Purpose: Allows an authorized resend while protecting other merchants documents from disclosure.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. As authorized merchant, resend to a controlled approved recipient.
2. Attempt foreign-document resend.

Expected result: Authorized send is audited with correct attachment. Foreign or unauthorized resend is denied.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-006 / Notification targeting

P1 | Staging | Result: Not Run

Purpose: Shows business events only to their intended account recipients.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Trigger low balance, profile review and transaction-related notifications for A.
2. Sign in as B.

Expected result: Only intended recipients see notifications; read/unread state and links resolve correctly.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-007 / Notification preferences and SMTP settings

P1 | Staging | Result: Not Run

Purpose: Lets authorized users manage delivery preferences and mail configuration without exposing credentials.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Change supported preferences; test admin SMTP save/test and non-admin access.

Expected result: Preferences apply per user. Secrets stay masked and unauthorized configuration is denied.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-008 / Signed outbound webhook

P0 | Staging | Result: Not Run

Purpose: Lets a merchant receiver authenticate a webhook payload and associate it with the correct event.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Send to the controlled HTTPS receiver.
2. Verify signature and event identity using documented example code.

Expected result: Receiver can authenticate the exact payload; event maps to the correct tenant and environment.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-009 / Webhook replay, timeout and ordering

P0 | Isolated lab | Result: Not Run

Purpose: Supports reliable asynchronous delivery without replaying the underlying business transaction.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Replay a delivery; return 5xx/timeout; process out-of-order deliveries.

Expected result: Receiver deduplicates; NUERS retries within policy and preserves delivery evidence without duplicate sales.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

MAIL-010 / Webhook target security

P0 | Isolated lab | Result: Not Run

Purpose: Prevents webhook configuration from sending sensitive data to unsafe or unauthorized destinations.

Preconditions: Actor: Integration QA / Merchant / Admin. Fixtures: D09, D10, D11. Complete the module setup and baseline first.

Procedure

1. Attempt private-network/loopback target, redirect and another merchant webhook configuration.

Expected result: Unsafe or unauthorized destinations are rejected. Secrets are not disclosed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

11 / Wallet, deposits and pricing

14 test cases / WAL / All results: Not Run

Feature purpose / Para saan ito

The wallet funds eligible NUERS transaction fees and records deposits, deductions and adjustments. Administrative pricing controls the fee and minimum eligible transaction amount, while the ledger preserves historical charges.

> **Plain-language explanation**
> Para saan: makita ang natitirang prepaid balance at matiyak na tama at isang beses lamang ang singil sa eligible transaction.

Where it is used

Merchant dashboard wallet card, Wallet/Top-Up, admin Wallets and Transaction Pricing, ledger statements.

Workflow to follow

Fund request -> independent review -> posted credit -> eligibility/funding check -> single fee debit -> reconcile available balance.

Prepare before testing

Use synthetic funds with PHP 3 fee and minimum 0 or 500. Include exact/insufficient balances and distinct requester/reviewer accounts.

Capture baseline: Record opening balance, pricing revision, eligible sale count and posted versus pending credit/debit entries.

Evidence and cross-check

Before/after balances, accepted event IDs, fee/pricing revision, credit approval and a ledger reconciliation.

Check carefully: Opening balance + posted credits - posted debits = closing balance. Pending top-ups are not spendable funds.

WAL-001 / Zero minimum charges every eligible sale

P0 | Staging | Result: Not Run

Purpose: Makes a zero minimum mean every eligible finalized Live sale is chargeable under the selected fee.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Set test fee PHP 3 and minimum PHP 0.
2. Accept five distinct finalized eligible Live-mode sales.

Expected result: Total NUERS charges PHP 15. No amount exemption applies to valid eligible sales.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-002 / Configurable minimum boundaries

P0 | Staging | Result: Not Run

Purpose: Applies the administrator minimum precisely at its boundary rather than retaining the old fixed exemption.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Set minimum PHP 500 and fee PHP 3.
2. Submit valid amounts PHP 499.99, 500.00 and 500.01.

Expected result: Below minimum is uncharged; at/above minimum charged once each. Admin configuration is authoritative.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-003 / Pricing permission and history

P0 | Staging | Result: Not Run

Purpose: Lets only authorized administrators change pricing and preserves the fee originally applied to older records.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Change fee/minimum as Super Admin; try as merchant/ordinary unauthorized role.
2. Reopen earlier debits.

Expected result: Only authorized pricing changes work. Historical fees retain their original rate/revision.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-004 / Exact and insufficient balance

P0 | Staging | Result: Not Run

Purpose: Allows an exactly funded sale while stopping an underfunded sale before any partial commit.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Use PHP 3 balance for a PHP 3 fee; then PHP 2.99.
2. Repeat through API and portal.

Expected result: Exact funding succeeds once. Insufficient balance rejects without sale, sequence consumption or negative balance.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-005 / Concurrent wallet spends

P0 | Isolated lab | Result: Not Run

Purpose: Prevents concurrent transactions from spending the same available balance multiple times.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Start several paid issues simultaneously with funds sufficient for only some.

Expected result: Successful commits reconcile to available funds; no overdraft, duplicate fee or partial accepted record.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-006 / Draft and supplementary fee policy

P0 | Staging | Result: Not Run

Purpose: Distinguishes draft/finalized/supplementary activity so the wallet is charged at the intended event only.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Save draft, publish once, then create supported payment copy/adjustment and retry it.

Expected result: Funding check follows policy; actual fee is once per eligible finalized sale, without duplicate charging.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-007 / Merchant wallet card and Top-Up

P1 | Staging | Result: Not Run

Purpose: Gives the merchant a current available balance and a direct route to request funding.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Compare dashboard Available Wallet card with Wallet page and posted ledger.
2. Open Top-Up.

Expected result: Same available amount with peso currency; button opens the correct funding workflow.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-008 / Submit funding request

P0 | Staging | Result: Not Run

Purpose: Records a funding request without treating unapproved funds as available money.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Request top-up with required method/reference/evidence.
2. Re-submit same request.

Expected result: One pending request; available balance is unchanged until approved credit.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-009 / Independent top-up approval

P0 | Staging | Result: Not Run

Purpose: Requires the intended independent review and prevents duplicate credits from repeated approval.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Review a request as authorized independent reviewer; test self-approval and repeated approval.

Expected result: Policy is enforced. Exactly one posted credit; requester cannot bypass independent review.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-010 / Reject or cancel funding

P0 | Staging | Result: Not Run

Purpose: Ensures rejected or cancelled funding requests never increase the wallet balance.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Reject/cancel a pending request with reason; retry approval afterward.

Expected result: No credited funds. Final state and review history are consistent.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-011 / Withdrawals and ledger integrity

P0 | Isolated lab | Result: Not Run

Purpose: Keeps ledger changes traceable, balanced and resistant to duplicate or tampered adjustment requests.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Exercise permitted withdrawal/adjustment with evidence, then tampered or duplicate identifiers in the lab.

Expected result: Ledger stays balanced, immutable and attributable; unsupported debit/credit is denied.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-012 / Wallet history and statements

P1 | Staging | Result: Not Run

Purpose: Provides a statement that independently reconciles the displayed wallet balance.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Filter date/type/status; page and export wallet entries.
2. Compare opening + credits - debits = closing.

Expected result: Statement and displayed balances reconcile in centavos for the same scope.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-013 / Low-balance threshold

P1 | Staging | Result: Not Run

Purpose: Warns the correct merchant before insufficient funds interrupt eligible sales.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Set permitted threshold; cross it using test transactions; replenish and cross again.

Expected result: Correct targeted notices and current balance; no alert storm or cross-merchant notification.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

WAL-014 / Admin wallet totals

P1 | Staging | Result: Not Run

Purpose: Aggregates merchant financial positions without mixing pending, Sandbox or unposted amounts into Live balances.

Preconditions: Actor: Merchant / Super Admin / finance QA. Fixtures: D07, D12. Complete the module setup and baseline first.

Procedure

1. Compare total available wallet, credited deposits, fees, withdrawals and pending requests against two-merchant fixture.

Expected result: Each metric uses its labeled basis. Pending deposits and Sandbox sales are excluded from posted Live balances.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

12 / Dashboards and live monitoring

9 test cases / DASH / All results: Not Run

Feature purpose / Para saan ito

Dashboards summarize financial and operational activity so administrators and merchants can monitor the correct scope without opening individual records. Realtime refresh should update committed changes while preserving the user context.

> **Plain-language explanation**
> Para saan: mabilis makita ang sales, fees, wallet at activity, at mapagkatiwalaan ang mga bilang at oras na ipinapakita.

Where it is used

Super Admin dashboard, Merchant dashboard, Live Transaction Monitoring, merchant connection summaries.

Workflow to follow

Commit activity -> revise scoped summary -> refresh active view -> preserve filters/selection -> show freshness and errors accurately.

Prepare before testing

Use independently counted fixtures across merchants, states, environments and PHT date boundaries. Include offline and slow-response simulations.

Capture baseline: Record the metric definition, merchant/environment/period and independent expected count or amount.

Evidence and cross-check

Before/after metric screenshots, commit/refresh timestamps, network-call trace and independent fixture totals.

Check carefully: Do not combine source documents, payment events and failed attempts as if all were successful sales. Unknown telemetry stays unknown.

DASH-001 / Sales and transaction reconciliation

P0 | Staging | Result: Not Run

Purpose: Makes operational counts represent their documented populations rather than double-counting payment copies or failures.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Create a fixture with issued, failed, pending, cancelled and supplementary records.
2. Compare admin and merchant metrics.

Expected result: Counts and amounts use documented definitions; payment copies and failed attempts are not double-counted as sales.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-002 / Admin financial widgets

P1 | Staging | Result: Not Run

Purpose: Gives the administrator reliable financial totals and clear merchant-based labels.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Check transaction amount, NUERS charged, merchant wallet, deposits and Registered Merchants.

Expected result: All widgets match independent fixture totals, correct labels, period and peso formatting.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-003 / Merchant daily metrics

P1 | Staging | Result: Not Run

Purpose: Shows each merchant its own daily activity under the correct PHT period.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Compare daily sales, issued invoices, transactions, failures and wallet with merchant source data.

Expected result: Only that merchant and the stated PHT period are included.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-004 / Live charts and merchant connections

P1 | Staging | Result: Not Run

Purpose: Displays observed transaction flow and connection activity rather than replaying historical traffic.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Create new activity, then inspect flow, distribution, region and connection tables.

Expected result: Charts and timestamps reflect observed activity. Historical rows are not replayed as current traffic.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-005 / Today and midnight boundary

P1 | Staging | Result: Not Run

Purpose: Assigns transactions to the correct reporting day at PHT date boundaries.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Use records at 23:59:59 and 00:00:00 PHT, prior days and future times.

Expected result: Correct PHT date boundaries; future and unrelated historical records do not inflate Today.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-006 / One-second refresh coordination

P1 | Staging | Result: Not Run

Purpose: Delivers timely committed changes without re-running heavy full queries every second.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Open active tables/widgets and observe network calls while adding a fixture record.

Expected result: Revision refresh runs at the configured one-second cadence without overlapping full scans. Changed data appears within agreed freshness target.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-007 / Refresh preserves user work

P1 | Staging | Result: Not Run

Purpose: Keeps realtime updates from disrupting filtering, selection, scrolling or unfinished edits.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. While data updates, change page/filter/sort, scroll, select rows and type into an unsaved form.

Expected result: Updates preserve context and edits; stale responses cannot replace newer results.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-008 / Background tabs and errors

P1 | Staging | Result: Not Run

Purpose: Recovers from backgrounding, offline conditions or throttling without a polling storm.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Background/resume tabs; simulate slow API, offline state and 429.

Expected result: Polling backs off/pauses appropriately, indicates stale/error state and recovers without request storms.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

DASH-009 / Observed status versus BIR acceptance

P0 | Staging | Result: Not Run

Purpose: Prevents local availability or planned telemetry from being misrepresented as verified external success.

Preconditions: Actor: Super Admin / Merchant. Fixtures: D04, D07, D13. Complete the module setup and baseline first.

Procedure

1. Show unconfigured BIR and planned server states alongside actual NUERS activity.

Expected result: No fake BIR success, production acknowledgment or online server claim is derived from local data availability.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

13 / Tables, filters and record actions

8 test cases / LIST / All results: Not Run

Feature purpose / Para saan ito

Tables and filters help users find, compare and act on a bounded subset of records. Stable pagination and explicit action scope prevent accidental work on the wrong business or transaction.

> **Plain-language explanation**
> Para saan: madaling hanapin at buksan ang tamang record kahit marami ang rows, at siguradong tama ang maaapektuhan ng action.

Where it is used

All business, transaction, receipt, wallet, user, application, report and infrastructure tables.

Workflow to follow

Choose scope -> apply filters -> sort/page -> select exact records -> inspect action -> reset or navigate without losing context.

Prepare before testing

Seed no-match, single-row, page-boundary and equal-sort-key fixtures. Know the expected matching IDs before applying filters.

Capture baseline: Record URL/filter state, matching IDs/count, sort order, page size and selected rows.

Evidence and cross-check

Applied-filter screenshot, relevant request parameters, row IDs across pages and action target.

Check carefully: Rows, counts, totals and exports must describe the same authorized filter scope, not just the visible page.

LIST-001 / Search exact and partial values

P1 | Staging | Result: Not Run

Purpose: Makes common business and document identifiers usable for accurate record discovery.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Search business name, formatted/unformatted TIN, invoice number and transaction reference; include Unicode.

Expected result: Expected matches only; no stale query or excessive data return.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

LIST-002 / Combined filters

P1 | Staging | Result: Not Run

Purpose: Combines filters predictably so the displayed list represents the intended subset.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Combine date, merchant, branch, document type, status, payment method, category, tax class, amount and environment where offered.

Expected result: Rows and counts satisfy every selected condition. Reset clears all applied state.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

LIST-003 / Date and amount bounds

P1 | Staging | Result: Not Run

Purpose: Handles boundary and invalid filter values without silently broadening the search.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Test inclusive date endpoints, missing endpoints, reversed range, amount zero and min greater than max.

Expected result: Valid boundaries work; invalid combinations show clear validation and do not silently broaden results.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

LIST-004 / Pagination and stable sorting

P1 | Staging | Result: Not Run

Purpose: Keeps paging and ordering reliable when many records share dates or amounts.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Use first/last/deep pages and each supported sort with duplicate dates/amounts.
2. Change page size.

Expected result: Stable tie-breaking prevents unexplained duplicates/skips; row numbering and counts are consistent.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

LIST-005 / Select rows and bulk scope

P1 | Staging | Result: Not Run

Purpose: Makes the scope of a selection or bulk action explicit before work is applied.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Select page rows, change filters and invoke supported bulk action preview.

Expected result: Selected scope is explicit; old hidden selections cannot affect unintended companies/records.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

LIST-006 / Enterprise action controls

P1 | Staging | Result: Not Run

Purpose: Makes record actions clear, accessible and connected to the correct document.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Use Details, View Receipt, PDF and overflow actions with mouse, keyboard and narrow screen.

Expected result: Clear labels/tooltips, correct target, no duplicated Details link, clipped menu or accidental action.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

LIST-007 / Empty, error and retry states

P1 | Staging | Result: Not Run

Purpose: Replaces indefinite loading with a meaningful data, empty or recoverable error state.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Query no results; return an error/timeout; retry successfully.

Expected result: Loading always resolves into data, empty or actionable error. No permanent spinner.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

LIST-008 / URL and browser navigation

P1 | Staging | Result: Not Run

Purpose: Supports investigation across lists and details without unexpectedly losing authorized context.

Preconditions: Actor: All authorized portals. Fixtures: D04, D13. Complete the module setup and baseline first.

Procedure

1. Apply filters, open detail, use Back/Forward, then reload a supported deep link.

Expected result: Navigation preserves expected state and correct scope without requesting the entire dataset.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

14 / Reports and PDF/CSV exports

12 test cases / REP / All results: Not Run

Feature purpose / Para saan ito

Reports convert source transactions into operational and financial summaries. PDF supports review/printing, while CSV supports reconciliation and downstream analysis without losing identifiers or numerical meaning.

> **Plain-language explanation**
> Para saan: makakuha ng malinaw na summary at portable file na tugma sa actual records, filters at merchant scope.

Where it is used

Sales Summary, merchant sales reports, category reports, audit/wallet/registry reports and every Export control.

Workflow to follow

Define scope/cutoff -> calculate approved aggregation -> generate PDF/CSV or queued export -> authorize download -> reconcile output.

Prepare before testing

Use a known report oracle and varied CSV characters. Include short and long reports plus datasets beyond a single UI page.

Capture baseline: Record scope, filters, data cutoff, complete matching count and independent financial totals.

Evidence and cross-check

Export file/hash, request filters, generation time, row count, reconciled totals and printed page review.

Check carefully: A successful download is not sufficient: verify completeness, ownership, filter parity and readable output.

REP-001 / Summary List of Sales

P0 | Staging | Result: Not Run

Purpose: Summarizes sales under consistent aggregation rules and identifies records excluded for evidence problems.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Run daily, monthly, business, type, payment and branch summaries against approved fixture totals.

Expected result: Sales, transaction counts, taxable base and VAT reconcile; excluded/invalid evidence is disclosed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-002 / Merchant sales reports

P0 | Staging | Result: Not Run

Purpose: Gives the merchant an owned sales view that reconciles with the equivalent administrator scope.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Run date/branch/type/category filters and each displayed breakdown.

Expected result: Only owned records; totals match source fixtures and admin totals for the same scope.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-003 / Statutory category reports

P0 | Staging | Result: Not Run

Purpose: Separates benefit-category activity for review while preserving its link to issued documents.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Generate separate senior citizen, PWD, national athlete/coach and solo-parent reports.

Expected result: Category, discount, VAT and sales amounts reconcile with the reviewed fixtures; reports are not mislabeled as official submissions.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-004 / Other report catalog

P1 | Staging | Result: Not Run

Purpose: Ensures every advertised operational report produces useful output or an honest dependency state.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Run transaction, wallet/deposit/fee, failed-attempt, audit, user, registry, PTI and infrastructure reports offered by the UI.

Expected result: Each advertised report either produces accurate output or clearly states its unmet dependency. No decorative dead actions.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-005 / Every Export control supports its promised formats

P0 | Staging | Result: Not Run

Purpose: Makes advertised export choices functional throughout the system instead of leaving decorative controls.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Inventory all export controls on Page Inventory; generate PDF and CSV for each supported report/list.

Expected result: Working PDF/CSV actions with meaningful filenames, actual file types and explicit scope. Missing promised format is logged as a defect.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-006 / Export filter and scope parity

P0 | Staging | Result: Not Run

Purpose: Carries the full authorized filter scope into the exported result.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Filter a dataset, select a merchant/environment and export.
2. Compare row count and totals with the complete matching result.

Expected result: Export uses the same authorized filters, not just the visible page unless explicitly chosen. No foreign records.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-007 / Enterprise report PDF details

P1 | Staging | Result: Not Run

Purpose: Makes the exported PDF independently understandable, branded and usable for review or printing.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Inspect cover/header, NUERS official logo/colors, report title, date/time PHT, filters, merchant identity, totals, columns and page numbers.

Expected result: Readable complete details, repeated table headers where needed, no clipping and correct branding.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-008 / CSV fidelity and formula safety

P0 | Staging | Result: Not Run

Purpose: Preserves data meaning in a machine-readable file while preventing spreadsheet formula execution.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Export leading-zero identifiers, peso amounts, Unicode, commas/quotes/newlines and formula-like text.

Expected result: Rows parse correctly, identifiers retain meaning, numbers reconcile and spreadsheet formula injection is neutralized.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-009 / Large export job lifecycle

P1 | Staging | Result: Not Run

Purpose: Produces large outputs without blocking ordinary requests or silently omitting matching records.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Request a large filtered export; observe queued/running/completed/failed states; download as owner.

Expected result: Bounded background processing, useful progress/status, authorized download and clear limits without silent truncation.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-010 / Concurrent export and snapshot consistency

P0 | Isolated lab | Result: Not Run

Purpose: Keeps an export internally coherent while the source dataset continues to change.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Export while new sales arrive.
2. Compare recorded scope/cutoff and totals.

Expected result: Output uses a coherent documented cutoff and does not contain duplicate/missing rows caused by pagination races.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-011 / Export failure, retry and expiry

P1 | Isolated lab | Result: Not Run

Purpose: Handles interrupted and expired export work safely without exposing another user download.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Interrupt a worker, retry according to workflow, then access an expired or foreign download link.

Expected result: No duplicate uncontrolled jobs; failed/expired state is clear; unauthorized downloads are denied.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

REP-012 / Print each report

P1 | Staging | Result: Not Run

Purpose: Ensures a report remains readable and complete outside the browser on physical or PDF pages.

Preconditions: Actor: Merchant / Admin / finance QA. Fixtures: D07, D08, D13, D14. Complete the module setup and baseline first.

Procedure

1. Print representative short/long reports and every distinct report template.

Expected result: All columns/totals remain legible; print output has no UI controls, blank filler pages or cut-off text.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

15 / Compliance operations and evidence

11 test cases / COMP / All results: Not Run

Feature purpose / Para saan ito

Compliance workspaces organize application preparation, authority evidence, corrections, outage recovery and fee statements. Controlled review links records to evidence and preserves the distinction between internal readiness and an official external decision.

> **Plain-language explanation**
> Para saan: may maayos na application, review at evidence trail; hindi basta maituturing na approved ng BIR ang isang uploaded file o internal status.

Where it is used

PTI Applications, PTI/PTT register, ESP Accreditation, Compliance Operations and immutable audit history.

Workflow to follow

Prepare evidence -> review scope/revision -> record supported decision -> preserve original links -> monitor expiry and history.

Prepare before testing

Use synthetic authorities/evidence and independent review accounts. Prepare wrong-tenant, expired, stale-revision and tampered-file variants.

Capture baseline: Record application/authority ID, effective identity, system/version/branch scope, revision and relevant original document.

Evidence and cross-check

Application package, evidence hash, review decision/reason, audit events and original-to-replacement links.

Check carefully: Internal preparation does not issue a government permit. A correction, memo or statement must preserve original financial records.

COMP-001 / PTI application preparation

P0 | Staging | Result: Not Run

Purpose: Lets a merchant prepare a PTI application package while distinguishing internal review from government issuance.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Create merchant PTI draft, fill required evidence, submit for internal review and export the package.

Expected result: Scoped preparation workflow works. Preparing/submitting internally does not claim BIR issued a permit.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-002 / PTI review and filing history

P0 | Staging | Result: Not Run

Purpose: Tracks the application from corrections to evidenced filing and recorded outcome without duplicated authority records.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Request corrections, resubmit, record filing reference and attach issued-authority evidence in a test workflow.

Expected result: Status transitions require evidence/reason, revisions and authorized reviewers; exactly one linked authority when appropriate.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-003 / PTI ownership and attachment integrity

P0 | Staging | Result: Not Run

Purpose: Protects application ownership, evidence integrity and concurrent review changes.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Attempt foreign application read/update/download; alter a test attachment or submit stale revision.

Expected result: Access/integrity/revision failures stop the operation without changing the accepted record.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-004 / PTI, PTT and CAS/POS distinctions

P0 | Staging | Result: Not Run

Purpose: Preserves the distinct purpose and scope of taxpayer permits and source-system registration.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Record separate synthetic permits/registration for branch/system/environment; test wrong scope and expired dates.

Expected result: One type of authority never automatically grants another. Applicable scope and dates are enforced.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-005 / ESP accreditation evidence

P0 | Staging | Result: Not Run

Purpose: Ties solution readiness to verified accreditation evidence, approved version and configuration.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Record approved solution/version/configuration evidence and test expiry or material version change.

Expected result: Readiness follows verified evidence and approved scope; uploaded files alone cannot establish accreditation.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-006 / Prepared intake enforcement

P0 | Isolated lab | Result: Not Run

Purpose: Allows enforcement to be prepared without unintentionally stopping the currently authorized continuity mode.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Test continuity mode and then enforcement mode in isolated configuration.
2. Retry an already accepted event.

Expected result: Current authorized continuity behavior remains intact; enforced mode blocks new ineligible intake without corrupting prior records/retries.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-007 / Outage and manual recovery

P0 | Staging | Result: Not Run

Purpose: Links outage/manual recovery documents to a single traceable replacement after restoration.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Record a test outage, manual document and restored-service evidence; create one replacement with matching identity.

Expected result: Manual record remains linked; recovery replacement is scoped, traceable and not duplicated or double-charged.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-008 / CWT and supplementary memo

P0 | Staging | Result: Not Run

Purpose: Records a supplementary withholding memo without rewriting the original invoice.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Create a valid memo linked to an owned issued invoice; try foreign original or conflicting draft.

Expected result: Original financial data stays immutable. Scope and competing-revision checks are enforced.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-009 / NUERS fee statement

P0 | Staging | Result: Not Run

Purpose: Creates an accountable statement of existing NUERS fee entries without charging those entries a second time.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Generate a statement for eligible fee entries; repeat the same claim and try missing issuer identity.

Expected result: Entries are claimed once with correct issuer/details and no additional wallet charge.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-010 / Retention and audit integrity

P0 | Isolated lab | Result: Not Run

Purpose: Protects retained financial/audit history and detects alteration or removal of evidence.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Attempt ordinary edit/delete of protected records.
2. In lab modify/tail-delete audit evidence and verify integrity.

Expected result: Protected history remains retained; tampering is detected and cannot be silently marked verified.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

COMP-011 / Compliance notices and documentation

P1 | Staging | Result: Not Run

Purpose: Keeps product notices and manuals aligned with the capability and evidence actually available.

Preconditions: Actor: Merchant / compliance Admin. Fixtures: D05, D06, D15. Complete the module setup and baseline first.

Procedure

1. Compare UI labels, downloadable guides and current workflow capabilities.

Expected result: Unconfigured transport, internal preparation and official acceptance are distinguished. No unsupported certification claim.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

16 / BIR EIS preparation and adapter

13 test cases / BIR / All results: Not Run

Feature purpose / Para saan ito

BIR EIS preparation selects eligible company documents, maps the approved contract and manages durable submission identities. The wire adapter must distinguish preparation, sending, uncertain outcome and authenticated per-invoice acceptance.

> **Plain-language explanation**
> Para saan: maihanda ang tamang transactions bawat company at makapag-transmit nang controlled kapag may actual credentials at authorization na.

Where it is used

BIR Transmission Center, BIR EIS Setup, company connection profiles, prepared batches and result inquiry.

Workflow to follow

Select scoped candidates -> validate/map -> prepare immutable batch -> check authority -> release -> inquire -> reconcile final results.

Prepare before testing

Keep external sending disabled for local cases and use maintained HTTP fakes. Official authentication/certification/production tests require the separately listed external prerequisites.

Capture baseline: Record company/branch/environment, source hashes, selected contract dialect, mapped invoice count and Submit ID.

Evidence and cross-check

Redacted prepared payload, batch/source hashes, gate checks, request-attempt history and exact expected/returned invoice identities.

Check carefully: A submission receipt, timeout or callback is not complete acceptance. Unknown outcomes require inquiry without blind resubmission.

BIR-001 / Company candidate and transmission lists

P0 | Staging | Result: Not Run

Purpose: Makes stored candidate documents discoverable even before a transmission record exists.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Open candidate documents separately from transmission attempts; filter by company, branch, dates, status and environment.

Expected result: Eligible stored transactions are discoverable even with no submission attempt. Candidate and transmission counts remain distinct.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-002 / Prepare selected or company batch

P0 | Staging | Result: Not Run

Purpose: Prepares company-scoped batches with valid mapped documents and correct post-mapping limits.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Prepare selected owned documents or a filtered company batch; inspect final mapped count and payload.

Expected result: Company/branch/environment scope is retained, required source checks run, and limits apply after any tax-class split.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-003 / Prepared batch idempotency

P0 | Staging | Result: Not Run

Purpose: Prevents repeated preparation from claiming the same source documents in duplicate batches.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Prepare same request twice; change payload under same request identity; cancel a never-sent batch.

Expected result: No duplicate batch claim; changed payload conflicts; cancellation preserves audit history.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-004 / Disabled outbound controls

P0 | Isolated lab | Result: Not Run

Purpose: Keeps external communication disabled until the deliberate release gates are satisfied.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Keep outbound disabled, configure synthetic connection and try authentication, release and worker execution.

Expected result: No external request is sent; UI explains the missing gate and no document is marked BIR accepted.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-005 / Private credential storage and roles

P0 | Isolated lab | Result: Not Run

Purpose: Protects BIR connection secrets and restricts configuration to the required privileged identity.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Save synthetic credential bundle and inspect API/list/export/logs with multiple roles.

Expected result: Secrets are encrypted and never returned; privileged configuration requires authorized MFA.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-006 / Mapper and protocol fixtures

P0 | Isolated lab | Result: Not Run

Purpose: Checks deterministic mapping and cryptographic/protocol formatting against the selected maintained contract fixtures.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Run maintained CAS/POS fixtures for IDs, signatures, precision, tax classes, correction references and response parsing.

Expected result: Outputs match the selected documented dialect and immutable source totals. Unsupported/inconsistent input is blocked.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-007 / Unknown submission outcome

P0 | Isolated lab | Result: Not Run

Purpose: Avoids duplicate BIR submission when the first request may have reached the destination.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Fake a timeout after potential send, then return inquiry results using the same Submit ID.

Expected result: No second invoice POST. State stays uncertain until authenticated per-invoice evidence resolves it.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-008 / Partial, duplicate and malformed results

P0 | Isolated lab | Result: Not Run

Purpose: Prevents partial, ambiguous or mismatched evidence from becoming a false accepted state.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Fake partial success, duplicate result, missing/extra UID, wrong identity and unknown response code.

Expected result: No false full acceptance. Exact expected identities/counts are checked and exceptions remain reviewable.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-009 / Release authority recheck

P0 | Isolated lab | Result: Not Run

Purpose: Rechecks authority at send time so a previously prepared batch cannot bypass a newly failed gate.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Prepare a valid test batch, then expire/revoke permit, key or profile before release.

Expected result: New send is blocked by current gates. Safe inquiry of prior sends remains independently controlled.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-010 / Callback and environment isolation

P0 | Isolated lab | Result: Not Run

Purpose: Keeps callback evidence and certification activity from directly changing production acceptance.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. With fakes, test bad signature, replay and wrong tenant/environment callback.

Expected result: Callback cannot directly declare acceptance; certification never increases production acceptance totals.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-011 / BIR-issued authentication and contract

P0 | BIR credentials required | Result: Not Run

Purpose: Confirms actual interoperability with the credentials and contract issued to the organization.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. When credentials arrive, confirm official endpoint/version/dialect and run prescribed certification authentication.

Expected result: Actual issued credentials interoperate with the confirmed contract; retain real certification evidence.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-012 / Official certification scenario suite

P0 | BIR credentials required | Result: Not Run

Purpose: Obtains the actual scenario evidence required by the official certification process.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. Run the BIR-prescribed positive/negative and representative CAS/POS scenarios after authorized setup.

Expected result: Each required official scenario has actual evidence and resolved discrepancies; lab passes are not substituted.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

BIR-013 / Production activation and acceptance

P0 | BIR authorization required | Result: Not Run

Purpose: Validates the authorized production path and final acceptance reconciliation before its operational release.

Preconditions: Actor: Super Admin / integration QA. Fixtures: D15, D16. Complete the module setup and baseline first.

Procedure

1. After authority/certification approval, test controlled production release, inquiry and reconciliation under the approved plan.

Expected result: Authentic complete per-invoice acceptance is recorded; remaining activation gates are signed off.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

17 / Server management and recovery

13 test cases / OPS / All results: Not Run

Feature purpose / Para saan ito

Server management and recovery controls provide operational visibility, authorized infrastructure actions and a way to recover or migrate data. Telemetry and recovery claims must be based on observed evidence rather than planned architecture.

> **Plain-language explanation**
> Para saan: makontrol at mabantayan ang infrastructure at maibalik ang data kapag may incident, na may totoong measured recovery result.

Where it is used

Server Management, Infrastructure Health, Backup and Disaster Recovery, Data Governance/Portability.

Workflow to follow

Observe trusted state -> review permitted action -> authorize -> execute/reconcile -> verify recovery -> retain evidence.

Prepare before testing

Use fake controllers and isolated restore targets for present lab cases. Keep independent recovery-key custody and known fixture checksums. Real DR/HA waits for provisioned infrastructure.

Capture baseline: Record node/controller state, backup identifier/hash, latest recoverable commit time and pre-action data counts/balances.

Evidence and cross-check

Preflight/approval logs, telemetry timestamps, backup manifest, restore reconciliation and recovery start/end/commit times.

Check carefully: A backup file is not proof of restorability. A planned provider, metric or failover path must not be reported as live and verified.

OPS-001 / Inventory and standard font sizes

P1 | Staging | Result: Not Run

Purpose: Makes server state readable while distinguishing planned inventory from observed operating hosts.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Inspect grid/table, all server tabs, search/filter and responsive details.

Expected result: Readable controls and metrics; planned/unconfigured nodes are labeled accurately with no fabricated telemetry.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-002 / Privileged infrastructure access

P0 | Staging | Result: Not Run

Purpose: Protects infrastructure actions and sensitive operational records from ordinary application users.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Try server/backup settings and actions as anonymous, merchant and unauthorized admin.

Expected result: Denied before dispatch, including direct endpoints and exports.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-003 / Disabled controller and action preflight

P0 | Isolated lab | Result: Not Run

Purpose: Prevents an unconfigured controller from producing a false action success or issuing a command.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. With controller disabled, try reboot/shutdown/service action review using a test inventory.

Expected result: No command runs. Missing prerequisites are clearly shown.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-004 / Approval, MFA and stale preflight

P0 | Isolated lab | Result: Not Run

Purpose: Ensures disruptive actions use fresh authorization and safe infrastructure preconditions.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. With fake controller, test step-up expiry, replay, self-approval, changed revision and unsafe peer/quorum conditions.

Expected result: Unsafe or unauthorized action is blocked. Dispatch rechecks current conditions.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-005 / Command allowlist and idempotency

P0 | Isolated lab | Result: Not Run

Purpose: Limits infrastructure execution to approved actions and preserves uncertain outcomes for reconciliation.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Use fake controller to test duplicate action IDs, invalid service/command/target and ambiguous response.

Expected result: Only allowlisted actions dispatch once. Ambiguous outcomes stay locked for reconciliation.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-006 / Telemetry freshness

P1 | Isolated lab | Result: Not Run

Purpose: Keeps server health based on fresh, correctly attributed telemetry.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Inject fresh, stale, repeated and wrong-identity synthetic telemetry.

Expected result: Only valid fresh telemetry updates live status. Old samples do not extend freshness.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-007 / Backup creation and corruption detection

P0 | Isolated lab | Result: Not Run

Purpose: Checks that encrypted backups are verifiable and reject corrupted or wrongly decrypted content.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Create encrypted lab backup; verify checksum; try wrong key, truncated archive and altered bytes.

Expected result: Valid archive verifies; corruption/wrong key fail closed. Credentials remain separately controlled.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-008 / Isolated restore and reconciliation

P0 | Isolated lab | Result: Not Run

Purpose: Proves the lab backup can restore a coherent dataset into an isolated target.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Restore lab backup to empty isolated targets; compare counts, balances, documents, attachments and sequences.

Expected result: Data reconciles to the backup snapshot. Restore cannot overwrite unintended paths/targets.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-009 / Measured lab RTO and RPO

P1 | Isolated lab | Result: Not Run

Purpose: Measures actual lab recovery time and recoverable-data loss instead of presenting estimates as test results.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Record incident time, latest recoverable committed timestamp, restore start and service validation finish.

Expected result: RTO = incident to validated recovery; RPO = incident minus latest recovered committed data time. Report actual lab results and workload.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-010 / Offsite backup and production DR

P0 | Infrastructure required | Result: Not Run

Purpose: Proves recovery from a separately stored copy after offsite storage and custody are provisioned.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. After storage is provisioned, test separate custody, restore access and controlled production-equivalent recovery.

Expected result: Real evidence meets approved recovery targets. Planned providers/regions are not reported as already deployed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-011 / Real controller and failover

P0 | Infrastructure required | Result: Not Run

Purpose: Validates real controller, identity, HA and failover behavior beyond simulated local tests.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. When agents/controller/HA are provisioned, execute approved isolated service/failover/quorum/network recovery drills.

Expected result: Actual identity, mTLS, locking, rollback and postchecks succeed with documented evidence.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-012 / Alerts and operational recovery

P1 | Isolated lab | Result: Not Run

Purpose: Alerts operators to failing dependencies and provides an observable path back to service.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Simulate stale worker, storage pressure, failed backup, certificate expiry and unavailable dependency in lab.

Expected result: Correct actionable alerts and runbooks; no false healthy state or lost queued work.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

OPS-013 / Exit and portability package

P0 | Isolated lab | Result: Not Run

Purpose: Makes merchant data usable outside the system through a complete, scoped and verifiable portability package.

Preconditions: Actor: Super Admin / operations QA. Fixtures: D17, D18. Complete the module setup and baseline first.

Procedure

1. Export one synthetic merchant package, verify manifest/hashes and restore/import into an isolated target.

Expected result: Complete authorized data is usable and reconciled, including attachments and references, with no other tenant data.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

18 / Scale, resilience and realtime load

12 test cases / PERF / All results: Not Run

Feature purpose / Para saan ito

Performance and resilience testing verifies that correct behavior remains usable as data volume and concurrency grow. It measures worst-case and tail latency, resource use, queue recovery and fairness across merchants.

> **Plain-language explanation**
> Para saan: masigurong mabilis at stable ang pages at API kahit million rows, maraming users at may temporary failure.

Where it is used

Large admin/merchant grids, summaries, exports, realtime refresh, intake workers and recovery paths.

Workflow to follow

Approve workload/targets -> seed realistic data -> warm/cold baseline -> ramp/soak/fault -> measure -> reconcile and retest.

Prepare before testing

Use an isolated production-like environment with 1M total rows and separately 1M for one merchant. Agree hardware, concurrency and targets before starting.

Capture baseline: Record build, resources, data distribution, query mix, network profile, fixture totals and idle/steady-state measurements.

Evidence and cross-check

p50/p95/p99 latency, throughput, error counts, query plans, CPU/RAM, connection/queue metrics and post-run reconciliations.

Check carefully: Fast averages do not excuse tenant leakage, duplicated fees or long tail timeouts. Proposed targets are not measured guarantees.

PERF-001 / Million-row admin and merchant grids

P0 | Isolated lab | Result: Not Run

Purpose: Checks that paged access remains fast for both a large platform and one very large merchant.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Run first page, filters and deep pagination over 1 million total rows and separately 1 million rows for one merchant.

Expected result: Approved p95/p99 targets met with bounded page payloads; no full dataset sent to browser or tenant leakage.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-002 / Summary List of Sales at scale

P0 | Isolated lab | Result: Not Run

Purpose: Targets expensive summary queries that can otherwise leave sales pages loading indefinitely.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Run daily/monthly/merchant breakdowns over large and skewed datasets with cold and warm caches.

Expected result: Correct totals and bounded queries; loading resolves within agreed target without timeouts.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-003 / Every authenticated page performance

P1 | Isolated lab | Result: Not Run

Purpose: Finds slow secondary pages rather than assuming a fast dashboard proves the whole application is fast.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Apply the performance protocol to each Page Inventory route and its largest table/widget.

Expected result: First useful content and API timings recorded per page; slow pages are filed as defects, not hidden in averages.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-004 / Concurrent intake and reads

P0 | Isolated lab | Result: Not Run

Purpose: Tests whether financial correctness and useful response times survive concurrent reading and writing.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Ramp approved concurrent users while accepting idempotent transactions and reading dashboards/exports.

Expected result: No overspend/duplicate records/deadlocks escaping recovery; latency/error targets remain within agreed limits.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-005 / One-second refresh load

P0 | Isolated lab | Result: Not Run

Purpose: Checks the real cost of per-second refresh under multiple active users and tabs.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Open multiple merchant/admin tabs under load; measure revision checks, full queries and DB/worker usage.

Expected result: No overlapping scans or default 429 storm. Freshness target met while server resource limits remain stable.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-006 / Large exports under active traffic

P1 | Isolated lab | Result: Not Run

Purpose: Verifies large exports do not consume all capacity needed by interactive users.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Export 100k and 1 million matching rows where supported, while ordinary pages remain in use.

Expected result: Background/streamed processing stays bounded; explicit limits are disclosed; ordinary pages remain responsive.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-007 / Cold start and index/query plan review

P0 | Isolated lab | Result: Not Run

Purpose: Detects inefficient query plans and cold-start behavior hidden by a warm cache.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Restart only lab components; test common and worst-case search patterns; capture plans and query counts.

Expected result: No unbounded hydration/N+1 loops; supported query plans meet agreed performance targets.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-008 / Slow network, offline and reconnect

P1 | Isolated lab | Result: Not Run

Purpose: Preserves user understanding and transaction identity through network interruption and reconnection.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Throttle test network; disconnect during read and queued write; restore connectivity.

Expected result: Bounded errors and recovery; local outbox retains identity without duplicate sales or cross-account replay.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-009 / Worker/database interruption

P0 | Isolated lab | Result: Not Run

Purpose: Checks safe recovery across the commit boundary and worker interruption.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Kill lab worker during job and simulate dependency loss before/after commit.
2. Recover and reconcile.

Expected result: Durable work resumes safely with no lost committed record, duplicate fee or blind BIR resubmission.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-010 / Sustained workload and resource trend

P1 | Isolated lab | Result: Not Run

Purpose: Finds accumulating resource leaks, queue backlog and latency degradation during sustained use.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Run agreed mixed workload for 2 hours or the approved duration.
2. Track CPU, memory, connections, queues and browser heap.

Expected result: No unbounded growth or degrading latency; final counts/balances reconcile.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-011 / Hot-merchant fairness

P0 | Isolated lab | Result: Not Run

Purpose: Prevents one high-volume tenant from starving or contaminating another tenant workflow.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Give one merchant 95% of data/traffic; concurrently use a small merchant.

Expected result: One tenant cannot exhaust shared capacity or cause another tenant to receive wrong/stale data.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PERF-012 / Backoff and recovery from 429/5xx

P1 | Isolated lab | Result: Not Run

Purpose: Ensures clients back off and recover instead of multiplying transient failures with retry loops.

Preconditions: Actor: Performance QA / operations. Fixtures: D13, D18, D19. Complete the module setup and baseline first.

Procedure

1. Apply controlled throttling and transient errors; observe clients and return service to normal.

Expected result: Clients honor retry policy without tight loops; recover automatically and preserve clear state.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

19 / Common checks for every page

8 test cases / PAGE / All results: Not Run

Feature purpose / Para saan ito

Common page checks provide consistent coverage across all declared routes, including redirects, nested tabs and dialogs. They catch incomplete actions, access gaps, unreadable layouts and failure states that a happy-path transaction test may miss.

> **Plain-language explanation**
> Para saan: walang page o button na makakalimutang i-test, kahit secondary screen, dialog o lumang route na nagre-redirect.

Where it is used

Every route in the 166-entry Page Inventory and each exposed tab, action, modal and download within it.

Workflow to follow

Open permitted route -> verify server scope -> exercise controls -> test edge states/device sizes -> record evidence and timings.

Prepare before testing

Use the approved account/role matrix and representative empty, normal and high-volume data. Replace dynamic URL parameters with authorized synthetic IDs.

Capture baseline: Record route, role, release/build, screen size, browser/network profile and underlying data scope.

Evidence and cross-check

Route checklist, key screenshots, console/network errors, timing results and linked failed case IDs.

Check carefully: Route-level wrappers are only the starting inventory; underlying APIs, files and hidden actions need their own authorization checks.

PAGE-001 / Navigation and direct URL

P1 | Staging | Result: Not Run

Purpose: Makes each route discoverable, reloadable and consistent with its expected navigation destination.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. For every Page Inventory entry, open via menu and direct URL, then reload and use Back/Forward.

Expected result: Correct page/redirect and title. No blank screen, infinite loader or broken navigation.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PAGE-002 / Page and underlying API access

P0 | Staging | Result: Not Run

Purpose: Ensures every page and its real data requests enforce the approved access policy.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. For each route, test allowed and disallowed roles plus ownership/branch restrictions on actual data requests.

Expected result: Server-side access matches approved RBAC, regardless of route wrapper or hidden menus.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PAGE-003 / Controls and form lifecycle

P1 | Staging | Result: Not Run

Purpose: Catches incomplete buttons, tabs, dialogs and form paths beyond the main happy path.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. Exercise every tab, primary button, modal, cancel/back, submit, validation and error path.

Expected result: No dead controls, accidental double submission, inaccessible dialog or lost unsaved work without notice.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PAGE-004 / Mobile, zoom and accessibility

P1 | Staging | Result: Not Run

Purpose: Makes the interface readable and operable across common sizes, zoom levels and input methods.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. Check 390px, tablet, desktop, 200% zoom, keyboard focus, labels, contrast and screen-reader names.

Expected result: Readable standard fonts, usable actions and meaningful focus. No hidden required controls or unusable clipping.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PAGE-005 / Loading, empty, offline and error

P1 | Staging | Result: Not Run

Purpose: Ensures users can distinguish an empty result from an outage, expired session or stale dataset.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. Check first load, zero data, high volume, slow/offline network, session expiry and recovery.

Expected result: Each state is distinct and actionable; no fake zero totals or stale success.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PAGE-006 / Official branding and version

P1 | Staging | Result: Not Run

Purpose: Uses the official brand assets and a consistent declared software version across public and private screens.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. Inspect login, public pages, portals, loading screen, browser icon and documentation links.

Expected result: Official global logo/favicon/loading animation and declared version appear consistently with legible fonts.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PAGE-007 / Exports and print actions

P1 | Staging | Result: Not Run

Purpose: Finds and validates every exposed export and print action on the page.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. List every export/print control found on the route and execute the applicable REP test cases.

Expected result: Every advertised action works with correct filters, ownership and output details.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

PAGE-008 / Runtime quality and timing

P1 | Staging | Result: Not Run

Purpose: Captures runtime errors and timings that may not be visible in a static screenshot.

Preconditions: Actor: QA for each authorized role. Fixtures: D01, D13, Page Inventory. Complete the module setup and baseline first.

Procedure

1. Record console errors, failed requests, useful-content time and slow API responses for each route.

Expected result: No unhandled errors or repetitive failures. Results meet approved targets and evidence is attached.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

---

20 / Customers, support and additional portals

8 test cases / AUX / All results: Not Run

Feature purpose / Para saan ito

Customer directories, support, notifications and additional portals complete the operational experience around transactions. Documentation and release smoke tests help users and integrators follow the actual deployed behavior.

> **Plain-language explanation**
> Para saan: maayos ang customer records, support at help, at siguradong gumagana pa ang critical user journey sa bagong release.

Where it is used

Customers, client/consumer and other enabled portals, Support, global search, Help and documentation downloads.

Workflow to follow

Resolve permitted account -> maintain owned records or conversation -> deliver scoped response -> use current documentation -> verify release smoke.

Prepare before testing

Use distinguishable synthetic customers/conversations per tenant and the exact release candidate. Keep controlled recipients for any communication tests.

Capture baseline: Record customer/conversation ownership, unread state, release version and expected public/private document visibility.

Evidence and cross-check

Scoped list/detail result, message or notification audit, document version check and exact-build smoke record.

Check carefully: Support or global search must not become another path to cross-merchant data. Historical successful tests do not prove the new build.

AUX-001 / Customer directory lifecycle

P1 | Staging | Result: Not Run

Purpose: Maintains a usable owned customer directory without silently rewriting issued document history.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. Create/update a test customer; validate duplicate fields, search, filters, details and export.

Expected result: Correct owned customer records with validation and stable paging; issued invoice history is preserved.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUX-002 / Customer receipt access

P0 | Staging | Result: Not Run

Purpose: Lets a customer access permitted receipt information without exposing unrelated private transactions.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. Use supported client/consumer/verification flows with owned and unrelated receipt identities.

Expected result: Only permitted customer data is disclosed; guessing a number does not expose full private records.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUX-003 / Support conversations

P1 | Staging | Result: Not Run

Purpose: Supports accountable support conversations with correct ownership and message state.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. Create a test support request, reply as permitted support account and mark read/update status.

Expected result: Messages stay in the correct conversation/account with accurate unread state and attachments policy.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUX-004 / Support and notifications isolation

P0 | Staging | Result: Not Run

Purpose: Prevents support links and notification identifiers from bypassing merchant isolation.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. Attempt another merchant conversation/message/notification ID and links after logout.

Expected result: Unauthorized access is denied without leaking private content.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUX-005 / Additional role portals

P1 | Staging | Result: Not Run

Purpose: Checks permitted secondary role portals without assuming every displayed module is fully provisioned.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. For enabled BIR/RDO/client/consumer/API portals, run common page checks and approved role-specific use cases.

Expected result: Only explicitly approved scope is visible. Unsupported functionality is clearly identified, not shown as completed.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUX-006 / Public documentation downloads

P1 | Staging | Result: Not Run

Purpose: Gives users and integrators current downloadable instructions that match the system they use.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. Open website/merchant documentation links and download each advertised guide/report/manual.

Expected result: Files open, have correct name/version/branding, and match the current published capabilities.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUX-007 / Search and help links

P1 | Staging | Result: Not Run

Purpose: Helps users find permitted records and guidance without turning search into a private-data directory.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. Use global search and Help from each portal; open a permitted result and an inaccessible target.

Expected result: Search is role/tenant scoped. Help routes and deep links work without exposing private content.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

AUX-008 / Release smoke and regression

P0 | Staging | Result: Not Run

Purpose: Checks the critical end-to-end journey on the exact candidate build before release sign-off.

Preconditions: Actor: Merchant / Admin / scoped users. Fixtures: D01, D04, D20. Complete the module setup and baseline first.

Procedure

1. On the exact release candidate run login, scoped sale, fee, receipt PDF, report export, retry and logout.
2. Record build/hash.

Expected result: Critical smoke cases pass with evidence; no acceptance conclusion is based solely on earlier test runs.

Record actual result, evidence, defect (if any), tester, timestamp, build and environment in the execution register.

Appendix A / Test data catalogue

Use these fixture IDs from the test cards. These are preparation requirements, not supplied production data. Keep secrets in the approved secret store and put only redacted aliases or evidence references in QA records.

D01 / Accounts and roles

Prepare: Two unrelated merchants A/B; two branches each; owner, restricted staff, Admin and Super Admin; suspended/unassigned users.

Control / expected use: Synthetic identities only. Record exact role/capability matrix and account aliases; no passwords in workbook.

D02 / Login identities

Prepare: Controlled registered Google account, controlled unregistered email, expired sessions and recovery tokens.

Control / expected use: Use approved test identities. Tokens are secret; store only redacted evidence.

D03 / MFA devices

Prepare: Two physical/test authenticators, pending/expired enrollment and one-use recovery codes.

Control / expected use: Keep secrets outside the workbook. Record device alias and test time.

D04 / Tenant collision fixture

Prepare: A and B each own the same visible invoice number, plus distinct IDs, customers, attachments and balances.

Control / expected use: Expected access: own permitted data only. Admin lookup must use exact source and merchant identity.

D05 / Registry and branches

Prepare: Complete/incomplete identity, protected change request, accepted/rejected evidence, active/inactive branch and terminal.

Control / expected use: Use synthetic TIN/registration references valid for the staging validators. Never submit fictitious records to BIR.

D06 / Numbering and documents

Prepare: Active/expired/exhausted/missing series; issued, draft, voided, corrected and payment-copy records.

Control / expected use: Record approved sequence range and expected original links before execution.

D07 / Arithmetic baseline

Prepare: Regression fixture: VAT-inclusive PHP 1,120 = PHP 1,000 base + PHP 120 VAT. Manual discount PHP 112 gives PHP 900 base + PHP 108 VAT = PHP 1,008.

Control / expected use: Application regression oracle only. Finance/compliance reviewer approves applicable tax fixtures before execution.

D08 / Benefit fixtures

Prepare: Separate senior citizen, PWD, national athlete/coach and solo-parent cases; eligible/ineligible lines and valid/missing/expired proof.

Control / expected use: Use reviewed current eligibility/rate/scope rules. Do not infer legal eligibility from age/category alone.

D09 / Receipt rendering

Prepare: Different profile and invoice logos; short/long receipt, Unicode, missing image, multi-page items and all templates.

Control / expected use: Preserve financial oracle. The globally removed lower section must stay absent.

D10 / API events

Prepare: Unique/replayed/conflicting event IDs, key scopes/environments, malformed payload, atomic batch and dropped response.

Control / expected use: Use staging API keys and fresh synthetic identities. Never place keys in evidence or this workbook.

D11 / Delivery sinks

Prepare: Controlled test mailbox/mail sink and HTTPS webhook receiver with signature verification.

Control / expected use: No real customer notifications. Capture delivery ID, recipient alias and attachment hash.

D12 / Wallet fixtures

Prepare: Fee PHP 3; threshold PHP 0 then PHP 500; balances PHP 0, 2.99, 3.00 and funded wallet; pending/approved/rejected deposits.

Control / expected use: Five distinct eligible sales at minimum 0 must deduct PHP 15. Boundary amounts 499.99/500/500.01.

D13 / Paging and dates

Prepare: 0, 1, page-size, page-size+1, 100k and 1M rows; equal timestamps; PHT midnight/month/year boundaries; future rows.

Control / expected use: Record independent totals per tenant, environment, status and period. Include skewed distributions.

D14 / Exports

Prepare: Unicode, commas/quotes/newlines, leading-zero identifiers, formula-like text and multiple report pages.

Control / expected use: Compare full matching scope against independent expected count and sum, not only visible page.

D15 / Authority evidence

Prepare: Synthetic permit/accreditation/coverage/version profiles, valid and expired records, current and stale revisions.

Control / expected use: Internal preparation only; never label synthetic evidence as BIR approval.

D16 / BIR adapter fakes

Prepare: Maintained protocol fixtures, fake auth/inquiry, 1/100/over-limit mapped invoices, partial/unknown/duplicate responses.

Control / expected use: No external requests during local tests. Actual interoperability waits for issued credentials and permission.

D17 / Infrastructure fixtures

Prepare: Planned nodes; fake controller; fresh/stale telemetry; unsafe peer/quorum; independent test reviewers.

Control / expected use: Do not reboot/shutdown production to run this checklist.

D18 / Recovery fixtures

Prepare: Encrypted synthetic backup, known hashes, wrong key, corrupt archive, empty isolated restore target and timestamped commits.

Control / expected use: Record lab RTO/RPO. Production claims require a separate real approved recovery exercise.

D19 / Scale workload

Prepare: Run 1M total rows across merchants and separately 1M in one tenant; skew 95% toward hot tenant; mixed reads/writes/exports.

Control / expected use: Agree hardware, concurrency, query mix, duration and target metrics before the run.

D20 / Auxiliary records

Prepare: Synthetic customer/client records, private support conversations, unread notifications and public document links.

Control / expected use: Give each tenant recognizably different fixture data to detect leaks.

Appendix B / Complete route inventory

Apply PAGE-001 through PAGE-008 to every applicable route, and link feature-specific cases where an action is exposed. Expand nested tabs, dialogs, row actions, downloads and related endpoints in the execution notes. Replace dynamic parameters with authorized synthetic record IDs.

Role labels are inventory, not proof
Declared route access describes the frontend inventory. Verify server authorization, redirects, API calls and file access independently. A hidden link or route wrapper does not establish tenant isolation.

ID	URL pattern	Declared access / behavior
URL-001	/	Public Page
URL-002	/developers/integration	Public Page
URL-003	/api/docs	Public Page
URL-004	/api/sandbox	Public Page
URL-005	/verify	Public Page
URL-006	/activate-business	Public Page
URL-007	/verify-email	Public Page
URL-008	/forgot-password	Public Page
URL-009	/reset-password	Public Page
URL-010	/security/account	Authenticated; verify resource policy Page
URL-011	/security/mfa	Public Page
URL-012	/accept-team-invite	Public Page
URL-013	/login	Guest only Page
URL-014	/register	Public Page
URL-015	/terms-of-service	Public Page
URL-016	/privacy-notice	Public Page
URL-017	/terms	Public Redirect /terms-of-service

ID	URL pattern	Declared access / behavior
URL-018	/privacy	Public Redirect /privacy-notice
URL-019	/super-admin	admin, super_admin Page
URL-020	/super-admin/profile	admin, super_admin Page
URL-021	/super-admin/transactions	admin, super_admin Page
URL-022	/super-admin/revenue-analytics	admin, super_admin Page
URL-023	/super-admin/blueprint	admin, super_admin Page
URL-024	/super-admin/merchants	admin, super_admin Page
URL-025	/super-admin/bir-accounts	admin, super_admin Page
URL-026	/super-admin/client-accounts	admin, super_admin Page
URL-027	/super-admin/citizen-approval	admin, super_admin Page
URL-028	/super-admin/taxpayer-onboarding	admin, super_admin Page
URL-029	/super-admin/rdo-mappings	admin, super_admin Page
URL-030	/super-admin/users-rbac	admin, super_admin Page
URL-031	/super-admin/subscriptions	admin, super_admin Page
URL-032	/super-admin/wallets	admin, super_admin Page
URL-033	/super-admin/compliance-operations	admin, super_admin Page
URL-034	/super-admin/branch-reviews	admin, super_admin Page
URL-035	/super-admin/support	admin, super_admin Page
URL-036	/super-admin/compliance	admin, super_admin Page
URL-037	/super-admin/fraud	admin, super_admin Page
URL-038	/super-admin/tax-filings	admin, super_admin Page
URL-039	/super-admin/reports	admin, super_admin Page
URL-040	/super-admin/ai-recommendations	admin, super_admin Page
URL-041	/super-admin/tax-operations	admin, super_admin Page

ID	URL pattern	Declared access / behavior
URL-042	/super-admin/tax-intelligence	admin, super_admin Page
URL-043	/super-admin/tax-rules	admin, super_admin Page
URL-044	/super-admin/fraud-models	admin, super_admin Page
URL-045	/super-admin/reconciliation	admin, super_admin Page
URL-046	/super-admin/tax-analytics	admin, super_admin Page
URL-047	/super-admin/graph	admin, super_admin Page
URL-048	/super-admin/security	admin, super_admin Page
URL-049	/super-admin/soc-operations	admin, super_admin Page
URL-050	/super-admin/audit	admin, super_admin Page
URL-051	/super-admin/certificates	admin, super_admin Page
URL-052	/super-admin/mfa-device-trust	admin, super_admin Page
URL-053	/super-admin/pti-ptt	admin, super_admin Page
URL-054	/super-admin/api-platform	admin, super_admin Page
URL-055	/super-admin/eis-readiness	admin, super_admin Page
URL-056	/super-admin/eis-transmissions	admin, super_admin Page
URL-057	/super-admin/eis-gateway	admin, super_admin Page
URL-058	/super-admin/api-keys	admin, super_admin Page
URL-059	/super-admin/webhooks	admin, super_admin Page
URL-060	/super-admin/payment-gateways	admin, super_admin Page
URL-061	/super-admin/system-health	admin, super_admin Page
URL-062	/super-admin/server-management	super_admin Page
URL-063	/super-admin/backups	admin, super_admin Page
URL-064	/super-admin/data-archive	admin, super_admin Page
URL-065	/super-admin/notifications	admin, super_admin Page

ID	URL pattern	Declared access / behavior
URL-066	/bir	admin, bir, super_admin Page
URL-067	/bir/rdo-registration	admin, bir, super_admin Page
URL-068	/bir/citizen-approval	admin, bir, super_admin Page
URL-069	/bir/transactions	admin, bir, super_admin Page
URL-070	/bir/business-accounts	admin, bir, super_admin Page
URL-071	/bir/compliance	admin, bir, super_admin Page
URL-072	/bir/reports	admin, bir, super_admin Page
URL-073	/bir/tax-filings	admin, bir, super_admin Page
URL-074	/bir/forecasts	admin, bir, super_admin Page
URL-075	/bir/tax-intelligence	admin, bir, super_admin Page
URL-076	/bir/vat-reconciliation	admin, bir, super_admin Page
URL-077	/bir/invoice-matching	admin, bir, super_admin Page
URL-078	/bir/network	admin, bir, super_admin Page
URL-079	/bir/risk-scoring	admin, bir, super_admin Page
URL-080	/bir/ai-audit	admin, bir, super_admin Page
URL-081	/bir/eis-readiness	admin, bir, super_admin Page
URL-082	/bir/eis-transmissions	admin, bir, super_admin Page
URL-083	/rdo	rdo, bir, admin, super_admin Page
URL-084	/merchant	merchant, admin, super_admin Page
URL-085	/merchant/transactions	merchant, admin, super_admin Page
URL-086	/merchant/receipts	merchant, admin, super_admin Page
URL-087	/merchant/sales-reports	merchant, admin, super_admin Page

ID	URL pattern	Declared access / behavior
URL-088	/merchant/vat-reports	merchant, admin, super_admin Redirect /merchant/sales-reports
URL-089	/merchant/wallet	merchant, admin, super_admin Page
URL-090	/merchant/compliance-operations	merchant, admin, super_admin Page
URL-091	/merchant/users	merchant, admin, super_admin Page
URL-092	/merchant/security	merchant, admin, super_admin Page
URL-093	/merchant/billing	merchant, admin, super_admin Page
URL-094	/merchant/pos-settings	merchant, admin, super_admin Page
URL-095	/merchant/api-keys	merchant, admin, super_admin Page
URL-096	/merchant/profile	merchant, admin, super_admin Page
URL-097	/merchant/branches	merchant, admin, super_admin Redirect /merchant/api-keys
URL-098	/merchant/pti-applications	merchant, admin, super_admin Page
URL-099	/merchant/customers	merchant, admin, super_admin Page
URL-100	/merchant/notifications	merchant, admin, super_admin Page
URL-101	/merchant/expenses	merchant, admin, super_admin Page
URL-102	/merchant/invoices	merchant, admin, super_admin Page
URL-103	/merchant/b2b-tax	merchant, admin, super_admin Redirect /merchant/sales-reports

ID	URL pattern	Declared access / behavior
URL-104	/merchant/output-vat	merchant, admin, super_admin Redirect /merchant/sales-reports
URL-105	/merchant/input-vat	merchant, admin, super_admin Redirect /merchant/sales-reports
URL-106	/merchant/invoice-matching	merchant, admin, super_admin Redirect /merchant/sales-reports
URL-107	/merchant/withholding-tax	merchant, admin, super_admin Redirect /merchant/sales-reports
URL-108	/merchant/suppliers	merchant, admin, super_admin Redirect /merchant/sales-reports
URL-109	/merchant/invoices/create	merchant, admin, super_admin Page
URL-110	/merchant/invoices/recurring	merchant, admin, super_admin Redirect /merchant/invoices
URL-111	/merchant/invoices/bulk	merchant, admin, super_admin Redirect /merchant/invoices
URL-112	/merchant/invoices/:id	merchant, admin, super_admin Page
URL-113	/admin	admin, super_admin Page
URL-114	/admin/transactions	admin, super_admin Page
URL-115	/admin/fraud	admin, super_admin Page
URL-116	/admin/merchants	admin, super_admin Page
URL-117	/admin/tax-filings	admin, super_admin Page
URL-118	/admin/compliance	admin, super_admin Page
URL-119	/admin/audit	admin, super_admin Page
URL-120	/admin/users	admin, super_admin Page
URL-121	/admin/notifications	admin, super_admin Page
URL-122	/admin/reports	admin, super_admin Page

ID	URL pattern	Declared access / behavior
URL-123	/consumer	Authenticated; verify resource policy Page
URL-124	/client	client, consumer, admin, super_admin Page
URL-125	/client/transactions	client, consumer, admin, super_admin Page
URL-126	/client/receipts	client, consumer, admin, super_admin Page
URL-127	/client/barcode	client, consumer, admin, super_admin Page
URL-128	/client/wallet	client, consumer, admin, super_admin Page
URL-129	/client/notifications	client, consumer, admin, super_admin Page
URL-130	/client/security	client, consumer, admin, super_admin Page
URL-131	/client/profile	client, consumer, admin, super_admin Page
URL-132	/api	Authenticated; verify resource policy Page
URL-133	/api/keys	Authenticated; verify resource policy Page
URL-134	/api/webhooks	Authenticated; verify resource policy Page
URL-135	/api/sdks	Authenticated; verify resource policy Page
URL-136	/api/guides	Authenticated; verify resource policy Page
URL-137	/api/monitoring	Authenticated; verify resource policy Page
URL-138	/api/eis	Authenticated; verify resource policy Page

ID	URL pattern	Declared access / behavior
URL-139	/api/eis/transmissions	Authenticated; verify resource policy Page
URL-140	/api/eis/performance	Authenticated; verify resource policy Page
URL-141	/api/eis/errors	Authenticated; verify resource policy Page
URL-142	/taxpayer	admin, super_admin, bir Page
URL-143	/taxpayer/registry	admin, super_admin, bir Page
URL-144	/taxpayer/businesses	admin, super_admin, bir Page
URL-145	/taxpayer/verification	admin, super_admin, bir Page
URL-146	/taxpayer/portal	admin, super_admin, bir Page
URL-147	/taxpayer/users	admin, super_admin, bir Page
URL-148	/engine	admin, super_admin, bir Page
URL-149	/eis	Authenticated; verify resource policy Page
URL-150	/eis/transmissions	Authenticated; verify resource policy Page
URL-151	/invoices	Authenticated; verify resource policy Page
URL-152	/monitoring	admin, super_admin, bir Page
URL-153	/compliance	admin, super_admin, bir Page
URL-154	/audit	admin, super_admin, bir Page
URL-155	/notifications	admin, super_admin, bir Page
URL-156	/certificates	admin, super_admin, bir Page
URL-157	/archive	admin, super_admin, bir Page
URL-158	/bcdr	admin, super_admin Redirect /super-admin/backups
URL-159	/soc	admin, super_admin, bir Page

ID	URL pattern	Declared access / behavior
URL-160	/soc/operations	admin, super_admin, bir Page
URL-161	/accreditation	admin, super_admin, bir Page
URL-162	/executive	admin, super_admin, bir Page
URL-163	/ai	Authenticated; verify resource policy Page
URL-164	/system	admin, super_admin Page
URL-165	/platform	admin, super_admin, bir Page
URL-166	/analytics	admin, super_admin, bir Page

Appendix C / Performance and resilience protocol

The following values are proposed QA acceptance targets carried from the checklist. Agree them with the release owner before testing. They are not benchmark results or production guarantees. Record hardware, dataset, cache state, browser/network, concurrency and build with every measurement.

Measure	Proposed acceptance target / control
Paged reads	p95 <= 2 seconds; p99 <= 5 seconds under the agreed workload. Measure API duration separately from page rendering.
Useful page content	p95 <= 3 seconds on the agreed desktop and network; data must be usable, not just a loading shell.
Realtime freshness	Revision checks around 1 second when active; commit-to-visible update p95 <= 5 seconds. Record actual polling and backend refresh behavior.
Data integrity	Zero tenant leaks, duplicate accepted sales or fees, and unexplained count or centavo reconciliation differences.
Unexpected errors	Unexpected 5xx/timeouts < 0.1% during steady state. Report expected validation/throttle responses separately; separate fault-injection windows.
Export / recovery	Agree maximum export duration, resource budget, RTO and RPO before the run. Measure actual values; do not invent a target or successful recovery.

Dataset and workload design

1. Create one million total rows across merchants and a separate one-million-row single-merchant dataset. Include realistic line counts, periods, statuses, branches, refunds/corrections and text lengths.
2. Include a skewed distribution, such as one merchant owning 95% of rows, while another merchant performs ordinary work. Verify fairness and isolation.
3. Measure warm and cold cache separately. Test shallow and deep pages, selective and broad filters, empty matches, expensive summaries and large exports.
4. Ramp through 1, 10, 50 and 100 concurrent users when the approved capacity permits; only go higher by agreement. Use a realistic mix of reads, intake, refresh and exports.
5. Measure each ramp stage for at least 15 minutes after stabilization and run a two-hour soak for the agreed steady workload. Agree emergency stop thresholds before starting.

What to collect and how to decide

Evidence	Required observation
Latency	p50, p95 and p99; sample count; request type; time window; server time versus client render time.
Capacity	Throughput, concurrent sessions, active DB connections, CPU/RAM, disk I/O and queue depth/oldest job age.
Query behavior	Representative query plans, rows examined, indexed access, bounded page sizes and summary behavior. Avoid performance conclusions based only on total row count.
Reliability	Unexpected error numerator and request denominator; retries and throttles reported separately; no overlapping refresh storm.
Correctness	Before/after document and ledger totals by tenant/environment, unique event IDs and export completeness.
Recovery	Time to recover normal behavior after faults, queue drain, retry safety, and no missing or duplicate financial effects.

Fault and overload scenarios

Use controlled slow responses, network loss, worker restarts, delivery errors and dependency unavailability. Observe timeouts, cancellation, exponential/backoff behavior where specified and a usable retry state. Stop when agreed safety thresholds are breached. A page must not remain indefinitely at Loading without a bounded error or recovery path.

Report template

Run ID / build / dataset version / hardware / workload / target / observed p50-p95-p99 / throughput / unexpected error rate / peak resources / reconciliation outcome / defects / reviewer decision. Attach graphs and raw measurements; state limitations and differences from production.

Appendix D / External dependency register

Run the local preparation, validation and disabled-transport cases now in the authorized lab. The five cases below need external prerequisites. Keep them Blocked or approved Deferred until those prerequisites exist; do not relabel fake responses as official verification.

BIR-011 / BIR-issued authentication and contract

Required phase: BIR credentials required

Prerequisite / procedure: When credentials arrive, confirm official endpoint/version/dialect and run prescribed certification authentication.

Evidence needed to pass: Actual issued credentials interoperate with the confirmed contract; retain real certification evidence.

BIR-012 / Official certification scenario suite

Required phase: BIR credentials required

Prerequisite / procedure: Run the BIR-prescribed positive/negative and representative CAS/POS scenarios after authorized setup.

Evidence needed to pass: Each required official scenario has actual evidence and resolved discrepancies; lab passes are not substituted.

BIR-013 / Production activation and acceptance

Required phase: BIR authorization required

Prerequisite / procedure: After authority/certification approval, test controlled production release, inquiry and reconciliation under the approved plan.

Evidence needed to pass: Authentic complete per-invoice acceptance is recorded; remaining activation gates are signed off.

OPS-010 / Offsite backup and production DR

Required phase: Infrastructure required

Prerequisite / procedure: After storage is provisioned, test separate custody, restore access and controlled production-equivalent recovery.

Evidence needed to pass: Real evidence meets approved recovery targets. Planned providers/regions are not reported as already deployed.

OPS-011 / Real controller and failover

Required phase: Infrastructure required

Prerequisite / procedure: When agents/controller/HA are provisioned, execute approved isolated service/failover/quorum/network recovery drills.

Evidence needed to pass: Actual identity, mTLS, locking, rollback and postchecks succeed with documented evidence.

Dependency decision record

For each dependency record: owner, missing prerequisite, expected availability, allowed local coverage, release impact, approving reviewer and next check date. Production activation needs explicit authorized scope, not only a successful certification test.

Appendix E / Evidence and defect reporting

Minimum evidence per execution

1. Test ID and variant; exact release/build; environment; tester; PHT timestamp and UTC correlation time if needed.
2. Actor alias, role, merchant/branch/environment scope and fixture IDs; do not record passwords, API tokens, OTP seeds or recovery codes.
3. Before state, actions performed and actual result. Capture redacted request/response IDs for integration, concurrency and failure tests.
4. Expected-versus-actual comparison using an independent oracle. Include counts, centavos, statuses and ownership, not only a success screenshot.
5. Evidence links and hashes for downloaded PDFs/CSVs or restore manifests where relevant. Use controlled private storage with retention rules.
6. Defect ID, impact, reproducibility and retest record. Maintain the failed evidence as well as the later passing result.

Suggested severity scale

Severity	Examples / response
S1 - Critical	Cross-tenant disclosure, unauthorized privileged access, widespread outage, unrecoverable loss. Stop the affected run and escalate to the incident owner.
S2 - High	Incorrect financial results, duplicate debit/sale, broken core workflow or significant control failure. Release-blocking unless an accountable exception is explicitly approved.
S3 - Medium	Limited workflow failure with a viable workaround and no financial/security corruption. Prioritize by affected scope.
S4 - Low	Minor visual or wording issue that does not impair correct operation. Capture readability/accessibility impacts before assuming severity.

A reproducible defect

Title: [API-004] Duplicate retry creates a second fee debit (illustrative only). Include the affected build/environment, exact event ID, opening and closing balances, retry sequence, expected single debit, observed debit count, frequency and redacted evidence. This example is a reporting format, not a finding about NUERS.

Execution record template

Field	Fill in during QA
Test / variant	Test ID; variant name; related route IDs
Release / environment	Exact build; URL/environment; configuration revision
Tester / time	Name or alias; start/end PHT; correlation UTC if needed
Prerequisites	Role/tenant aliases; fixture versions; oracle version
Baseline	Counts, balance, record identity, state and revision
Actual actions	Steps performed; payload or attachment reference
Expected / actual	Specific comparison and differences
Evidence	Private links; screenshots; redacted response; file hashes
Result / defect	Not Run / In Progress / Pass / Fail / Blocked / Deferred / N/A; defect IDs or reason
Retest	Fix build; actual retest result; related regression IDs; reviewer

Release sign-off record

Approval area	Record before release
Scope and baseline	Candidate build; test window; included modules; approved exclusions
Execution summary	Total in scope; Pass; Fail; Blocked; Deferred; N/A; outstanding variants
Risk review	Open defects and explicit disposition; security/financial/data-integrity review
Dependency review	BIR, DR and infrastructure prerequisites; retained gates and owners
Recovery and monitoring	Verified rollback/recovery references and post-deploy smoke/monitoring owner
Decision	Go / No-Go; accountable reviewers; date/time; any conditions and expiry

Appendix F / Glossary and scope notes

Term	Meaning for QA
Tenant / merchant scope	The ownership boundary for a business and its users, records, files, balances and jobs.
Authorization / permission	The server-side decision that a caller may perform an action on the specific resource.
Idempotency	Repeating the same supported event identity does not repeat its committed business effect.
Source event / correlation ID	An event identifies the business submission; a correlation ID links related request, job and audit evidence.
Atomic processing	A declared unit either commits completely or leaves no partial financial effect.
Independent oracle	A separately reviewed expected result, not a value copied from the same system display being tested.
Live / Sandbox	Different record/processing scopes. Test environments can exercise Live-mode rules with controlled fixtures.
NUERS / delivery / BIR outcome	Separate states for source acceptance, communication delivery and official external transmission/acceptance.
PTI / PTT	Permit to Issue / Permit to Transmit records and related preparation workflows; an internal screen does not issue an official authority.
CAS / POS	Computerized accounting / point-of-sale systems. Apply the approved system/registration scope to the relevant fixture.
p95 / p99	95% / 99% of measured requests finish within the reported duration for the stated sample and workload.
RTO	Recovery Time Objective is an agreed target. Measure actual elapsed recovery time from the declared start to verified usable service.
RPO	Recovery Point Objective is an agreed data-loss-time target. Measure the gap between the failure reference time and latest verified recovered commit.
Lab versus production evidence	A synthetic lab drill proves only its stated setup, data and scope; it cannot be labeled a tested production recovery result.
PHT / UTC	Philippine time / coordinated universal time. Record the zone explicitly and test date boundaries.

Coverage baseline and change control

This manual expands the NUERS QA Master Checklist v1.0.0 prepared for the 29 October 2026 baseline. The 225 case IDs, priorities, roles, phase labels, fixture references, procedures and expected results are preserved. The feature-purpose text, plain-language explanations and execution guidance are added for testers.

The 166-entry route list is a frontend inventory snapshot. Changes to routes, permissions, API schemas, invoice rules, pricing or infrastructure require a new coverage review. Add new cases through controlled revision; preserve the original IDs for traceability.

> **Plan completion is not test completion**
> Use this PDF to understand and execute QA. The completed execution register, defect/retest history, measured results and accountable release decision provide the evidence for readiness.