Elastic Beanstalk

AWS Elastic Beanstalk

- PAAS platform
- Quick Deployment and application Management
- Do not need to know IAAS
- Reduce Management Complexity
- Just Upload your app
- Beanstalk manages
  - Capacity Provisioning
  - Load Balancing
  - Scaling
  - App Health Monitoring

AWS Elastic Beanstalk

- Supports apps written in
  - Go
  - Java
  - .NET
  - Node.js
  - PHP
  - Python
  - Ruby
  - Docker platforms

AWS Elastic Beanstalk

- You can use Beanstalk using
  - Console
  - AWS CLI
  - AWS EB CLI – Another CLI geared for Elastic Beanstalk
    - Requires Python 3.8+
    - On Windows also requires IIS Server to be installed
- Basic Flow
  - Create an Application locally
  - Upload an Application Version (WAR/JAR)
  - Provide Configure the application
  - AWS Beanstalk will automatically launch an environment and create resources

AWS Elastic Beanstalk



AWS Elastic Beanstalk

- There is no additional charges for AWS Elastic Beanstalk
- However, it will use resources which may attract charges

AWS Elastic Beanstalk



AWS Elastic Beanstalk

- An AWS Elastic Beanstalk application is a logical collection of components
- These are
  - Environments
  - Versions
  - Environment Configurations

AWS Elastic Beanstalk

- **An AWS Elastic Beanstalk application** is conceptually similar to a folder
- AWS Elastic Beanstalk allows you to run applications as environments.
- **An Application version** is a **specific, labeled iteration** of deployable code for a web application
- An Application Version points to an Amazon Simple Storage Service (Amazon S3) object that contains the deployable code.
- An Application can have multiple versions.

AWS Elastic Beanstalk

- **An AWS Elastic Beanstalk Environment** is a collection of AWS resources
- Each Environment runs only one Application Version at a time.
- We can run same application version or different application versions on multiple environments at same time.
- To do so, we first choose an Environment Tier.
- An environment Tier selects the type of application and controls what resources are required. Examples are:
  - Web Server Environment Tier
  - Backend services run in worker environment tiers

AWS Elastic Beanstalk

- An Environment Configuration is a collection of parameters and settings that define how an environment and its associated resources behave.
- When you update an environment's configuration settings, Elastic Beanstalk automatically applies the changes to existing resources or deletes and deploys new resources (depending on the type of change).
- You can use templates for re-use - these are "saved Configurations"

AWS Elastic Beanstalk

- A Platform is a combination of an operating system, programming language runtime, web server, application server, and Elastic Beanstalk components.
- Design and target your web application to a platform.
- Elastic Beanstalk provides a variety of platforms on which you can build your applications.

AWS Elastic Beanstalk



AWS Elastic Beanstalk



AWS Elastic Beanstalk

- Beanstalk Applications do not have persistent storage as default. You can configure either
  - EBS
  - EFS
  - S3
  - DynamoDB
  - RDS
- Security of data in/out is customer security.
- Network Traffic has to be over HTTPS not HTTP (get certificate from AWS Certificate Manager – ACM)

AWS Elastic Beanstalk

- Required Roles
  - Service Role - assume this role to run the application. Assigned via managed policies
  - Instance Profile – Applied to EC2 Instances. Allows them to write/read logs to S3 for example.

AWS Elastic Beanstalk

- A service role is the IAM role that Elastic Beanstalk assumes when calling other services on your behalf.
- 2 Managed roles are attached
  - AWSElasticBeanstalkEnhancedHealth
  - AWSElasticBeanstalkManagedUpdatesCustomerRolePolicy
- An instance profile is in an IAM role that's applied to Amazon EC2 instances that are launched in your Elastic Beanstalk environment.

AWS Elastic Beanstalk

- An instance profile is in an IAM role that's applied to Amazon EC2 instances that are launched in your Elastic Beanstalk environment.
- Used when
  - Retrieve application versions from Amazon Simple Storage Service (Amazon S3)
  - Write logs to Amazon S3
  - In worker environments, read from an Amazon Simple Queue Service (Amazon SQS) queue
  - In worker environments, publish instance health metrics to Amazon CloudWatch
-

AWS Elastic Beanstalk

- Uses these policies
  - AWSElasticBeanstalkWebTier
  - AWSElasticBeanstalkWorkerTier
  - AWSElasticBeanstalkMulticontainerDocker
-