

Quest1

August 27, 2018

1 CSE 5345 Quest 1

Basic Python Quest

```
CLASS = CSE5345
NAME = Lee, SeungKi
STUDENT_ID = 35460312
CODING_NAME = MonsterPeach
```

1.1 1. isSorted(list)

Iterate through the list and see if value of the left is ever greater than the right

```
In [1]: def isSorted(list):
        for i in range (len(list)-1):
            if list[i] > list[i+1]:
                return False
        return True

In [2]: print(isSorted([2,4,7,7,99,122]))
        print(isSorted(['a', 'b', 'c']))
        print(isSorted(['a', 'z', 'b', 'c']))
```

```
True
True
False
```

1.2 2. hasUniqueValues(list)

Put every element of a list into a dictionary as keys, then check the number of keys against number of elements.

```
In [3]: def hasUniqueValues(list):
        return len({}.fromkeys(list)) == len(list)
```

```
In [4]: print(hasUniqueValues([2,4,7,99,122, 7]))
        print(hasUniqueValues(['a', 'b', 'c']))
        print(hasUniqueValues(['a', 'z', 'b', 'c', 'c']))
```

```
False
True
False
```

1.3 3. isSortedAndUnique(list)

Just utilize two functions above

```
In [5]: def isSortedAndUnique(list):

        return isSorted(list) and hasUniqueValues(list)

In [6]: print(isSortedAndUnique([2,4,7,7,99,122]))
        print(isSortedAndUnique(['a', 'b', 'c']))
        print(isSortedAndUnique(['a', 'z', 'b', 'b', 'c']))
```

```
False
True
False
```

1.4 4. genSortedArrayUniqueValues(list)

use fromkeys of dictionary to eliminate duplicates, then sort and return the list

Dr. Coyle, I am using the sorted() function here because it does not appear in the constraints for this function. If you would like me to write my own sort functions, I would be happy to do it. Please let me know.

```
In [7]: def genSortedArrayUniqueValues(list):

        return_list = []

        for key in {}.fromkeys(list):
            return_list.append(key)

        return sorted(return_list)

In [8]: print(genSortedArrayUniqueValues([2,4,7,7,122,99]))
        print(genSortedArrayUniqueValues(['a','b','z','c', 'a']))
```

```
[2, 4, 7, 99, 122]
['a', 'b', 'c', 'z']
```

1.5 5. listToMapTwoByTwo(list)

check the size of the list, then even items in the list will be key, odd items will be value

```
In [9]: def listToMapTwoByTwo(list):  
  
    return_dict = {}  
  
    if len(list) > 1:  
        for i in range (len(list)-1):  
            if i%2 == 0:  
                return_dict[list[i]] = list[i+1]  
  
    return return_dict
```

```
In [10]: print(listToMapTwoByTwo(['foo', 'bar']))  
         print(listToMapTwoByTwo(['a', 2, 3, 'foo']))  
         print(listToMapTwoByTwo([]))
```

```
{'foo': 'bar'}  
{'a': 2, 3: 'foo'}  
{}
```

1.6 6. wordsInStringToDictWordCount(str)

Split the string by whitespace character and put them in a list. For every item in the list, if the item is already in the dictionary add to its count. If not, set its count to 1. Return the count.

```
In [11]: def wordsInStringToDictWordCount(str):  
  
    return_dict = {}  
  
    if len(str) > 1:  
        temp_list = str.split()  
  
        for i in temp_list:  
            if i in return_dict:  
                return_dict[i] += 1  
            else:  
                return_dict[i] = 1  
  
    return return_dict  
  
In [12]: print(wordsInStringToDictWordCount("foo bar  bar"))  
         print(wordsInStringToDictWordCount(''))
```

```
{'foo': 1, 'bar': 2}  
{}
```

1.7 7. reverseWordsInString(str)

Split by whitespace and put str into a list, reverse the list using [::-1], then join the list as char. Make sure to leave a space between the joined items

```
In [13]: def reverseWordsInString(str):  
  
        temp_list = str.split()  
        temp_list = temp_list[::-1]  
  
        return ' '.join(temp_list)  
  
In [14]: print(reverseWordsInString('foo bar bar baz'))  
  
baz bar bar foo
```

1.8 8. def genListOfOverlaps(list1, list2)

Put unique items of list1 into a dict. Put unique items of list2 into the dict using word counter. Return a list with value = 2

Dr. Coyle,

If I can use set it would be much shorter... but I am not sure if set is one of the constraints for this function. If you would like a better big(o), please let me know and I will happily write the function using intersection.

```
In [15]: def genListOfOverlaps(list1, list2):  
  
        return_list = []  
        temp_dict = {}  
  
        for i in list1:  
            if i not in temp_dict:  
                temp_dict[i] = 1  
        for i in {}.fromkeys(list2):  
            if i in temp_dict:  
                temp_dict[i] += 1  
            else:  
                temp_dict[i] = 1  
  
        for key in temp_dict:  
            if temp_dict[key] == 2:  
                return_list.append(key)  
  
        return sorted(return_list)  
  
In [16]: print(genListOfOverlaps([2,4,6,8],[6,2,2,9,7]))  
         print(genListOfOverlaps([2,4,6,8],[2,4,6,8]))  
         print(genListOfOverlaps([2,4,6,8],[1,1,9,7]))
```