```java
/*
CSE 3342
Seung Ki Lee
HW03
*/

package hw03j;
import java.net.*;
import java.io.*;
import java.util.*;

public class HW03J {

    static List<String> strToList = new ArrayList<String>();

    //return the whole string
    public static String f1URLReader(String inputURL) throws Exception
    {
        URL webpage = new URL(inputURL); // Set the URL to my index.html
        BufferedReader in = new BufferedReader(new InputStreamReader(webpage.openStream())); // Dynamically allocate the BufferedReader
        String inputLine = null; // Create a String to hold the readLine address
        String holdLine = null;
        while((holdLine = in.readLine()) != null) // While the read in is not empty, print the line to check
        {
            //add to list for processing -> call function on strToList
            inputLine += holdLine;
        }
        //close the file
        in.close();

        return inputLine;
    }

    public static List<String> f2CleanString(String inputString)
    {
        List<String> strInList = new ArrayList<String>();
        String[] cleanedString = null;
        String[] splittedString = inputString.replaceAll("[^a-zA-Z]", " ").toLowerCase().split("\\W+");

        //for debugging
            for(int i=0; i<splittedString.length; i++) {
                //get rid of known html header
                if(!"null".equals(splittedString[i]) && !"div".equals(splittedString[i]) && !"h".equals(splittedString[i]) && !"charset".equals(splittedString[i]) && !"utf".equals(splittedString[i]) && !"meta".equals(splittedString[
                {
                    strInList.add(splittedString[i]);
                }
            }
        //return the list
        return strInList;
    }

    public static Map<String, Integer> f3ListToMap(List<String> inputList) throws Exception {

        //Read in the list of ignorewords from the URL
        List<String> ignoreList = new ArrayList<String>();

        URL ignoreWordsTxt = new URL("http://lyle.smu.edu/~coyle/3342/hw3.ignoreWords.txt"); // Set the URL to my index.html
        BufferedReader in = new BufferedReader(new InputStreamReader(ignoreWordsTxt.openStream())); // Dynamically allocate the BufferedReader
        String ignoreWords = null; // Create a String to hold the readLine address

        //Store the ignorewords into list for comparison
        while((ignoreWords = in.readLine()) != null) {
            //add to list for processing
            ignoreList.add(ignoreWords);
        }
        //close the file
        in.close();

        //Compare inputList vs ignoreList and erase if inputList has anything with ignoreList
        //Have the words in Either List by putting the inputList and adding ignoreLists
        List<String> inEitherList = new ArrayList<String>(inputList);
        inEitherList.addAll(ignoreList);

        //Have the words in Both Lists by putting the inputList, retaining everything in ignoreList, and remove everything that's in both lists from eitherlist
        List<String> inBothList = new ArrayList<String>(inputList);
        inBothList.retainAll(ignoreList);
        inEitherList.removeAll(inBothList);

        //build map from the checked and trimmed list
        Map<String, Integer> pairedMap = new HashMap<String, Integer>();

        //if the function does not hold a key, add it. If it does, add the count
        for(int i=0; i< inEitherList.size(); i++) {
                if(!pairedMap.containsKey(inEitherList.get(i)))
                    pairedMap.put(inEitherList.get(i), 1);
                else {
                    Integer eachWordCount = pairedMap.get(inEitherList.get(i));
                    pairedMap.put(inEitherList.get(i), eachWordCount+1);
                }
        }
        return pairedMap;
    }

    public static String f4jsonOutput(Map <String, Integer> inputMap, Integer nOfWords) throws Exception {

        //initialize the string for usage
        String jsonString = "";
        Map<String,Integer> newMap = new HashMap<String, Integer>();

        for(int i=0; i<nOfWords; i++) {
            int max = 0;
            String word = null;

            Iterator iterat = inputMap.keySet().iterator();

            while(iterat.hasNext()) {
                Object key = iterat.next();
                Object value = inputMap.get(key);

//                  pop off the biggest key value pair
                if((int)value > max) {
                    max = (int)value;
                    word = (String) key;
                }
                newMap.put(word, max);
                iterat.remove();
            }
        }

        //Get the top N words in order

        for(int i=0; i<1; i++) {
            int max = 0;
            String word = "";

            Iterator iterat = newMap.keySet().iterator();

            while(iterat.hasNext()) {
                Object key = iterat.next();
```

```
                while(iterat.hasNext()) {
                    Object key = iterat.next();
                    Object value = newMap.get(key);

//                  pop off the biggest key value pair
                    if((int)value > max) {
                        max = (int)value;
                        word = (String) key;
                    }
                    jsonString += "{"" + word + """:" + max + "}";
                    iterat.remove();
                }
            }

            System.out.println(jsonString);

            return jsonString;
        }

        /**
         * @param args the command line arguments
         */
        public static void main(String[] args) throws Exception {

            String stringedURL = f1URLReader("https://lyle.smu.edu/~seungkil/3342/index.html");
            List<String> listOfStrings = f2CleanString(stringedURL);
            Map<String, Integer> filteredMap = f3ListToMap(listOfStrings);
            f4jsonOutput(filteredMap,3);
        }

    }

```

Output - HW03J (run)

```
run:
{"mostly":2}{"inter":7}{"interpreter":3}
BUILD SUCCESSFUL (total time: 0 seconds)
```